

Aadhaar Biometric Updates - Deep Ecosystem Analysis

Objective

Go beyond surface-level analytics to identify **actionable improvements** for:

-  **Privacy-by-Design Gaps** - Data exposure risks in update workflows
-  **Low-Connectivity Region Challenges** - Authentication failure patterns
-  **Update/Deduplication Inefficiencies** - Workflow bottlenecks
-  **Service Delivery Issues** - Citizen & operator pain points

Dataset: Biometric Updates

Records of fingerprint/iris biometric updates across India by:

- Geographic location (State, District, Pincode)
- Age groups (5-17 years, 17+ years)
- Date of update

```
In [43]: %pip install scipy -q
```

Note: you may need to restart the kernel to use updated packages.

```
In [44]: # Setup and Data Loading
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from glob import glob
from scipy import stats
import warnings
warnings.filterwarnings('ignore')

# Plotting configuration
plt.style.use('seaborn-v0_8-whitegrid')
plt.rcParams['figure.figsize'] = (14, 6)
plt.rcParams['font.size'] = 11

# Load all biometric data files
files = glob("dataset/api_data_aadhar_biometric/*.csv")
df = pd.concat([pd.read_csv(f) for f in files], ignore_index=True)

# Preprocess
df['date'] = pd.to_datetime(df['date'], format='%d-%m-%Y')
df['year'] = df['date'].dt.year
df['month'] = df['date'].dt.month
```

```

df['month_name'] = df['date'].dt.month_name()
df['day_of_week'] = df['date'].dt.day_name()
df['week'] = df['date'].dt.isocalendar().week
df['day_of_month'] = df['date'].dt.day

print("Data Loaded Successfully")
print(df.head())

# Calculate totals
df['total_bio_updates'] = df['bio_age_5_17'] + df['bio_age_17_']
df['youth_ratio'] = df['bio_age_5_17'] / df['total_bio_updates'].replace(0,

print(f"Loaded {len(df):,} records")
print(f"Date Range: {df['date'].min().date()} to {df['date'].max().date()}")
print(f"States: {df['state'].nunique()} | Districts: {df['district'].nunique()}")
print(f"Pincodes: {df['pincode'].nunique():,}")

```

Data Loaded Successfully

	date	state	district	pincode	bio_age_5_17	bio_age_17_	year	\
0	2025-09-19	Goa	North Goa	403502	0	4	2025	
1	2025-09-19	Goa	North Goa	403508	1	4	2025	
2	2025-09-19	Goa	North Goa	403513	2	0	2025	
3	2025-09-19	Goa	North Goa	403527	2	2	2025	
4	2025-09-19	Goa	South Goa	403601	7	3	2025	

	month	month_name	day_of_week	week	day_of_month
0	9	September	Friday	38	19
1	9	September	Friday	38	19
2	9	September	Friday	38	19
3	9	September	Friday	38	19
4	9	September	Friday	38	19

Loaded 1,861,108 records

Date Range: 2025-03-01 to 2025-12-29

States: 57 | Districts: 974

Pincodes: 19,707

PART 1: Identifying Low-Connectivity & Underserved Regions

Real-World Problem: Many rural and remote areas face authentication failures due to:

- Poor internet connectivity
- Inadequate biometric device deployment
- Seasonal workforce migration patterns

Analysis Goal: Identify regions with abnormally LOW biometric update activity (potential service gaps)

In [45]: *# 1.1 Identify Underserved Districts – Service Gap Analysis*
Districts with LOW updates relative to expected population activity

```

district_stats = df.groupby(['state', 'district']).agg({
    'total_bio_updates': ['sum', 'mean', 'std', 'count'],
    'pincode': 'nunique',
    'date': ['min', 'max']
}).reset_index()

district_stats.columns = ['state', 'district', 'total_updates', 'daily_avg',
                          'daily_std', 'active_days', 'pincode_count', 'first_date']

# Calculate service coverage score (higher = better served)
district_stats['coverage_score'] = (
    district_stats['daily_avg'] *
    district_stats['active_days'] /
    district_stats['pincode_count']
).fillna(0)

# Identify UNDERSERVED districts (bottom 10% by coverage score)
threshold = district_stats['coverage_score'].quantile(0.10)
underserved = district_stats[district_stats['coverage_score'] <= threshold].

print("TOP 20 UNDERSERVED DISTRICTS (Potential Connectivity/Infrastructure Gaps)")
print("=" * 80)
display(underserved[['state', 'district', 'total_updates', 'daily_avg', 'pincode_count', 'first_date']])

# Visualize underserved by state
underserved_by_state = underserved.groupby('state').size().sort_values(ascending=True)

fig, ax = plt.subplots(figsize=(12, 6))
underserved_by_state.plot(kind='barh', ax=ax, color='#e74c3c', edgecolor='black')
ax.set_xlabel('Number of Underserved Districts')
ax.set_title('📊 States with Most Underserved Districts\n(Potential Low-Connectivity Areas)')
ax.invert_yaxis()
plt.tight_layout()
plt.show()

print(f"\nINSIGHT: {len(underserved)} districts identified as underserved (below 10% coverage score).")


```

TOP 20 UNDERSERVED DISTRICTS (Potential Connectivity/Infrastructure Gaps)

=====

=====

	state	district	total_updates	daily_avg	pincode_count	coverage_score
1071	west Bengal	South 24 Parganas	1	1.0	1	1.0
337	Jammu and Kashmir	Poonch	1	1.0	1	1.0
347	Jammu and Kashmir	udhampur	1	1.0	1	1.0
430	Karnataka	Udupi *	3	1.0	3	1.0
964	Uttar Pradesh	Raebareli	9	1.0	9	1.0
573	Manipur	Pherzawl	2	1.0	2	1.0
951	Uttar Pradesh	Mahoba *	1	1.0	1	1.0
916	Uttar Pradesh	Chandauli *	1	1.0	1	1.0
897	Uttar Pradesh	Auraiya *	1	1.0	1	1.0
322	Jammu and Kashmir	?	1	1.0	1	1.0
626	Odisha	BALANGIR	1	1.0	1	1.0
669	Orissa	Anugul *	1	1.0	1	1.0
840	Tamilnadu	Chennai	1	1.0	1	1.0
688	Orissa	Khorda	4	1.0	4	1.0
690	Orissa	Khordha *	1	1.0	1	1.0
703	Orissa	Sundergarh	2	1.0	2	1.0
788	Sikkim	Namchi	5	1.0	5	1.0
780	Rajasthan	Salumbar	1	1.0	1	1.0
777	Rajasthan	Phalodi	2	1.0	2	1.0
667	Orissa	Angul	2	1.0	2	1.0



INSIGHT: 110 districts identified as underserved (10.3% of total)

```
In [46]: # 1.2 Pincode-Level Service Deserts Analysis
# Identify pincodes with sporadic/zero activity – potential authentication b

pincode_activity = df.groupby('pincode').agg({
    'total_bio_updates': ['sum', 'mean', 'count'],
    'state': 'first',
    'district': 'first'
}).reset_index()
pincode_activity.columns = ['pincode', 'total', 'daily_avg', 'active_days',

# Service desert = very few active days OR very low daily average
pincode_activity['is_service_desert'] = (
    (pincode_activity['active_days'] < pincode_activity['active_days'].quant
    (pincode_activity['daily_avg'] < pincode_activity['daily_avg'].quantile(
)

service_deserts = pincode_activity[pincode_activity['is_service_desert']]
service_desert_by_state = service_deserts.groupby('state').size().sort_value

print("SERVICE DESERTS – Pincodes with Minimal Biometric Update Activity")
print("=" * 80)
print(f"Total Service Desert Pincodes: {len(service_deserts):,} ({len(servic
print(f"\nTop 10 States with Most Service Desert Pincodes:")
for state, count in service_desert_by_state.head(10).items():
    print(f"    • {state}: {count:,} pincodes")

# Recommendation Framework
print("\n" + "=" * 80)
print("💡 RECOMMENDATION: Mobile Biometric Update Units")
print("=" * 80)
print("""
PROBLEM IDENTIFIED:
    - Certain pincodes show consistently low biometric update activity
    - This correlates with citizens facing difficulty accessing Aadhaar servic

PROPOSED SOLUTION:
```

1. Deploy Mobile Biometric Update Vans to service deserts quarterly
2. Partner with CSCs (Common Service Centers) in underserved areas
3. Enable offline-first biometric capture with delayed sync capability
4. Prioritize infrastructure investment in states with most service deserts

SERVICE DESERTS – Pincodes with Minimal Biometric Update Activity

Total Service Desert Pincodes: 2,346 (11.9%)

Top 10 States with Most Service Desert Pincodes:

- West Bengal: 335 pincodes
- Karnataka: 265 pincodes
- Kerala: 260 pincodes
- Tamil Nadu: 181 pincodes
- Uttar Pradesh: 137 pincodes
- Himachal Pradesh: 134 pincodes
- Gujarat: 122 pincodes
- Assam: 114 pincodes
- Maharashtra: 97 pincodes
- Odisha: 95 pincodes

💡 RECOMMENDATION: Mobile Biometric Update Units

PROBLEM IDENTIFIED:

- Certain pincodes show consistently low biometric update activity
- This correlates with citizens facing difficulty accessing Aadhaar services

PROPOSED SOLUTION:

1. Deploy Mobile Biometric Update Vans to service deserts quarterly
2. Partner with CSCs (Common Service Centers) in underserved areas
3. Enable offline-first biometric capture with delayed sync capability
4. Prioritize infrastructure investment in states with most service deserts

PART 2: Update Workflow Inefficiencies & Bottlenecks

Real-World Problem: Biometric update centers face:

- Unpredictable demand surges causing long wait times
- Uneven distribution of workload across days/weeks
- End-of-month/quarter rushes for welfare scheme compliance

Analysis Goal: Identify temporal patterns to optimize resource allocation

```

In [47]: # 2.1 Temporal Demand Pattern Analysis
daily_totals = df.groupby('date')['total_bio_updates'].sum().reset_index()
daily_totals['day_of_week'] = daily_totals['date'].dt.day_name()
daily_totals['day_of_month'] = daily_totals['date'].dt.day
daily_totals['is_weekend'] = daily_totals['day_of_week'].isin(['Saturday', 'Sunday'])
daily_totals['is_month_end'] = daily_totals['day_of_month'] >= 25

# Weekly pattern analysis
day_order = ['Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday', 'Saturday', 'Sunday']
weekly_pattern = daily_totals.groupby('day_of_week')['total_bio_updates'].agg(['mean', 'std'])
weekly_pattern = weekly_pattern.reindex(day_order)

fig, axes = plt.subplots(1, 3, figsize=(18, 5))

# Day of week distribution
colors = ['#e74c3c' if day in ['Saturday', 'Sunday'] else '#3498db' for day in day_order]
weekly_pattern['mean'].plot(kind='bar', ax=axes[0], color=colors, edgecolor='black')
axes[0].set_title('📅 Average Daily Updates by Day of Week', fontweight='bold')
axes[0].set_xlabel('Day')
axes[0].set_ylabel('Average Updates')
axes[0].tick_params(axis='x', rotation=45)

# Month-end surge analysis
month_period = daily_totals.groupby('is_month_end')['total_bio_updates'].mean()
axes[1].bar(['Regular Days\n(1-24)', 'Month-End\n(25-31)'], month_period.values,
            color=['#3498db', '#e74c3c'], edgecolor='black')
axes[1].set_title('📅 Month-End Surge Pattern', fontweight='bold')
axes[1].set_ylabel('Average Daily Updates')
surge_pct = (month_period[True] - month_period[False]) / month_period[False]
axes[1].annotate(f'+{surge_pct:.1f}% surge', xy=(1, month_period[True]),
                 xytext=(1.2, month_period[True]*0.9), fontsize=12, color='red')


# Time series with highlighted peaks
axes[2].plot(daily_totals['date'], daily_totals['total_bio_updates'], alpha=0.5)
axes[2].fill_between(daily_totals['date'], daily_totals['total_bio_updates'], color='red', alpha=0.1)

# Highlight anomalous peaks
mean_val = daily_totals['total_bio_updates'].mean()
std_val = daily_totals['total_bio_updates'].std()
peaks = daily_totals[daily_totals['total_bio_updates'] > mean_val + 2*std_val]
axes[2].scatter(peaks['date'], peaks['total_bio_updates'], color='red', s=50)
axes[2].axhline(y=mean_val, color='green', linestyle='--', label=f'Avg: {mean_val:.1f}')
axes[2].set_title('📅 Daily Biometric Updates Timeline (Spikes Highlighted)')
axes[2].legend()

plt.tight_layout()
plt.show()

print(f"\nKEY FINDINGS:")
print(f"    • Weekend vs Weekday difference: {(weekly_pattern.loc['Saturday', 'mean'] - weekly_pattern.loc['Monday', 'mean']).round(1)}%")
print(f"    • Month-end surge: +{surge_pct:.1f}% increase in last week")
print(f"    • Demand spike days identified: {len(peaks)}")

```



KEY FINDINGS:

- Weekend vs Weekday difference: 37.2%
- Month-end surge: +54.1% increase in last week
- Demand spike days identified: 5

```
In [48]: # 2.2 State-Level Workload Imbalance Analysis
# Identify states with highly variable demand (operational planning challenge)

state_daily = df.groupby(['state', 'date'])['total_bio_updates'].sum().reset_index()
state_variability = state_daily.groupby('state')['total_bio_updates'].agg(['min', 'max', 'std'])
state_variability['cv'] = state_variability['std'] / state_variability['mean']
state_variability['demand_range'] = state_variability['max'] - state_variability['min']
state_variability = state_variability.sort_values('cv', ascending=False)

# High variability = difficult to plan resources
high_variability_states = state_variability[state_variability['cv'] > state_variability['cv'].median()]

print("STATES WITH HIGH DEMAND VARIABILITY (Resource Planning Challenge)")
print("=" * 80)
print("High CV (Coefficient of Variation) indicates unpredictable demand - harder to staff")
display(state_variability.head(15).round(2))

fig, axes = plt.subplots(1, 2, figsize=(16, 6))

# CV by state
top_cv_states = state_variability['cv'].head(15)
colors = ['#e74c3c' if cv > state_variability['cv'].median() else '#3498db']
top_cv_states.plot(kind='barh', ax=axes[0], color=colors, edgecolor='black')
axes[0].set_xlabel('Coefficient of Variation (Higher = More Unpredictable)')
axes[0].set_title('📊 Demand Unpredictability by State\n(Red = Above Median CV)')
axes[0].invert_yaxis()
axes[0].axvline(x=state_variability['cv'].median(), color='black', linestyle='dashed')
axes[0].legend()

# Demand range visualization
top_range = state_variability.nlargest(15, 'demand_range')
axes[1].barh(range(len(top_range)), top_range['demand_range'], color='#9b59b6')
axes[1].set_yticks(range(len(top_range)))
axes[1].set_yticklabels(top_range.index)
axes[1].set_xlabel('Demand Range (Max - Min daily updates)')
axes[1].set_title('📊 States with Widest Demand Swings\n(Hardest to Staff Operate)')
axes[1].invert_yaxis()

plt.tight_layout()
plt.show()
```

```

print("\n" + "=" * 80)
print("💡 RECOMMENDATION: Dynamic Resource Allocation System")
print("=" * 80)
print("""
PROBLEM IDENTIFIED:
    - High demand variability makes fixed staffing inefficient
    - Month-end surges cause long wait times and poor citizen experience
    - Weekend patterns differ significantly from weekdays

PROPOSED SOLUTIONS:
    1. PREDICTIVE STAFFING MODEL: Use ML to forecast demand 7-14 days ahead
    2. FLEXIBLE WORKFORCE: Train operators as "flex staff" deployable across c
    3. APPOINTMENT SYSTEM: Reduce walk-in variability with online scheduling
    4. MONTH-END INCENTIVES: Offer discounts/priority for updates before day 2
    5. EXTENDED WEEKEND HOURS: In high-demand states during peak periods
""")

```


STATES WITH HIGH DEMAND VARIABILITY (Resource Planning Challenge)

=====

====

High CV (Coefficient of Variation) indicates unpredictable demand – hard to staff efficiently

	mean	std	min	max	cv	demand_range
state						
Mizoram	1383.09	6120.34	5	51069	4.43	51064
Chandigarh	866.07	3714.94	2	32547	4.29	32545
Dadra and Nagar Haveli and Daman and Diu	32.46	100.12	1	459	3.08	458
Sikkim	271.67	813.08	1	4554	2.99	4553
Delhi	14822.30	43985.91	3	273966	2.97	273963
Manipur	3248.13	9566.42	24	86754	2.95	86730
Tripura	3282.64	9632.93	1	61839	2.93	61838
Madhya Pradesh	66559.22	190666.21	1	1004035	2.86	1004034
Jharkhand	22767.38	65039.73	1	378962	2.86	378961
Gujarat	35915.89	100523.13	4	541874	2.80	541870
Meghalaya	1007.20	2764.16	4	14360	2.74	14356
Punjab	19768.99	53363.21	7	277717	2.70	277710
Bihar	55029.07	147171.08	2	795719	2.67	795717
Dadra & Nagar Haveli	7.79	20.75	1	139	2.66	138
Kerala	18292.39	48210.92	2	247491	2.64	247489



RECOMMENDATION: Dynamic Resource Allocation System

PROBLEM IDENTIFIED:

- High demand variability makes fixed staffing inefficient
- Month-end surges cause long wait times and poor citizen experience
- Weekend patterns differ significantly from weekdays

PROPOSED SOLUTIONS:

1. PREDICTIVE STAFFING MODEL: Use ML to forecast demand 7-14 days ahead
2. FLEXIBLE WORKFORCE: Train operators as "flex staff" deployable across centers
3. APPOINTMENT SYSTEM: Reduce walk-in variability with online scheduling
4. MONTH-END INCENTIVES: Offer discounts/priority for updates before day 20
5. EXTENDED WEEKEND HOURS: In high-demand states during peak periods

👶 PART 3: Age-Group Specific Analysis - Youth Biometric Challenges

Real-World Problem:

- Children (5-17) have rapidly changing biometrics requiring frequent updates
- Schools as enrollment centers have capacity constraints
- UIDAI mandates: Update biometrics every 5 years for children

Analysis Goal: Identify youth-specific service gaps and optimization opportunities

```
In [49]: # 3.1 Youth vs Adult Update Ratio Analysis
# Low youth ratio may indicate children missing mandatory updates
```

```
state_age_analysis = df.groupby('state').agg({
    'bio_age_5_17': 'sum',
    'bio_age_17_': 'sum',
```

```

    'total_bio_updates': 'sum'
}).reset_index()

state_age_analysis['youth_percentage'] = (state_age_analysis['bio_age_5_17']
state_age_analysis['adult_percentage'] = (state_age_analysis['bio_age_17_']
state_age_analysis = state_age_analysis.sort_values('youth_percentage')

# National average
national_youth_pct = df['bio_age_5_17'].sum() / df['total_bio_updates'].sum()

print(f"NATIONAL YOUTH UPDATE PERCENTAGE: {national_youth_pct:.1f}%")
print("=" * 80)

fig, axes = plt.subplots(1, 2, figsize=(16, 8))

# States with lowest youth percentage (potential gap)
low_youth_states = state_age_analysis.head(15)
axes[0].barh(low_youth_states['state'], low_youth_states['youth_percentage'])
axes[0].axvline(x=national_youth_pct, color='blue', linestyle='--', linewidth=2)
axes[0].set_xlabel('Youth (5-17) as % of Total Updates')
axes[0].set_title('🚩 States with LOWEST Youth Biometric Updates\n(Potential Gap)')
axes[0].legend()
axes[0].invert_yaxis()

# Stacked comparison - top 20 states by volume
top_volume_states = state_age_analysis.nlargest(20, 'total_bio_updates')
width = 0.8
y_pos = range(len(top_volume_states))
axes[1].barh(y_pos, top_volume_states['youth_percentage'], width, label='Youth')
axes[1].barh(y_pos, top_volume_states['adult_percentage'], width, left=top_volume_states['youth_percentage'], label='Adult')
axes[1].set_yticks(y_pos)
axes[1].set_yticklabels(top_volume_states['state'])
axes[1].set_xlabel('Percentage')
axes[1].set_title('📊 Age Distribution of Updates (Top 20 States by Volume)')
axes[1].legend(loc='lower right')
axes[1].invert_yaxis()

plt.tight_layout()
plt.show()


# Identify states needing youth outreach
print("\nSTATES REQUIRING YOUTH BIOMETRIC OUTREACH (Below National Average):")
below_avg_states = state_age_analysis[state_age_analysis['youth_percentage'] < national_youth_pct]
print(f"    {len(below_avg_states)} states have below-average youth update rates")
print(f"    Bottom 5: {' '.join(state_age_analysis.head(5)['state'].tolist())}")

```

NATIONAL YOUTH UPDATE PERCENTAGE: 49.1%

=====

=====



STATES REQUIRING YOUTH BIOMETRIC OUTREACH (Below National Average):

36 states have below-average youth update rates

Bottom 5: odisha, Uttaranchal, Westbengal, Dadra & Nagar Haveli, Andaman & Nicobar Islands

```
In [50]: # 3.2 School Calendar Correlation – Academic Year Patterns
# Hypothesis: Youth updates should spike during school enrollment periods

monthly_age_breakdown = df.groupby('month').agg({
    'bio_age_5_17': 'sum',
    'bio_age_17_': 'sum'
}).reset_index()

monthly_age_breakdown['youth_pct'] = monthly_age_breakdown['bio_age_5_17'] /

month_names = {1: 'Jan', 2: 'Feb', 3: 'Mar', 4: 'Apr', 5: 'May', 6: 'Jun',
               7: 'Jul', 8: 'Aug', 9: 'Sep', 10: 'Oct', 11: 'Nov', 12: 'Dec'}
monthly_age_breakdown['month_name'] = monthly_age_breakdown['month'].map(month_names)

fig, axes = plt.subplots(1, 2, figsize=(16, 5))

# Youth updates by month
colors = ['#e74c3c' if m in [4, 5, 6] else '#3498db' for m in monthly_age_br
bars = axes[0].bar(monthly_age_breakdown['month_name'], monthly_age_breakdown
axes[0].set_xlabel('Month')
axes[0].set_ylabel('Youth Biometric Updates')
axes[0].set_title('Youth (5-17) Updates by Month\n(Red = School Admission Period)')
axes[0].tick_params(axis='x', rotation=45)

# Youth percentage trend
axes[1].plot(monthly_age_breakdown['month_name'], monthly_age_breakdown['youth_pct'],
             marker='o', linewidth=2, markersize=8, color='#9b59b6')
axes[1].fill_between(monthly_age_breakdown['month_name'], monthly_age_breakdown['youth_pct'],
                    color='red', alpha=0.1)
axes[1].axhline(y=national_youth_pct, color='red', linestyle='--', label=f'National Avg: {national_youth_pct}%')
axes[1].set_xlabel('Month')
axes[1].set_ylabel('Youth as % of Total Updates')
axes[1].set_title('Youth Update Share Trend Across Months', fontweight='bold')
axes[1].tick_params(axis='x', rotation=45)
```

```

axes[1].legend()



plt.tight_layout()
plt.show()

# Identify peak youth update months
peak_months = monthly_age_breakdown.nlargest(3, 'bio_age_5_17')['month_name']
print(f"\n📊 Peak Youth Update Months: {'', '.join(peak_months)}")

print("\n" + "=" * 80)
print("💡 RECOMMENDATION: School-Integrated Biometric Update Program")
print("=" * 80)
print("""
PROBLEM IDENTIFIED:
    - Youth updates don't strongly correlate with school calendar
    - Many children may be missing mandatory 5-year biometric updates
    - States with low youth ratios need targeted intervention

PROPOSED SOLUTIONS:
    1. SCHOOL CAMPS: Partner with education departments for in-school update c
    2. MID-DAY MEAL LINKAGE: Integrate biometric updates with MDM beneficiary
    3. ADMISSION REQUIREMENT: Coordinate with school admission cycles (Apr-Jun
    4. PARENT NOTIFICATION: SMS alerts to parents for children nearing 5-year
    5. PRIORITY QUEUES: Dedicated youth counters at enrolment centers during s
""")

```



📊 Peak Youth Update Months: Dec, Jul, Apr

```
=====
=====
💡 RECOMMENDATION: School-Integrated Biometric Update Program
=====
=====
```

PROBLEM IDENTIFIED:

- Youth updates don't strongly correlate with school calendar
- Many children may be missing mandatory 5-year biometric updates
- States with low youth ratios need targeted intervention

PROPOSED SOLUTIONS:

1. SCHOOL CAMPS: Partner with education departments for in-school update drives
2. MID-DAY MEAL LINKAGE: Integrate biometric updates with MDM beneficiary verification
3. ADMISSION REQUIREMENT: Coordinate with school admission cycles (Apr-Jun)
4. PARENT NOTIFICATION: SMS alerts to parents for children nearing 5-year update deadline
5. PRIORITY QUEUES: Dedicated youth counters at enrolment centers during school vacations

🔍 Part 4: Anomaly Detection & Data Quality Indicators

Objective: Identify potential fraud indicators, data quality issues, and suspicious patterns that could indicate system vulnerabilities or operational problems.

Analysis Focus:

- Statistical outliers in biometric update volumes
- Pincode-level anomalies (potential duplicate/fraudulent entries)
- Unusual age distribution patterns
- Day-over-day volatility indicating system issues

In [51]: *# 4.1 Pincode-Level Anomaly Detection – Identifying Suspicious Patterns
Using IQR and Z-score methods to find outliers*

```
pincode_stats = df.groupby('pincode').agg(
    total_updates=('total_bio_updates', 'sum'),
    bio_age_5_17=('bio_age_5_17', 'sum'),
    bio_age_17_=('bio_age_17_', 'sum'),
    days_active=('date', 'nunique'), # Days with activity
    district=('district', 'first'),
    state=('state', 'first')
).reset_index()
```

```

pincode_stats['avg_daily_updates'] = pincode_stats['total_updates'] / pincode_stats['population']
pincode_stats['youth_ratio'] = pincode_stats['bio_age_5_17'] / pincode_stats['population']

# IQR-based outlier detection for daily updates
Q1 = pincode_stats['avg_daily_updates'].quantile(0.25)
Q3 = pincode_stats['avg_daily_updates'].quantile(0.75)
IQR = Q3 - Q1
lower_bound = Q1 - 1.5 * IQR
upper_bound = Q3 + 1.5 * IQR

pincode_stats['is_outlier'] = (pincode_stats['avg_daily_updates'] < lower_bound) | (pincode_stats['avg_daily_updates'] > upper_bound)
pincode_stats['outlier_type'] = pincode_stats.apply(
    lambda x: 'HIGH' if x['avg_daily_updates'] > upper_bound else ('LOW' if x['avg_daily_updates'] < lower_bound else 'NORMAL'),
    axis=1
)

# Z-score for extreme outliers
pincode_stats['z_score'] = stats.zscore(pincode_stats['avg_daily_updates'])
pincode_stats['extreme_outlier'] = abs(pincode_stats['z_score']) > 3

# Visualization
fig, axes = plt.subplots(2, 2, figsize=(16, 12))

# 1. Distribution with outlier bounds
axes[0, 0].hist(pincode_stats['avg_daily_updates'], bins=100, edgecolor='black')
axes[0, 0].axvline(x=upper_bound, color='red', linestyle='--', linewidth=2)
axes[0, 0].axvline(x=lower_bound, color='orange', linestyle='--', linewidth=2)
axes[0, 0].set_xlabel('Avg Daily Updates per Pincode')
axes[0, 0].set_ylabel('Frequency')
axes[0, 0].set_title('📊 Distribution of Daily Updates with Outlier Thresholds')
axes[0, 0].legend()
axes[0, 0].set_xlim(0, pincode_stats['avg_daily_updates'].quantile(0.95))

# 2. High-volume anomalies by state
high_outliers = pincode_stats[pincode_stats['outlier_type'] == 'HIGH']
state_outliers = high_outliers.groupby('state').size().sort_values(ascending=False)
colors = plt.cm.Reds(np.linspace(0.3, 0.9, len(state_outliers)))
state_outliers.plot(kind='barh', ax=axes[0, 1], color=colors, edgecolor='black')
axes[0, 1].set_xlabel('Number of High-Volume Outlier Pincodes')
axes[0, 1].set_title('📍 States with Most High-Volume Anomalies\n(Potential for Abuse)')

# 3. Extreme outliers scatter plot
extreme = pincode_stats[pincode_stats['extreme_outlier']]
normal = pincode_stats[~pincode_stats['extreme_outlier']]
axes[1, 0].scatter(normal['total_updates'], normal['youth_ratio'], alpha=0.3)
axes[1, 0].scatter(extreme['total_updates'], extreme['youth_ratio'], alpha=0.3)
axes[1, 0].set_xlabel('Total Updates')
axes[1, 0].set_ylabel('Youth Ratio (%)')
axes[1, 0].set_title('🔴 Extreme Outliers: Volume vs Youth Ratio\n(Red points are outliers)')
axes[1, 0].legend()

# 4. Outlier summary
outlier_counts = pincode_stats['outlier_type'].value_counts()
# Dynamically set colors and explode based on actual number of categories
color_map = {'NORMAL': '#27ae60', 'HIGH': '#e74c3c', 'LOW': '#f39c12'}
explode_map = {'NORMAL': 0, 'HIGH': 0.1, 'LOW': 0.05}

```

```

pie_colors = [color_map.get(label, '#95a5a6') for label in outlier_counts.index]
pie_explode = [explode_map.get(label, 0) for label in outlier_counts.index]
wedges, texts, autotexts = axes[1, 1].pie(outlier_counts, labels=outlier_counts.index, autopct='%1.1f%%',
axes[1, 1].set_title('📊 Pincode Classification by Update Volume', fontweight='bold')

# plt.tight_layout()
# plt.show()

# Print detailed findings
print("\n" + "=" * 80)
print("ANOMALY DETECTION SUMMARY")
print("=" * 80)
print(f"\nTotal Pincodes Analyzed: {len(pincodes_stats):,}")
print(f"High-Volume Outliers: {len(high_outliers):,} ({len(high_outliers)/len(pincodes_stats):.1%})")
print(f"Extreme Outliers (|Z|>3): {len(extreme):,} ({len(extreme)/len(pincodes_stats):.1%})")

print("\nTOP 10 SUSPICIOUS HIGH-VOLUME PINCODES (Require Investigation):")
print("-" * 70)
top_suspicious = pincodes_stats[pincodes_stats['extreme_outlier']].nlargest(10, 'avg_daily_updates')
for _, row in top_suspicious.iterrows():
    print(f"Pincode: {row['pincode']} | {row['district']}, {row['state']}")
    print(f"    Avg Daily: {row['avg_daily_updates']:.0f} | Z-Score: {row['z_score']:.1f} | Youth%: {row['youth_percent']:.1%}")

```

```

=====
====
ANOMALY DETECTION SUMMARY
=====
=====

```


Total Pincodes Analyzed: 19,707
High-Volume Outliers: 1,455 (7.4%)
Extreme Outliers (|Z|>3): 392 (1.99%)

TOP 10 SUSPICIOUS HIGH-VOLUME PINCODES (Require Investigation):

```

-----
Pincode: 431001 | Chatrapati Sambhaji Nagar, Maharashtra
    Avg Daily: 959 | Z-Score: 16.5 | Youth%: 33.7%
Pincode: 110094 | North West Delhi, Delhi
    Avg Daily: 895 | Z-Score: 15.3 | Youth%: 40.4%
Pincode: 244001 | Sambhal, Uttar Pradesh
    Avg Daily: 886 | Z-Score: 15.2 | Youth%: 58.7%
Pincode: 110086 | North West Delhi, Delhi
    Avg Daily: 797 | Z-Score: 13.6 | Youth%: 40.1%
Pincode: 247001 | Saharanpur, Uttar Pradesh
    Avg Daily: 731 | Z-Score: 12.4 | Youth%: 51.8%
Pincode: 202001 | Aligarh, Uttar Pradesh
    Avg Daily: 711 | Z-Score: 12.0 | Youth%: 63.2%
Pincode: 110059 | West Delhi, Delhi
    Avg Daily: 696 | Z-Score: 11.7 | Youth%: 42.6%
Pincode: 110053 | North East Delhi, Delhi
    Avg Daily: 690 | Z-Score: 11.6 | Youth%: 38.4%
Pincode: 423203 | Nashik, Maharashtra
    Avg Daily: 688 | Z-Score: 11.6 | Youth%: 48.7%
Pincode: 421302 | Thane, Maharashtra
    Avg Daily: 641 | Z-Score: 10.7 | Youth%: 35.9%

```



```
In [52]: # 4.2 Temporal Anomalies - Detecting Unusual Spikes/Drops
# Identify days with abnormal activity that could indicate system issues or

daily_totals = df.groupby('date')['total_bio_updates'].sum().reset_index()
daily_totals.columns = ['date', 'total_updates'] # Rename column for clarity
daily_totals['rolling_avg_7d'] = daily_totals['total_updates'].rolling(window=7).mean()
daily_totals['rolling_std_7d'] = daily_totals['total_updates'].rolling(window=7).std()

# Identify anomalies (>2 std from rolling mean)
daily_totals['deviation'] = (daily_totals['total_updates'] - daily_totals['rolling_avg_7d']) / daily_totals['rolling_std_7d']
daily_totals['is_anomaly'] = abs(daily_totals['deviation']) > 2
daily_totals['anomaly_type'] = daily_totals.apply(
    lambda x: 'SPIKE' if x['deviation'] > 2 else ('DROP' if x['deviation'] < -2 else 'NORMAL'),
    axis=1
)

# Visualization
fig, axes = plt.subplots(2, 1, figsize=(16, 10))

# Time series with anomalies highlighted
anomaly_dates = daily_totals[daily_totals['is_anomaly']]
spike_dates = daily_totals[daily_totals['anomaly_type'] == 'SPIKE']
drop_dates = daily_totals[daily_totals['anomaly_type'] == 'DROP']

axes[0].plot(daily_totals['date'], daily_totals['total_updates'], alpha=0.7, color='blue')
axes[0].plot(daily_totals['date'], daily_totals['rolling_avg_7d'], color='red', lw=2)
axes[0].scatter(spike_dates['date'], spike_dates['total_updates'], color='red', s=100)
axes[0].scatter(drop_dates['date'], drop_dates['total_updates'], color='green', s=100)
```

```

axes[0].scatter(drop_dates['date'], drop_dates['total_updates'], color='#9b59b6')
axes[0].set_xlabel('Date')
axes[0].set_ylabel('Total Daily Updates')
axes[0].set_title('📊 Daily Biometric Updates with Anomaly Detection\n(Spike Detection & Drop Analysis)')
axes[0].legend()
axes[0].tick_params(axis='x', rotation=45)

# Deviation plot
axes[1].bar(daily_totals['date'], daily_totals['deviation'],
            color=['#e74c3c' if abs(d) > 2 else '#3498db' for d in daily_totals['deviation']])
axes[1].axhline(y=2, color='red', linestyle='--', label='Upper Threshold (+2σ)')
axes[1].axhline(y=-2, color='red', linestyle='--', label='Lower Threshold (-2σ)')
axes[1].set_xlabel('Date')
axes[1].set_ylabel('Standard Deviations from Mean')
axes[1].set_title('📊 Deviation from Expected (Red = Anomaly)', fontweight='bold')
axes[1].legend()
axes[1].tick_params(axis='x', rotation=45)

plt.tight_layout()
plt.show()

# Analyze anomaly patterns
print("\n" + "=" * 80)
print("TEMPORAL ANOMALY ANALYSIS")
print("=" * 80)
print(f"\nTotal Days Analyzed: {len(daily_totals)}")
print(f"Unusual Spikes Detected: {len(spike_dates)}")
print(f"Unusual Drops Detected: {len(drop_dates)}")



if len(spike_dates) > 0:
    print("\nTOP SPIKE DAYS (Potential rush/backlog processing):")
    for _, row in spike_dates.nlargest(5, 'total_updates').iterrows():
        print(f"📅 {row['date'].strftime('%Y-%m-%d')} | 📈 {row['total_updates']} updates")

if len(drop_dates) > 0:
    print("\nTOP DROP DAYS (Potential system issues/holidays):")
    for _, row in drop_dates.nsmallest(5, 'total_updates').iterrows():
        print(f"📅 {row['date'].strftime('%Y-%m-%d')} | 📉 {row['total_updates']} updates")

print("\n" + "=" * 80)
print("💡 RECOMMENDATION: Anomaly Response Protocol")
print("=" * 80)
print("""
ISSUES IDENTIFIED:
    - Spikes may indicate backlog processing, data upload delays, or bulk fraud attempts.
    - Drops may indicate system outages, network issues, or holiday closures.

PROPOSED SOLUTIONS:
    1. REAL-TIME MONITORING: Implement automated alerts when daily volume exceeds 3σ deviation.
    2. ROOT CAUSE ANALYSIS: Mandatory investigation for anomalies exceeding 3σ.
    3. FRAUD DETECTION: Cross-reference spike days with specific center/operational hours.
    4. CAPACITY PLANNING: Predict and pre-allocate resources for known high-volume periods.
    5. SYSTEM HEALTH DASHBOARD: Track uptime correlation with update volumes.
""")

```



```
=====
====
TEMPORAL ANOMALY ANALYSIS
=====
=====
```

Total Days Analyzed: 89
Unusual Spikes Detected: 0
Unusual Drops Detected: 3

TOP DROP DAYS (Potential system issues/holidays):
2025-10-13 (Monday): 3,378 updates (-2.0σ)
2025-09-14 (Sunday): 51,409 updates (-2.1σ)
2025-11-09 (Sunday): 231,988 updates (-2.1σ)

```
=====
====
💡 RECOMMENDATION: Anomaly Response Protocol
=====
=====
```

ISSUES IDENTIFIED:

- Spikes may indicate backlog processing, data upload delays, or bulk fraud attempts
- Drops may indicate system outages, network issues, or holiday closures not synced

PROPOSED SOLUTIONS:

1. REAL-TIME MONITORING: Implement automated alerts when daily volume exceeds $\pm 2\sigma$
2. ROOT CAUSE ANALYSIS: Mandatory investigation for anomalies exceeding 3σ
3. FRAUD DETECTION: Cross-reference spike days with specific center/operator activity
4. CAPACITY PLANNING: Predict and pre-allocate resources for known high-volume periods
5. SYSTEM HEALTH DASHBOARD: Track uptime correlation with update volumes

```
In [53]: # 4.3 Age Distribution Anomalies - Potential Data Quality Issues
# Check for unusual youth-to-adult ratios that might indicate data entry errors

district_age_analysis = df.groupby(['state', 'district']).agg({
    'bio_age_5_17': 'sum',
    'bio_age_17_': 'sum',
    'total_bio_updates': 'sum'
}).reset_index()

district_age_analysis['youth_pct'] = district_age_analysis['bio_age_5_17'] /
district_age_analysis['adult_pct'] = district_age_analysis['bio_age_17_'] /
# Flag unusual ratios (youth should typically be 10-40% of updates)
district_age_analysis['ratio_flag'] = district_age_analysis.apply(
    lambda x: 'UNUSUAL_HIGH_YOUTH' if x['youth_pct'] > 50 else
              ('UNUSUAL_LOW_YOUTH' if x['youth_pct'] < 5 and x['total_bio_updates'] > 100000 else 'OK'),
    axis=1
)
```

```

# Visualization
fig, axes = plt.subplots(1, 3, figsize=(18, 5))

# Youth percentage distribution
axes[0].hist(district_age_analysis['youth_pct'], bins=50, edgecolor='black',
axes[0].axvline(x=5, color='orange', linestyle='--', linewidth=2, label='Low
axes[0].axvline(x=50, color='red', linestyle='--', linewidth=2, label='High
axes[0].set_xlabel('Youth Percentage')
axes[0].set_ylabel('Number of Districts')
axes[0].set_title('📊 Youth % Distribution Across Districts', fontweight='bo
axes[0].legend()

# Scatter of youth vs adult with flags
colors = {'NORMAL': '#3498db', 'UNUSUAL_HIGH_YOUTH': '#e74c3c', 'UNUSUAL_LOW
for flag, color in colors.items():
    subset = district_age_analysis[district_age_analysis['ratio_flag'] == fl
    axes[1].scatter(subset['bio_age_17_'], subset['bio_age_5_17'],
                    alpha=0.6, color=color, label=flag, s=30)
axes[1].set_xlabel('Adult Updates (17+)')
axes[1].set_ylabel('Youth Updates (5-17)')
axes[1].set_title('Youth vs Adult Updates by District\n(Colored by Anomaly F
axes[1].legend()

# Flag distribution
flag_counts = district_age_analysis['ratio_flag'].value_counts()
wedges, texts, autotexts = axes[2].pie(flag_counts, labels=flag_counts.index
    colors=['#27ae60', '#e74c3c', '#f39c12'], explode=[0, 0.1, 0.05])
axes[2].set_title('📊 District Classification by Age Ratio', fontweight='bo

plt.tight_layout()
plt.show()


# Detailed findings
unusual_high = district_age_analysis[district_age_analysis['ratio_flag'] ==
unusual_low = district_age_analysis[district_age_analysis['ratio_flag'] == '

print("\n" + "=" * 80)
print("AGE DISTRIBUTION ANOMALY ANALYSIS")
print("=" * 80)
print(f"\nDistricts with Unusually HIGH Youth Ratio (>50%): {len(unusual_high)}")
print(f"Districts with Unusually LOW Youth Ratio (<5%): {len(unusual_low)}")

if len(unusual_high) > 0:
    print("\n TOP UNUSUAL HIGH-YOUTH DISTRICTS (Potential data issues or sch
    for _, row in unusual_high.nlargest(5, 'total_bio_updates').iterrows():
        print(f" {row['district']}, {row['state']}: {row['youth_pct']:.1f}%

if len(unusual_low) > 0:
    print("\n TOP UNUSUAL LOW-YOUTH DISTRICTS (Youth underserved or demograp
    for _, row in unusual_low.nlargest(5, 'total_bio_updates').iterrows():
        print(f" {row['district']}, {row['state']}: {row['youth_pct']:.1f}%

```



AGE DISTRIBUTION ANOMALY ANALYSIS

Districts with Unusually HIGH Youth Ratio (>50%): 422
 Districts with Unusually LOW Youth Ratio (<5%): 3

TOP UNUSUAL HIGH-YOUTH DISTRICTS (Potential data issues or school-focused centers):

Kurnool, Andhra Pradesh: 69.3% youth (350,633 total)
 Visakhapatnam, Andhra Pradesh: 62.8% youth (311,303 total)
 East Godavari, Andhra Pradesh: 67.9% youth (301,850 total)
 Guntur, Andhra Pradesh: 64.3% youth (291,694 total)
 Sitapur, Uttar Pradesh: 75.8% youth (264,311 total)

TOP UNUSUAL LOW-YOUTH DISTRICTS (Youth underserved or demographic anomaly):

Nawanshahr, Punjab: 4.3% youth (4,189 total)
 Nandurbar *, Maharashtra: 1.0% youth (1,645 total)
 Gondiya *, Maharashtra: 4.8% youth (1,408 total)

🔮 Part 5: Predictive Insights & Future Trend Analysis

Objective: Use historical patterns to predict future demand, identify growth trajectories, and provide capacity planning recommendations.

Analysis Focus:

- Month-over-month growth trends
- State-level demand forecasting indicators
- Seasonal pattern identification for resource planning

In [54]: *# 5.1 Growth Trajectory Analysis – Month-over-Month Trends*

```
monthly_trends = df.groupby(['year', 'month']).agg({
    'total_bio_updates': 'sum',
    'bio_age_5_17': 'sum',
    'bio_age_17_': 'sum'
}).reset_index()
```

```

monthly_trends['date_str'] = monthly_trends.apply(lambda x: f"{int(x['year'])}{int(x['month'])}", axis=1)
monthly_trends = monthly_trends.sort_values(['year', 'month'])

# Calculate month-over-month growth
monthly_trends['mom_growth'] = monthly_trends['total_bio_updates'].pct_change()
monthly_trends['cumulative'] = monthly_trends['total_bio_updates'].cumsum()

# Calculate moving averages for trend
monthly_trends['ma_3m'] = monthly_trends['total_bio_updates'].rolling(window=3).mean()

fig, axes = plt.subplots(2, 2, figsize=(16, 10))

# 1. Monthly volume with trend
axes[0, 0].bar(range(len(monthly_trends)), monthly_trends['total_bio_updates'])
axes[0, 0].plot(range(len(monthly_trends)), monthly_trends['ma_3m'], color='red')
axes[0, 0].set_xticks(range(len(monthly_trends)))
axes[0, 0].set_xticklabels(monthly_trends['date_str'], rotation=45, ha='right')
axes[0, 0].set_xlabel('Month')
axes[0, 0].set_ylabel('Total Updates')
axes[0, 0].set_title('📊 Monthly Biometric Updates with Trend Line', fontweight='bold')
axes[0, 0].legend()

# 2. Month-over-month growth rate
colors = ['#27ae60' if x > 0 else '#e74c3c' for x in monthly_trends['mom_growth']]
axes[0, 1].bar(range(len(monthly_trends)), monthly_trends['mom_growth'], fill=colors)
axes[0, 1].axhline(y=0, color='black', linewidth=1)
axes[0, 1].set_xticks(range(len(monthly_trends)))
axes[0, 1].set_xticklabels(monthly_trends['date_str'], rotation=45, ha='right')
axes[0, 1].set_xlabel('Month')
axes[0, 1].set_ylabel('Growth Rate (%)')
axes[0, 1].set_title('📈 Month-over-Month Growth Rate\n(Green = Growth, Red = Decline)', fontweight='bold')

# 3. Cumulative growth
axes[1, 0].fill_between(range(len(monthly_trends)), monthly_trends['cumulative'], color='red')
axes[1, 0].plot(range(len(monthly_trends)), monthly_trends['cumulative'], color='red')
axes[1, 0].set_xticks(range(len(monthly_trends)))
axes[1, 0].set_xticklabels(monthly_trends['date_str'], rotation=45, ha='right')
axes[1, 0].set_xlabel('Month')
axes[1, 0].set_ylabel('Cumulative Updates')
axes[1, 0].set_title('📈 Cumulative Biometric Updates Over Time', fontweight='bold')

# 4. Youth vs Adult trend comparison
axes[1, 1].plot(range(len(monthly_trends)), monthly_trends['bio_age_5_17'], color='blue')
axes[1, 1].plot(range(len(monthly_trends)), monthly_trends['bio_age_17_'], color='red')
axes[1, 1].set_xticks(range(len(monthly_trends)))
axes[1, 1].set_xticklabels(monthly_trends['date_str'], rotation=45, ha='right')
axes[1, 1].set_xlabel('Month')
axes[1, 1].set_ylabel('Updates')
axes[1, 1].set_title('👤 Youth vs Adult Update Trends', fontweight='bold')
axes[1, 1].legend()

plt.tight_layout()
plt.show()

# Statistical analysis
avg_monthly = monthly_trends['total_bio_updates'].mean()


```

```

peak_month = monthly_trends.loc[monthly_trends['total_bio_updates'].idxmax()]
low_month = monthly_trends.loc[monthly_trends['total_bio_updates'].idxmin()]
avg_growth = monthly_trends['mom_growth'].mean()

print("\n" + "=" * 80)
print("GROWTH TRAJECTORY SUMMARY")
print("=" * 80)
print(f"\n Average Monthly Updates: {avg_monthly:,.0f}")
print(f"Peak Month: {peak_month['date_str']} with {peak_month['total_bio_updates']}")
print(f"Lowest Month: {low_month['date_str']} with {low_month['total_bio_updates']}")
print(f" Average MoM Growth: {avg_growth:.1f}%")
print(f"Total Updates in Dataset: {monthly_trends['total_bio_updates'].sum()}")

```



GROWTH TRAJECTORY SUMMARY

Average Monthly Updates: 7,751,455
 Peak Month: 2025-07 with 9,792,552 updates
 Lowest Month: 2025-10 with 4,582,655 updates
 Average MoM Growth: 4.3%
 Total Updates in Dataset: 69,763,095

In [55]: # 5.2 State-Level Growth Projections & Demand Forecasting

```

# Calculate state-level growth metrics
state_monthly = df.groupby(['state', 'year', 'month'])['total_bio_updates'].
state_monthly = state_monthly.sort_values(['state', 'year', 'month'])

# Calculate growth rate per state
def calculate_state_growth(group):
    if len(group) < 2:

```

```

        return pd.Series({
            'avg_monthly_volume': group['total_bio_updates'].mean(),
            'total_volume': group['total_bio_updates'].sum(),
            'avg_growth': 0,
            'volatility': 0,
            'trend': 'STABLE'
        })

    growth_rates = group['total_bio_updates'].pct_change().dropna() * 100
    avg_growth = growth_rates.mean() if len(growth_rates) > 0 else 0
    volatility = growth_rates.std() if len(growth_rates) > 0 else 0

    # Determine trend
    if avg_growth > 10:
        trend = 'GROWING'
    elif avg_growth < -10:
        trend = 'DECLINING'
    else:
        trend = 'STABLE'

    return pd.Series({
        'avg_monthly_volume': group['total_bio_updates'].mean(),
        'total_volume': group['total_bio_updates'].sum(),
        'avg_growth': avg_growth,
        'volatility': volatility,
        'trend': trend
    })

state_growth = state_monthly.groupby('state', group_keys=False).apply(calculate_state_growth)

# Visualization
fig, axes = plt.subplots(2, 2, figsize=(16, 12))

# 1. State growth vs volatility scatter
trend_colors = {'GROWING': '#27ae60', 'DECLINING': '#e74c3c', 'STABLE': '#34495e'}
for trend, color in trend_colors.items():
    subset = state_growth[state_growth['trend'] == trend]
    if len(subset) > 0:
        axes[0, 0].scatter(subset['avg_growth'], subset['volatility'],
                           color=color, label=trend, s=subset['total_volume'])
axes[0, 0].axvline(x=0, color='gray', linestyle='--', alpha=0.5)
axes[0, 0].axhline(y=state_growth['volatility'].median(), color='gray', linestyle='--', alpha=0.5)
axes[0, 0].set_xlabel('Average Growth Rate (%)')
axes[0, 0].set_ylabel('Volatility (Std Dev)')
axes[0, 0].set_title('📊 State Growth Rate vs Volatility\n(Size = Total Volume)')
axes[0, 0].legend()

# 2. Top growing states
growing = state_growth[state_growth['avg_growth'] > 0].nlargest(10, 'avg_growth')
if len(growing) > 0:
    colors = plt.cm.Greens(np.linspace(0.3, 0.9, len(growing)))
    growing_sorted = growing.sort_values('avg_growth')
    axes[0, 1].barh(growing_sorted['state'], growing_sorted['avg_growth'], color=colors)
axes[0, 1].set_xlabel('Average Monthly Growth Rate (%)')
axes[0, 1].set_title('🚀 Top 10 Fastest Growing States\n(Highest Avg Monthly Growth Rate)')

```

```

# 3. States needing attention (declining or high volatility)
attention_needed = state_growth[(state_growth['avg_growth'] < 0) | (state_growth['total_volume'] > 1000000)]
attention_needed = attention_needed.nlargest(10, 'total_volume')
if len(attention_needed) > 0:
    colors = ['#e74c3c' if x < 0 else '#f39c12' for x in attention_needed['avg_growth']]
    axes[1, 0].barh(attention_needed['state'], attention_needed['avg_growth'], color=colors)
    axes[1, 0].axvline(x=0, color='black', linewidth=1)
    axes[1, 0].set_xlabel('Average Growth Rate (%)')
    axes[1, 0].set_title('⚠ States Needing Attention\n(Declining Growth or High Volatility)')

# 4. Trend distribution
trend_counts = state_growth['trend'].value_counts()
pie_colors = ['#27ae60', '#e74c3c', '#3498db'][:len(trend_counts)]
pie_explode = [0.05, 0.1, 0][:len(trend_counts)]
wedges, texts, autotexts = axes[1, 1].pie(trend_counts, labels=trend_counts.index, colors=pie_colors, explode=pie_explode)
axes[1, 1].set_title('📊 State Trend Distribution', fontweight='bold')

plt.tight_layout()
plt.show()

# Detailed forecasting insights
print("\n" + "=" * 80)
print("🔮 DEMAND FORECASTING INSIGHTS")
print("=" * 80)

print(f"\n📈 States with GROWING Trend: {len(state_growth[state_growth['trend'] == 'growing'])}")
print(f"\n📉 States with DECLINING Trend: {len(state_growth[state_growth['trend'] == 'declining'])}")
print(f"\n➡ States with STABLE Trend: {len(state_growth[state_growth['trend'] == 'stable'])}")

print("\n🚀 TOP 5 HIGHEST GROWTH STATES (Priority for capacity expansion):")
for _, row in state_growth.nlargest(5, 'avg_growth').iterrows():
    print(f"📍 {row['state']}: {row['avg_growth']:.1f}% avg monthly growth | 📊 {row['total_volume']:.1f} units")

print("\n⚠ TOP 5 DECLINING STATES (Investigate barriers to access):")
for _, row in state_growth.nsmallest(5, 'avg_growth').iterrows():
    print(f"📍 {row['state']}: {row['avg_growth']:.1f}% avg monthly growth | 📊 {row['total_volume']:.1f} units")

print("\n" + "=" * 80)
print("RECOMMENDATION: Capacity Planning Framework")
print("=" * 80)
print("""
PREDICTIVE INSIGHTS FOR UIDAI PLANNING:

1. GROWING STATES – Capacity Expansion Priority:
   - Add more enrolment centers in high-growth states
   - Pre-position mobile units for anticipated demand surge
   - Increase operator training and certification in these regions

2. DECLINING STATES – Access Investigation:
   - Survey population to understand barriers (distance, awareness, trust)
   - Partner with state governments for awareness campaigns
   - Check if center closures/relocations caused the decline

3. HIGH VOLATILITY STATES – Demand Smoothing:
   - Implement appointment-based systems to reduce unpredictable spikes


```

- Analyze root causes of volatility (seasonal, event-driven)
- Create buffer capacity for handling sudden demand surges

4. SEASONAL PLANNING:

- Use monthly patterns to predict peak periods
- Deploy additional temporary staff during high-demand months
- Coordinate with schools for youth update drives in off-peak periods

))))



DEMAND FORECASTING INSIGHTS

- States with GROWING Trend: 22
- States with DECLINING Trend: 3
- States with STABLE Trend: 32

TOP 5 HIGHEST GROWTH STATES (Priority for capacity expansion):

odisha: +122.2% avg monthly growth | Vol: 16
Manipur: +78.9% avg monthly growth | Vol: 282,587
WESTBENGAL: +76.7% avg monthly growth | Vol: 12
Chandigarh: +56.3% avg monthly growth | Vol: 74,482
Chhatisgarh: +50.0% avg monthly growth | Vol: 5

TOP 5 DECLINING STATES (Investigate barriers to access):

WEST BENGAL: -26.7% avg monthly growth | Vol: 37
andhra pradesh: -17.7% avg monthly growth | Vol: 41
Mizoram: -17.5% avg monthly growth | Vol: 120,329
Sikkim: -9.2% avg monthly growth | Vol: 22,820
Meghalaya: -6.2% avg monthly growth | Vol: 87,626

RECOMMENDATION: Capacity Planning Framework

PREDICTIVE INSIGHTS FOR UIDAI PLANNING:

- GROWING STATES – Capacity Expansion Priority:**
 - Add more enrolment centers in high-growth states
 - Pre-position mobile units for anticipated demand surge
 - Increase operator training and certification in these regions
- DECLINING STATES – Access Investigation:**
 - Survey population to understand barriers (distance, awareness, trust)
 - Partner with state governments for awareness campaigns
 - Check if center closures/relocations caused the decline
- HIGH VOLATILITY STATES – Demand Smoothing:**
 - Implement appointment-based systems to reduce unpredictable spikes
 - Analyze root causes of volatility (seasonal, event-driven)
 - Create buffer capacity for handling sudden demand surges
- SEASONAL PLANNING:**
 - Use monthly patterns to predict peak periods
 - Deploy additional temporary staff during high-demand months
 - Coordinate with schools for youth update drives in off-peak periods

Part 6: Privacy-by-Design & System Improvement Recommendations

Objective: Based on data patterns, identify privacy vulnerabilities and propose privacy-preserving improvements to the Aadhaar ecosystem.

Analysis Focus:

- Data concentration risks (single points of failure)
- Geographic coverage gaps that force privacy-compromising alternatives
- Recommendations for decentralized architecture
- Offline authentication capability assessment

```
In [56]: # 6.1 Data Concentration Risk Analysis
# Identify regions with high data concentration that create single points of failure

# Calculate concentration metrics
state_concentration = df.groupby('state').agg({
    'total_bio_updates': 'sum',
    'pincode': 'nunique',
    'district': 'nunique'
}).reset_index()

state_concentration['updates_per_pincode'] = state_concentration['total_bio_updates'] / state_concentration['pincode']
state_concentration['updates_per_district'] = state_concentration['total_bio_updates'] / state_concentration['district']
state_concentration['concentration_score'] = (state_concentration['updates_per_pincode'] * state_concentration['updates_per_district'])

# High concentration = higher privacy risk (more data in fewer locations)
total_updates = state_concentration['total_bio_updates'].sum()
state_concentration['data_share_pct'] = state_concentration['total_bio_updates'] / total_updates

# Pareto analysis - what % of states hold what % of data
state_concentration_sorted = state_concentration.sort_values('total_bio_updates', ascending=False)
state_concentration_sorted['cumulative_share'] = state_concentration_sorted['total_bio_updates'].cumsum() / total_updates

# Visualization
fig, axes = plt.subplots(2, 2, figsize=(16, 12))

# 1. Data concentration by state (Pareto chart)
ax1_bar = axes[0, 0].bar(range(len(state_concentration_sorted)),
                        state_concentration_sorted['data_share_pct'],
                        color='#3498db', alpha=0.7, label='State Share')
ax1_line = axes[0, 0].twinx()
ax1_line.plot(range(len(state_concentration_sorted)),
              state_concentration_sorted['cumulative_share'],
              color='#e74c3c', linewidth=2, marker='o', markersize=4, label='Cumulative Share')
ax1_line.axhline(y=80, color='orange', linestyle='--', label='80% threshold')
axes[0, 0].set_xticks(range(0, len(state_concentration_sorted), 2))
axes[0, 0].set_xticklabels(state_concentration_sorted['state'].iloc[::2], rotation=45)
axes[0, 0].set_xlabel('State')
axes[0, 0].set_ylabel('Share of Total Data (%)')
ax1_line.set_ylabel('Cumulative Share (%)')
axes[0, 0].set_title('Data Concentration by State (Pareto Analysis)\n80% threshold line')
```

```

# 2. Updates per pincode distribution (concentration metric)
axes[0, 1].hist(state_concentration['updates_per_pincode'], bins=20, edgecolor='black')
axes[0, 1].axvline(x=state_concentration['updates_per_pincode'].median(), color='red',
                  label=f'Median: {state_concentration["updates_per_pincode"].median():.0f}')
axes[0, 1].set_xlabel('Avg Updates per Pincode')
axes[0, 1].set_ylabel('Number of States')
axes[0, 1].set_title('📊 Data Density Distribution\n(Higher = More Concentration)')
axes[0, 1].legend()

# 3. High concentration states (potential privacy hotspots)
high_concentration = state_concentration.nlargest(15, 'updates_per_pincode')
colors = plt.cm.Reds(np.linspace(0.3, 0.9, len(high_concentration)))
high_concentration_sorted = high_concentration.sort_values('updates_per_pincode')
axes[1, 0].barh(high_concentration_sorted['state'], high_concentration_sorted['updates_per_pincode'],
                color=colors, edgecolor='black')
axes[1, 0].set_xlabel('Average Updates per Pincode')
axes[1, 0].set_title('📊 Highest Data Concentration States\n(More data per location)')

# 4. Risk matrix: Volume vs Concentration
axes[1, 1].scatter(state_concentration['total_bio_updates'] / 1e6,
                  state_concentration['concentration_score'],
                  s=state_concentration['pincode'] * 0.5,
                  alpha=0.6, c=state_concentration['concentration_score'],
                  edgecolor='black')
axes[1, 1].set_xlabel('Total Updates (Millions)')
axes[1, 1].set_ylabel('Concentration Score (0-1)')
axes[1, 1].set_title('🔍 Privacy Risk Matrix\n(Size = Unique Pincodes, Color = Risk Level)')

# Add state labels for high-risk quadrant
high_risk = state_concentration[(state_concentration['concentration_score'] > 0.5) &
                                (state_concentration['total_bio_updates'] / 1e6 > 10)]
for _, row in high_risk.iterrows():
    axes[1, 1].annotate(row['state'], (row['total_bio_updates']/1e6, row['concentration_score']),
                        xytext=(15, 0.9), textcoords='point', align='left',
                        fontweight='bold', color='white')


plt.tight_layout()
plt.show()

# Calculate key metrics
states_for_80pct = (state_concentration_sorted['cumulative_share'] <= 80).sum()

print("\n" + "=" * 80)
print("🔒 DATA CONCENTRATION & PRIVACY RISK ANALYSIS")
print("=" * 80)
print(f"\n📊 Total States/UTs in Dataset: {len(state_concentration)}")
print(f"📊 States holding 80% of biometric data: {states_for_80pct}")
print(f"🔍 Data Concentration Ratio: {len(state_concentration)/states_for_80pct:.2f}")

print("\n🔴 TOP 5 HIGHEST CONCENTRATION STATES (Privacy Hotspots):")
for _, row in state_concentration.nlargest(5, 'updates_per_pincode').iterrows():
    print(f"📍 {row['state']}: {row['updates_per_pincode']:,.0f} avg updates/loc")

```



🔒 DATA CONCENTRATION & PRIVACY RISK ANALYSIS

- 📊 Total States/UTs in Dataset: 57
- 📈 States holding 80% of biometric data: 13
- 🎯 Data Concentration Ratio: 4.4x (higher = more concentrated)

- 🔥 TOP 5 HIGHEST CONCENTRATION STATES (Privacy Hotspots):
 - Delhi: 13,876 avg updates/pincode | 1.9% of total data
 - Chhattisgarh: 9,847 avg updates/pincode | 3.8% of total data
 - Madhya Pradesh: 7,433 avg updates/pincode | 8.5% of total data
 - Dadra and Nagar Haveli: 6,809 avg updates/pincode | 0.0% of total data
 - Maharashtra: 5,741 avg updates/pincode | 13.2% of total data

In [57]: # 6.2 Comprehensive Privacy & System Improvement Recommendations

```
print("=" * 100)
print("PRIVACY-BY-DESIGN RECOMMENDATIONS FOR AADHAAR ECOSYSTEM")
print("=" * 100)

print("""
```

ISSUE 1: HIGH DATA CONCENTRATION IN FEW STATES

FINDING: 80% of biometric updates concentrated in limited states

PRIVACY RISK: Single point of failure, mass data breach potential

RECOMMENDATIONS:

- ✓ Implement federated data storage – each state maintains local encrypted data
- ✓ Use differential privacy for aggregated statistics
- ✓ Deploy regional data centers with strict access controls
- ✓ Implement data minimization – only store what's necessary

ISSUE 2: LOW-CONNECTIVITY REGIONS UNDERSERVED

FINDING: Service deserts identified at pincode level with low coverage

PRIVACY RISK: Forces citizens to travel to urban centers, exposing data to potentially less secure third-party centers

RECOMMENDATIONS:

- ✓ Deploy OFFLINE AUTHENTICATION capability using secure local devices
- ✓ Implement store-and-forward for low-connectivity areas
- ✓ Use mobile enrolment vans with end-to-end encrypted transmission
- ✓ Partner with rural banks/post offices with established security protocols

ISSUE 3: TEMPORAL SPIKES CREATE VULNERABILITY WINDOWS

FINDING: Month-end surges and weekday patterns create predictable peaks

PRIVACY RISK: Overwhelmed systems may bypass security checks
High-volume periods are attractive for fraud attempts

RECOMMENDATIONS:

- ✓ Implement APPOINTMENT SCHEDULING to flatten demand curves
- ✓ Deploy additional fraud detection during peak periods
- ✓ Use rate limiting per operator/center to prevent bulk fraud
- ✓ Mandatory cooling-off period between updates from same operator

ISSUE 4: YOUTH BIOMETRIC DATA REQUIRES SPECIAL PROTECTION

FINDING: Significant youth (5–17) updates without proper age-verification

PRIVACY RISK: Children's biometrics stored indefinitely, consent issues

RECOMMENDATIONS:

- ✓ Implement GUARDIAN CONSENT framework with separate authorization
- ✓ Age-appropriate data retention policies (enhanced protection for minors)
- ✓ Separate youth data in encrypted partitions with additional access controls
- ✓ Automatic review triggers when minor turns 18 (data re-consent required)

ISSUE 5: ANOMALOUS PATTERNS SUGGEST DATA QUALITY/FRAUD RISKS

FINDING: Statistical outliers at pincode level, unusual age distributions

PRIVACY RISK: Fraudulent entries, duplicate identities, data manipulation

RECOMMENDATIONS:

- ✓ Implement ML-based ANOMALY DETECTION for real-time fraud prevention
- ✓ Cross-reference with demographic databases for validation
- ✓ Mandatory operator verification for high-volume entries
- ✓ Regular audit cycles for outlier pincodes/districts

****)

=====

=====

PRIVACY-BY-DESIGN RECOMMENDATIONS FOR AADHAAR ECOSYSTEM

=====

=====

ISSUE 1: HIGH DATA CONCENTRATION IN FEW STATES

FINDING: 80% of biometric updates concentrated in limited states

PRIVACY RISK: Single point of failure, mass data breach potential

RECOMMENDATIONS:

- ✓ Implement federated data storage – each state maintains local encrypted copy
- ✓ Use differential privacy for aggregated statistics
- ✓ Deploy regional data centers with strict access controls
- ✓ Implement data minimization – only store what's necessary

ISSUE 2: LOW-CONNECTIVITY REGIONS UNDERSERVED

FINDING: Service deserts identified at pincode level with low coverage

PRIVACY RISK: Forces citizens to travel to urban centers, exposing data to potentially less secure third-party centers

RECOMMENDATIONS:

- ✓ Deploy OFFLINE AUTHENTICATION capability using secure local devices
- ✓ Implement store-and-forward for low-connectivity areas

- ✓ Use mobile enrolment vans with end-to-end encrypted transmission
- ✓ Partner with rural banks/post offices with established security protocols

ISSUE 3: TEMPORAL SPIKES CREATE VULNERABILITY WINDOWS

FINDING: Month-end surges and weekday patterns create predictable peaks

PRIVACY RISK: Overwhelmed systems may bypass security checks

High-volume periods are attractive for fraud attempts

RECOMMENDATIONS:

- ✓ Implement APPOINTMENT SCHEDULING to flatten demand curves
- ✓ Deploy additional fraud detection during peak periods
- ✓ Use rate limiting per operator/center to prevent bulk fraud
- ✓ Mandatory cooling-off period between updates from same operator

ISSUE 4: YOUTH BIOMETRIC DATA REQUIRES SPECIAL PROTECTION

FINDING: Significant youth (5-17) updates without proper age-verification

PRIVACY RISK: Children's biometrics stored indefinitely, consent issues

RECOMMENDATIONS:

- ✓ Implement GUARDIAN CONSENT framework with separate authorization
- ✓ Age-appropriate data retention policies (enhanced protection for minors)


```
unique_pincodes = df['pincode'].nunique()
total_youth = df['bio_age_5_17'].sum()
total_adult = df['bio_age_17_'].sum()
total_updates = df['total_bio_updates'].sum()

print(f"""
```

Dataset Overview	
Total Records Analyzed:	{total_records:>15,}
Total Biometric Updates:	{total_updates:>15,}
States/UTs Covered:	{unique_states:>15,}
Districts Covered:	{unique_districts:>15,}
Unique Pincodes:	{unique_pincodes:>15,}
Youth Updates (5-17):	{total_youth:>15,}
Adult Updates (17+):	{total_adult:>15,}
Youth Percentage:	{total_youth/total_updates*100:>14.1f}%

```
""")
```

```
print("""
```

Key Findings & Insights	
CRITICAL FINDINGS: - Significant geographic disparities in service coverage - Youth biometric updates don't align with school calendars - High data concentration creates privacy vulnerabilities - Temporal spikes indicate workflow inefficiencies	
MODERATE CONCERNS: - Statistical outliers at pincode level need investigation - Some states show declining update trends - Weekday vs weekend imbalance affects accessibility	
POSITIVE OBSERVATIONS: - Overall growth trajectory is positive - Wide geographic coverage across most states - Data patterns are analyzable for predictive planning	

```
""")
```

```
print("""
```

Prioritized Recommendations for UIDAI	
HIGH PRIORITY (Immediate Action Required): - DEPLOY MOBILE UNITS to underserved pincodes identified in analysis Impact: ↑ Coverage Effort: Medium Timeline: 3-6 months - IMPLEMENT APPOINTMENT SYSTEM to reduce temporal spikes Impact: ↓ Fraud Risk, ↑ UX Effort: Low Timeline: 1-3 months	

- 3. INTEGRATE WITH SCHOOLS for youth biometric update drives
Impact: ↑ Youth Coverage | Effort: Medium | Timeline: Next academic year

🟡 MEDIUM PRIORITY (Plan for next quarter):

- 4. FEDERATED DATA ARCHITECTURE to reduce concentration risks
Impact: ↑ Privacy | Effort: High | Timeline: 12–18 months
- 5. ML-BASED ANOMALY DETECTION for real-time fraud prevention
Impact: ↓ Fraud | Effort: Medium | Timeline: 6–9 months
- 6. OFFLINE AUTHENTICATION for low-connectivity regions
Impact: ↑ Access | Effort: High | Timeline: 9–12 months

🟢 LONG-TERM INITIATIVES:

- 7. PREDICTIVE CAPACITY PLANNING using ML forecasting
- 8. YOUTH DATA PROTECTION FRAMEWORK with enhanced consent
- 9. OPERATOR CERTIFICATION & CONTINUOUS MONITORING

"""

print("""

HACKATHON PRESENTATION TALKING POINTS

- 💡 UNIQUE VALUE PROPOSITION:
"We identified actionable gaps in Aadhaar biometric coverage using data-driven analysis, providing specific pincode-level recommendations that can improve service delivery for underserved populations."
- 📊 KEY METRICS TO HIGHLIGHT:
 - X% of pincodes classified as "service deserts"
 - Y states with declining trends need intervention
 - Z% of data concentrated in limited regions (privacy concern)
 - Youth updates misaligned with school calendar by N months
- 🎯 IMPACT POTENTIAL:
 - Improved coverage for underserved populations
 - Reduced fraud through anomaly detection
 - Enhanced privacy through architectural recommendations
 - Better resource allocation through predictive insights

"""

AADHAAR BIOMETRIC UPDATE ANALYSIS – EXECUTIVE SUMMARY

DATASET OVERVIEW

Total Records Analyzed:	1,861,108
Total Biometric Updates:	69,763,095
States/UTs Covered:	57
Districts Covered:	974
Unique Pincodes:	19,707
Youth Updates (5–17):	34,226,855
Adult Updates (17+):	35,536,240
Youth Percentage:	49.1%

KEY FINDINGS & INSIGHTS

● CRITICAL FINDINGS:

- Significant geographic disparities in service coverage
- Youth biometric updates don't align with school calendars
- High data concentration creates privacy vulnerabilities
- Temporal spikes indicate workflow inefficiencies

● MODERATE CONCERNS:

- Statistical outliers at pincode level need investigation

- Some states show declining update trends
- Weekday vs weekend imbalance affects accessibility

● POSITIVE OBSERVATIONS:

- Overall growth trajectory is positive
- Wide geographic coverage across most states
- Data patterns are analyzable for predictive planning

PRIORITIZED RECOMMENDATIONS FOR UIDAI

● HIGH PRIORITY (Immediate Action Required):

1. DEPLOY MOBILE UNITS to underserved pincodes identified in analysis

Impact: ↑ Coverage | Effort: Medium | Timeline: 3–6 months

2. IMPLEMENT APPOINTMENT SYSTEM to reduce temporal spikes

Impact: ↓ Fraud Risk, ↑ UX | Effort: Low | Timeline: 1–3 months

3. INTEGRATE WITH SCHOOLS for youth biometric update drives

Impact: ↑ Youth Coverage | Effort: Medium | Timeline: Next academic

year

● MEDIUM PRIORITY (Plan for next quarter):

4. FEDERATED DATA ARCHITECTURE to reduce concentration risks

Impact: ↑ Privacy | Effort: High | Timeline: 12–18 months

5. ML-BASED ANOMALY DETECTION for real-time fraud prevention

Impact: ↓ Fraud | Effort: Medium | Timeline: 6–9 months

6. OFFLINE AUTHENTICATION for low-connectivity regions

Impact: ↑ Access | Effort: High | Timeline: 9–12 months

● LONG-TERM INITIATIVES:

7. PREDICTIVE CAPACITY PLANNING using ML forecasting

8. YOUTH DATA PROTECTION FRAMEWORK with enhanced consent

9. OPERATOR CERTIFICATION & CONTINUOUS MONITORING

HACKATHON PRESENTATION TALKING POINTS

💡 UNIQUE VALUE PROPOSITION:

"We identified actionable gaps in Aadhaar biometric coverage using data-driven analysis, providing specific pincode-level recommendation that can improve service delivery for underserved populations."

📊 KEY METRICS TO HIGHLIGHT:

- X% of pincodes classified as "service deserts"
- Y states with declining trends need intervention

- Z% of data concentrated in limited regions (privacy concern)
- Youth updates misaligned with school calendar by N months

🎯 IMPACT POTENTIAL:

- Improved coverage for underserved populations
- Reduced fraud through anomaly detection
- Enhanced privacy through architectural recommendations
- Better resource allocation through predictive insights