

Design a Tic-Tac-Toe Game

[Problem Statement](#)

[Overview](#)

[Requirements](#)

[Components](#)

1. PieceType

2. PlayingPiece

3. Board

4. Player

5. TicTacToeGame

[Class Diagram](#)

[Implementation](#)

[Output](#)

▼ Resources


- [7. Design Tic Tac Toe game \(Hindi\) | Tic-Tac-Toe LLD Java | Low Level Design, System Design](#)
- Code Repo → [src/main/java/com/conceptcoding/interviewquestions/tictactoe · main · shrayansh jain / LLD-LowLevelDesign · GitLab](#)

Problem Statement

Design a comprehensive 2-player tic-tac-toe game of Xs and Os with the executable code following all design principles, patterns, best practices and guidelines discussed before.

Overview

Tic-tac-toe is a simple two-player paper-and-pencil game. Each player selects a piece before the game and takes turns placing it on the 3x3 grid. A player wins by placing three pieces in a row, column, or diagonal. The game ends when a player wins or when all grid cells are filled, resulting in a draw.




TicTacToe Winner: PlayerX

Requirements

- A 3x3 board should be used to play the game.
- 2 Players are marked by the piece they choose to play with - PlayerX and PlayerO
- The game should end when a player wins.
- The game should end when it's a draw(the players are out of free cells to play).
- The game should not allow any invalid moves.


Components

1. PieceType




- It's a symbol that is used to represent the cell value.
- Here we are using X and O. We can also choose different symbols.

2. PlayingPiece



- The base class represents **PlayingPiece**, used to represent the symbol used.
- Holds a reference to **PieceType** used to represent a piece.
- The concrete classes **PlayingPieceX** and **PlayingPieceO** denote specific **PlayingPiece**s associated with the corresponding **PieceType**.

3. Board




- **Board** is a concrete class that contains a 3x3 matrix of **PlayingPiece** used for playing the game and marking the positions where players place their pieces.
- We can create a grid of any size we want and define corresponding rules to extend the game in future.
- Includes methods to play the game, such as placing a piece, updating the cell value, checking for free cells, and detecting a winning move or game end.

4. Player



- **Player** is a concrete class that represents a Player in the game.
- It is composed of a **PlayingPiece** type, a symbol that a **Player** chooses to represent at the beginning of the game.


5. TicTacToeGame



- This concrete class contains core Game control logic.
- This class handles alternating turns between players, validating their moves, checking for a winning move, displaying the board after each step, and declaring the game winner or a draw before ending the game.
- Hence, it is composed of **Players** and a game **Board** reference for orchestrating the **Game** flow.
- Once the Game is over, the appropriate **GameStatus** value is returned.

Class Diagram

We combine the components above to produce a final solution to the TicTacToe Game Design problem.



Implementation

Refer Code Repository for Executable Code → [src/main/java/com/conceptcoding/interviewquestions/tictactoe](https://github.com/shrayansh-jain/LLD-LowLevelDesign) · main · shrayansh jain / LLD-LowLevelDesign · GitLab

Output

```
====>> TicTacToe Game

  |   |   |
  |   |   |
  |   |   |
Player:Player1 - Please enter [row, column]: 1,6
  |   |   |
X  |   |   |
  |   |   |
Player:Player2 - Please enter [row, column]: 0,6
0  |   |   |
X  |   |   |
  |   |   |
Player:Player1 - Please enter [row, column]: 1,2
0  |   |   |
X  |   | X  |
  |   |   |
Player:Player2 - Please enter [row, column]: 0,2
0  |   | 0  |
X  |   | X  |
  |   |   |
Player:Player1 - Please enter [row, column]: 1,1
0  |   | 0  |
X  | X  | X  |
  |   |   |

====>> GAME OVER: Player1 won the game
Process finished with exit code 0
```