DATABASE RELIABILITY ENGINEERING • OUTAGE POST-MORTEM

How an Edge Case Took Down GitHub: MySQL Primary Degradation


Dissection of Query Amplification, Unhandled Zero-Values, and Database Thread Pool Exhaustion

EXECUTIVE SUMMARY

In August 2021, GitHub suffered a widespread outage caused by an edge case in input parsing within one of its highest-throughput core services. By ignoring a type-conversion error on an optional parameter, the application silently fell back to a zero-value (0), mutating a narrow, indexed 30-day range scan into an unbounded scan across hundreds of millions of historical records on the write primary. This overwhelmed CPU capacity and cascaded sitewide.

1. ARCHITECTURE CONTEXT: MASTER WRITE-PATH VULNERABILITY

In scalable tiered database topologies, reads are load-balanced across replicas, while transactional state mutations and consistency-critical lookups target the **MySQL Primary (Writer)**:



2. MECHANISM OF AMPLIFICATION: THE SWALLOWED ERROR BUG

The critical failure mode stemmed from an unhandled error condition in an input parser handling HTTP query arguments:

```
// Fictional equivalent of the edge-case error pattern:
sinceParam := r.URL.Query().Get("since") // e.g. "" or "undefined"
sinceTimestamp, _ := strconv.ParseInt(sinceParam, 10, 64) // Error ignored!

// Fallback is Go's zero-value: sinceTimestamp = 0
// Unintended generated SQL query:
SELECT COUNT(id) FROM user_commits
WHERE author_id = ? AND created_at > 0;
```

Expected Query Profile

Query intended to count activity over past 30 days (`created_at > NOW() - 30d`). Traversed 10–50 rows using secondary index (`author_id, created_at`). Latency: **0.5ms**.

Pathological Path Profile

Evaluating `created_at > 0` forces the query engine to scan 100% of historical events across all years. For high-volume automated bots, this required reading 5,000,000+ rows per request. Latency: **>45s**.

3. MATHEMATICAL FORMALISM: RESOURCE CONSUMPTION DYNAMICS

When an unoptimized query strikes a high-concurrency database, the thread pool saturates exponentially according to Little's Law ($L = \lambda W$):

```
Normal Baseline:
  Arrival Rate: \lambda = 1,000 queries/sec
  Execution Time: W = 0.001 sec (1 ms)
  Required Active Threads: L = 1,000 * 0.001 = 1 concurrent connection

Pathological State (0.5% edge case frequency):
  Pathological Arrival Rate: \lambda_{bad} = 5 queries/sec
  Pathological Execution Time: W_{bad} = 30.0 sec
  Required Pathological Threads: L_{bad} = 5 * 30 = 150 concurrent connections!

Total MySQL Max Connections: 150 -> Saturated in under 30 seconds!
```

4. OUTAGE INCIDENT CHRONOLOGY

Timestamp	Component	Observed Telemetry & Anomaly	Severity Tier
T + 00:00	Client Frontend / API	Release triggers client edge cases omitting timestamp parameter.	Normal Traffic
T + 00:45	MySQL Primary Core	InnoDB Buffer Pool cache hit ratio drops from 99.8% to 64%.	Degraded Buffer Eviction
T + 01:30	Connection Manager	Active thread count reaches hard limit (`max_connections=500`).	Critical Pool Exhausted
T + 02:15	Application Workers	Database query timeouts trigger automated client retry storm.	Amplification 3x Retries
T + 05:00	GitHub Ingress Edge	Upstream HTTP reverse proxies emit 504 Gateway Timeouts.	Sitewide Outage

5. DEEP ROOT CAUSE ANALYSIS

1. Blast Radius Violation

Non-essential user profile card metrics queries were directed to the primary write cluster instead of read replicas, directly placing critical transaction writes at risk of read starvation.

2. Absence of Query Guardrails

The MySQL primary lacked statement-level execution deadlines (`MAX_EXECUTION_TIME`), allowing single long-running queries to lock thread slots for tens of seconds indefinitely.

6. ARCHITECTURAL MITIGATIONS & HARDENING PATTERN

Defending against edge-case query degradation requires multi-layered defensive validation, strict database execution timeouts, and intelligent query interception:

1. Fail-Fast Validation

Enforce strict parameter validation before dispatching SQL. Return HTTP 400 Bad Request if arguments fail schema checks.

2. Query Execution Caps

Attach optimizer hints `/*+ MAX_EXECUTION_TIME(500) */` to abort rogue full-table scans before worker exhaustion.

3. Strict Read Routing

Route all non-transactional aggregations exclusively to read-replicas, isolating primary writers from analytic load.

7. HARDENED CODE IMPLEMENTATION

```
// Hardened Go Pattern with Context Timeout and Boundary Clamping
func QueryUserEventsDefensive(ctx context.Context, db *sql.DB, uid int64, sinceRaw string) (int64, error) {
    if sinceRaw == "" {
        return 0, fmt.Errorf("param 'since' required")
    }
    sinceVal, err := strconv.ParseInt(sinceRaw, 10, 64)
    if err != nil || sinceVal <= 0 {
        return 0, fmt.Errorf("invalid timestamp param")
    }

    // Business Invariant: Search window strictly bounded to last 90 days
    minAllowed := time.Now().AddDate(0, 0, -90).UnixMilli()
    if sinceVal < minAllowed {
        sinceVal = minAllowed // Clamp lower bound
    }

    queryCtx, cancel := context.WithTimeout(ctx, 800*time.Millisecond)
    defer cancel()

    query := `/*+ MAX_EXECUTION_TIME(800) */
              SELECT COUNT(id) FROM user_commits
              WHERE author_id = ? AND created_at > ?;`
    var count int64
    err = db.QueryRowContext(queryCtx, query, uid, sinceVal).Scan(&count)
    return count, err
}
```

8. PRODUCTION ENGINEERING CHECKLIST

Key Engineering Takeaways

1. **Never swallow type conversion errors:** Configure linters like `errcheck` to fail builds on ignored errors.
2. **Enforce range clamping:** Always bound user-supplied date ranges programmatically in the application layer.
3. **Configure statement timeouts:** Set global and per-query `MAX_EXECUTION_TIME` on database writers.
4. **Protect the primary writer:** Offload all historical counts, search queries, and profile badges to replicas.
5. **Apply Circuit Breakers:** Shed non-critical read queries immediately when database latency degrades.