API Composition Pattern: Query Aggregation & In-Memory Joins


Decomposition of Distributed Joins, Concurrent Fan-Out, Tail Latency Amplification, and Partial Failure Modes

EXECUTIVE SUMMARY

When microservices encapsulate private databases, executing cross-domain queries requires an architectural mechanism to replace SQL JOINs. The API Composition Pattern delegates query aggregation to an API Composer that concurrently queries participating microservices over RPC and merges results in memory. While simple and immediate, it is constrained by tail latency and network fan-out.

1. THE DISTRIBUTED JOIN PARADOX

In a monolithic database, joining 4 tables takes ~2ms inside the query optimizer. In microservices, joining data across 4 independent services requires network RPCs:



2. MATHEMATICAL LATENCY DYNAMICS: SERIAL VS. PARALLEL FAN-OUT

Serial Execution (Anti-Pattern)

```
T_total = L_order + L_user + L_shipment
T_total = 25ms + 30ms + 45ms = 100ms
Sequential network roundtrips accumulate linearly.
```

Concurrent Execution (Optimal)

```
T_total = max(L_1, L_2, ..., L_k) + T_join
T_total = max(25ms, 30ms, 45ms) + 2ms = 47ms
Total latency bounded by slowest dependency.
```

3. TAIL LATENCY AMPLIFICATION IN DISTRIBUTED FAN-OUT

If a system has N downstream dependencies each with probability p of suffering a high-latency spike, the aggregate probability P_tail of the composer experiencing a tail event compounds:

```
P_tail = 1 - (1 - p)^N
If p = 0.01 (p99 tail event = 1%) and N = 10 microservices:
P_tail = 1 - (0.99)^10 = 1 - 0.904 = 0.0956  -->  9.6% Tail Spike Probability!
Nearly 1 in 10 client requests suffers tail latency amplification.
```

4. CONCURRENT GO IMPLEMENTATION WITH ERRGROUP

```
// Concurrent API Composition in Go
func (c *OrderComposer) GetOrderSummary(ctx context.Context, orderID string) (*Summary, error) {
    g, ctx := errgroup.WithContext(ctx)
    var order *Order; var customer *Customer; var tracking *Tracking

    g.Go(func() error {
        var err error; order, err = c.orderClient.Get(ctx, orderID)
        return err
    })
    g.Go(func() error {
        var err error; customer, err = c.customerClient.Get(ctx, orderID)
        return err
    })
    g.Go(func() error {
        var err error; tracking, err = c.shippingClient.Get(ctx, orderID)
        return err
    })

    if err := g.Wait(); err != nil { return nil, err }
    // Execute In-Memory Hash Join
    return &Summary{Order: order, Customer: customer, Tracking: tracking}, nil
}
```

5. PARTIAL FAILURE HANDLING: GRACEFUL DEGRADATION MATRIX

Service Dependency	Business Criticality	Failure Degradation Strategy
Order Core Service	Critical	Fail-Closed: Abort request immediately; return HTTP 502 / 504.
Loyalty Points Svc	Non-Critical	Fail-Open: Return order details with `"loyalty_points": "Unavailable"`.
Product Recommendations	Optional	Fail-Open: Fallback to cached top-10 global bestseller list.

6. API COMPOSITION VS. CQRS: ARCHITECTURAL TRADE-OFFS

Architecture Metric	API Composition Pattern	CQRS Materialized Read Views
Query Complexity	Best for point queries (single ID lookups).	Superior Multi-attribute filtering, sorting, full-text search.
Memory Footprint	High Risk In-memory join can exhaust container RAM.	Zero Done inside database index engine.
Freshness	Strong Queries live primary databases.	Eventual Lags by Kafka replication time (~20ms).
Network Overhead	N RPC network hops per aggregated request.	Single RPC to the CQRS read service.

7. WHEN TO AVOID API COMPOSITION

Large-Volume Pagination

If querying requires sorting 50,000 orders across 4 criteria, fetching 50,000 JSON payloads over RPC to sort in memory crashes the gateway. Use CQRS.

Deep Multilevel Nesting

Avoid Composer A calling Composer B which calls Composer C. Call stacks beyond depth 2 exponentially multiply tail latency.

8. PRODUCTION ENGINEERING VERIFICATION CHECKLIST

API Composition Production Gates

1. **Deadline Propagation:** Always pass parent request context with strict timeout down to all concurrent child calls.
2. **Limit Payload Bounds:** Enforce strict ceiling on the number of items aggregated in a single request.
3. **Documented Fallbacks:** Ensure every non-critical dependency has a documented, automated fallback response.
4. **Circuit Breaker Isolation:** Do not share circuit breaker thresholds across disparate downstream service calls.