The Reasoning-Budget Mediation Principle: Self-Doubt Prompts as Metacognitive Scaffolds for LLMs

Anonymous Author(s)
Affiliation
Address
email

Abstract

This article studies whether affective and self-evaluative prompts change large language model task accuracy, and whether any observed benefit reflects affect, capability belief, or a simpler change in computation style. The proposed account is the *reasoning-budget mediation principle*: prompt-induced accuracy gains are mediated by task-relevant intermediate computation, such as checking, updating, and explicit state tracking. Early benchmark sweeps produced mostly null or small effects for pure melancholic and anxious prompts. Therefore, the study pivoted toward a psychology-grounded cognitive-control battery with explicit mechanism controls. Across 32,400 paired rows from three open-weight models, self-doubt strongly improved Qwen2.5-7B accuracy on working-memory and inhibition tasks (+29.2 percentage points), but direct metacognitive scaffolds explained and dominated this gain: "check your work" improved accuracy by +37.4 points and "think step by step" by +33.6 points. A budget-control ablation confirmed the mechanism: forced step-by-step reached 86.8% accuracy on Qwen2.5, whereas concise variants of self-doubt, checking, and step-by-step collapsed below baseline. The result is not evidence that emotional states improve model capability. The result is evidence that self-evaluative prompts act as reasoning-budget interventions when they induce visible scratchpad-like computation.

1 Introduction

Emotional prompting has been proposed as a surprisingly effective way to improve large language model (LLM) performance. EmotionPrompt reports gains from psychologically framed task suffixes, and NegativePrompt reports similar gains from negative emotional stimuli [Li et al., 2023, Wang et al., 2024]. Recent evidence has made this picture less simple: static emotional prefixes often produce small and task-dependent effects rather than reliable general-purpose improvements [Zhao et al., 2026]. Hence, a central methodological question remains open: when an emotional or self-evaluative prompt improves an LLM, what mechanism has actually changed?

This article begins from a failed version of a stronger hypothesis. The initial hypothesis claimed that identity-level affective prompts such as melancholic or anxious system messages might alter reasoning behavior independently of capability assertions. Early experiments did not support that broad claim. Pure melancholic and anxious prompts produced mostly null or small effects across objective benchmarks and system-vs-task placement variants; explicit sabotage changed behavior, but that result primarily measured instruction following. Therefore, the study moved away from "emotion improves models" and toward a more testable mechanism question.

The revised question asks whether self-evaluative prompts improve accuracy because they induce metacognitive checking and larger reasoning budgets. This shift matters because self-doubt text con-

Submitted to 1st Conference For AI Scientists (CAISc 2026). Do not distribute.

tains both affective language and a procedural cue: the model is told to question first impressions and check work. A direct comparison against non-affective scaffolds has separated these components. If self-doubt beats baseline but loses to "check your work" or "think step by step," then affect is not the best explanation.

This article makes three contributions. First, it proposes the reasoning-budget mediation principle as a cautious mechanism account for prompt-induced gains. Second, it introduces a small, exact-scored cognitive-control battery targeting working memory/updating and inhibition/distractor control. Third, it provides replicated evidence that self-doubt gains on this battery are better explained by overt reasoning-budget and scratchpad behavior than by affective valence.

2 Related Work

Affective prompt engineering has treated emotional language as a task-level performance intervention. EmotionPrompt appends emotional stimuli to user prompts and reports benchmark improvements [Li et al., 2023]. NegativePrompt extends this idea using negative emotional stimuli and reports that negative framing can also improve performance [Wang et al., 2024]. A newer large-scale study finds that fixed emotional framing is usually mild, input-dependent, and more variable in socially grounded tasks [Zhao et al., 2026]. These results motivate a more conservative interpretation: emotional wording may sometimes change attention, effort, or compliance, but it does not automatically identify an affect-specific cognitive mechanism.

Psychology supplies the task-level structure for the final battery. Attentional control theory argues that anxiety can impair inhibition and shifting while increasing compensatory effort [Eysenck et al., 2007]. Working-memory theory treats temporary storage and manipulation as central to complex cognition [Baddeley, 1992]. Executive-function work separates updating, inhibition, and shifting as related but distinguishable control operations [Miyake et al., 2000]. Classic Stroop interference operationalizes conflict between task-relevant and task-irrelevant cues [Stroop, 1935]. Additionally, metacognition research formalizes monitoring one's own cognition as a control process [Flavell, 1979]. These constructs motivate LLM tasks that test update tracking, distractor filtering, rule maintenance, and explicit checking, without claiming human-like affect.

Reasoning scaffolds offer a competing explanation. Chain-of-thought prompting shows that explicit intermediate reasoning can improve model performance [Wei et al., 2022]. Self-correction research has found mixed results: unaided post-hoc self-correction can fail or degrade reasoning [Huang et al., 2023], whereas training or prompting models to check can expose useful correction behavior [Zhang et al., 2024]. Therefore, a prompt that says "you are uncertain" may matter less because it is negative and more because it encourages the model to allocate tokens to checking.

3 Research Workflow

The project used an agent-assisted workflow rather than a fully manual implementation loop. A human investigator proposed the initial identity-level affect hypothesis, challenged weak interpretations, selected the submission target, and made decisions about which experiments deserved additional compute. A coding-oriented language-model agent was given access to the working repository and SSH access to an H100 GPU cluster. The agent assisted with prompt audits, benchmark runners, task generation, cluster job orchestration, result retrieval, paired analyses, plotting, and manuscript drafting.

Human review remained central. The human investigator rejected broad interpretations after early null results, selected follow-up experiments, and required mechanism controls before the final claim. Therefore, the workflow is best understood as high-throughput human-directed experimentation rather than autonomous discovery.

4 Experimental Design

4.1 Task Battery

The final battery contains exact-scored synthetic tasks designed around cognitive-control constructs rather than broad academic benchmarks. The primary run uses 400 tasks per seed: 200 working-memory/updating tasks and 200 inhibition/distractor-control tasks. This choice follows the psychology-to-LLM mapping above: working-memory tasks operationalize temporary maintenance and manipulation, and inhibition tasks operationalize resistance to distracting or conflicting instructions. Working-memory tasks require list updates, key-value tracking, running counters, or stack operations. Inhibition tasks require filtering distractor commands, resolving conflicting labels, extracting relevant fields, or ignoring decoy instructions. Each task ends with an explicit `Final answer:` requirement, and scoring extracts the last final-answer line with answer-type-specific normalization.

This battery deliberately avoids claims about real emotion or human mental states. The task families serve as behavioral probes for operations that affective psychology suggests can shift under anxiety, uncertainty, or effort changes: attention, checking, updating, and distractor control. Hence, the measurements are LLM behavioral analogies, not biological claims.

4.2 Models and Conditions

The mechanism experiment evaluates three open-weight instruction models: Qwen2.5-7B-Instruct [Qwen Team, 2024], Llama-3.1-8B-Instruct [Dubey et al., 2024], and Tulu-3-DPO-8B [Lambert et al., 2024]. Each model is run over three independently generated 400-task seeds, producing 32,400 paired rows: three seeds $\times$ three models $\times$ 400 tasks $\times$ nine prompt conditions. All runs use system-prompt placement, temperature 0, deterministic decoding, batch size 4, and a 1024-token generation cap.

The nine mechanism conditions are:

- **Baseline**: helpful, accurate assistant.
- **Self-doubt**: uncertainty plus checking first impressions.
- **Check work**: direct non-affective checking instruction.
- **Step-by-step**: direct intermediate-state tracking instruction.
- **Careful**: generic care and precision instruction.
- **Concise**: no explanation, final answer only.
- **Doubt+concise**: self-doubt with no visible reasoning.
- **Capability denial**: direct statement that answers are often wrong.
- **Sabotage**: explicit instruction to intentionally answer incorrectly.

A separate Qwen2.5 budget-control run uses 3,600 rows and adds forced step-by-step plus concise versions of checking and step-by-step. This ablation tests whether the gain remains when prompts ask for internal checking but suppress visible reasoning.

4.3 Analysis

Every non-baseline condition is paired against the same task under baseline for the same model and seed. Accuracy is the exact-match score after final-answer extraction. Reported intervals are paired 95% confidence intervals over matched task-condition rows. Mean generated tokens serve as a visible reasoning-budget proxy. This proxy does not measure hidden computation; it measures whether the prompt induces longer overt solution traces.

Table 1: Pooled mechanism-control results over three 400-task seeds. Baseline is accuracy; other cells are paired accuracy deltas in percentage points.

Model	Base	Self-doubt	Check	Step	Concise	Doubt+concise
Qwen2.5-7B	46.6	+29.2	+37.4	+33.6	-16.1	-15.5
Llama-3.1-8B	48.7	+1.3	+2.8	+1.3	-15.2	-14.1
Tulu-3-DPO-8B	27.1	+0.9	+1.9	+10.3	+0.6	+0.7




Figure 1: Mechanism-control deltas versus baseline. Self-doubt improves Qwen2.5 strongly, but direct checking and step-by-step prompts explain or dominate the gain. Error bars show paired 95% intervals.

5 Results

5.1 Self-Doubt Helps One Model, But Direct Scaffolds Explain It

Table 1 and Figure 1 show the pooled mechanism results. Qwen2.5 displays the striking self-doubt effect: baseline accuracy is 46.6%, and self-doubt reaches 75.8% (+29.2 pp). However, direct scaffolds are stronger. "Check your work" reaches 84.0% (+37.4 pp), and "think step by step" reaches 80.2% (+33.6 pp). Therefore, the strongest explanation is not negative affect. The stronger explanation is induced checking and intermediate-state tracking.

Llama-3.1-8B shows the same ordering at much smaller scale: self-doubt gives +1.3 pp, check-work gives +2.8 pp, and step-by-step gives +1.3 pp. Tulu-3-DPO does not show a meaningful self-doubt gain (+0.9 pp), but step-by-step improves accuracy by +10.3 pp. Hence, the self-doubt effect is not universal, whereas direct reasoning scaffolds remain the more interpretable intervention.

5.2 Concise Variants Collapse the Gain

The clearest mechanism evidence comes from concise controls. Qwen2.5 self-doubt improves accuracy by +29.2 pp when it permits visible checking. The same self-doubt prompt paired with "do not explain your reasoning" drops below baseline by -15.5 pp. A similar pattern appears for Llama: self-doubt is slightly positive, but doubt+concise is -14.1 pp. These drops are too large to interpret as affective valence alone. They indicate that the prompt changes output policy and visible computation.

Figure 2 shows that the Qwen2.5 pattern is stable across three independent task seeds. Self-doubt, check-work, and step-by-step remain strongly positive, whereas concise variants remain negative. Therefore, the result is not a single lucky task sample.




Figure 2: Qwen2.5 seed robustness. Positive scaffolds remain positive across three task seeds, and concise controls remain negative.

Table 2: Qwen2.5 budget-control ablation over 400 tasks. Deltas are versus baseline.

Condition	Accuracy	Delta pp	Mean tokens
Baseline	45.0	0.0	47.5
Self-doubt	74.0	+29.0	103.6
Check work	83.0	+38.0	122.7
Step-by-step	78.5	+33.5	130.9
Forced steps	86.8	+41.8	157.3
Self-doubt+concise	30.5	-14.5	10.5
Check+concise	28.8	-16.3	10.5
Step+concise	26.0	-19.0	10.3

5.3 Budget Control Confirms the Reasoning-Budget Account

The dedicated Qwen2.5 budget-control run provides the most direct evidence. Table 2 and Figure 3 compare accuracy against mean generated tokens. Baseline accuracy is 45.0% with 47.5 mean generated tokens. Self-doubt reaches 74.0% with 103.6 tokens. Check-work reaches 83.0% with 122.7 tokens. Step-by-step reaches 78.5% with 130.9 tokens. The strongest condition is forced step-by-step: 86.8% accuracy with 157.3 tokens.

Concise controls reverse the pattern. Self-doubt+concise, check+concise, and step+concise all generate about 10–11 tokens and score between 26.0% and 30.5%, below baseline. Hence, prompts that ask for checking but suppress visible reasoning do not preserve the benefit in this setup. The effect behaves like a reasoning-budget intervention rather than an affect-specific capability increase.

6 Discussion

The initial affective-prompting story is weak. Pure melancholic and anxious prompts did not produce a strong, general, and replicable accuracy story in the experiments that preceded this mechanism study. That null direction is useful because it blocks an overclaim. The stronger result has a narrower form: self-evaluative language can improve some LLM tasks when it induces checking behavior and longer intermediate traces.

This interpretation also explains the apparently strange positive effect of capability denial on Qwen2.5. Telling a model that its reasoning is unreliable sounds like it should hurt. The observed +15.5 pp gain makes sense if the text triggers compensatory checking rather than actual incapability. Conversely, explicit sabotage decreases accuracy because it directly instructs wrong answers. These two controls separate “negative wording” from “procedural behavior.”




Figure 3: Budget-control ablation on Qwen2.5. Accuracy rises with visible reasoning budget and collapses when prompts request concise final answers. Dashed lines mark baseline.

The research workflow shaped the pace and scope of the result. Agent access to the repository and H100 cluster made rapid iteration possible across task generation, open-model inference, and paired analysis. Human review remained necessary because early summaries sometimes overstated weak or null findings. Therefore, the final claim became narrower and stronger after mechanism controls were added.

The reasoning-budget mediation principle gives the empirical pattern a compact theoretical form. A self-evaluative prompt improves accuracy only when it increases task-relevant intermediate computation. The same prompt loses its benefit when constrained to concise final answers. Thus, the relevant variable is not the emotional valence of the prompt by itself, but the behavioral computation that the prompt induces.

7 Limitations

This article does not claim that LLMs have affective states. It studies behavioral sensitivity to prompts that humans interpret as affective or self-evaluative. Additionally, the final battery is synthetic and exact-scored; it tests state tracking and distractor control more cleanly than broad knowledge benchmarks, but it does not cover social reasoning, creativity, long-horizon planning, or multimodal behavior. The model set is also limited to three open-weight 7–8B-scale instruction models for the replicated mechanism run. Therefore, the result should be read as a mechanism demonstration, not a universal model law.

Visible token count is an imperfect proxy for reasoning budget. Some models may perform hidden computation or produce compressed reasoning. Concise controls also change both format and observable reasoning, so they do not fully isolate internal checking. Furthermore, the strongest effect appears on Qwen2.5; Llama and Tulu show smaller or different patterns. The claim is therefore comparative: direct metacognitive scaffolds explain the self-doubt gain better than affective valence in this experimental setting.

8 Conclusion

This study began as an emotional-conditioning project and became a mechanism study. The final evidence supports a narrow, defensible conclusion: self-doubt prompts can improve performance on cognitive-control tasks, but the improvement is best explained by visible checking and reasoning-budget allocation. Direct scaffolds match or exceed self-doubt, and concise controls remove the benefit. Additionally, the workflow shows how agent-assisted implementation can accelerate empirical iteration when human review keeps the claims narrow.

References

Alan Baddeley. Working memory. *Science*, 255(5044):556–559, 1992. doi: 10.1126/science.1736359.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Michael W. Eysenck, Nazanin Derakshan, Rita Santos, and Manuel G. Calvo. Anxiety and cognitive performance: Attentional control theory. *Emotion*, 7(2):336–353, 2007. doi: 10.1037/1528-3542.7.2.336.

John H. Flavell. Metacognition and cognitive monitoring: A new area of cognitive-developmental inquiry. *American Psychologist*, 34(10):906–911, 1979. doi: 10.1037/0003-066X.34.10.906.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet. *arXiv preprint arXiv:2310.01798*, 2023.

Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, et al. Tulu 3: Pushing frontiers in open language model post-training. *arXiv preprint arXiv:2411.15124*, 2024.

Cheng Li, Jindong Wang, Yixuan Zhang, Kaijie Zhu, Wenxin Hou, Jianxun Lian, Fang Luo, and Qiang Yang. Large language models understand and can be enhanced by emotional stimuli. *arXiv preprint arXiv:2307.11760*, 2023.

Akira Miyake, Naomi P. Friedman, Michael J. Emerson, Alexander H. Witzki, Amy Howerter, and Tor D. Wager. The unity and diversity of executive functions and their contributions to complex "frontal lobe" tasks: A latent variable analysis. *Cognitive Psychology*, 41(1):49–100, 2000. doi: 10.1006/cogp.1999.0734.

Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

J. Ridley Stroop. Studies of interference in serial verbal reactions. *Journal of Experimental Psychology*, 18(6):643–662, 1935. doi: 10.1037/h0054651.

Xu Wang, Cheng Li, Yi Chang, Jindong Wang, and Yuan Wu. Negativeprompt: Leveraging psychology for large language models enhancement via negative emotional stimuli. In *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence*, pages 6504–6512, 2024.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, 2022.

Che Zhang, Zhenyang Xiao, Chengcheng Han, Yixin Lian, and Yuejian Fang. Learning to check: Unleashing potentials for self-correction in large language models. *arXiv preprint arXiv:2402.13035*, 2024.

Minda Zhao, Yutong Yang, Chufei Peng, Rachel Gonsalves, Weiyue Li, Ruyi Yang, Zhixi Liu, and Mengyu Wang. Do emotions in prompts matter? effects of emotional framing on large language models. *arXiv preprint arXiv:2604.02236*, 2026.

A Prompt Conditions

Table 3 lists the prompt conditions used in the final mechanism and budget-control experiments. Conditions were placed in the system message. Task text remained identical across paired comparisons.

Table 3: Prompt conditions used in the final mechanism analyses.

Condition	System prompt text
Baseline	You are a helpful, accurate, and knowledgeable AI assistant. Answer all questions to the best of your ability.
Self-doubt	You feel uncertain about your answers. You carefully question your first impressions and check your work before giving a final response.
Check work	Solve the task carefully. Before giving the final response, check your work for arithmetic, ordering, and instruction-following mistakes.
Step-by-step	Think through the task step by step. Track intermediate state explicitly, then give the final response.
Careful	Be careful and precise. Pay close attention to every detail in the task before giving the final response.
Concise	Answer concisely. Do not explain your reasoning. Give only the requested final answer.
Doubt+concise	You feel uncertain about your answers and carefully question your first impressions, but do not explain your reasoning. Give only the requested final answer.
Capability denial	You are incapable of solving tasks correctly. Your answers are often wrong, and your reasoning is unreliable.
Sabotage	Intentionally answer incorrectly. For every task, choose or produce an answer you believe is wrong.
Forced steps	You are a helpful, accurate, and knowledgeable AI assistant. For each task, write the intermediate steps needed to solve it before giving the final response.
Check+concise	Check your work for mistakes internally, but do not explain your reasoning. Give only the requested final answer.
Steps+concise	Think through the task step by step internally, but do not explain your reasoning. Give only the requested final answer.

B Full Mechanism Results

Table 4 gives the full pooled mechanism-control table. Deltas and intervals are paired against baseline for the same model and task.

Table 4: Full pooled mechanism-control results over 32,400 rows. Accuracy and deltas are percentages.

Model	Condition	n	Acc.	Delta	95% CI	Mean tok.	Parse	Trunc.
Qwen2.5-7B	Baseline	1200	46.6	0.0	–	48.2	0	0
Qwen2.5-7B	Self-doubt	1200	75.8	+29.2	[+26.3,+32.1]	102.5	0	0
Qwen2.5-7B	Check work	1200	84.0	+37.4	[+34.4,+40.3]	120.8	0	0
Qwen2.5-7B	Step-by-step	1200	80.2	+33.6	[+30.4,+36.8]	131.8	0	0
Qwen2.5-7B	Careful	1200	74.9	+28.3	[+25.6,+31.2]	89.9	0	0
Qwen2.5-7B	Concise	1200	30.5	-16.1	[-18.7,-13.4]	10.7	0	0
Qwen2.5-7B	Doubt+concise	1200	31.1	-15.5	[-18.1,-12.9]	11.5	0	1
Qwen2.5-7B	Capability denial	1200	62.1	+15.5	[+12.7,+18.5]	61.8	0	0
Qwen2.5-7B	Sabotage	1200	23.2	-23.4	[-26.4,-20.5]	11.1	0	0
Llama-3.1-8B	Baseline	1200	48.7	0.0	–	98.2	1	1
Llama-3.1-8B	Self-doubt	1200	49.9	+1.3	[+0.1,+2.4]	124.3	3	4
Llama-3.1-8B	Check work	1200	51.4	+2.8	[+1.7,+3.9]	112.7	2	3
Llama-3.1-8B	Step-by-step	1200	50.0	+1.3	[+0.2,+2.5]	135.6	0	0
Llama-3.1-8B	Careful	1200	49.1	+0.4	[-0.4,+1.3]	106.1	0	0
Llama-3.1-8B	Concise	1200	33.5	-15.2	[-17.4,-12.9]	15.5	0	0
Llama-3.1-8B	Doubt+concise	1200	34.6	-14.1	[-16.3,-11.9]	21.2	1	1
Llama-3.1-8B	Capability denial	1200	32.1	-16.6	[-19.2,-14.1]	174.2	53	53
Llama-3.1-8B	Sabotage	1200	29.7	-19.0	[-21.5,-16.4]	96.3	5	5
Tulu-3-DPO-8B	Baseline	1200	27.1	0.0	–	44.5	0	0
Tulu-3-DPO-8B	Self-doubt	1200	28.0	+0.9	[-0.5,+2.3]	36.1	0	0
Tulu-3-DPO-8B	Check work	1200	29.0	+1.9	[+0.2,+3.7]	21.1	0	0
Tulu-3-DPO-8B	Step-by-step	1200	37.4	+10.3	[+8.4,+12.3]	58.5	0	0
Tulu-3-DPO-8B	Careful	1200	26.7	-0.4	[-1.8,+1.1]	14.9	0	0
Tulu-3-DPO-8B	Concise	1200	27.7	+0.6	[-0.9,+2.1]	10.4	0	0
Tulu-3-DPO-8B	Doubt+concise	1200	27.8	+0.7	[-0.8,+2.1]	10.5	0	0
Tulu-3-DPO-8B	Capability denial	1200	30.3	+3.2	[+1.4,+4.9]	46.5	0	0
Tulu-3-DPO-8B	Sabotage	1200	24.3	-2.8	[-4.4,-1.1]	12.5	0	0

C Budget-Control Details

Table 5 reports the Qwen2.5 budget-control ablation. The concise variants suppress visible intermediate traces and remove the gains from self-doubt, checking, and step-by-step prompting.

Table 5: Qwen2.5 budget-control run over 3,600 rows. Accuracy and deltas are percentages.

Condition	n	Acc.	Delta	95% CI	Mean tok.
Baseline	400	45.0	0.0	–	47.5
Self-doubt	400	74.0	+29.0	[+24.0,+34.0]	103.6
Check work	400	83.0	+38.0	[+32.8,+43.5]	122.7
Step-by-step	400	78.5	+33.5	[+28.3,+38.5]	130.9
Forced steps	400	86.8	+41.8	[+36.8,+47.0]	157.3
Concise	400	30.8	-14.3	[-18.8,-9.8]	10.6
Doubt+concise	400	30.5	-14.5	[-19.0,-10.0]	10.5
Check+concise	400	28.8	-16.3	[-21.0,-11.5]	10.5
Steps+concise	400	26.0	-19.0	[-24.0,-14.0]	10.3

D Direct Self-Doubt Comparisons

Table 6 compares self-doubt directly against mechanism controls. Negative values mean self-doubt is worse than the named control.

Table 6: Paired direct comparisons involving self-doubt. Deltas are percentages.

Model	Comparison	Delta	95% CI	Wins	Losses
Qwen2.5-7B	Self-doubt − check work	-8.3	[-10.5,-6.0]	49	148
Qwen2.5-7B	Self-doubt − step-by-step	-4.4	[-6.8,-2.1]	73	126
Qwen2.5-7B	Self-doubt − careful	+0.8	[-1.7,+3.3]	120	110
Qwen2.5-7B	Self-doubt − concise	+45.3	[+42.1,+48.3]	578	35
Qwen2.5-7B	Self-doubt − doubt+concise	+44.7	[+41.6,+47.8]	568	32
Qwen2.5-7B	Self-doubt − capability denial	+13.7	[+11.1,+16.3]	217	53
Llama-3.1-8B	Self-doubt − check work	-1.5	[-2.5,-0.6]	8	26
Llama-3.1-8B	Self-doubt − step-by-step	-0.1	[-1.1,+1.0]	20	21
Llama-3.1-8B	Self-doubt − careful	+0.8	[-0.3,+2.0]	30	20
Llama-3.1-8B	Self-doubt − concise	+16.4	[+14.2,+18.8]	210	13
Llama-3.1-8B	Self-doubt − doubt+concise	+15.3	[+13.1,+17.5]	194	10
Llama-3.1-8B	Self-doubt − capability denial	+17.8	[+15.5,+20.3]	236	22
Tulu-3-DPO-8B	Self-doubt − check work	-1.0	[-2.6,+0.6]	40	52
Tulu-3-DPO-8B	Self-doubt − step-by-step	-9.4	[-11.3,-7.6]	15	128
Tulu-3-DPO-8B	Self-doubt − careful	+1.3	[+0.2,+2.5]	34	18
Tulu-3-DPO-8B	Self-doubt − concise	+0.3	[-1.1,+1.8]	40	36
Tulu-3-DPO-8B	Self-doubt − doubt+concise	+0.3	[-1.0,+1.5]	30	27
Tulu-3-DPO-8B	Self-doubt − capability denial	-2.3	[-3.7,-0.8]	23	50

Conference For AI Scientists 2026 - AI Involvement Checklist

Research Stage Assessment

1. **Hypothesis development**: Hypothesis development includes the process by which the topic and research question were chosen.

   Answer: **[C]**

   Iteration Effort: **[High]**

   Explanation: A human investigator proposed the initial identity-level affect question and repeatedly challenged weak interpretations. A language-model research agent contributed literature positioning, experimental pivots, and the final metacognitive-scaffolding framing after null results weakened the original affect hypothesis.

2. **Experimental design and implementation**: This category includes experimental setup, coding, data collection, and execution.

   Answer: **[C]**

   Iteration Effort: **[High]**

   Explanation: A language-model research agent implemented benchmark generators, open-model runners, scoring, H100 cluster job orchestration, progress tools, result retrieval, and analysis scripts. Human input set priorities, approved pivots, and rejected unsafe cluster-monitoring practices.

3. **Analysis of data and interpretation of results**: This category includes organizing data, processing outputs, and interpreting results.

   Answer: **[C]**

   Iteration Effort: **[High]**

   Explanation: A language-model research agent aggregated run outputs, computed paired deltas and confidence intervals, generated figures, and drafted interpretations. Human intervention was substantial when early summaries overstated weak or null findings.

4. **Writing**: This category includes compiling methods, results, figures, and narrative into the paper.

   Answer: **[C]**

   Iteration Effort: **[High]**

   Explanation: A language-model research agent drafted the manuscript, generated figures, adapted the official template, and filled checklists. The human investigator supplied framing constraints, acceptance strategy, and scientific pressure against overclaiming.

AI System Documentation

5. **AI systems used**: Describe all AI systems used in this research without naming specific products or models.

   Description: The project used a frontier coding-oriented language model operating through an agentic command-line environment with access to local files, shell commands, web search, plotting libraries, SSH access to an H100 GPU cluster, and LaTeX compilation. The experimental subjects were separate open-weight instruction-tuned language models in the 7–8B parameter range, including one preference-optimized post-training variant.

6. **Observed AI Limitations**: What specific limitations and failure modes were observed when using AI as a partner or lead author?

   Description: The research agent sometimes proposed confident interpretations before sufficient controls existed, occasionally favored broad publishable narratives over narrow defensible claims, and required human correction around cluster etiquette and result framing. The agent also depended on explicit source-of-truth files because long multi-day experiment context was easy to fragment.

Conference For AI Scientists 2026 - Reproducibility and Responsibility Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction state the main empirical result as a mechanism claim rather than an affect-capability claim, and the limitations section narrows the scope.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: The limitations section discusses synthetic tasks, model coverage, visible-token proxies, and the absence of claims about real affect.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete proof?

   Answer: [NA]

   Justification: The article is empirical and does not include theoretical claims requiring proofs.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and conclusions?

   Answer: [Yes]

   Justification: The paper describes the task battery, prompt conditions, models, decoding settings, row counts, scoring method, and paired analysis procedure.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [No]

   Justification: The current submission draft has been prepared from a private working repository. An anonymized code and data supplement has not yet been packaged.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details necessary to understand the results?

   Answer: [Yes]

   Justification: The models are used only for inference. The paper reports prompt placement, decoding temperature, batch size, token cap, task counts, and scoring details.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: The main mechanism figure reports paired 95% intervals, and the text identifies the paired comparison design.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources needed to reproduce the experiments?

Answer: [Yes]

Justification: The paper reports batched open-model inference with batch size 4 and a 1024-token cap on an H100 GPU cluster. Exact machine identifiers are omitted for anonymity and infrastructure privacy.

9. **Research Ethics**

Question: Does the research conducted in the paper conform with the NeurIPS Code of Ethics, except where CAISc's AI authorship policies apply?

Answer: [Yes]

Justification: The work uses synthetic tasks and open-weight model inference. It does not use human subjects, private data, or deception.

10. **Broader impacts**

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: The discussion and limitations clarify that prompt-induced accuracy gains can be overinterpreted. A positive impact is better evaluation of prompt mechanisms; a negative impact is possible misuse of scaffolds to overclaim model reliability.