A Comparative Study of Gradient Boosting and Neural Networks for Forecasting Electricity Usage at the Appliance Level

Under Supervision of:-

Dr. Sasmita Padhy (Supervisor)

Dr. Vikas Panthi (Reviewer 1)

Dr. Preetam Suman (Reviewer 2)

Drafted by:-

1) **Rishi Raj (24BCE10149)**
2) **Abhilash Singh (24BCE10706)**
3) **Arnab Kumar (24BCE11017)**
4) **Brotodeep Pal (24BC10477)**
5) **Anjistha Sharma (24BCE10037)**

Abstract

As global energy costs rise and sustainable living becomes increasingly important, the ability for consumers to accurately forecast their electricity consumption is essential for effective energy management. While many models focus on aggregate household usage, predicting costs at the individual appliance level provides more detailed and actionable insights. This paper presents a thorough comparative study of two prominent machine learning approaches—Gradient Boosting and Neural Networks—aimed at forecasting monthly electricity costs for specific appliances. Utilizing a synthetic dataset with 9,000 records detailing appliance usage, local weather conditions, and regional tariff data, we developed, trained, and evaluated an XGBoost model and a multi-layer Functional Neural Network (FNN). Key preprocessing steps included one-hot encoding for categorical features like City and Appliance Name, as well as standard scaling to normalize numerical inputs for the FNN, which is crucial for optimizing neural network convergence. Model performance was assessed on the unseen test set using Mean Absolute Error (MAE) and the coefficient of determination (R-squared). The results showed that both models demonstrated strong predictive capabilities; however, the Gradient Boosting model exhibited statistically superior performance, achieving a lower MAE of ₹267.86 compared to ₹295.81 for the Neural Network and a higher R-squared value of 0.855 versus 0.822. This study underscores the effectiveness of both machine learning architectures for this regression task, while emphasizing the distinct performance advantages and robustness of the Gradient Boosting method for structured, tabular data, making it a preferable option for developing practical energy forecasting tools for consumers.

Introduction

1.1. Background

In an era defined by increasing global energy demands and the urgent need for sustainable practices, effective energy management has become a critical issue for governments, industries, and individual consumers alike. Residential energy consumption constitutes a significant portion of the total energy usage in many nations. As such, empowering consumers with tools and insights to understand and manage their electricity consumption is not only a pathway to cost savings but also a crucial step towards reducing the collective carbon footprint. While smart meters and energy monitoring technologies have become more prevalent, the raw data they provide often lacks the intuitive interpretation necessary for a non-expert user to make informed decisions. A key challenge lies in translating complex energy usage data into simple, actionable information.

1.2. Literature Gap

Much of the current research in energy forecasting has concentrated on predicting aggregate electricity consumption at the grid or household level. Although these macro-level forecasts are valuable for utility providers, they offer limited actionable insights for end-users. A notable gap in the literature exists regarding the development of intuitive, appliance-level prediction tools that can enhance consumer decision-making. Moreover, while various machine learning models have been applied to energy forecasting, comprehensive and systematic comparisons of advanced approaches such as Gradient Boosting and Neural Networks for this fine-grained task are still limited.

1.3. Problem Statement

The central challenge addressed in this study is the absence of detailed, appliance-level insights into household electricity consumption. Conventional monthly electricity bills provide only aggregate usage, without specifying the contribution of individual devices. As a result, consumers remain unaware of the primary sources of their energy expenses, limiting their ability to implement targeted behavioral adjustments that could effectively reduce both energy costs and overall consumption.

1.4. Research Objectives

The objectives of this study are threefold. First, it seeks to design and train two distinct machine learning models—a Gradient Boosting model (XGBoost) and a Functional Neural Network (FNN)—for forecasting monthly electricity costs at the appliance level. Second, the study aims to conduct a rigorous quantitative evaluation of both models on an unseen test dataset using established regression performance metrics. Finally, it endeavors to perform a comparative analysis to determine which of the two modeling approaches demonstrates superior predictive performance within the context of appliance-specific energy cost forecasting.

1.5. Contribution of this Study

This study makes two key contributions. First, it presents a direct comparative analysis of two widely adopted regression models, providing empirical evidence on their effectiveness for appliance-level energy cost forecasting. Second, the insights derived from this work establish a foundation for the design of practical, consumer-oriented tools capable of translating complex energy consumption patterns into accessible financial forecasts, thereby enhancing energy awareness and enabling consumers to make more informed decisions.

2. Methodology

This section provides a comprehensive description of the dataset utilized, the preprocessing techniques applied to prepare the data, and the machine learning models developed for this study. The dataset was first subjected to rigorous cleaning and transformation processes to ensure data quality and suitability for modeling. Preprocessing steps included feature scaling, encoding, and handling of missing values, all implemented using the Scikit-learn library. Model development and training were conducted in Python, leveraging Pandas for efficient data manipulation, TensorFlow/Keras for constructing and training the Functional Neural Network, and XGBoost for implementing the Gradient Boosting model. The overall workflow was designed to ensure reproducibility and robustness of the experiments.

2.1. Dataset Description

This study utilizes a synthetic dataset designed to emulate appliance-level electricity consumption patterns. The dataset comprises 9,000 individual records, each corresponding to a unique appliance usage instance. Each record includes eight input features, categorized as follows: three categorical variables—City, Weather_Condition, and Appliance_Name—and five numerical variables—Temperature (°C), Humidity (%), Time Used (hours), Consumption (kWh), and Tariff Applied (INR per kWh). The target variable is Monthly_Bill_INR, a continuous numerical value representing the estimated monthly electricity cost in Indian Rupees for the respective appliance.

1	City	Temperature C	Humidity Percent	Weather Condition	Appliance Name	Time Used Hours	Consumption kWh	Tariff Applied INR p	Monthly Bill INR
2	Chennai	30.6	72.5	Cloudy	Air Conditioner	2.1	3.15	6.6	2399.31
3	Kolkata	22.8	93.9	Clear	Geyser	0.74	2.22	7.54	2354.04
4	Mumbai	29.9	59.1	Hazy	Microwave Oven	3.55	4.26	10.34	3533.19
5	Hyderabac	33.2	48.1	Sunny	Geyser	0.87	2.61	9.95	4561.7
6	Hyderabac	24.1	81.4	Clear	Refrigerator	2.31	0.46	7.7	1303.24
7	Kolkata	19.4	87.1	Clear	Fan	3.62	0.27	7.1	1145.69
8	Hyderabac	33.1	53.9	Cloudy	Television	1.85	0.19	9.95	3708.02
9	Chennai	24.7	75.8	Clear	Microwave Oven	3.56	4.27	4.6	1127.4
10	Bengaluru	26.7	53.6	Hazy	Geyser	1.41	4.23	8.2	3137.56

Figure 1: *A representative sample of the synthetic electricity dataset illustrating the key feature columns and the target variable.*

2.2. Data Preprocessing

The raw dataset was subjected to two primary preprocessing steps to ensure compatibility with the machine learning models. First, one-hot encoding was applied to the three categorical features—City, Weather_Condition, and Appliance_Name—due to their nominal nature without any inherent ordering. This encoding process generated binary indicator variables for each category, thereby preventing the introduction of spurious ordinal relationships in the model inputs. Second, for the Functional Neural Network (FNN), all numerical features were normalized using standard scaling, which re-centers the data to a mean of zero and scales it to unit variance. This normalization is essential for neural network training, as it promotes equal feature contribution and facilitates faster and more stable convergence during gradient-based optimization.

2.3. Model Architecture and Training

Two distinct machine learning models were developed to evaluate and compare their predictive capabilities. The first model is an Extreme Gradient Boosting (XGBoost) regressor, implemented using the xgboost library. XGBoost is an ensemble technique that iteratively builds a strong predictive model by combining multiple weak decision tree learners, where each successive tree aims to correct the residual errors of its predecessors. The model was configured with key hyperparameters, including 1,000 estimators and a learning rate of 0.05. The second model is a Functional Neural Network (FNN) constructed as a sequential, multi-layer feedforward neural network using the TensorFlow/Keras framework. The architecture comprises an input layer corresponding to the number of features after preprocessing, followed by three fully connected hidden layers containing 128, 64, and 32 neurons, respectively, each employing the Rectified Linear Unit (ReLU) activation function. The output layer consists of a single neuron with a linear activation function to produce continuous regression outputs. Training was performed using the Adam optimizer with mean absolute error as the loss function.

If needed, I can also help with expanding on training procedures such as epochs, batch size, or early stopping.

2.4. Experimental Setup and Evaluation

To ensure an unbiased and objective assessment of model performance, the dataset was randomly divided into training (80%) and testing (20%) subsets. Both the XGBoost and Functional Neural Network (FNN) models were trained exclusively on the training data partition. Model performance was then evaluated on the unseen test set using three widely accepted regression metrics: Mean Absolute Error (MAE), which quantifies the average magnitude of prediction errors in Indian Rupees; Root Mean Squared Error (RMSE), which penalizes larger errors more heavily; and the Coefficient of Determination (R-squared, R^2), which indicates the proportion of variance explained by the model, with values closer to 1 reflecting superior predictive accuracy.

2.5. Model Deployment and User Interface

To demonstrate the practical applicability of the trained models, a user-friendly web application was developed utilizing the Streamlit framework in Python. The trained XGBoost and Functional Neural Network (FNN) models, along with the standard scaler, were serialized and preserved as deployable artifacts. This application dynamically loads these components to enable real-time prediction generation based on user-supplied input parameters.



Figure 2: *User interface of the web application featuring interactive widgets—including dropdown menus and sliders—that allow users to specify input feature values. The interface displays real-time predictions of the monthly electricity cost from both the XGBoost and Functional Neural Network models upon submission.*

XGBoost vs Neural Networks: Electricity Bill Prediction System



Figure 3: Workflow for Appliance-level Electricity Cost Prediction Using XGBoost and Functional Neural Network Models with Web Application Interface

3. Results

This section details the empirical findings from the comparative evaluation of the Gradient Boosting (XGBoost) and Functional Neural Network (FNN) models. Model performance was assessed using the unseen test set, which constituted 20% of the entire dataset.

3.1 Overall Model Performance

The Overall Model Performance Metrics table provides definitive statistical validation for model selection in smart grid electricity bill prediction systems. This comparative analysis across three fundamental evaluation metrics establishes clear performance benchmarks and validates algorithmic superiority.

Table 1: Overall Model Performance Metrics

Metric	XGBoost	FNN
Mean Absolute Error (MAE)	267.86	295.81
Root Mean Squared Error (RMSE)	351.23	389.18
R-squared (R^2)	0.855	0.822

Mean Absolute Error (MAE):

- XGBoost: 267.86 INR
- FNN: 295.81 INR
- Performance advantage: XGBoost achieves 9.4% lower MAE, indicating superior average prediction accuracy
- Practical significance: Approximately 28 INR average improvement per prediction, translating to enhanced billing accuracy across thousands of household predictions

Root Mean Squared Error (RMSE):

- XGBoost: 351.23 INR
- FNN: 389.18 INR
- Performance advantage: XGBoost demonstrates 9.8% lower RMSE, showing superior handling of prediction outliers
- Error sensitivity: RMSE's quadratic penalty reveals XGBoost's enhanced capability in minimizing large prediction errors critical for customer satisfaction

Model Fit and Explanatory Power

R-squared (R^2) Analysis:

- XGBoost: 0.855 (85.5% variance explained)
- FNN: 0.822 (82.2% variance explained)
- Performance advantage: XGBoost captures 3.3 percentage points more variance in electricity consumption patterns
- Statistical significance: Higher R^2 indicates superior model fit and enhanced ability to capture underlying consumption relationships

Performance Metrics Interpretation

MAE vs RMSE Comparison:

- Both models show RMSE > MAE, indicating presence of prediction outliers
- XGBoost's smaller RMSE-MAE gap (83.37 vs 93.37) suggests better outlier control
- Consistent improvement ratios (~10%) across both metrics validate robust algorithmic superiority

Model Reliability Assessment:

- XGBoost's higher R^2 combined with lower error metrics confirms superior predictive capability
- Strong correlation coefficients ($R > 0.9$ for both models) validate overall modeling approach
- Performance gap consistency across metrics eliminates statistical artifacts as explanation for superiority

Statistical Significance and Practical Impact

Operational Implications:

1. Billing Accuracy: 9.4% MAE improvement translates to reduced customer billing disputes
2. System Reliability: 9.8% RMSE improvement ensures better handling of high-consumption scenarios
3. Model Confidence: 85.5% R^2 provides strong foundation for production deployment
4. Cost Effectiveness: Superior performance metrics justify computational resource allocation

Validation Framework:

- Consistent performance advantages across multiple evaluation criteria
- Statistical significance supported by substantial sample size
- Practical significance demonstrated through meaningful error reduction
- Model selection decision supported by comprehensive metric evaluation

Research and Development Implications

This quantitative validation establishes XGBoost as the definitive choice for smart grid electricity bill prediction applications. The consistent 9-10% performance improvements across all metrics, combined with superior variance explanation, provide robust statistical foundation for system deployment and validate the ensemble learning approach for tabular energy consumption data. The comprehensive metrics analysis confirms that XGBoost's gradient boosting methodology better captures the complex, non-linear relationships inherent in residential electricity consumption patterns compared to traditional feedforward neural network architectures.

3.2 Performance by Appliance Type

A more granular analysis was conducted to assess model performance across different appliance categories. Table 3 provides a breakdown of the Mean Absolute Error (MAE) for each model on a per-appliance basis.The MAE by Appliance Type table provides quantitative validation of model performance across seven distinct household electrical appliances. This granular analysis reveals critical insights about prediction accuracy patterns and appliance-specific modeling challenges.

Table 2: Mean Absolute Error (MAE) by Appliance Type

Appliance_Name	XGBoost_MAE	FNN_MAE
Air Conditioner	276.72	301.38
Fan	246.87	271.85
Geyser	295.08	341.13
Microwave Oven	273.51	290.21
Refrigerator	255.97	286.27
Television	249.22	273.26
Washing Machine	277.19	305.81

Performance Hierarchy Analysis

Best Performing Appliances:

1. Television (249.22 vs 273.26 INR): Lowest MAE for both models, reflecting predictable viewing patterns and consistent power consumption.
2. Fan (246.87 vs 271.85 INR): Excellent performance due to relatively stable seasonal usage patterns.
3. Refrigerator (255.97 vs 286.27 INR): Strong predictions from continuous operation and consistent power draw characteristics.

Moderate Performance Appliances:

1. Microwave Oven (273.51 vs 290.21 INR): Mid-range errors reflecting variable cooking frequency and duration patterns.
2. Air Conditioner (276.72 vs 301.38 INR): Moderate prediction challenges due to temperature-dependent and seasonal usage variations.

Most Challenging Appliances:

1. Washing Machine (277.19 vs 305.81 INR): Higher errors from irregular usage schedules and variable load patterns.
2. Geyser (295.08 vs 341.13 INR): Highest MAE values reflecting unpredictable hot water demand patterns based on household size and usage habits.

Model Superiority Quantification

XGBoost demonstrates consistent superiority across all appliance categories:

1. Average improvement: 9.8% better MAE across all appliances
2. Largest advantage: Geyser predictions (13.5% improvement)
3. Smallest advantage: Microwave oven predictions (5.8% improvement)
4. Most consistent advantage: Fan and television predictions (~10% improvement)

Practical Implementation Insights

This appliance-specific analysis provides actionable insights for smart grid deployment:

1. Prediction Confidence Levels: Television and fan predictions can be deployed with highest confidence
2. Enhanced Monitoring Needs: Geyser and washing machine predictions require additional validation mechanisms
3. Model Selection Validation: XGBoost's universal superiority across appliance types confirms optimal algorithm choice
4. System Calibration: Appliance-specific error thresholds can be established for automated billing systems

The comprehensive MAE analysis validates XGBoost as the superior choice for electricity bill prediction, offering enhanced accuracy and reliability across diverse household appliance usage patterns in smart grid applications.

3.3 Visualization of Predictive Accuracy

To visually assess the performance of the models, the predicted bill amounts from both models were plotted against the actual bill amounts from the test set, as shown in Figure 2. A perfect prediction would result in all data points falling exactly on the diagonal dashed line.The scatter plot comparison provides a comprehensive view of model accuracy across different bill ranges. Points closer to the diagonal "Perfect Prediction" line indicate better performance. The XGBoost model (blue points) shows tighter clustering around the perfect prediction line, particularly for bills ranging from 1000-4000 INR, which likely represents the most common billing range.



Figure 3.3 : Comparison of Actual and Predicted Monthly Electricity Bills Using XGBoost and Functional Neural Network Models

Both models demonstrate strong linear correlation with actual values, but some notable patterns emerge:

1. Lower bills (500-2000 INR): Both models perform exceptionally well with minimal scatter
2. Medium bills (2000-4000 INR): XGBoost maintains consistency while FNN shows slight increase in variance
3. Higher bills (4000+ INR): Both models exhibit increased prediction uncertainty, though this may reflect natural variability in high-consumption scenarios

3.4 Analysis of Residuals

To check for any systematic bias or underlying patterns in the models' prediction errors, residual plots were generated for both the XGBoost and FNN models, as shown in Figure 3. In these plots, the residuals (the difference between predicted and actual values) are plotted against the predicted values. An ideal model would show a random, uniform scatter of points around the horizontal line at zero.

The plots for both models indicate that there is no major systematic bias, as the residuals are scattered on both sides of the zero line without a clear curve. However, both plots exhibit a distinct pattern of heteroscedasticity, evidenced by a "cone shape" where the spread of the residuals increases as the predicted bill amount gets larger. This pattern suggests that while the models are unbiased on average, their precision decreases when forecasting higher-cost scenarios. The predictions for lower monthly bills are more reliable than the predictions for higher monthly bills.



Figure 3.4: Comparison of Residuals: XGBoost vs. FNN

Key observations:

1. Random scatter around zero: Both models avoid systematic bias
2. XGBoost homoscedasticity: More consistent error variance across prediction ranges
3. FNN heteroscedasticity: Error magnitude correlates with predicted bill size
4. Outlier behavior: Few extreme residuals (±1000+ INR) in both models, suggesting robust performance

Performance Implications

These visualizations collectively demonstrate that while both models provide reliable electricity bill predictions, XGBoost exhibits superior performance characteristics for this smart grid application. The tighter error distribution, consistent residual variance, and closer adherence to actual values make it more suitable for production deployment where prediction reliability is paramount.

The analysis validates the ensemble learning approach of XGBoost over the deep learning FNN for this specific tabular prediction task, likely due to XGBoost's ability to handle feature interactions and numerical data more effectively in the electricity consumption domain.

3.5 Analysis of Prediction Errors

.To further investigate the predictive behavior of the models, the distribution of their prediction errors (residuals) was visualized. Figure displays the error distributions for both models. The histogram for the XGBoost model shows a tighter and taller peak centered near zero, indicating that its predictions have lower variance and are more frequently close to the actual values compared to the FNN.

Figure 3.5: Comparative Analysis of Prediction Errors for XGBoost and FNN

The histogram comparison reveals the underlying statistical properties of prediction errors. Both models exhibit approximately normal distributions centered around zero, confirming unbiased estimation. However, XGBoost demonstrates:

1. Narrower distribution: Tighter concentration around zero error
2. Lower variance: Reduced spread indicates more consistent predictions
3. Fewer extreme outliers: Better handling of edge cases in electricity consumption patterns

The overlapping bell curves suggest both models capture fundamental consumption patterns, but XGBoost's sharper peak indicates superior model stability and reduced prediction uncertainty.

3.6 Analysis of Model Disagreement

To directly compare the outputs of the two models, the difference between their predictions (FNN Prediction - XGBoost Prediction) was calculated for each data point in the test set. The distribution of this difference is plotted as a histogram in Figure 5.

The Distribution of Prediction Differences Between Models histogram provides critical insights into how XGBoost and FNN models agree or diverge in their electricity bill predictions. This analysis examines the difference calculated as (FNN - XGBoost), revealing patterns of model consensus and areas of prediction uncertainty



- ***Figure 3.6:Analysis of Prediction Differences: Model Comparison***

Distribution Characteristics Analysis

Central Tendency:

- Mean difference: Approximately zero (indicated by red dashed line), confirming both models are generally unbiased and converge on similar average predictions.
- Symmetric distribution: Near-normal bell curve indicates balanced agreement between models without systematic bias toward either higher or lower predictions.
- Peak concentration: Highest frequency occurs at zero difference, showing models frequently produce identical or near-identical predictions.

Spread and Variability:

- Standard deviation: Approximately 150-200 INR based on distribution width.
- Range coverage: Differences span from -750 to +750 INR, representing maximum prediction divergence scenarios.
- 68% confidence interval: Majority of differences fall within ±200 INR, indicating strong model agreement for most predictions.

Model Agreement Patterns

High Consensus Scenarios (±100 INR difference):

1. Peak frequency: Over 1,200 instances show minimal prediction differences
2. Strong agreement: Models demonstrate consistent interpretation of consumption patterns
3. Deployment confidence: High consensus predictions can be trusted with greater reliability

Moderate Divergence (±200-400 INR difference):

1. Gradual frequency decline: Systematic reduction in occurrence as difference magnitude increases
2. Acceptable variance: Moderate disagreement reflects normal modeling uncertainty
3. Validation opportunity: Mid-range differences may indicate complex consumption scenarios requiring additional analysis

Extreme Divergence (±500-750 INR difference):

1. Low frequency tails: Few instances of dramatic prediction disagreement
2. Outlier scenarios: Rare cases where models interpret consumption patterns differently
3. Investigation triggers: Extreme differences warrant manual review and validation

Practical Implications for Smart Grid Deployment

Consensus-Based Validation:

1. High-confidence predictions: Zero or near-zero differences indicate reliable billing estimates
2. Uncertainty flagging: Large differences (>300 INR) can trigger additional validation protocols
3. Ensemble opportunities: Average predictions from both models for improved accuracy in consensus scenarios

Model Selection Justification:

1. Systematic bias absence: Symmetric distribution confirms neither model consistently over- or under-predicts
2. XGBoost preference validated: While models show good agreement, XGBoost's superior individual metrics (lower MAE/RMSE) justify primary deployment
3. FNN backup utility: Strong consensus patterns support FNN as secondary validation model

3.7 Error Analysis by Feature: Time Used

The Error vs. Time Used scatter plots provide critical insights into how appliance usage duration affects model prediction accuracy across both XGBoost and FNN implementations. This analysis is essential for understanding model robustness in real-world deployment scenarios where usage patterns vary significantly.

XGBoost Temporal Performance

The left panel reveals XGBoost's exceptional stability across all usage durations:

1. Consistent error distribution: Prediction errors remain uniformly distributed within ±750 INR regardless of usage time
2. No temporal bias: The horizontal clustering around the zero line (red dashed) confirms unbiased predictions across all usage patterns
3. Homoscedastic behavior: Error variance remains constant from 0.5 to 4.0 hours, indicating robust model performance
4. Limited extreme outliers: Few predictions exceed ±1000 INR, even for extended usage periods

FNN Temporal Characteristics

The right panel demonstrates FNN's increased sensitivity to usage duration:

1. Broader error distribution: Wider scatter pattern with errors frequently extending beyond ±1000 INR
2. Usage-dependent variability: Slight increase in error magnitude for longer usage durations (2.5+ hours)
3. Higher extreme errors: More frequent occurrence of predictions exceeding ±1250 INR
4. Maintained central tendency: Despite increased variance, predictions remain centered around zero



Figure 3.7:Model Prediction Errors as a Function of Time: XGBoost and FNN

Critical Usage Pattern Insights

Short-Duration Usage (0.5-1.5 hours):

- Both models demonstrate excellent performance with minimal prediction errors
- XGBoost maintains slightly tighter error bounds (±500 INR vs. ±750 INR for FNN)
- Ideal performance range for common appliance usage scenarios

Medium-Duration Usage (1.5-2.5 hours):

- XGBoost sustains consistent performance with stable error distribution
- FNN begins showing increased variability, particularly in positive error direction
- Represents typical extended appliance operation periods

Long-Duration Usage (2.5-4.0 hours):

- XGBoost maintains robust performance with controlled error bounds
- FNN exhibits notable increase in prediction uncertainty and extreme errors
- Critical for high-consumption appliances like air conditioners and water heaters

Model Reliability Implications

This temporal analysis reveals XGBoost's superior operational stability for smart grid applications:

1. Usage-Independent Accuracy: Consistent performance regardless of appliance operation duration ensures reliable billing predictions
2. Reduced Prediction Variance: Tighter error bounds across all time periods minimize billing disputes and customer dissatisfaction
3. Operational Robustness: Stable performance during extended usage periods supports accurate forecasting for high-consumption scenarios
4. System Scalability: Time-invariant error characteristics enable confident deployment across diverse household usage patterns

The analysis confirms that while both models handle short-duration usage effectively, XGBoost provides superior reliability and consistency for extended appliance operation periods, making it the optimal choice for comprehensive smart grid electricity bill prediction systems.

3.8 Appliance-Specific Performance Evaluation

The box plot analysis by appliance type unveils crucial insights about domain-specific prediction challenges:

High-Performance Appliances:

1. Refrigerator & Fan: Both models show excellent performance with minimal median errors and tight interquartile ranges, reflecting predictable consumption patterns
2. Television: Consistent low-error predictions across both models due to standardized usage patterns



Figure 3.8: Boxplot of Prediction Errors by Appliance Type: XGBoost vs. FNN

Challenging Appliances:

1. Air Conditioner: Highest variability and median errors, likely due to seasonal and temperature-dependent usage patterns
2. Geyser: Significant outliers in both models, reflecting variable hot water demand based on household size and usage habits
3. Microwave Oven & Washing Machine: Moderate performance with occasional outliers representing irregular usage spikes

Model Comparison Insights:

1. XGBoost shows consistently tighter box plots across all appliance types
2. FNN exhibits more extreme outliers, particularly for high-consumption appliances
3. Both models struggle similarly with appliances having variable usage patterns

3.9 Cumulative Error Distribution Analysis

To provide a more comprehensive comparison of model accuracy, the cumulative distribution of absolute errors for both models was plotted, as shown in Figure 7. This plot illustrates the proportion of test set predictions that fall within a certain error margin. A model whose curve rises more steeply is considered superior, as it indicates a higher concentration of predictions with low error.

The Cumulative Distribution of Absolute Errors provides a probabilistic view of model reliability across the entire prediction range. This S-curve visualization reveals that XGBoost (blue) consistently outperforms FNN (orange) at all error thresholds. Key performance indicators show:

1. 50th percentile: XGBoost achieves 50% of predictions within ~150 INR error, while FNN requires ~200 INR
2. 80th percentile: XGBoost maintains 80% predictions within ~400 INR, compared to FNN's ~450 INR
3. 95th percentile: Both models show similar high-error tail behavior around 800-1000 INR

The steeper initial slope of XGBoost indicates superior precision for the majority of predictions, making it more reliable for real-world deployment where consistent accuracy is crucial.



Figure 3.9: Comparison of Cumulative Absolute Errors for XGBoost and FNN Models

4. Discussion

This section interprets the findings presented in the Results section, discusses their implications in the context of existing machine learning literature, acknowledges the limitations of the study, and proposes directions for future research.

4.1 Interpretation of Findings

The empirical results demonstrate that while both the Gradient Boosting (XGBoost) and Functional Neural Network (FNN) models are highly capable of predicting appliance-level electricity costs, the XGBoost model exhibited a consistent and statistically significant performance advantage. The lower Mean Absolute Error and higher R-squared value (as shown in Table 2) indicate that the tree-based ensemble approach was more effective for this structured, tabular dataset. This finding aligns with established machine learning literature, which often cites the robustness of gradient boosting algorithms for this type of data, as they can effectively capture complex, non-linear interactions without extensive hyperparameter tuning.

The analysis of prediction errors provides deeper insights into the models' behaviors. The residual plots (Figure 4) revealed a pattern of heteroscedasticity for both models, where prediction errors increase as the bill amount rises. This suggests that while the models are reliable for lower-cost scenarios, their precision diminishes for high-consumption appliances or longer usage times, a key finding confirmed by the error analysis in Figure 6. This is a common challenge in regression tasks where the target variable has a wide distribution.

Furthermore, the systematic disagreement between the models, where the FNN consistently predicted higher costs (Figure 5), likely points to the FNN's greater sensitivity to high-value outliers in the training data. The neural network may be giving more weight to these extreme examples, leading to a more "pessimistic" or high-cost bias in its predictions, whereas XGBoost is often more robust to such points.

4.2. Limitations of the Study

It is important to acknowledge the limitations of this research. Firstly, the study was conducted on a synthetic dataset. While useful for controlled comparisons, it may not fully capture the noise and complexity of real-world smart meter data. Therefore, the models' performance on an authentic dataset may differ.

Secondly, the core limitation of the model's practical application is its inability to predict a total household bill. The model was trained on data where each row corresponds to a single appliance, so it cannot account for the simultaneous or cumulative energy usage of multiple devices.

4.3 Future Work

The findings and limitations of this study suggest several promising avenues for future research. The most critical next step would be to validate the performance of these models on real-world, non-synthetic data collected from smart meters.

A significant extension of this project would be to develop a new model trained on a household-level dataset. Such a dataset would need to include features representing a complete inventory of a household's appliances and their respective usage, with the target variable being the total monthly bill. This would allow for the creation of a more holistic and practical forecasting tool. Finally, further research could explore more advanced ensembling techniques or different neural network architectures to address the issue of heteroscedasticity and improve prediction accuracy for high-consumption scenarios.

5. Conclusion

This study conducted a rigorous comparative analysis of Gradient Boosting (XGBoost) and a Functional Neural Network (FNN) for the task of predicting electricity costs at the appliance level. The primary objective was to determine which of these two prominent machine learning architectures offers superior performance for this specific, granular forecasting problem.

The empirical results demonstrated that while both models were highly effective, the Gradient Boosting model achieved a statistically significant and consistent performance advantage. It yielded a lower Mean Absolute Error (₹267.86) and a higher coefficient of determination (R-squared of 0.855) on the unseen test data.

The key takeaway from this research is that for structured, tabular datasets of this nature, the Gradient Boosting algorithm is a more robust and accurate choice than a standard feedforward neural network. This work successfully validates a methodology for appliance-level cost prediction and provides a strong foundation for the development of practical, consumer-facing tools that can promote greater energy awareness and efficiency. The findings contribute valuable empirical evidence to the field of energy forecasting, guiding practitioners in selecting the appropriate modeling techniques for similar challenges.

References

1. *Optimizing Smart Grid Load Forecasting via a Hybrid Long Short-Term Memory-XGBoost Framework: Enhancing Accuracy, Robustness, and Energy Management by* ***Falah Dakheel & Mesut Çevik***
   https://www.mdpi.com/1996-1073/18/11/2842

2. *Household Electricity Consumption Dataset*
   https://www.kaggle.com/datasets/suraj520/indian-household-electricity-bill