

Name: Rishi Tiku

Class: SE DS

Subject: DAA LAB

UID: 2021700067

Experiment – 4

Aim: To implement Dynamic Programming technique on LCS – Longest Common Subsequence Problem.

Theory:

The longest common subsequence (LCS) is defined as the longest subsequence that is common to all the given sequences, provided that the elements of the subsequence are not required to occupy consecutive positions within the original sequences.

If S_1 and S_2 are the two given sequences then, Z is the common subsequence of S_1 and S_2 if Z is a subsequence of both S_1 and S_2 . Furthermore, Z must be a strictly increasing sequence of the indices of both S_1 and S_2 .

In a strictly increasing sequence, the indices of the elements chosen from the original sequences must be in ascending order in Z .

Algorithm:

1) Naïve:

function LCS(S , T)

 if S is empty or T is empty then

 return empty string

 if first char of S == first char of T then

return (first char of S) + LCS(S - first char, T - first char)

otherwise // first chars are different

return longer of LCS(S - first char, T) and LCS(S, T - first char)

2) Dynamic Programming

- Create a 2D array `dp[][]` with rows and columns equal to the length of each input string plus 1 [the number of rows indicates the indices of S1 and the columns indicate the indices of S2].
- Initialize the first row and column of the dp array to 0.
- Iterate through the rows of the dp array, starting from 1 (say using iterator `i`).
- For each `i`, iterate all the columns from `j = 1` to `n`:
- If `S1[i-1]` is equal to `S2[j-1]`, set the current element of the dp array to the value of the element to `(dp[i-1][j-1] + 1)`.
- Else, set the current element of the dp array to the maximum value of `dp[i-1][j]` and `dp[i][j-1]`.
- After the nested loops, the last element of the dp array will contain the length of the LCS

Code:

```
#include <stdio.h>
#include <string.h>

int i, j, m, n, LCS_table[20][20];
char S1[20], S2[20];

void print()
{
    printf("\t");
    for(int k = 0; k<=n; k++)
        printf(" \t%c", S2[k]);
    printf("\n\n");
    for(int k = 0; k<=n; k++)
        printf("\t%d", LCS_table[k][0]);
    printf("\n\n");

    for(int k = 1; k<=m; k++)
    {
        printf("%c\t", S1[k-1]);
        for(int l = 0; l<=n; l++)
```

```

    {
        printf("%d\t", LCS_table[k][1]);
    }
    printf("\n\n");
}
}

void lcsAlgo() {
    m = strlen(S1);
    n = strlen(S2);

    // Filling 0's in the matrix
    for (i = 0; i <= m; i++)
        LCS_table[i][0] = 0;
    for (i = 0; i <= n; i++)
        LCS_table[0][i] = 0;

    // Building the matrix in bottom-up way
    for (i = 1; i <= m; i++)
        for (j = 1; j <= n; j++) {
            if (S1[i - 1] == S2[j - 1]) {
                LCS_table[i][j] = LCS_table[i - 1][j - 1] + 1;
            } else if (LCS_table[i - 1][j] >= LCS_table[i][j - 1]) {
                LCS_table[i][j] = LCS_table[i - 1][j];
            } else {
                LCS_table[i][j] = LCS_table[i][j - 1];
            }
        }

    int index = LCS_table[m][n];
    char lcsAlgo[index + 1];
    lcsAlgo[index] = '\0';

    print();
    int i = m, j = n;
    while (i > 0 && j > 0) {
        if (S1[i - 1] == S2[j - 1]) {
            lcsAlgo[index - 1] = S1[i - 1];
            i--;
            j--;
            index--;
        }
    }
}

```

```

        else if (LCS_table[i - 1][j] > LCS_table[i][j - 1])
            i--;
        else
            j--;
    }

    // Printing the sub sequences
    printf("S1 : %s \nS2 : %s \n", S1, S2);
    printf("LCS: %s", lcsAlgo);
}

int main() {
    printf("Enter the first String.\n");
    scanf("%s", S1);
    printf("Enter the second String.\n");
    scanf("%s", S2);
    lcsAlgo();
    printf("\n");
}

```

Output:

Enter the first String.

Rishi

Enter the second String.

Shashi

		S	h	a	s	h	i
	0	0	0	0	0	0	0
R	0	0	0	0	0	0	0
i	0	0	0	0	0	0	1
s	0	0	0	0	1	1	1
h	0	0	1	1	1	2	2
i	0	0	1	1	1	2	3

S1 : Rishi

S2 : Shashi

LCS: shi

Enter the first String.

101010

Enter the second String.

1001001

		1	0	0	1	0	0	1
	0	0	0	0	0	0	0	0
1	0	1	1	1	1	1	1	1
0	0	1	2	2	2	2	2	2
1	0	1	2	2	3	3	3	3
0	0	1	2	3	3	4	4	4
1	0	1	2	3	4	4	4	5
0	0	1	2	3	4	5	5	5

S1 : 101010

S2 : 1001001

LCS: 10010

Conclusion:

Dynamic Programming technique is implemented for LCS problem. Its time complexity is $O(m * n)$ which is much faster than naive solution $O(2^n)$.