Practical – 8

AIM: Apply FP oriented estimation model for selected application.

Step 1: Identify the Functional Components

External Inputs (EI) – Inputs from the user:

- User login
- User registration
- Data entry
- Updating data

Total EI = 4

External Outputs (EO) – Outputs generated by the system:

- Generate report
- Display user details
- Dashboard statistics

Total EO = 3

User Inquiries (UI) – Interactive data retrieval:

- Search
- Filter

Total UI = 2

Internal Logical Files (ILF) – Internal databases:

- User database
- Activity log
- System configuration/settings

Total ILF = 3

External Interface Files (EIF) – External data sources used:

• External authentication system

Total EIF = 1

Step 2: Assign Weights

(Assumed complexity = average unless stated)

Component Type	Count	Complexity	Weight	Total
EI	4	Average	5	20
ЕО	3	Average	5	15
UI	2	Low	4	8
ILF	3	Average	10	30
EIF	1	Average	7	7

Step 3: Calculate Unadjusted Function Points (UFP)

$$UFP = 20 + 15 + 8 + 30 + 7 = 80$$

Step 4: Apply Value Adjustment Factor (VAF)

Assume VAF = 1.1 (based on general system characteristics)

Step 5: Calculate Adjusted Function Points (AFP)

$$AFP = UFP \times VAF = 80 \times 1.1 = 88$$

Step 6: Estimate Effort

Assume Productivity rate = 20 function points/person-month

Effort = AFP / Productivity rate = $88 / 20 = 4.4 \approx 4$ person-months