MATGEO: 7-7.2-19

Al24BTECH11020 - Rishika Kotha

November 5, 2024

Question

Equation of the circle with centre on the Y axis and passing through the origin and the point (2, 3) is

$$3x^2 + 3y^2 - 13y = 0$$

$$3x^2 + 3y^2 + 13x + 3 = 0$$

$$36x^2 + 6y^2 - 13x = 0$$

$$x^2 + y^2 + 13x + 3 = 0$$

(MATGEO 7-7.2-19)

Solution: Theory

parameter	Description	value
С	Centre	$\begin{pmatrix} 0 \\ 13/6 \end{pmatrix}$
0	point1	$\begin{pmatrix} 0 \\ 0 \end{pmatrix}$
Р	point2	$\binom{2}{3}$
r	radius	13/6

Given Data

From the given information,

$$x_1 = \begin{pmatrix} 2 \\ 3 \end{pmatrix}, x_2 = \begin{pmatrix} 0 \\ 0 \end{pmatrix}, n = \begin{pmatrix} 1 \\ 0 \end{pmatrix}, c = 0 \tag{1}$$

$$\begin{pmatrix} 4 & 6 & 1 \\ 0 & 0 & 1 \\ -1 & 0 & 0 \end{pmatrix} \begin{pmatrix} u \\ f \end{pmatrix} = \begin{pmatrix} -13 \\ 0 \\ 0 \end{pmatrix}$$
 (2)

The augmented matrix is expressed as

$$\begin{pmatrix}
4 & 6 & 1 & | & -13 \\
0 & 0 & 1 & | & 0 \\
-1 & 0 & 0 & | & 0
\end{pmatrix}$$
(3)




Row Operations

performing sequences of row operations to transform into Echelon form

$$\underbrace{R_1 \to R_1/4, R_2 \to R_2/-6}_{\text{0 0 1}} \begin{pmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & -13/6 \\ 0 & 0 & 1 & 0 & 0 \end{pmatrix} (6)$$

$$u = \begin{pmatrix} 0 \\ -13/6 \end{pmatrix}, f = 0 \tag{7}$$

Graph



C-Code

```
1 #include <stdio.h>
2 int main() {
     float centerX = 0.0f, centerY = 2.1667f;
     float radius = 2.1667f;
     float points[2][2] = { {0.0f, 0.0f}, {2.0f, 3.0f} }:
     float *center = &centerX;
     float *radiusPtr = &radius:
     float (*pointsPtr)[2] = points;
     FILE *file = fopen("data.txt", "w");
     if (file == NULL) {
         perror("Error opening file"):
         return 1:}
     fprintf(file, "Center: %.4f, %.4f\n", *center, *(center + 1));
     fprintf(file, "Radius: %.4f\n", *radiusPtr);
     fprintf(file, "Points: (%.1f, %.1f), (%.1f, %.1f)\n",
             pointsPtr[0][0], pointsPtr[0][1], pointsPtr[1][0], pointsPtr[1][1]);
     fclose(file):
     printf("Data written to data.txt successfully.\n");
     return 0:
```

Python Code

```
1 import numpy as no
2 import matplotlib.pvplot as plt
3 def read data(file name):
      with open(file name, 'r') as file:
          lines = file.readlines()
      center = tuple(map(float, lines[0].strip().split(':')[1].strip().split('.')))
      radius = float(lines[1].strip().split(':')[1].strip())
      points line = lines[2].strip().split(':')[1].strip()
      points = [tuple(map(float, p.strip(), strip('()'), split(','))) for p in points line.split(').
      return center, radius, points
11 center, radius, points = read_data('data.txt')
12 theta = np.linspace(0, 2 * np.pi, 100)
13 x circle = radius * np.cos(theta) + center[0]
14 v circle = radius * np.sin(theta) + center[1]
15 plt.figure(figsize=(8, 8))
16 plt.plot(x circle, y circle, label='Circle', color='blue')
17 plt.scatter(center[0], center[1], color='purple', label=f'Center {center}')
18 for point in points:
      plt.scatter(*point, label=f'Point {point}')
20 for point in points:
      plt.plot([center[0], point[0]], [center[1], point[1]], color='orange', linestyle='--')
      mid_x = (center[0] + point[0]) / 2
      mid v = (center[1] + point[1]) / 2
      plt.text(mid x. mid v. f' Radius = {radius:.2f}'. fontsize=10. color='orange'.
  verticalalignment='bottom')
25 for point in points:
      plt.text(point[0], point[1], f' {point}', fontsize=10, verticalalignment='bottom',
  horizontalalignment='right')
27 plt.axis('equal')
28 plt.xlim(center[0] - radius - 1, center[0] + radius + 1)
29 plt.ylim(center[1] - radius - 1, center[1] + radius + 1)
30 plt.axhline(0, color='black', linewidth=0.5, ls='--')
31 plt.axvline(0, color='black', linewidth=0.5, ls='--')
32 plt.xlabel('X-axis')
33 plt.vlabel('Y-axis')
34 plt.legend()
35 plt.arid()
36 plt.show()
```