

# Toast

Toast The <ava-toast> system provides a comprehensive notification solution with multiple variants, flexible positioning, smooth animations, and action buttons. Built around a service-based architecture, it offers both simple and advanced toast configurations for various user feedback scenarios.

**How to use** ■ **import** { AavaToastService } from "@aava/play-core"; // Inject the service constructor ( private toastService : AavaToastService ) { } // Show different types of toasts this . toastService . success ( { message : 'Operation completed!' } ) ; this . toastService . error ( { message : 'Something went wrong!' } ) ;

**Basic Usage** ■ **Simple** toast notifications with default configurations. Angular Preview Code < aava-button label = " Show Success Toast " variant = " success " (userClick) = " showSuccessToast() " > </ aava-button > // Inject the toast service in your component constructor ( private toastService : ToastService ) { } // Show different types of toasts showSuccessToast ( ) { this . toastService . success ( { title : 'Successfully created!' , message : 'Your changes have been saved successfully' , duration : 2000 , customWidth : '400px' , design : 'modern' , size : 'large' , } ) ; }

**Variants** ■ Six distinct toast variants for different notification types and user feedback scenarios. Angular Preview Code < aava-button label = " Show Success Toast " variant = " success " (userClick) = " showSuccessToast() " > </ aava-button > < aava-button label = " Show Error Toast " variant = " danger " (userClick) = " showErrorToast() " > </ aava-button > < aava-button label = " Show Warning Toast " variant = " warning " (userClick) = " showWarningToast() " > </ aava-button > < aava-button label = " Show Info Toast " variant = " info " (userClick) = " showInfoToast() " > </ aava-button > < aava-button label = " Show Default Toast " variant = " secondary " (userClick) = " showDefaultToast() " > </ aava-button > // Inject the toast service in your component constructor ( private toastService : ToastService ) { } // Show different toast variants showSuccessToast ( ) { this . toastService . success ( { title : 'Successfully created!' , message : 'Your changes have been saved successfully' , duration : 2000 , customWidth : '300px' , design : 'modern' , size : 'small' , } ) ; } showErrorToast ( ) { this . toastService . error ( { title : 'Error Occurred' , message : 'Connection error. Unable to connect to the server at present' , duration : 2000 , customWidth : '300px' , design : 'modern' , size : 'small' , } ) ; } showWarningToast ( ) { this . toastService . warning ( { title : 'Warning Occurred' , message : 'Please review your input carefully before proceeding.' , duration : 2000 , customWidth : '300px' , design : 'modern' , size : 'small' , } ) ; } showInfoToast ( ) { this . toastService . info ( { title : 'Action Required' , message : 'Please review your input carefully before proceeding.' , duration : 2000 , customWidth : '300px' , design : 'modern' , size : 'small' , } ) ; } showDefaultToast ( ) { this . toastService . default ( { title : 'Default Toast Occurred' , message : 'This is a default toast with neutral styling.' , duration : 2000 , customWidth : '300px' , design : 'modern' , size : 'small' , } ) ; } showCustomToast ( ) { this . toastService . custom ( { title : 'Custom Toast' , message : 'This is a fully customizable toast with unique styling.' , customBackground : 'var(--color-primary)' , customTextColor : 'var(--color-text-primary)' , customWidth : '300px' , design : 'modern' , size : 'small' , } ) ; }

**Available Variants** ■ Success - Green styling for successful operations and confirmations Error - Red styling for errors and critical issues Warning - Orange/yellow styling for warnings and cautions Info - Blue styling for informational messages and tips Default - Neutral styling for general notifications Custom - Fully customizable styling and content

**Sizes** ■ Three size variants to accommodate different content lengths and interface requirements. Angular Preview Code < aava-button label = " Show Small Success " variant = " success " size = " small " (userClick) = " showSmallSuccess() " > </ aava-button > < aava-button label = " Show Medium Warning " variant = " warning " size = " small " (userClick) = " showMediumWarning() " > </ aava-button > < aava-button label = " Show Large Success " variant = " danger " size = " small " (userClick) = " showLargeError() " > </ aava-button > // Inject the toast service in your component constructor ( private toastService : ToastService ) { } // Show different toast sizes showSmallSuccess ( ) { this . toastService . success ( { title : 'Successfully created!' , message : 'Your changes have been saved successfully' , duration : 1000 , customWidth : '300px' , design : 'modern' , size : 'small' , } ) ; } showMediumWarning ( ) { this . toastService . warning ( { title : 'Action Required' , message : 'Incomplete fields.Please fill in all required information.' , duration : 1000 , customWidth : '350px' , design :

```

'modern' , size : 'medium' , } ) ; } showLargeError ( ) { this . toastService . error ( { title : 'Error Occurred' ,
message : 'Connection error. Unable to connect to the server at present' , duration : 1000 , customWidth :
'400px' , design : 'modern' , size : 'large' , } ) ; } Available Sizes ■ Small - Compact size for minimal content and
dense interfaces Medium - Standard size for most notification scenarios (default) Large - Prominent size for
important messages and detailed content Service Methods ■ The ToastService provides convenient methods
for different toast types: Success Toast ■ this . toastService . success ( { title : "Success!" , message :
"Operation completed successfully." , duration : 4000 , showCloseButton : true , } ) ; Error Toast ■ this .
toastService . error ( { title : "Error!" , message : "Something went wrong. Please try again." , showRetryButton :
true , retryButtonText : "Retry" , } ) ; Warning Toast ■ this . toastService . warning ( { title : "Warning" , message :
"Please review the information carefully." , showActionButton : true , actionButtonText : "Review" , } ) ; Info
Toast ■ this . toastService . info ( { title : "Information" , message : "Here is some important information." ,
showLearnMoreButton : true , learnMoreButtonText : "Learn More" , } ) ; Custom Toast ■ this . toastService .
custom ( { title : "Custom Toast" , message : "This is a fully customizable toast." , customWidth : "500px" ,
customBackground : "#6366f1" , customTextColor : "#ffffff" , } ) ; API Reference ■ ToastService Methods ■
Method Parameters Return Type Description success() SuccessToastConfig? Promise<ToastResult> Show
success toast with green styling error() ErrorToastConfig? Promise<ToastResult> Show error toast with red
styling warning() WarningToastConfig? Promise<ToastResult> Show warning toast with orange styling info()
InfoToastConfig? Promise<ToastResult> Show info toast with blue styling default() DefaultToastConfig?
Promise<ToastResult> Show default toast with neutral styling custom() CustomToastConfig?
Promise<ToastResult> Show custom toast with full customization setPosition() ToastPosition void Set global
toast position dismissAll() - void Dismiss all active toasts Toast Configuration Interfaces ■ Base ToastConfig ■
Property Type Default Description title string? " Toast header text message string? " Toast body text duration
number? 4000 Auto-dismiss duration in milliseconds position ToastPosition? 'top-right' Toast position on screen
showCloseButton boolean? true Whether to show close button showProgress boolean? true Whether to show
progress bar icon string? " Custom icon name iconColor string? " Custom icon color customWidth string? "
Custom toast width customHeight string? " Custom toast height design 'classic' | 'modern' 'classic' Toast design
variant size 'large' | 'medium' | 'small' 'large' Toast size variant SuccessToastConfig ■ Property Type Default
Description type 'success' 'success' Toast type (always 'success') ErrorToastConfig ■ Property Type Default
Description type 'error' 'error' Toast type (always 'error') showRetryButton boolean? false Whether to show retry
button retryButtonText string? 'Retry' Text for retry button WarningToastConfig ■ Property Type Default
Description type 'warning' 'warning' Toast type (always 'warning') showActionButton boolean? false Whether to
show action button actionButtonText string? 'Action' Text for action button InfoToastConfig ■ Property Type
Default Description type 'info' 'info' Toast type (always 'info') showLearnMoreButton boolean? false Whether to
show learn more button learnMoreButtonText string? 'Learn More' Text for learn more button
CustomToastConfig ■ Property Type Default Description type 'custom' 'custom' Toast type (always 'custom')
customContent string? " Custom HTML content customBackground string? " Custom background color
customTextColor string? " Custom text color progressColor string? " Custom progress bar color
showCustomActions boolean? false Whether to show custom action buttons customActions CustomAction[]? "
Array of custom action buttons Toast Position Options ■ Position Description 'top-left' Top-left corner of the
screen 'top-center' Top-center of the screen 'top-right' Top-right corner of the screen (default) bottom-left
Bottom-left corner of the screen bottom-center Bottom-center of the screen bottom-right Bottom-right corner of
the screen Toast Result Interface ■ Property Type Description action 'close' | 'retry' | 'action' | 'learn-more' |
'timeout' | string Action that triggered toast dismissal data any? Additional data from custom actions Custom
Action Interface ■ Property Type Description action string Unique identifier for the action label string Display
text for the action button data any? Additional data to pass with the action Best Practices ■ Design Guidelines
■ Choose appropriate variants - Use semantic colors that match the message type Keep messages concise -
Toast notifications should be brief and actionable Use consistent positioning - Stick to one position for your
application Consider duration carefully - Longer durations for important messages, shorter for confirmations

```

Limit concurrent toasts - Avoid overwhelming users with too many notifications Accessibility ■ Provide meaningful titles - Use descriptive headers for screen readers Include action alternatives - Ensure all toast actions are keyboard accessible Test with screen readers - Verify proper announcement of toast content Maintain focus management - Ensure focus returns to appropriate elements Use sufficient contrast - Maintain readability in both light and dark themes Performance ■ Limit toast instances - Avoid creating excessive toast components Use appropriate timeouts - Set reasonable auto-dismiss durations Clean up resources - Ensure proper cleanup of event listeners Optimize animations - Use CSS transforms for smooth performance User Experience ■ Position strategically - Choose positions that don't block important content Provide clear actions - Make action buttons descriptive and intuitive Handle errors gracefully - Use error toasts with retry options when appropriate Consider mobile users - Ensure toasts are readable on small screens Respect user preferences - Allow users to control toast behavior Use Cases ■ Success Confirmations - Operation completion, form submissions Error Notifications - Validation failures, API errors, network issues Warning Messages - Important reminders, confirmation requirements Information Updates - System status, feature announcements Action Prompts - User decisions, next steps, navigation hints Technical Notes ■ Service Architecture ■ The toast system uses a service-based architecture where: ToastService manages all toast operations and lifecycle ToastContainerComponent provides the positioning and container logic Individual toast components handle specific styling and behavior Dynamic component creation enables programmatic toast generation Positioning System ■ Toasts are positioned using CSS transforms and positioning: Fixed positioning ensures toasts appear above all content Responsive behavior adapts to different screen sizes Z-index management maintains proper layering Mobile optimization provides full-width toasts on small screens Animation System ■ Toast animations include: Entrance animations - Slide and fade in effects Exit animations - Slide and fade out effects Progress bars - Visual countdown for auto-dismiss Hover interactions - Timer pause/resume functionality Event Handling ■ The system handles multiple event types: Close events - User-initiated dismissal Action events - Button clicks and custom actions Timeout events - Auto-dismiss completion Hover events - Timer pause/resume functionality

```
<aava-button
  label="Show Success Toast"
  variant="success"
  (userClick)="showSuccessToast()"
></aava-button>

---

// Inject the toast service in your component
constructor(private toastService: ToastService) {}

// Show different types of toasts
showSuccessToast() {
  this.toastService.success({
    title: 'Successfully created!',
    message: 'Your changes have been saved successfully',
    duration: 2000,
    customWidth: '400px',
    design: 'modern',
    size: 'large',
  });
}
```

```

<aava-button
  label="Show Success Toast"
  variant="success"
  (userClick)="showSuccessToast()"
></aava-button>
<aava-button
  label="Show Error Toast"
  variant="danger"
  (userClick)="showErrorToast()"
></aava-button>
<aava-button
  label="Show Warning Toast"
  variant="warning"
  (userClick)="showWarningToast()"
></aava-button>
<aava-button
  label="Show Info Toast"
  variant="info"
  (userClick)="showInfoToast()"
></aava-button>
<aava-button
  label="Show Default Toast"
  variant="secondary"
  (userClick)="showDefaultToast()"
></aava-button>

```

---

```

// Inject the toast service in your component
constructor(private toastService: ToastService) {}

// Show different toast variants
showSuccessToast() {
  this.toastService.success({
    title: 'Successfully created!',
    message: 'Your changes have been saved successfully',
    duration: 2000,
    customWidth: '300px',
    design: 'modern',
    size: 'small',
  });
}

showErrorToast() {
  this.toastService.error({
    title: 'Error Occurred',
    message: 'Connection error. Unable to connect to the server at present',
    duration: 2000,
    customWidth: '300px',
    design: 'modern',
    size: 'small',
  });
}

showWarningToast() {
  this.toastService.warning({
    title: 'Warning Occurred',
    message: 'Please review your input carefully before proceeding.',
    duration: 2000,
    customWidth: '300px',
    design: 'modern',
    size: 'small',
  });
}

showInfoToast() {
  this.toastService.info({
    title: 'Action Required',
    message: 'Please review your input carefully before proceeding.',
    duration: 2000,
    customWidth: '300px',
    design: 'modern',
    size: 'small',
  });
}

showDefaultToast() {
  this.toastService.default({
    title: 'Default Toast Occurred',
    message: 'This is a default toast with neutral styling.',

```

```

        duration: 2000,
        customWidth: '300px',
        design: 'modern',
        size: 'small',
    });
}

showCustomToast() {
    this.toastService.custom({
        title: 'Custom Toast',
        message: 'This is a fully customizable toast with unique styling.',
        customBackground: 'var(--color-primary)',
        customTextColor: 'var(--color-text-primary)',
        customWidth: '300px',
        design: 'modern',
        size: 'small',
    });
}

<aava-button
    label="Show Small Success"
    variant="success"
    size="small"
    (userClick)="showSmallSuccess()"
></aava-button>
<aava-button
    label="Show Medium Warning"
    variant="warning"
    size="small"
    (userClick)="showMediumWarning()"
></aava-button>
<aava-button
    label="Show Large Success"
    variant="danger"
    size="small"
    (userClick)="showLargeError()"
></aava-button>

---

// Inject the toast service in your component
constructor(private toastService: ToastService) {}

// Show different toast sizes
showSmallSuccess() {
    this.toastService.success({
        title: 'Successfully created!',
        message: 'Your changes have been saved successfully',
        duration: 1000,
        customWidth: '300px',
        design: 'modern',
        size: 'small',
    });
}

showMediumWarning() {
    this.toastService.warning({
        title: 'Action Required',
        message: 'Incomplete fields. Please fill in all required information.',
        duration: 1000,
        customWidth: '350px',
        design: 'modern',
        size: 'medium',
    });
}

showLargeError() {
    this.toastService.error({
        title: 'Error Occurred',
        message: 'Connection error. Unable to connect to the server at present',
        duration: 1000,
        customWidth: '400px',
        design: 'modern',
        size: 'large',
    });
}

```