

# Dialog

Dialog The <ava-dialog> system provides a comprehensive dialog solution with multiple variants, modal support, and flexible configuration options. Built around a service-based architecture, it offers both predefined dialog types and custom modal dialogs for various user interaction scenarios.

How to use ■ import { AavaDialogService } from "@aava/play-core" ; // Inject the service constructor ( private dialogService : AavaDialogService ) { } // Show different types of dialogs this . dialogService . success ( { message : 'Operation completed!' } ) ; this . dialogService . confirmation ( { message : 'Are you sure?' } ) ;

Basic Usage ■ Simple dialog implementation with default settings and integrated functionality. Angular Preview Code < aava-button label = " Show Warning Dialog " variant = " warning " (userClick) = " showWarningDialog() " > </ aava-button > constructor ( private dialogService : DialogService ) { } showWarningDialog ( ) { this . dialogService . warning ( { title : 'Unsaved Changes' , message : 'You have unsaved changes that will be lost if you continue. Are you sure you want to proceed?' , showProceedButton : true , proceedButtonText : 'Discard Changes' , } ) . then ( ( result ) => { console . log ( 'Warning dialog closed:' , result ) ; if ( result . action === 'proceed' ) { console . log ( 'User chose to discard changes!' ) ; } } ) ; }

Basic Features ■ Service-Based : Programmatic dialog creation via DialogService Multiple Variants : Success, error, warning, info, confirmation, loading, and custom dialogs Modal Support : Full modal dialog capabilities with content projection Responsive Design : Adapts to different screen sizes and content Accessibility : Built-in accessibility features and keyboard navigation Dialog Variants ■ Seven distinct dialog variants for different user interaction scenarios. Angular Preview Code < aava-button label = " Show Success Dialog " variant = " success " (userClick) = " showSuccessDialog() " > </ aava-button > < aava-button label = " Show Error Dialog " variant = " danger " (userClick) = " showErrorDialog() " > </ aava-button > < aava-button label = " Show Warning Dialog " variant = " warning " (userClick) = " showWarningDialog() " > </ aava-button > < aava-button label = " Show Info Dialog " variant = " primary " (userClick) = " showInfoDialog() " > </ aava-button > < aava-button label = " Show Confirmation Dialog " variant = " secondary " (userClick) = " showConfirmationDialog() " > </ aava-button > < aava-button label = " Show Loading Dialog " variant = " secondary " (userClick) = " showLoadingDialog() " > </ aava-button > constructor ( private dialogService : DialogService ) { } showSuccessDialog ( ) { this . dialogService . success ( { title : 'Operation Successful!' , message : 'Your action has been completed successfully.' , size : 'lg' , bottomBorder : true , } ) . then ( ( result : unknown ) => { console . log ( 'Success dialog closed:' , result ) ; } ) ; } showErrorDialog ( ) { this . dialogService . error ( { title : 'Operation Failed' , message : 'Something went wrong. Please try again.' , showRetryButton : true , retryButtonText : 'Retry' , size : 'md' , } ) . then ( ( result : unknown ) => { console . log ( 'Error dialog closed:' , result ) ; } ) ; } showWarningDialog ( ) { this . dialogService . warning ( { title : 'Please Review' , message : 'Please review the information carefully before proceeding.' , showProceedButton : true , proceedButtonText : 'Proceed' ,

```

showCancelButton : true , cancelButtonText : 'Cancel' , } ) . then ( ( result : unknown ) => { console
. log ( 'Warning dialog closed:' , result ) ; } ) ; } showInfoDialog ( ) { this . dialogService . info ( { title
: 'Information' , message : 'This is an informational message with helpful details.' , showOkButton :
true , okButtonText : 'Got it' , showLearnMoreButton : true , learnMoreButtonText : 'Learn More' , }
) . then ( ( result : unknown ) => { console . log ( 'Info dialog closed:' , result ) ; } ) ; }
showConfirmationDialog ( ) { this . dialogService . confirmation ( { title : 'Confirm Action' , message
: 'Are you sure you want to perform this action?' , confirmButtonText : 'Confirm' , cancelButtonText
: 'Cancel' , confirmButtonVariant : 'primary' , cancelButtonVariant : 'secondary' , } ) . then ( ( result :
unknown ) => { console . log ( 'Confirmation dialog closed:' , result ) ; } ) ; } showLoadingDialog ( ) {
this . dialogService . loading ( { title : 'Processing' , message : 'Please wait while we process your
request.' , showProgress : true , progress : 0 , showCancelButton : true , cancelButtonText :
'Cancel' , } ) . then ( ( result : unknown ) => { console . log ( 'Loading dialog closed:' , result ) ; } ) ; }

```

Available Variants ■ Success - Green styling for successful operations and confirmations Error - Red styling for errors and critical issues with retry options Warning - Orange/yellow styling for warnings and cautions Info - Blue styling for informational messages and tips Confirmation - Neutral styling for user confirmations and decisions Loading - Animated loading states with progress indicators Custom - Fully customizable styling and content Custom Dialogs ■ Fully customizable dialogs with custom content and styling options.

Angular Preview Code

```

<aava-button label = " Show Info Custom Dialog " variant = " info " (userClick) = "
showInfoCustomDialog() " > </aava-button> showInfoCustomDialog ( ) { this . dialogService .
custom ( { title : 'New Features Available' , message : 'We have added several new features to
improve your experience:' , variant : 'info' , bottomBorder : true , customContent : ` <div
style="text-align: left; margin: 1rem 0;"> <div style="display: grid; grid-template-columns: 1fr 1fr;
gap: 1rem;"> <div style="background: #dbeafe; padding: 1rem; border-radius: 4px;"> <strong>■
Mobile App</strong><br> New mobile app with offline support </div> <div style="background:
#dbeafe; padding: 1rem; border-radius: 4px;"> <strong>■ Enhanced Security</strong><br>
Two-factor authentication support </div> </div> ` , buttons : [ { label : 'Learn More' , variant :
'primary' , action : 'learn' } , { label : 'Try Now' , variant : 'primary' , action : 'try' } , { label : 'Maybe
Later' , variant : 'secondary' , action : 'later' } , ] , } ) . then ( ( result : unknown ) => { console . log (
'Info custom dialog closed:' , result ) ; const dialogResult = result as { action ? : string } ; switch (
dialogResult . action ) { case 'learn' : console . log ( 'User chose to learn more' ) ; break ; case 'try'
: console . log ( 'User chose to try now' ) ; break ; case 'later' : console . log ( 'User chose to try
later' ) ; break ; } } ) ; } Custom Features ■ Custom Content : HTML content or component
rendering Variant Styling : Multiple visual variants (default, success, error, warning, info) Flexible
Layouts : Custom button configurations and layouts Icon Customization : Optional icons with
custom colors and sizes Bottom Borders : Optional decorative bottom borders Service Methods ■
The DialogService provides convenient methods for different dialog types: Success Dialog ■ this .
dialogService . success ( { title : "Success!" , message : "Operation completed successfully." , size
: "lg" , showButtons : true , buttons : [ { label : "Continue" , variant : "primary" , action : "continue" } ]
, } ) ; Error Dialog ■ this . dialogService . error ( { title : "Error!" , message : "Something went

```

```
wrong. Please try again." , showRetryButton : true , retryButtonText : "Retry" , size : "md" , } ) ;
Warning Dialog ■ this . dialogService . warning ( { title : "Warning" , message : "Please review the
information carefully." , showProceedButton : true , proceedButtonText : "Proceed" ,
showCancelButton : true , cancelButtonText : "Cancel" , } ) ; Confirmation Dialog ■ this .
dialogService . confirmation ( { title : "Delete Item" , message : "Are you sure you want to delete
this item?" , confirmButtonText : "Delete" , cancelButtonText : "Cancel" , confirmButtonVariant :
"danger" , destructive : true , } ) ; Loading Dialog ■ this . dialogService . loading ( { title :
"Processing" , message : "Please wait while we process your request." , showProgress : true ,
progress : 0 , showCancelButton : true , cancelButtonText : "Cancel" , } ) ; Custom Dialog ■ this .
dialogService . custom ( { title : "Custom Dialog" , message : "This is a custom dialog with unique
content." , variant : "success" , customContent : "<div>Custom HTML content here</div>" ,
buttons : [ { label : "OK" , variant : "primary" , action : "ok" } , { label : "Cancel" , variant :
"secondary" , action : "cancel" } , ] , } ) ; Modal Dialog ■ this . dialogService . openModal (
MyCustomComponent , { width : "600px" , maxWidth : "90vw" , showCloseButton : true , } , { data :
{ id : 123 , name : "Example" } , } ) ;
```

**API Reference ■ DialogService Methods ■ Method**

Parameters	Return Type	Description
success()	SuccessDialogConfig? Promise<DialogResult>	Show success dialog with green styling
error()	ErrorDialogConfig? Promise<DialogResult>	Show error dialog with red styling
warning()	WarningDialogConfig? Promise<DialogResult>	Show warning dialog with orange styling
info()	InfoDialogConfig? Promise<DialogResult>	Show info dialog with blue styling
confirmation()	ConfirmationDialogConfig? Promise<DialogResult>	Show confirmation dialog for user decisions
loading()	LoadingDialogConfig? Promise<DialogResult>	Show loading dialog with progress indicators
custom()	CustomDialogConfig? Promise<DialogResult>	Show custom dialog with full customization
feedback()	CustomDialogConfig? Promise<DialogResult>	Show feedback dialog for user input
open(component, data?)	Promise<any>	Open custom component in dialog container
openModal(component, config?, data?)	Promise<any>	Open custom component in modal dialog
close()	- void	Close the currently open dialog

**Base Dialog Configuration ■ Property Type Default Description**

Property	Type	Default	Description
title	string?	" "	Dialog header text
message	string?	" "	Dialog body text
icon	string?	" "	Icon name for the dialog
iconColor	string?	" "	Custom icon color
iconSize	number?	" "	Custom icon size in pixels
showCloseButton	boolean?	true	Whether to show close button
backdrop	boolean?	true	Whether to show backdrop
width	string?	" "	Custom dialog width
height	string?	" "	Custom dialog height
data	any?	" "	Additional data to pass to dialog

**Success Dialog Configuration ■ Property Type Default Description**

Property	Type	Default	Description
buttons	DialogButton[]?	[]	Array of custom buttons
showButtons	boolean?	false	Whether to show custom buttons
bottomBorder	boolean?	true	Whether to show decorative bottom border
size	'lg'   'md'   'sm'	'lg'	Dialog size variant

**Error Dialog Configuration ■ Property Type Default Description**

Property	Type	Default	Description
showRetryButton	boolean?	false	Whether to show retry button
retryButtonText	string?	'Retry'	Text for retry button
closeButtonText	string?	'Close'	Text for close button
bottomBorder	boolean?	true	Whether to show decorative bottom border
buttons	ErrorButton[]?	[]	Array of custom error buttons
showButtons	boolean?	false	Whether to show custom buttons
size	'lg'   'md'   'sm'	'lg'	Dialog size variant

**Warning Dialog Configuration ■ Property Type Default**

Description showProceedButton boolean? false Whether to show proceed button  
 proceedButtonText string? 'Proceed' Text for proceed button showCancelButton boolean? true  
 Whether to show cancel button cancelButtonText string? 'Cancel' Text for cancel button  
 bottomBorder boolean? true Whether to show decorative bottom border buttons WarningButton[]?  
 [] Array of custom warning buttons showButtons boolean? false Whether to show custom buttons  
 size 'lg' | 'md' | 'sm' 'lg' Dialog size variant Info Dialog Configuration ■ Property Type Default  
 Description showOkButton boolean? true Whether to show OK button okButtonText string? 'OK'  
 Text for OK button showLearnMoreButton boolean? false Whether to show learn more button  
 learnMoreButtonText string? 'Learn More' Text for learn more button bottomBorder boolean? true  
 Whether to show decorative bottom border buttons InfoButton[]? [] Array of custom info buttons  
 showButtons boolean? false Whether to show custom buttons size 'lg' | 'md' | 'sm' 'lg' Dialog size  
 variant Confirmation Dialog Configuration ■ Property Type Default Description confirmButtonText  
 string? 'Confirm' Text for confirm button cancelButtonText string? 'Cancel' Text for cancel button  
 confirmButtonVariant 'primary' | 'secondary' | 'success' | 'warning' | 'danger' 'primary' Confirm  
 button styling variant cancelButtonVariant 'primary' | 'secondary' | 'success' | 'warning' | 'danger'  
 'secondary' Cancel button styling variant destructive boolean? false Whether this is a destructive  
 action bottomBorder boolean? false Whether to show decorative bottom border Loading Dialog  
 Configuration ■ Property Type Default Description progress number? 0 Progress value (0-100)  
 showProgress boolean? false Whether to show progress bar showCancelButton boolean? false  
 Whether to show cancel button cancelButtonText string? 'Cancel' Text for cancel button  
 spinnerColor string? " Custom spinner color indeterminate boolean? true Whether progress is  
 indeterminate bottomBorder boolean? false Whether to show decorative bottom border Custom  
 Dialog Configuration ■ Property Type Default Description buttons DialogButton[]? [] Array of  
 custom buttons variant 'default' | 'success' | 'error' | 'warning' | 'info' 'default' Visual variant for  
 styling customContent string? " Custom HTML content showIcon boolean? true Whether to show  
 icon showTitle boolean? true Whether to show title showMessage boolean? true Whether to show  
 message bottomBorder boolean? false Whether to show decorative bottom border label string? "  
 Custom label text confirmButtonText string? " Text for confirm button cancelButtonText string? "  
 Text for cancel button destructive boolean? false Whether this is a destructive action Modal Dialog  
 Configuration ■ Property Type Default Description maxWidth string? " Maximum width constraint  
 maxHeight string? " Maximum height constraint showCloseButton boolean? true Whether to show  
 close button Dialog Button Interface ■ Property Type Default Description label string - Button  
 display text variant 'primary' | 'secondary' | 'success' | 'warning' | 'danger' 'primary' Button styling  
 variant action string? " Action identifier for button click disabled boolean? false Whether button is  
 disabled Dialog Result Interface ■ Property Type Description action string? Action that triggered  
 dialog closure data any? Additional data from dialog interaction confirmed boolean? Whether user  
 confirmed the action Best Practices ■ Design Guidelines ■ Clear Purpose : Make dialog purpose  
 obvious through title and content Consistent Styling : Use consistent visual hierarchy across  
 dialog types Appropriate Sizing : Choose dialog sizes that fit content without overwhelming Button  
 Placement : Follow standard button placement conventions Visual Feedback : Provide clear visual

feedback for user actions

**Accessibility** ■ **Keyboard Navigation** : Ensure full keyboard accessibility (Tab, Escape, Enter) **Screen Reader Support** : Provide descriptive titles and content **Focus Management** : Trap focus within dialog and restore on close **ARIA Attributes** : Use appropriate ARIA roles and labels **High Contrast** : Maintain sufficient contrast for all text and elements

**Performance** ■ **Lazy Loading** : Load dialog content only when needed **Memory Management** : Properly clean up dialog instances **Change Detection** : Use OnPush strategy for optimal performance **Event Handling** : Clean up event listeners and subscriptions **Bundle Optimization** : Import only needed dialog types

**User Experience** ■ **Clear Actions** : Make button actions and consequences clear **Progressive Disclosure** : Use dialogs for focused, single-purpose interactions **Error Handling** : Provide clear error messages and recovery options **Loading States** : Show appropriate loading indicators for long operations **Responsive Design** : Ensure dialogs work well on all screen sizes

**Implementation Considerations** ■ **Service Injection** : Inject DialogService where dialogs are needed **Promise Handling** : Use async/await or .then() for dialog results **Error Boundaries** : Handle dialog errors gracefully **State Management** : Integrate with application state management **Testing** : Test dialog interactions and accessibility features

**Technical Notes** ■ **Component Architecture** ■ The dialog system uses a service-based architecture: DialogService manages all dialog operations and lifecycle DialogContainerComponent provides the base container and backdrop Individual Dialog Components handle specific dialog types and styling ModalComponent provides advanced modal capabilities with content projection

**Dialog Lifecycle** ■ The dialog system manages complete lifecycle: **Creation** : Dynamic component creation via service methods **Rendering** : Automatic DOM insertion and view attachment **Interaction** : Event handling and user input processing **Cleanup** : Proper cleanup of views, components, and event listeners

**Content Projection** ■ Modal dialogs support advanced content projection: **Header Content** : Use [dialog-header] attribute for header sections **Body Content** : Use [dialog-body] attribute for main content **Footer Content** : Use [dialog-footer] attribute for action areas **Dynamic Content** : Any component can be rendered inside dialogs

**Event Handling** ■ The system handles multiple event types: **Close Events** : User-initiated closure via close button or backdrop **Button Events** : Custom button click handling with action identification **Result Events** : Promise resolution with user action results **Cleanup Events** : Proper cleanup of resources and event listeners

**CSS Integration** ■ The component integrates with the design system: **CSS Variables** : Uses semantic CSS variables for theming **Responsive Design** : Adapts to different screen sizes **State Management** : Handles various dialog states **Accessibility** : Maintains proper contrast and focus indicators

```
<aava-button
  label="Show Warning Dialog"
  variant="warning"
  (userClick)="showWarningDialog()"
></aava-button>
```

---

```
constructor(private dialogService: DialogService) {}

showWarningDialog() {
  this.dialogService
    .warning({
      title: 'Unsaved Changes',
      message:
        'You have unsaved changes that will be lost if you continue. Are you sure you want to proceed?',
      showProceedButton: true,
      proceedButtonText: 'Discard Changes',
    })
    .then((result) => {
      console.log('Warning dialog closed:', result);
      if (result.action === 'proceed') {
        console.log('User chose to discard changes!');
      }
    });
}
```

```

<aava-button
  label="Show Success Dialog"
  variant="success"
  (userClick)="showSuccessDialog()"
></aava-button>
<aava-button
  label="Show Error Dialog"
  variant="danger"
  (userClick)="showErrorDialog()"
></aava-button>
<aava-button
  label="Show Warning Dialog"
  variant="warning"
  (userClick)="showWarningDialog()"
></aava-button>
<aava-button
  label="Show Info Dialog"
  variant="primary"
  (userClick)="showInfoDialog()"
></aava-button>
<aava-button
  label="Show Confirmation Dialog"
  variant="secondary"
  (userClick)="showConfirmationDialog()"
></aava-button>
<aava-button
  label="Show Loading Dialog"
  variant="secondary"
  (userClick)="showLoadingDialog()"
></aava-button>

```

---

```

constructor(private dialogService: DialogService) {}

showSuccessDialog() {
  this.dialogService
    .success({
      title: 'Operation Successful!',
      message: 'Your action has been completed successfully.',
      size: 'lg',
      borderBottom: true,
    })
    .then((result: unknown) => {
      console.log('Success dialog closed:', result);
    });
}

showErrorDialog() {
  this.dialogService
    .error({
      title: 'Operation Failed',
      message: 'Something went wrong. Please try again.',
      showRetryButton: true,
    })

```

```

        retryButtonText: 'Retry',
        size: 'md',
    })
    .then((result: unknown) => {
        console.log('Error dialog closed:', result);
    });
}

showWarningDialog() {
    this.dialogService
        .warning({
            title: 'Please Review',
            message: 'Please review the information carefully before proceeding.',
            showProceedButton: true,
            proceedButtonText: 'Proceed',
            showCancelButton: true,
            cancelButtonText: 'Cancel',
        })
        .then((result: unknown) => {
            console.log('Warning dialog closed:', result);
        });
}

showInfoDialog() {
    this.dialogService
        .info({
            title: 'Information',
            message: 'This is an informational message with helpful details.',
            showOkButton: true,
            okButtonText: 'Got it',
            showLearnMoreButton: true,
            learnMoreButtonText: 'Learn More',
        })
        .then((result: unknown) => {
            console.log('Info dialog closed:', result);
        });
}

showConfirmationDialog() {
    this.dialogService
        .confirmation({
            title: 'Confirm Action',
            message: 'Are you sure you want to perform this action?',
            confirmButtonText: 'Confirm',
            cancelButtonText: 'Cancel',
            confirmButtonVariant: 'primary',
            cancelButtonVariant: 'secondary',
        })
        .then((result: unknown) => {
            console.log('Confirmation dialog closed:', result);
        });
}

showLoadingDialog() {
    this.dialogService
        .loading({

```

```
    title: 'Processing',
    message: 'Please wait while we process your request.',
    showProgress: true,
    progress: 0,
    showCancelButton: true,
    cancelButtonText: 'Cancel',
  })
  .then((result: unknown) => {
    console.log('Loading dialog closed:', result);
  });
}
```

```

<aava-button
  label="Show Info Custom Dialog"
  variant="info"
  (userClick)="showInfoCustomDialog()"
></aava-button>

```

---

```

showInfoCustomDialog() {
  this.dialogService
    .custom({
      title: 'New Features Available',
      message:
        'We have added several new features to improve your experience:',
      variant: 'info',
      bottomBorder: true,
      customContent: `
<div style="text-align: left; margin: 1rem 0;">
  <div style="display: grid; grid-template-columns: 1fr 1fr; gap: 1rem;">
    <div style="background: #dbeafe; padding: 1rem; border-radius: 4px;">
      <strong>■ Mobile App</strong><br>
      New mobile app with offline support
    </div>
    <div style="background: #dbeafe; padding: 1rem; border-radius: 4px;">
      <strong>■ Enhanced Security</strong><br>
      Two-factor authentication support
    </div>
  </div>
</div>
`,
      buttons: [
        { label: 'Learn More', variant: 'primary', action: 'learn' },
        { label: 'Try Now', variant: 'primary', action: 'try' },
        { label: 'Maybe Later', variant: 'secondary', action: 'later' },
      ],
    })
    .then((result: unknown) => {
      console.log('Info custom dialog closed:', result);
      const dialogResult = result as { action?: string };
      switch (dialogResult.action) {
        case 'learn':
          console.log('User chose to learn more');
          break;
        case 'try':
          console.log('User chose to try now');
          break;
        case 'later':
          console.log('User chose to try later');
          break;
      }
    });
}

```