

# Date Picker

Date Picker The <aava-calendar> component provides a robust, accessible, and highly customizable calendar interface for selecting single dates or date ranges. It features structured input fields, keyboard navigation, glassmorphism effects, and seamless integration with Angular forms. The component is designed for both standalone display and as a building block for date pickers and scheduling interfaces.

How to use ■ import { AavaCalendarComponent } from "@aava/play-core" ;

Basic Usage ■ Simple calendar for single date selection with structured input fields.

Range Selection ■ Enable range mode for selecting a start and end date with dual structured inputs.

Always Open / Embedded Mode ■ Display the calendar inline (always open) for dashboards and embedded views.

Customization Options ■ Showcase selector shape and various customization options.

Size Variants ■ Five size variants to accommodate different design requirements and space constraints.

Available Sizes ■ xs (Extra Small) - Compact size for tight spaces and dense layouts sm (Small) - Smaller than default, suitable for secondary interfaces md (Medium) - Default size, balanced for most use cases lg (Large) - Larger size for enhanced readability and touch interfaces xl (Extra Large) - Maximum size for accessibility and prominent displays

Size Characteristics ■ Each size variant affects: Input field dimensions - Height, padding, and font sizes Calendar popup sizing - Overall dimensions and spacing Day selector sizes - Individual day cell dimensions Navigation elements - Button sizes and spacing Typography scaling - Font sizes for headers and content

Accessibility Features ■ Built-in accessibility features ensuring WCAG compliance and inclusive user experience.

Features ■ Single date and range selection with visual range indicators Structured input fields for direct date entry (DD/MM/YYYY format) Multiple size variants (xs, sm, md, lg, xl) for flexible layouts Keyboard navigation (arrow keys, Enter, Tab, Escape) Month/year navigation with dropdown selectors Customizable selector shape (square or circle) Glassmorphism surface effects with multiple strength levels Weekday format options (1, 2, or 3 letter formats) Full accessibility (ARIA, focus management, screen reader support) Angular forms integration (ControlValueAccessor implementation) Auto-advance input segments for seamless data entry Input validation and error handling Responsive design with mobile-friendly interactions

API Reference ■ Inputs ■ Property Type Default Description

isRange boolean false Enable range selection mode

selectedDate Date | null null Selected date (single mode)

dateRange { start: Date | null, end: Date | null } { start: null, end: null } Selected date range (range mode)

weekdayFormat 1 | 2 | 3 3 Weekday label format: 1 = single letter, 2 = two-letter, 3 = three-letter

alwaysOpen boolean false Display calendar inline (always open)

selectorShape 'square' | 'circle' 'square' Shape of day selector

calendarSize 'xs' | 'sm' | 'md' | 'lg' | 'xl' 'md' Size variant for calendar and input elements

surface boolean false Enable glassmorphism surface effect

surfaceStrength 'medium' | 'strong' | 'max' | undefined 'medium' Glassmorphism intensity

Outputs ■ Event Type Description

dateSelected EventEmitter<Date> Emitted when a date is selected (single mode)

rangeSelected EventEmitter<{ start: Date, end: Date }> Emitted

when a date range is selected (range mode) Computed Properties ■ Property Type Description  
weekDays string[] Computed weekday labels based on format yearRange number[] Array of years  
(current ± 50 years) calendarDays CalendarDay[] Array of days for current month display  
Interfaces ■ interface DateRange { start : Date | null ; end : Date | null ; } interface CalendarDay {  
date : Date ; isCurrentMonth : boolean ; isToday : boolean ; isSelected : boolean ; isInRange :  
boolean ; isRangeStart : boolean ; isRangeEnd : boolean ; } CSS Custom Properties ■ Property  
Description --calendar-font-family Font family for calendar text --calendar-size-sm-font Small font  
size for calendar elements --calendar-size-md-font Medium font size for headers (default)  
--calendar-input-padding Padding for input fields --calendar-input-border Border for input fields  
--calendar-input-border-radius Border radius for input fields --calendar-input-background  
Background color for input fields --calendar-popup-background Background for calendar popup  
--calendar-popup-border Border for calendar popup --calendar-popup-border-radius Border radius  
for calendar popup --calendar-popup-shadow Shadow for calendar popup  
--calendar-popup-z-index Z-index for calendar popup --calendar-nav-button-hover-background  
Hover background for navigation buttons Accessibility ■ The Calendar component is built with  
comprehensive accessibility features: Semantic HTML : Uses appropriate roles and elements for  
calendar, grid, and buttons ARIA attributes : Provides ARIA labels for navigation, days, and range  
selection Keyboard navigation : Full support for arrow keys, Enter, Tab, and Escape Screen  
reader support : Announces current month/year, selected dates, and range Focus management :  
Clear focus indicators and logical tab order High contrast : Supports high contrast and custom  
themes Reduced motion : Respects user motion preferences Keyboard Shortcuts ■ Arrow keys :  
Move focus between days Enter/Space : Select date or range endpoint Tab/Shift+Tab : Move  
between input segments and controls Escape : Close popup (if not always open) Home/End :  
Navigate to first/last day of month Page Up/Down : Navigate to previous/next month Structured  
Input Navigation ■ Tab : Move between day, month, year segments Arrow keys : Navigate within  
segments Auto-advance : Automatically moves to next segment when complete Validation :  
Real-time validation of date inputs Best Practices ■ Usage Guidelines ■ Single Date : Use for  
appointment booking, event scheduling, or simple date selection Range Selection : Use for  
booking periods, analytics date ranges, or vacation planning Always Open : Use for dashboards,  
embedded views, or when space allows Size Selection : Choose appropriate size based on  
context and space constraints Surface Effects : Use glassmorphism for modern, layered UI  
designs Forms Integration : Leverage ControlValueAccessor for seamless form integration Size  
Selection Guidelines ■ XS : Use in data tables, compact forms, or when space is extremely limited  
SM : Use in secondary interfaces, sidebars, or when you need subtle presence MD : Use as the  
default for most applications and primary interfaces LG : Use in touch interfaces, mobile  
applications, or when enhanced readability is needed XL : Use in accessibility-focused  
applications or when maximum visibility is required Implementation Considerations ■ Input  
Validation : Always validate user input from structured fields Error Handling : Provide clear  
feedback for invalid dates Mobile Experience : Test touch interactions and responsive behavior  
Performance : Calendar renders efficiently with OnPush change detection Theming : Use

semantic tokens for consistent design system integration Accessibility Implementation ■ Screen Reader Testing : Test with NVDA, JAWS, or VoiceOver Keyboard Testing : Verify complete keyboard navigation flow Focus Management : Ensure logical tab order and clear focus indicators Color Contrast : Maintain sufficient contrast ratios (4.5:1 minimum) Motion Preferences : Respect user's reduced motion settings

```
<aava-datepicker (dateSelected)="onDateSelected($event)"> </aava-datepicker>
```

---

```
onDateSelected(date: Date) {  
  console.log('Selected date:', date);  
}
```

```
<aava-datepicker [isRange]="true" (rangeSelected)="onRangeSelected($event)">  
</aava-datepicker>
```

---

```
selectedRange: DateRange = { start: null, end: null };
```

```
onRangeSelected(range: DateRange) {  
  this.selectedRange = range;  
  console.log('Selected range:', range);  
}
```

```
<aava-datepicker [alwaysOpen]="true" (dateSelected)="onDateSelected($event)">  
</aava-datepicker>
```

---

```
selectedDate: Date | null = null;
```

```
onDateSelected(date: Date) {  
  this.selectedDate = date;  
  console.log('Selected date:', date);  
}
```

```
<aava-datepicker
  [alwaysOpen]="true"
  selectorShape="square"
  (dateSelected)="onDateSelected($event)"
>
</aava-datepicker>
<aava-datepicker
  [alwaysOpen]="true"
  selectorShape="circle"
  (dateSelected)="onDateSelected($event)"
>
</aava-datepicker>
```

---

```
onDateSelected(date: Date) {
  console.log('Selected date:', date);
}
```

■ No code found

■ No code found