

Textbox

Textbox The <aava-textbox> component provides a highly sophisticated text input element with glass morphism effects, advanced content projection system, multiple processing animations, and comprehensive Angular forms integration. It supports semantic variants, validation states, and extensive customization options.

How to use ■ import { AavaTextboxComponent } from "@aava/play-core" ;

Basic Usage ■ Simple textbox implementation with label, placeholder, and two-way data binding. Angular Preview Code

```
< aava-textbox label = " Basic Input " placeholder = " Enter text here " (change) = " onTextboxChange($event) " > </ aava-textbox >
onTextboxChange ( event : Event ) { const target = event . target as HTMLInputElement ; console . log (
'Textbox value changed:' , target . value ) ; }
```

Variants ■ The textbox component supports 6 semantic variants that control visual appearance and focus colors. Angular Preview Code

```
< aava-textbox label = " Default Variant " placeholder = " Default variant... " variant = " default " (change) = " onTextboxChange($event) " > </
aava-textbox > < aava-textbox label = " Primary Variant " placeholder = " Primary variant... " variant = " primary
" (change) = " onTextboxChange($event) " > </ aava-textbox > < aava-textbox label = " Success Variant "
placeholder = " Success variant... " variant = " success " (change) = " onTextboxChange($event) " > </
aava-textbox > < aava-textbox label = " Error Variant " placeholder = " Error variant... " variant = " error "
(change) = " onTextboxChange($event) " > </ aava-textbox > < aava-textbox label = " Warning Variant "
placeholder = " Warning variant... " variant = " warning " (change) = " onTextboxChange($event) " > </
aava-textbox > < aava-textbox label = " Info Variant " placeholder = " Info variant... " variant = " info " (change) =
" onTextboxChange($event) " > </ aava-textbox >
onTextboxChange ( event : Event ) { const target = event .
target as HTMLInputElement ; console . log ( 'Textbox value changed:' , target . value ) ; }
```

Available Variants ■

- default - Standard neutral appearance with brand primary focus
- primary - Primary variant with enhanced brand focus color
- success - Positive states and confirmations (green)
- error - Error states and validation failures (red)
- warning - Warning states and cautions (orange/yellow)
- info - Informational states and tips (blue)

Sizes ■ Five size options to accommodate different interface densities and layout requirements. Angular Preview Code

```
< aava-textbox label = " Extra Small " placeholder = " Extra Small... " size = " xs " > </ aava-textbox > <
aava-textbox label = " Small " placeholder = " Small... " size = " sm " > </ aava-textbox > < aava-textbox label =
" Medium " placeholder = " Medium... " size = " md " > </ aava-textbox > < aava-textbox label = " Large "
placeholder = " Large... " size = " lg " > </ aava-textbox > < aava-textbox label = " Extra Large " placeholder =
" Extra Large... " size = " xl " > </ aava-textbox >
```

Available Sizes ■

- xs (Extra Small) - Extra small size for very compact interfaces
- sm (Small) - Small size for dense interfaces
- md (Medium) - Medium size for most use cases (default)
- lg (Large) - Large size for prominent inputs
- xl (Extra Large) - Extra large size for emphasis and accessibility

Icons & Affixes ■ Advanced content projection system supporting icons, prefixes, and suffixes through Angular's content projection. Angular Preview Code

```
< aava-textbox label = " Amount " placeholder = " 0.00 " type = " number " (on) > < span slot = " prefix " > $ </ span > < span slot = " suffix " > USD </ span > </
aava-textbox > < aava-textbox label = " Password " [type] = " showPassword ? 'text' : 'password' " placeholder =
" Enter password " > < aava-icon slot = " icon-end " [iconName] = " showPassword ? 'eye' : 'eye-off' " (click) =
" togglePasswordVisibility() " > </ aava-icon > </ aava-textbox > < aava-textbox label = " With Icon Separator
(Start) " placeholder = " Search... " [iconSeparator] = " true " > < aava-icon slot = " icon-start " iconName = "
search " > </ aava-icon > </ aava-textbox > < aava-textbox label = " With Icon Separator (End) " placeholder =
" Clear... " [iconSeparator] = " true " > < aava-icon slot = " icon-end " iconName = " x " > </ aava-icon > </
aava-textbox >
```

```
showPassword = false ; togglePasswordVisibility ( ) : void { this . showPassword = ! this .
showPassword ; }
```

Content Projection Slots ■

- icon-start - Icons at the beginning of the input
- icon-end - Icons at the end of the input
- prefix - Text or elements before the input text
- suffix - Text or elements after the input text

Input Masking ■ Advanced input masking system powered by ngx-mask for formatted input patterns like phone numbers, dates, currency, and credit cards. Angular Preview Code

Masking Features ■

- Pattern-Based Input : Define custom input patterns using mask syntax
- Real-time Formatting : Automatic formatting as users type

Special Character Handling : Control how special characters are processed Prefix/Suffix Support : Add currency symbols, units, or other prefixes/suffixes Validation Integration : Works seamlessly with existing validation system Accessibility : Maintains proper ARIA attributes and keyboard navigation Common Mask Patterns ■ Phone Numbers : (000) 000-0000 for US format Dates : 00/00/0000 for MM/DD/YYYY format Currency : separator.2 with thousand separators and decimal places Credit Cards : 0000 0000 0000 0000 for card number format Custom Patterns : Define your own patterns using 0 , 9 , A , S placeholders States & Validation ■ Comprehensive validation system with error messages, helper text, and various input states. Angular Preview Code Available States ■ Normal - Default input state Focused - Active input with enhanced border and shadow Disabled - Non-interactive state with dimmed appearance Readonly - Display-only state with modified styling Error - Validation error state with red styling and error message Required - Indicates mandatory fields with asterisk Validation Features ■ Error Handling: Error messages - Display validation errors with icon ARIA compliance - Proper aria-invalid and aria-describedby attributes Visual feedback - Error variant styling with red colors Icon integration - Alert icons automatically shown with errors Helper Text: Guidance messages - Helpful instructions below input Icon support - Info icons automatically shown with helper text Conditional display - Helper text hidden when errors are present Accessibility - Proper ARIA relationships Required Fields: Visual indicators - Asterisk (*) displayed for required fields Label integration - Required indicator integrated with label Form validation - Works with Angular form validation Processing Effects ■ Advanced processing states with multiple animation options for loading and async operations. Angular Preview Code Available Processing Effects ■ border-pulse - Pulsing border animation (default) shimmer - Text shimmer effect within input gradient-border - Animated multi-color border gradient Effects System ■ Modern effects system following Text Input Specifications for consistent visual behavior and accessibility. Hover Effects ■ tint - Subtle color tinting on hover (recommended) glow - Enhanced glow effect on hover (for interactive elements) Processing States ■ Default Processing - Border pulse animation with customizable colors Shimmer Effect - Text shimmer animation as alternative to border pulse Gradient Border - Animated multi-color gradient border for processing state Custom Colors - Configurable gradient colors for brand consistency Accessibility Features ■ High Contrast Support - Effects respect high contrast mode settings Reduced Motion - Animations respect user's motion preferences Focus Indicators - Clear focus states maintained with all effects Screen Reader Support - Proper ARIA attributes for all interactive states API Reference ■ Inputs ■ Property Type Default Description label string " Visible label text above input placeholder string " Placeholder text shown when empty variant TextboxVariant 'default' Visual variant: 'default' , 'primary' , 'success' , 'error' , 'warning' , 'info' size TextboxSize 'md' Input size: 'xs' , 'sm' , 'md' , 'lg' , 'xl' disabled boolean false Whether input is disabled readonly boolean false Whether input is read-only error string " Error message to display helper string " Helper text to display required boolean false Whether input is required fullWidth boolean false Whether input takes full container width type string 'text' HTML input type maxLength number " Maximum character length minLength number " Minimum character length autoComplete string " HTML autoComplete attribute id string " Custom element ID name string " HTML name attribute icon string " Icon name to display iconPosition 'start' | 'end' 'start' Position of the icon relative to input iconSeparator boolean false Whether to show separator between icon and input iconSpacing 'compact' | 'normal' | 'relaxed' 'normal' Icon spacing variant inputKind 'text' | 'phone' | 'currency' | 'password' 'text' Type of input for specialized behavior inputKindLabel string " Label for specialized input types (e.g., country code) phone boolean false Enable phone input functionality labelPosition 'start' | 'end' 'start' Position of country prefix label for phone inputs Masking Properties ■ Property Type Default Description mask string | null null Input mask pattern (e.g., "(000) 000-0000" for phone) maskPrefix string " Prefix to add before masked value (e.g., "\$" for currency) maskSuffix string " Suffix to add after masked value (e.g., "%" for percentage) maskDropSpecialCharacters boolean | string[] true Whether to drop special characters from value maskShowMaskTyped boolean false Show mask characters as user types maskThousandSeparator string " Thousand separator character (e.g., "," for numbers) maskDecimalMarker '.' | ',' | ['.', ','] '.' Decimal marker character maskPatterns Record<string, object> {} Custom mask patterns for special characters maskValidation boolean false Enable mask validation maskAllowNegativeNumbers boolean false Allow negative numbers in

numeric masks maskLeadZeroDateTime boolean false Show leading zeros in date/time masks Effects System Properties

Property	Type	Default	Description
hoverEffect	'tint' 'glow' "		Hover effect: Tint (recommended) or Glow
pressedEffect	'solid' 'solid'		Pressed effect: Solid (recommended and only allowed)
processing	boolean	false	Processing state - triggers border pulse by default
processingEffect	'shimmer' "		Alternative processing effect: Text shimmer animation
processingGradientBorder	boolean	false	Show animated gradient border for processing state
processingGradientColors	string[]	['#e91e63', '#fee140', '#ff9800', '#047857', '#ff9800', '#fee140', '#e91e63']	Colors for processing gradient border
decorativeEffect	'glowBox' 'borderFlow' 'attention' 'wave' "		Ambient decorative effects for future use
disabledState	'grey' 'grey'		Disabled state appearance: Grey (recommended and only allowed)
customStyles	Record<string, string> "		CSS custom properties override for advanced theming

Outputs

Event	Type	Description
iconStartClick	EventEmitter<Event>	Emitted when the start icon is clicked
iconEndClick	EventEmitter<Event>	Emitted when the end icon is clicked
clickOutside	EventEmitter<boolean>	Emitted when a click occurs outside the input
change	EventEmitter<Event>	Emitted when the input value changes
blur	EventEmitter<Event>	Emitted when the input loses focus
focus	EventEmitter<Event>	Emitted when the input gains focus
input	EventEmitter<Event>	Emitted on every input event
prefixSelect	EventEmitter<{ label: string; value: string; }>	Emitted when a prefix option is selected
suffixSelect	EventEmitter<{ label: string; value: string; }>	Emitted when a suffix option is selected

Properties

Property	Type	Description
value	string	Current input value
isFocused	boolean	Whether input currently has focus
hasError	boolean	Whether input has error state
hasHelper	boolean	Whether input has helper text

Methods

Method	Parameters	Return Type	Description
setValue()	value: string	void	Set input value programmatically
writeValue()	value: string	void	Set input value (ControlValueAccessor)
registerOnChange()	fn: (value: string) => void	void	Register change callback
registerOnTouched()	fn: () => void	void	Register touched callback
setDisabledState()	isDisabled: boolean	void	Set disabled state

Content Projection Slots

Slot	Description
icon-start	Icons displayed at the start of the input
icon-end	Icons displayed at the end of the input
prefix	Content displayed before the input text
suffix	Content displayed after the input text

CSS Custom Properties

Property	Description
--textbox-glass-default-background	Background color with glass effect
--textbox-glass-default-blur	Backdrop blur amount for glass effect
--textbox-glass-default-border	Border color for default state
--textbox-glass-default-shadow	Box shadow for glass effect
--textbox-border-radius	Border radius of the input container
--textbox-transition	Transition animation duration
--textbox-input-font	Font properties for input text
--textbox-input-color	Text color for input
--textbox-input-padding	Padding inside the input
--textbox-input-min-height	Minimum height of the input
--textbox-label-font	Font properties for label
--textbox-label-color	Text color for label
--textbox-label-weight	Font weight for label
--textbox-placeholder-color	Color for placeholder text
--textbox-error-color	Color for error messages and state
--textbox-helper-color	Color for helper text
--textbox-icon-color	Color for icons in normal state
--textbox-icon-focus-color	Color for icons when focused
--textbox-variant-default	Colors for default variant
--textbox-variant-primary	Colors for primary variant
--textbox-variant-success	Colors for success variant
--textbox-variant-error	Colors for error variant
--textbox-variant-warning	Colors for warning variant
--textbox-variant-info	Colors for info variant
--textbox-size-xs-padding	Padding for extra small size
--textbox-size-sm-padding	Padding for small size
--textbox-size-md-padding	Padding for medium size
--textbox-size-lg-padding	Padding for large size
--textbox-size-xl-padding	Padding for extra large size
--textbox-size-xs-height	Height for extra small size
--textbox-size-sm-height	Height for small size
--textbox-size-md-height	Height for medium size
--textbox-size-lg-height	Height for large size
--textbox-size-xl-height	Height for extra large size

Best Practices

Design Guidelines

- Choose appropriate variants - Use semantic variants that match the context
- Provide clear labels - Always include descriptive labels for accessibility
- Use helper text wisely - Provide guidance without cluttering the interface
- Handle errors gracefully - Show clear, actionable error messages
- Optimize for touch - Ensure adequate touch targets for mobile users
- Consider glass intensity - Use glass-10 for most cases, glass-50 for emphasis
- Select appropriate sizes - Use xs for very compact layouts, xl for emphasis and accessibility
- Implement masking thoughtfully - Choose mask patterns that match user expectations and data format
- Balance effects and performance - Use effects system for enhanced UX while maintaining performance

Accessibility ■ Proper labeling - Label elements correctly associated with inputs ARIA attributes - Use aria-invalid , aria-describedby , aria-required Error announcement - Error messages announced to screen readers Keyboard navigation - Full keyboard support for all interactions Focus management - Visible focus indicators and proper focus order Icon accessibility - Icons properly labeled and keyboard accessible Performance ■ Validate appropriately - Use client and server validation together Debounce input events - For real-time validation and API calls Optimize re-renders - Use OnPush change detection strategy Efficient icon handling - Load icons efficiently and cache appropriately Form Integration ■ Test with forms - Ensure proper integration with your form handling Handle validation - Implement comprehensive validation strategies Consider reset behavior - Define clear reset and initial state behavior Support reactive forms - Proper FormControlValueAccessor implementation Masking Best Practices ■ Choose intuitive patterns - Use mask patterns that users expect (e.g., phone formats) Handle edge cases - Consider what happens when users paste or clear masked input Provide clear examples - Use placeholders that show the expected format Test accessibility - Ensure screen readers can properly announce masked input Consider internationalization - Use appropriate separators and formats for different locales Balance flexibility - Allow users to edit parts of masked input without losing context

```
<aava-textbox
  label="Basic Input"
  placeholder="Enter text here"
  (change)="onTextboxChange($event)"
></aava-textbox>
```

```
onTextboxChange(event: Event) {
  const target = event.target as HTMLInputElement;
  console.log('Textbox value changed:', target.value);
}
```

```
<aava-textbox
  label="Default Variant"
  placeholder="Default variant..."
  variant="default"
  (change)="onTextboxChange($event)"
></aava-textbox>
```

```
<aava-textbox
  label="Primary Variant"
  placeholder="Primary variant..."
  variant="primary"
  (change)="onTextboxChange($event)"
></aava-textbox>
```

```
<aava-textbox
  label="Success Variant"
  placeholder="Success variant..."
  variant="success"
  (change)="onTextboxChange($event)"
></aava-textbox>
```

```
<aava-textbox
  label="Error Variant"
  placeholder="Error variant..."
  variant="error"
  (change)="onTextboxChange($event)"
></aava-textbox>
```

```
<aava-textbox
  label="Warning Variant"
  placeholder="Warning variant..."
  variant="warning"
  (change)="onTextboxChange($event)"
></aava-textbox>
```

```
<aava-textbox
  label="Info Variant"
  placeholder="Info variant..."
  variant="info"
  (change)="onTextboxChange($event)"
></aava-textbox>
```

```
onTextboxChange(event: Event) {
  const target = event.target as HTMLInputElement;
  console.log('Textbox value changed:', target.value);
}
```

```
<aava-textbox
  label="Extra Small"
  placeholder="Extra Small..."
  size="xs"
></aava-textbox>
```

```
<aava-textbox label="Small" placeholder="Small..." size="sm"></aava-textbox>
```

```
<aava-textbox label="Medium" placeholder="Medium..." size="md"></aava-textbox>
```

```
<aava-textbox label="Large" placeholder="Large..." size="lg"></aava-textbox>
```

```
<aava-textbox
  label="Extra Large"
  placeholder="Extra Large..."
  size="xl"
></aava-textbox>
```

```

<aava-textbox label="Amount" placeholder="0.00" type="number" (on)>
  <span slot="prefix">$</span>
  <span slot="suffix">USD</span>
</aava-textbox>

```

```

<aava-textbox
  label="Password"
  [type]="showPassword ? 'text' : 'password'"
  placeholder="Enter password"
>
  <aava-icon
    slot="icon-end"
    [iconName]="showPassword ? 'eye' : 'eye-off'"
    (click)="togglePasswordVisibility()"
  ></aava-icon>
</aava-textbox>

```

```

<aava-textbox
  label="With Icon Separator (Start)"
  placeholder="Search..."
  [iconSeparator]="true"
>
  <aava-icon slot="icon-start" iconName="search"></aava-icon>
</aava-textbox>

```

```

<aava-textbox
  label="With Icon Separator (End)"
  placeholder="Clear..."
  [iconSeparator]="true"
>
  <aava-icon slot="icon-end" iconName="x"></aava-icon>
</aava-textbox>

```

```

showPassword = false;

togglePasswordVisibility(): void {
  this.showPassword = !this.showPassword;
}

```

■ No code found

■ No code found

■ No code found