

Unit Testing Strategy

Play+ Unit Testing Guide : playtest Philosophy: Testing with Confidence & Clarity ■ In the Play+ ecosystem, testing is not an afterthought—it's a core part of how we build trust in our work. Just as we aim to design intuitive and adaptive experiences, we also strive to validate them with clarity and confidence. Testing allows us to explore new ideas fearlessly, knowing that well-crafted tests provide a safety net against regressions and subtle bugs. Our @playplus/testing-config package sets the foundation for this approach. It offers a zero-setup, opinionated environment that encourages: Frictionless Development : Get started quickly with tools that just work. User-Centric Thinking : Write tests that simulate real user behavior, not internals. Continuous Integration : Ensure quality is enforced through automated pipelines. This guide outlines how to write expressive, resilient unit tests for your Play+ React or Angular applications. Package Information ■ The Play+ testing toolchain is provided via the @playplus/testing-config package and is a core component of the Golden Path starter kits. Package / Path Description Golden Path (Recommended) Pre-installed as a devDependency Uplift Path npm install --save-dev @playplus/testing-config Folder Reference ■ Play+ follows a test co-location model , meaning test files live directly alongside the code they are testing. This improves discoverability and encourages test creation during development. File Location Purpose & Guidelines src/components/Button.test.tsx React test file, next to Button.tsx src/app/features/login.component.spec.ts Angular test file, next to login.component.ts reports/coverage/ Git-ignored directory for test coverage reports Helper - Pillars Alignment ■ Pillar How This Helper Aligns Intuitive Primary Pillar: Tests are written from a user's perspective to ensure predictability Adaptive Enables safe iteration and refactoring by having a comprehensive test suite Inclusive Ensures reliability for all users by testing diverse states and edge cases Helper Overview ■ The playtest toolchain is a set of pre-configured tools, patterns, and CLI helpers designed to abstract the plumbing of modern testing environments. What It Automates ■ Zero-Setup Environment : Pre-configured Vitest/Jest for React and Jasmine/Karma for Angular. Automated Test Scaffolding : CLI helper playtest:gen analyzes components and generates boilerplate. Automated Enforcement : Tests run on pre-commit and are required in CI/CD for Golden Path. Consistent Mocking : Provides standard mocking for dependencies like apiService . The goal is to make testing a fast, frictionless, and integral part of development. The Play+ Testing Stack ■ React ■ Test Runner : Vitest (or Jest) Testing Library : React Testing Library Assertions : expect with matchers from @testing-library/jest-dom Angular ■ Test Runner : Jasmine and Karma Testing Library : Angular TestBed Assertions : Jasmine's built-in matchers Coverage : Karma Coverage with 80% threshold Architecture : Standalone components with testing utilities Config Options ■ Config Variable Default Value Description Recommended Value coverage.threshold 80 Min % coverage required for CI pass 80 reporters ['default'] Output formats (can include html , json , etc.) ['default', 'html'] Key Scripts & CLI Commands ■ Command What It Does Example npm run playtest Runs full test suite once npm run playtest npm run playtest:watch Starts watch mode for

live test re-running `npm run playwright:watch` `npm run playwright:gen` Scaffolds a new test file for a given component `npm run playwright:gen src/app/components/UserProfile.ts` What `playtest:gen` Generates ■ **React** ■ Auto-imports for `render` and `screen` A describe block and default smoke test Placeholders for props and mocks **Angular** ■ Auto-imports for `TestBed` and `ComponentFixture` A describe block and default smoke test Placeholders for props and mocks Accessibility test structure **React** ■ `// src/components/Counter.test.tsx`

```
import { render, screen, fireEvent } from "@testing-library/react";
import Counter from "../Counter";
describe("Counter", () => {
  beforeEach(() => {
    render(<Counter />);
  });
  it("should render with an initial count of 0", () => {
    expect(screen.getByText("Count: 0")).toBeInTheDocument();
  });
  it("should increment the count when the button is clicked", () => {
    fireEvent.click(screen.getByRole("button", { name: /increment/i }));
    expect(screen.getByText("Count: 1")).toBeInTheDocument();
  });
});
```

`// src/app/counter/counter.component.spec.ts`

```
import { ComponentFixture, TestBed } from "@angular/core/testing";
import { By } from "@angular/platform-browser";
import { PLAY_TESTING_IMPORTS } from "../testing";
import { CounterComponent } from "../counter.component";
describe("CounterComponent", () => {
  let component: CounterComponent;
  let fixture: ComponentFixture<CounterComponent>;
  beforeEach(async () => {
    await TestBed.configureTestingModule({
      imports: [CounterComponent, ...PLAY_TESTING_IMPORTS],
    }).compileComponents();
    fixture = TestBed.createComponent(CounterComponent);
    component = fixture.componentInstance;
  });
  describe("Component Creation", () => {
    it("should create the component", () => {
      expect(component).toBeTruthy();
    });
  });
  describe("User Interface", () => {
    beforeEach(() => {
      fixture.detectChanges();
    });
    it("should render with a count of 0", () => {
      const countElement = fixture.debugElement.query(By.css(".count"));
      expect(countElement.nativeElement.textContent).toContain("Count: 0");
    });
  });
  describe("Component Behavior", () => {
    it("should increment the count on click", () => {
      const button = fixture.debugElement.query(By.css("button"));
      button.triggerEventHandler("click", null);
      fixture.detectChanges();
      expect(component.count).toBe(1);
      const countElement = fixture.debugElement.query(By.css(".count"));
      expect(countElement.nativeElement.textContent).toContain("Count: 1");
    });
  });
  describe("Accessibility", () => {
    beforeEach(() => {
      fixture.detectChanges();
    });
    it("should have proper button labeling", () => {
      const button = fixture.debugElement.query(By.css("button"));
      expect(button.nativeElement.getAttribute("aria-label")).toBeTruthy();
    });
  });
});
```

Core Testing Principles ■ Follow the AAA Pattern ■ **Arrange** : Setup component, props, and dependencies **Act** : Simulate user interaction **Assert** : Validate output matches expectations **Test Behavior, Not Implementation** ■ Avoid relying on internal variables: Don't ■ `expect(component.state.value).toBe("hello")` ; Do ■ `expect(screen.getByRole("textbox")).toHaveValue("hello")` ; **Mocking Dependencies: Isolating the Unit** ■ Unit tests should be isolated from external dependencies like APIs. If `apiProxy` is detected, `playtest:gen` will auto-generate mocks.

```
import { vi } from "vitest";
import { apiProxy } from "../lib/apiProxy";
vi.mock("../lib/apiProxy");
it("displays user name after fetch", async () => {
  vi.mocked(apiProxy).mockResolvedValue({ json: () => Promise.resolve({ name: "John Doe" }) });
  render(<
```

```

UserProfile / > ) ; expect ( await screen . findByText ( "John Doe" ) ) . toBeInTheDocument ( ) ; } ) ;
import { PlayTestingUtils } from "../testing" ; it ( "displays user name after fetch" , async ( ) => {
const mockResponse = PlayTestingUtils . createMockApiResponse ( { name : "John Doe" , } ) ;
spyOn ( apiService , "getUser" ) . and . returnValue ( Promise . resolve ( mockResponse ) ) ;
component . loadUser ( ) ; await fixture . whenStable ( ) ; expect ( fixture . debugElement . query (
By . css ( ".user-name" ) ) . nativeElement . textContent ) . toContain ( "John Doe" ) ; } ) ; Testing
Utilities ■ PLAY_TESTING_IMPORTS ■ Provides common testing imports for standalone
components: import { PLAY_TESTING_IMPORTS } from "../testing" ; await TestBed .
configureTestingModule ( { imports : [ YourComponent , ... PLAY_TESTING_IMPORTS ] , } ) .
compileComponents ( ) ; PlayTestingUtils ■ Common testing helpers: import { PlayTestingUtils }
from "../testing" ; // Create mock API responses const mockResponse = PlayTestingUtils .
createMockApiResponse ( { data : "test" } ) ; // Create mock services const mockService =
PlayTestingUtils . createMockService ( [ "method1" , "method2" ] ) ; // Wait for async operations
await PlayTestingUtils . waitForAsync ( 100 ) ; // Setup TestBed for standalone components
PlayTestingUtils . configureTestBed ( YourComponent , [ AdditionalImports ] ) ; Additional Info ■
Why We Built This ■ Configuring a modern testing toolchain is complex. It involves selecting and
integrating multiple tools (Jest/Vitest, Testing Library, Karma), plugins (for React, Angular,
accessibility), and defining hundreds of configuration options. Without a centralized solution, each
team would waste time on setup and debates, leading to inconsistencies across projects. The
@playplus/testing-config package solves this by providing a single, opinionated, and
production-ready configuration. It eliminates boilerplate and configuration drift , ensuring every
project starts with and maintains the same high-quality testing standards. Best Practices ■ Trust
the Automation : Let the pre-commit hooks and CI checks do their job. Test User Behavior : Focus
on what users see and do, not implementation details. Use Descriptive Names : Test names
should clearly describe the expected behavior. Keep Tests Independent : Each test should be able
to run in isolation. Developer Checklist ■ Are you testing from the user's perspective (DOM and
behavior, not internals)? Are you following the AAA (Arrange, Act, Assert) pattern? Are
dependencies like APIs properly mocked ? Did you cover edge cases and negative flows ? Are
tests independent , fast, and refactor-proof? Did you run npm run playtest to validate before
pushing? Do your tests include accessibility checks ? Are you using PLAY_TESTING_IMPORTS
for consistent setup? Forbidden Patterns ■ Don't Test Implementation Details ■ // Don't test
private methods expect ( component [ "privateMethod" ] ( ) ) . toBe ( true ) ; // Don't test internal
state directly expect ( component [ "internalState" ] ) . toBe ( "value" ) ; Don't Test Framework
Behavior ■ // Don't test Angular lifecycle (Angular tests this) expect ( component . ngOnInit ) .
toHaveBeenCalled ( ) ; // Don't test dependency injection (Angular tests this) expect ( component [
"service" ] ) . toBeDefined ( ) ; Don't Use Complex Setup ■ // Don't create complex test data const
complexData = { /* 50 lines of test data */ } ; // Do use simple, focused test data const user = {
name : "John" , email : "john@example.com" } ; Required Patterns ■ Test User Behavior ■ // Test
what the user sees and does it ( "should show error message when form is invalid" , ( ) => { const
submitButton = fixture . debugElement . query ( By . css ( 'button[type="submit"]' ) ) ; submitButton

```

```
. triggerEventHandler ( "click" , null ) ; fixture . detectChanges ( ) ; const errorMessage = fixture .
debugElement . query ( By . css ( ".error-message" ) ) ; expect ( errorMessage ) . toBeTruthy ( ) ; }
```

); Use Descriptive Test Names ■ // Good: Describes the behavior it ("should disable submit
button when form is invalid" , () => { }) ; // Bad: Vague description it ("should work correctly" , ()
=> { }) ; Group Related Tests ■ describe ("UserProfileComponent" , () => { describe (
"Component Creation" , () => { // Creation tests }) ; describe ("User Interface" , () => { // UI tests
}) ; describe ("Component Behavior" , () => { // Behavior tests }) ; describe ("Accessibility" , ()
=> { // Accessibility tests }) ; }) ; Summary ■ Unit testing in Play+ isn't just about preventing
bugs—it's about unlocking creative confidence. With robust tooling, opinionated helpers, and
automated pipelines, we make testing an asset—not a burden. User-Centric : Focus on behaviors
and outcomes Fully Automated : Enforced via CI to protect quality Zero-Setup : Start writing tests
immediately Isolated & Predictable : Mocks ensure accuracy Write tests. Refactor freely. Ship with
confidence. Let your tests reflect the experience you're building—not just the code behind it.