

Services

Services Overview ■ Services in the PlayPlus architecture handle data operations, business logic, and external API communication. They provide a clean abstraction layer between your application and external data sources, ensuring consistent data management across your application. Key

Characteristics ■ Data Layer Abstraction ■ Handle all external API communication Provide

consistent data interfaces Manage caching and state synchronization Handle error scenarios

gracefully State Management ■ Use RxJS BehaviorSubject for reactive state Provide observable streams for data updates Implement caching strategies Support real-time data synchronization

Error Handling ■ Comprehensive error handling Retry mechanisms User-friendly error messages

Logging and monitoring support Template Structure ■ TypeScript Service (service.ts.hbs) ■

```
import { Injectable } from "@angular/core"; import { HttpClient } from "@angular/common/http";
```

```
import { Observable, BehaviorSubject } from "rxjs"; import { map, catchError } from
```

```
"rxjs/operators"; export interface ExampleData { id: string; name: string; // Add more properties
```

```
as needed } @ Injectable ( { providedIn: "root", } ) export class ExampleService { private apiUrl =
```

```
"/api/example"; // Update with your API endpoint private dataSubject = new BehaviorSubject <
```

```
ExampleData [ ] > ( [ ] ); public data$ = this . dataSubject . asObservable ( ); constructor ( private
```

```
http: HttpClient ) { } /** * Get all example data */ getData ( ): Observable < ExampleData [ ] > {
```

```
return this . http . get < ExampleData [ ] > ( this . apiUrl ) . pipe ( map ( ( data ) => { this .
```

```
dataSubject . next ( data ); return data ; } ) , catchError ( ( error ) => { console . error ( "Error
```

```
fetching example data:" , error ); throw error ; } ) ) ; } /** * Get example by ID */ getByid ( id: string
```

```
): Observable < ExampleData > { return this . http . get < ExampleData > ( ` ${ this . apiUrl } / ${ id }
```

```
` ) . pipe ( catchError ( ( error ) => { console . error ( ` Error fetching example with ID ${ id } : ` ,
```

```
error ); throw error ; } ) ) ; } /** * Create new example */ create ( data: Omit < ExampleData , "id" >
```

```
): Observable < ExampleData > { return this . http . post < ExampleData > ( this . apiUrl , data ) .
```

```
pipe ( map ( ( newData ) => { const currentData = this . dataSubject . value ; this . dataSubject .
```

```
next ( [ ... currentData , newData ] ); return newData ; } ) , catchError ( ( error ) => { console . error
```

```
( "Error creating example:" , error ); throw error ; } ) ) ; } /** * Update existing example */ update (
```

```
id: string , data: Partial < ExampleData > ): Observable < ExampleData > { return this . http . put
```

```
< ExampleData > ( ` ${ this . apiUrl } / ${ id } ` , data ) . pipe ( map ( ( updatedData ) => { const
```

```
currentData = this . dataSubject . value ; const updatedIndex = currentData . findIndex ( ( item ) =>
```

```
item . id === id ) ; if ( updatedIndex !== - 1 ) { currentData [ updatedIndex ] = updatedData ; this .
```

```
dataSubject . next ( [ ... currentData ] ) ; } return updatedData ; } ) , catchError ( ( error ) => {
```

```
console . error ( ` Error updating example with ID ${ id } : ` , error ); throw error ; } ) ) ; } /** * Delete
```

```
example */ delete ( id: string ): Observable < void > { return this . http . delete < void > ( ` ${ this .
```

```
apiUrl } / ${ id } ` ) . pipe ( map ( ( ) => { const currentData = this . dataSubject . value ; const
```

```
filteredData = currentData . filter ( ( item ) => item . id !== id ) ; this . dataSubject . next (
```

```
filteredData ) ; } ) , catchError ( ( error ) => { console . error ( ` Error deleting example with ID ${ id }
```

```
: ` , error ); throw error ; } ) ) ; } /** * Get current data from cache */ getCurrentData ( ) :
```

```

ExampleData [ ] { return this . dataSubject . value ; } /** * Clear cached data */ clearCache ( ) : void
{ this . dataSubject . next ( [ ] ) ; } } Features ■ Built-in Features ■ CRUD Operations Create,
Read, Update, Delete operations Type-safe interfaces Consistent error handling Reactive State
Management BehaviorSubject for current state Observable streams for updates Automatic cache
updates Error Handling Comprehensive error catching Detailed error logging Graceful error
propagation Caching In-memory data caching Cache invalidation strategies Cache clearing
methods Type Safety Strongly typed interfaces Generic type support IntelliSense support Best
Practices ■ Service Structure @ Injectable ( { providedIn : "root" , } ) export class ExampleService
{ private apiUrl = "/api/example" ; private dataSubject = new BehaviorSubject < ExampleData [ ] >
( [ ] ) ; public data$ = this . dataSubject . asObservable ( ) ; } Error Handling getData ( ) :
Observable < ExampleData [ ] > { return this . http . get < ExampleData [ ] > ( this . apiUrl ) . pipe (
map ( data => { this . dataSubject . next ( data ) ; return data ; } ) , catchError ( error => { console .
error ( 'Error fetching data:' , error ) ; throw error ; } ) ) ; } Cache Management getCurrentData ( ) :
ExampleData [ ] { return this . dataSubject . value ; } clearCache ( ) : void { this . dataSubject . next
( [ ] ) ; } Basic Service ■ # Generate a basic service playplus generate service user This creates:
UserService with CRUD operations UserData interface Comprehensive error handling Caching
mechanisms Advanced Service ■ # Generate with custom interface playplus generate service
product --interface=Product This creates: ProductService with custom interface Advanced caching
strategies Real-time data synchronization // In container component export class
UserListContainerComponent { private userService = inject ( UserService ) ; protected users =
signal < User [ ] > ( [ ] ) ; constructor ( ) { this . loadUsers ( ) ; } private loadUsers ( ) : void { this .
userService . getData ( ) . pipe ( takeUntilDestroyed ( ) ) . subscribe ( { next : ( users ) => this .
users . set ( users ) , error : ( error ) => console . error ( "Failed to load users:" , error ) , } ) ; }
protected createUser ( userData : Omit < User , "id" > ) : void { this . userService . create (
userData ) . pipe ( takeUntilDestroyed ( ) ) . subscribe ( { next : ( newUser ) => { // User created
successfully this . loadUsers ( ) ; // Refresh the list } , error : ( error ) => console . error ( "Failed to
create user:" , error ) , } ) ; } } Multiple Services ■ // In complex container component export class
DashboardContainerComponent { private userService = inject ( UserService ) ; private
productService = inject ( ProductService ) ; private orderService = inject ( OrderService ) ;
protected users = signal < User [ ] > ( [ ] ) ; protected products = signal < Product [ ] > ( [ ] ) ;
protected orders = signal < Order [ ] > ( [ ] ) ; constructor ( ) { this . loadDashboardData ( ) ; }
private loadDashboardData ( ) : void { // Load all data in parallel combineLatest ( [ this .
userService . getData ( ) , this . productService . getData ( ) , this . orderService . getData ( ) , ] ) .
pipe ( takeUntilDestroyed ( ) ) . subscribe ( { next : ( [ users , products , orders ] ) => { this . users .
set ( users ) ; this . products . set ( products ) ; this . orders . set ( orders ) ; } , error : ( error ) =>
console . error ( "Failed to load dashboard data:" , error ) , } ) ; } } Data Interfaces ■ Basic Interface
■ export interface UserData { id : string ; name : string ; email : string ; isActive : boolean ;
createdAt : Date ; updatedAt : Date ; } Complex Interface ■ export interface ProductData { id :
string ; name : string ; description : string ; price : number ; category : ProductCategory ; images :
string [ ] ; specifications : Record < string , any > ; isAvailable : boolean ; stockQuantity : number ;

```

```

createdAt : Date ; updatedAt : Date ; } export enum ProductCategory { ELECTRONICS =
"electronics" , CLOTHING = "clothing" , BOOKS = "books" , HOME = "home" , } Advanced
Patterns ■ Caching Strategies ■ export class AdvancedExampleService { private cache = new
Map < string , { data : any ; timestamp : number } > ( ) ; private readonly CACHE_DURATION = 5 *
60 * 1000 ; // 5 minutes getDataWithCache ( id : string ) : Observable < ExampleData > { const
cached = this . cache . get ( id ) ; const now = Date . now ( ) ; if ( cached && now - cached .
timestamp < this . CACHE_DURATION ) { return of ( cached . data ) ; } return this . http . get <
ExampleData > ( ` ${ this . apiUrl } / ${ id } ` ) . pipe ( map ( ( data ) => { this . cache . set ( id , {
data , timestamp : now } ) ; return data ; } ) ) ; } invalidateCache ( id ? : string ) : void { if ( id ) { this .
cache . delete ( id ) ; } else { this . cache . clear ( ) ; } } Real-time Updates ■ export class
RealTimeExampleService { private dataSubject = new BehaviorSubject < ExampleData [ ] > ( [ ] ) ;
public data$ = this . dataSubject . asObservable ( ) ; // WebSocket connection for real-time
updates private wsConnection : WebSocket ; constructor ( ) { this . initializeWebSocket ( ) ; }
private initializeWebSocket ( ) : void { this . wsConnection = new WebSocket (
"ws://api.example.com/updates" ) ; this . wsConnection . onmessage = ( event ) => { const update
= JSON . parse ( event . data ) ; this . handleRealTimeUpdate ( update ) ; } } private
handleRealTimeUpdate ( update : any ) : void { const currentData = this . dataSubject . value ;
switch ( update . type ) { case "CREATE" : this . dataSubject . next ( [ ... currentData , update .
data ] ) ; break ; case "UPDATE" : const updatedData = currentData . map ( ( item ) => item . id
=== update . data . id ? update . data : item ) ; this . dataSubject . next ( updatedData ) ; break ;
case "DELETE" : const filteredData = currentData . filter ( ( item ) => item . id !== update . data . id
) ; this . dataSubject . next ( filteredData ) ; break ; } } Testing ■ Service Testing ■ describe (
"UserService" , ( ) => { let service : UserService ; let httpMock : HttpTestingController ; beforeEach
( ( ) => { TestBed . configureTestingModule ( { imports : [ HttpClientTestingModule ] , providers : [
UserService ] , } ) ; service = TestBed . inject ( UserService ) ; httpMock = TestBed . inject (
HttpTestingController ) ; } ) ; afterEach ( ( ) => { httpMock . verify ( ) ; } ) ; it ( "should fetch users
successfully" , ( ) => { const mockUsers : UserData [ ] = [ { id : "1" , name : "John Doe" , email :
"john@example.com" , isActive : true , createdAt : new Date ( ) , updatedAt : new Date ( ) , } , ] ;
service . getData ( ) . subscribe ( ( users ) => { expect ( users ) . toEqual ( mockUsers ) ; } ) ; const
req = httpMock . expectOne ( "/api/user" ) ; expect ( req . request . method ) . toBe ( "GET" ) ; req .
flush ( mockUsers ) ; } ) ; it ( "should handle errors gracefully" , ( ) => { service . getData ( ) .
subscribe ( { next : ( ) => fail ( "Should not succeed" ) , error : ( error ) => { expect ( error . status ) .
toBe ( 500 ) ; } , } ) ; const req = httpMock . expectOne ( "/api/user" ) ; req . flush ( "Server error" , {
status : 500 , statusText : "Internal Server Error" , } ) ; } ) ; } ) ; Error Handling Strategies ■ Retry
Logic ■ import { retry , delay } from 'rxjs/operators' ; getDataWithRetry ( ) : Observable <
ExampleData [ ] > { return this . http . get < ExampleData [ ] > ( this . apiUrl ) . pipe ( retry ( 3 ) , //
Retry 3 times delay ( 1000 ) , // Wait 1 second between retries catchError ( error => { console .
error ( 'Failed after retries:' , error ) ; throw error ; } ) ) ; } Error Transformation ■ import {
throwError } from 'rxjs' ; private handleError ( error : any ) : Observable < never > { let
errorMessage = 'An unknown error occurred' ; if ( error . status === 404 ) { errorMessage =

```

```
'Resource not found' ; } else if ( error . status === 500 ) { errorMessage = 'Server error occurred' ; }  
else if ( error . status === 0 ) { errorMessage = 'Network error - please check your connection' ; }  
console . error ( 'Service error:' , error ) ; return throwError ( ( ) => new Error ( errorMessage ) ) ; }
```

Performance Optimization ■ Lazy Loading ■ export class LazyExampleService { private
dataSubject = new BehaviorSubject < ExampleData [] > ([]) ; public data\$ = this . dataSubject .
asObservable () ; private loaded = false ; getData () : Observable < ExampleData [] > { if (! this .
loaded) { this . loadData () ; } return this . data\$; } private loadData () : void { this . loaded = true ;
this . http . get < ExampleData [] > (this . apiUrl) . pipe (map ((data) => { this . dataSubject .
next (data) ; return data ; }) , catchError ((error) => { this . loaded = false ; // Allow retry throw
error ; })) . subscribe () ; } } Next Steps ■ After creating a service: Define the data interface for

your specific domain Implement CRUD operations for your API endpoints Add error handling
specific to your use case Implement caching strategies if needed Write comprehensive tests for all
operations Integrate with container components for data flow Developer Checklist ■ Before
Creating Services: ■ Are data interfaces defined for all entities? Is HTTP error handling
implemented with meaningful messages? Is BehaviorSubject used for reactive state
management? Are CRUD operations implemented for all entities? Is retry logic added for network
failures? Are caching strategies implemented where needed? Are all API endpoints typed with
TypeScript? Is data validation and sanitization implemented? Do I have unit tests with HTTP
mocking? Is logging added for debugging and monitoring? Are RxJS operators used for async
operations? Are cache invalidation strategies implemented?