

Architecture

Overview Separation of Concerns ■ Container Components : Handle business logic and data management Presentational Components : Focus purely on rendering and user interaction Services : Manage data operations and external API communication

Unidirectional Data Flow ■ Services → Container Components → Presentational

Components → User Actions → Container Components → Services Modern Angular

Patterns ■ Angular Signals for reactive state management Standalone Components for better tree-shaking OnPush Change Detection for optimal performance TypeScript-first approach with strong typing Component Types ■ 1. Container Components ■ Purpose :

Handle business logic, data management, and state coordination. Characteristics : Inject and use services Manage application state with signals Handle loading, error, and data states

Coordinate between services and presentational components Transform data for presentation Example Structure : @ Component ({ ... }) export class

UserListContainerComponent { private userService = inject (UserService) ; protected users

= signal < User [] > ([]) ; protected loading = signal (false) ; protected error = signal <

Error | null > (null) ; protected userData = computed (() => this . users () . map (user => ({

id : user . id , title : user . name , description : user . email , isActive : user . isActive }))) ;

constructor () { this . loadUsers () ; } private loadUsers () : void { this . loading . set (true) ;

this . userService . getData () . pipe (takeUntilDestroyed ()) . subscribe ({ next : (users)

=> { this . users . set (users) ; this . loading . set (false) ; } , error : (error) => { this . error .

set (error) ; this . loading . set (false) ; } }) ; } } 2. Presentational Components ■ Purpose :

Focus purely on rendering and user interaction. Characteristics : Receive data through inputs

Emit events through outputs No direct service dependencies Highly reusable and testable

Built-in accessibility features Example Structure : @ Component ({ ... }) export class

UserCardComponent { readonly data = input . required < UserCardData > () ; readonly

disabled = input < boolean > (false) ; readonly actionTriggered = output < string > () ;

readonly itemClicked = output < UserCardData > () ; readonly isInteractive = computed (()

=> ! this . disabled () && this . data () . isActive) ; protected onClick () : void { if (this .

isInteractive ()) { this . itemClicked . emit (this . data ()) ; } } } 3. Services ■ Purpose :

Handle data operations and external API communication. Characteristics : CRUD operations

for data management Reactive state with BehaviorSubject Comprehensive error handling

Caching strategies Type-safe interfaces Example Structure : @ Injectable ({ providedIn :

"root" }) export class UserService { private apiUrl = "/api/users" ; private dataSubject = new

```

BehaviorSubject < User [ ] > ( [ ] ) ; public data$ = this . dataSubject . asObservable ( ) ;
getData ( ) : Observable < User [ ] > { return this . http . get < User [ ] > ( this . apiUrl ) . pipe (
map ( ( data ) => { this . dataSubject . next ( data ) ; return data ; } ) , catchError ( this .
handleError ) ) ; } create ( user : Omit < User , "id" > ) : Observable < User > { return this .
http . post < User > ( this . apiUrl , user ) . pipe ( map ( ( newUser ) => { const currentData =
this . dataSubject . value ; this . dataSubject . next ( [ ... currentData , newUser ] ) ; return
newUser ; } ) , catchError ( this . handleError ) ) ; } } Data Flow Patterns ■ 1. Data Loading
Flow ■ // 1. Container component loads data export class UserListContainerComponent {
private userService = inject ( UserService ) ; protected users = signal < User [ ] > ( [ ] ) ;
constructor ( ) { this . loadUsers ( ) ; } private loadUsers ( ) : void { this . userService . getData
( ) . pipe ( takeUntilDestroyed ( ) ) . subscribe ( { next : ( users ) => this . users . set ( users ) ,
error : ( error ) => console . error ( "Failed to load users:" , error ) , } ) ; } } 2. Data
Transformation Flow ■ // 2. Container transforms data for presentation export class
UserListContainerComponent { protected userData = computed ( ( ) => this . users ( ) . map (
( user ) => ( { id : user . id , title : user . name , description : user . email , isActive : user .
isActive , } ) ) ) ; } 3. User Interaction Flow ■ // 3. Presentational component emits events
export class UserCardComponent { readonly itemClicked = output < UserCardData > ( ) ;
protected onClick ( ) : void { this . itemClicked . emit ( this . data ( ) ) ; } } // 4. Container
handles events export class UserListContainerComponent { protected onUserSelect (
userData : UserCardData ) : void { // Handle user selection this . router . navigate ( [ "/users" ,
userData . id ] ) ; } } State Management Strategy ■ Signal-Based State ■ // Container
component state export class ExampleContainerComponent { // Core state protected data =
signal < Data [ ] > ( [ ] ) ; protected loading = signal ( false ) ; protected error = signal < Error |
null > ( null ) ; // Computed state protected hasData = computed ( ( ) => this . data ( ) . length
> 0 ) ; protected canLoadMore = computed ( ( ) => ! this . loading ( ) && ! this . error ( ) &&
this . hasData ( ) ) ; // Transformed state for presentation protected presentationData =
computed ( ( ) => this . data ( ) . map ( ( item ) => this . transformForPresentation ( item ) ) ) ;
} Reactive Updates ■ // Services provide reactive streams export class ExampleService {
private dataSubject = new BehaviorSubject < Data [ ] > ( [ ] ) ; public data$ = this .
dataSubject . asObservable ( ) ; getData ( ) : Observable < Data [ ] > { return this . http . get <
Data [ ] > ( this . apiUrl ) . pipe ( map ( ( data ) => { this . dataSubject . next ( data ) ; // Update
cache return data ; } ) ) ; } } Component Communication Patterns ■ 1. Parent-Child
Communication ■ // Container passes data to presentational < app - user - card [ data ] =
"userData()" [ disabled ] = "loading()" ( actionTriggered ) = "onUserAction($event)" (
itemClicked ) = "onUserSelect($event)" > < / app - user - card > 2. Service-Based

```

Communication ■ // Multiple containers share data through service export class

```
UserListComponent { private userService = inject ( UserService ) ; protected users
= signal < User [ ] > ( [ ] ) ; constructor ( ) { this . userService . data$ . pipe (
takeUntilDestroyed ( ) ) . subscribe ( ( users ) => this . users . set ( users ) ) ; } } export class
UserDetailContainerComponent { private userService = inject ( UserService ) ; protected
selectedUser = signal < User | null > ( null ) ; constructor ( ) { this . userService . data$ . pipe
( takeUntilDestroyed ( ) ) . subscribe ( ( users ) => { // Find selected user const user = users .
find ( ( u ) => u . id === this . route . snapshot . params [ "id" ] ) ; this . selectedUser . set (
user || null ) ; } ) ; } } Error Handling Strategy ■ 1. Service-Level Error Handling ■ export
class ExampleService { getData ( ) : Observable < Data [ ] > { return this . http . get < Data [ ]
> ( this . apiUrl ) . pipe ( catchError ( ( error ) => { console . error ( "Service error:" , error ) ;
throw error ; } ) ) ; } } 2. Container-Level Error Handling ■ export class
ExampleContainerComponent { protected error = signal < Error | null > ( null ) ; private
loadData ( ) : void { this . loading . set ( true ) ; this . error . set ( null ) ; this . exampleService .
getData ( ) . pipe ( takeUntilDestroyed ( ) ) . subscribe ( { next : ( data ) => { this . data . set (
data ) ; this . loading . set ( false ) ; } , error : ( error ) => { this . error . set ( error ) ; this .
loading . set ( false ) ; } , } ) ; } protected retry ( ) : void { this . loadData ( ) ; } } 3.
User-Friendly Error Display ■ @if (error(); as errorData) { < div class = " error-state " role = "
alert " > < h2 > Something went wrong </ h2 > < p > </ p > < button (click) = " retry() " > Try
Again </ button > </ div > } Performance Optimization ■ 1. OnPush Change Detection ■ @
Component ( { changeDetection : ChangeDetectionStrategy . OnPush , } ) export class
ExampleComponent { // Component only updates when inputs change } 2. Signal-Based
Reactivity ■ // Only updates when dependencies change protected computedValue =
computed ( ( ) => this . data ( ) . filter ( item => item . isActive ) . length ) ; 3. Lazy Loading ■
// Load data only when needed export class LazyContainerComponent { private loaded =
false ; protected loadData ( ) : void { if ( ! this . loaded ) { this . loaded = true ; this .
exampleService . getData ( ) . subscribe ( ) ; } } } Testing Strategy ■ 1. Presentational
Component Testing ■ describe ( "UserCardComponent" , ( ) => { let component :
UserCardComponent ; beforeEach ( ( ) => { component = new UserCardComponent ( ) ; } ) ;
it ( "should emit click event when interactive" , ( ) => { const spy = jasmine . createSpy ( ) ;
component . itemClicked . subscribe ( spy ) ; component . data . set ( { id : "1" , title : "Test" ,
isActive : true } ) ; component . disabled . set ( false ) ; component . onClick ( ) ; expect ( spy )
. toHaveBeenCalled ( ) ; } ) ; } ) ; 2. Container Component Testing ■ describe (
"UserListComponent" , ( ) => { let component : UserListComponent ; let
userService : jasmine . SpyObj < UserService > ; beforeEach ( ( ) => { const spy = jasmine .
```

```

createSpyObj ( "UserService" , [ "getData" ] ) ; TestBed . configureTestingModule ( {
providers : [ { provide : UserService , useValue : spy } ] , } ) ; component = TestBed .
createComponent ( UserListContainerComponent ) . componentInstance ; userService =
TestBed . inject ( UserService ) ; } ) ; it ( "should load users on init" , ( ) => { const mockUsers
= [ { id : "1" , name : "John" } ] ; userService . getData . and . returnValue ( of ( mockUsers ) )
; component . ngOnInit ( ) ; expect ( component . users ( ) ) . toEqual ( mockUsers ) ; } ) ; } ) ;
3. Service Testing ■ describe ( "UserService" , ( ) => { let service : UserService ; let
httpMock : HttpTestingController ; beforeEach ( ( ) => { TestBed . configureTestingModule ( {
imports : [ HttpClientTestingModule ] , providers : [ UserService ] , } ) ; service = TestBed .
inject ( UserService ) ; httpMock = TestBed . inject ( HttpTestingController ) ; } ) ; it ( "should
fetch users" , ( ) => { const mockUsers = [ { id : "1" , name : "John" } ] ; service . getData ( ) .
subscribe ( ( users ) => { expect ( users ) . toEqual ( mockUsers ) ; } ) ; const req = httpMock .
expectOne ( "/api/users" ) ; req . flush ( mockUsers ) ; } ) ; } ) ;

```

Best Practices ■ 1. Component Design ■ Single Responsibility : Each component has one clear purpose
Composition over Inheritance : Use composition for reusability Props Down, Events Up :
Data flows down, events flow up **Pure Functions :** Presentational components should be pure

2. State Management ■ Single Source of Truth : Services are the source of truth **Immutable Updates :** Use signals for immutable state updates **Computed Values :** Use computed for derived state **Error Boundaries :** Handle errors at appropriate levels

3. Performance ■ OnPush Change Detection : Use for all components **Signal-Based Reactivity :** Leverage Angular signals **Lazy Loading :** Load data only when needed **Memory Management :** Use takeUntilDestroyed for cleanup

4. Testing ■ Unit Tests : Test components in isolation **Integration Tests :** Test component interactions **Service Tests :** Mock HTTP requests **Accessibility Tests :** Test with screen readers

Migration Guide ■ From Traditional Angular ■ Replace Services : Update to use BehaviorSubject pattern **Add Signals :** Replace properties with signals **Update Components :** Split into container/presentational **Add Error Handling :** Implement comprehensive error handling **Update Tests :** Write tests for new patterns

From Other Patterns ■ Redux to Signals : Replace Redux with signal-based state **NgRx to Services :** Use services instead of NgRx **Smart/Dumb Pattern :** Align with container/presentational pattern

Developer Checklist ■ Before Implementing Architecture: ■
Are presentational components pure (no business logic, only rendering)? Do container components handle all data management and business logic? Are all state updates using Angular Signals? Is OnPush change detection enabled on all components? Do services use BehaviorSubject for reactive state? Are user interactions handled through presentational component outputs? Have I implemented error handling at service and component levels?

Are data interfaces defined for component communication? Is `takeUntilDestroyed()` used for subscription cleanup? Does the data flow follow: Services → Containers → Presentational → User Actions?

Services → Container Components → Presentational Components → User Actions → Container Components →

```
@Component({...})
export class UserListContainerComponent {
  private userService = inject(UserService);

  protected users = signal<User[]>([]);
  protected loading = signal(false);
  protected error = signal<Error | null>(null);

  protected userData = computed(() =>
    this.users().map(user => ({
      id: user.id,
      title: user.name,
      description: user.email,
      isActive: user.isActive
    })))
  );

  constructor() {
    this.loadUsers();
  }

  private loadUsers(): void {
    this.loading.set(true);
    this.userService.getData()
      .pipe(takeUntilDestroyed())
      .subscribe({
        next: (users) => {
          this.users.set(users);
          this.loading.set(false);
        },
        error: (error) => {
          this.error.set(error);
          this.loading.set(false);
        }
      });
  }
}
```

```
@Component({...})
```

```

export class UserCardComponent {
  readonly data = input.required<UserCardData>();
  readonly disabled = input<boolean>(false);

  readonly actionTriggered = output<string>();
  readonly itemClicked = output<UserCardData>();

  readonly isInteractive = computed(() =>
    !this.disabled() && this.data().isActive
  );

  protected onClick(): void {
    if (this.isInteractive()) {
      this.itemClicked.emit(this.data());
    }
  }
}

---

@Injectable({ providedIn: "root" })
export class UserService {
  private apiUrl = "/api/users";
  private dataSubject = new BehaviorSubject<User[]>([]);
  public data$ = this.dataSubject.asObservable();

  getData(): Observable<User[]> {
    return this.http.get<User[]>(this.apiUrl).pipe(
      map((data) => {
        this.dataSubject.next(data);
        return data;
      }),
      catchError(this.handleError)
    );
  }

  create(user: Omit<User, "id">): Observable<User> {
    return this.http.post<User>(this.apiUrl, user).pipe(
      map((newUser) => {
        const currentData = this.dataSubject.value;
        this.dataSubject.next([...currentData, newUser]);
        return newUser;
      }),
      catchError(this.handleError)
    );
  }
}

---

// 1. Container component loads data

```

```

export class UserListContainerComponent {
  private userService = inject(UserService);

  protected users = signal<User[]>([]);

  constructor() {
    this.loadUsers();
  }

  private loadUsers(): void {
    this.userService
      .getData()
      .pipe(takeUntilDestroyed())
      .subscribe({
        next: (users) => this.users.set(users),
        error: (error) => console.error("Failed to load users:", error),
      });
  }
}

```

```

// 2. Container transforms data for presentation
export class UserListContainerComponent {
  protected userData = computed(() =>
    this.users().map((user) => ({
      id: user.id,
      title: user.name,
      description: user.email,
      isActive: user.isActive,
    })))
  );
}

```

```

// 3. Presentational component emits events
export class UserCardComponent {
  readonly itemClicked = output<UserCardData>();

  protected onClick(): void {
    this.itemClicked.emit(this.data());
  }
}

```

```

// 4. Container handles events
export class UserListContainerComponent {
  protected onUserSelect(userData: UserCardData): void {
    // Handle user selection
    this.router.navigate(["/users", userData.id]);
  }
}

```

```
}
```

```
---
```

```
// Container component state
export class ExampleContainerComponent {
  // Core state
  protected data = signal<Data[]>([]);
  protected loading = signal(false);
  protected error = signal<Error | null>(null);

  // Computed state
  protected hasData = computed(() => this.data().length > 0);
  protected canLoadMore = computed(
    () => !this.loading() && !this.error() && this.hasData()
  );

  // Transformed state for presentation
  protected presentationData = computed(() =>
    this.data().map((item) => this.transformForPresentation(item))
  );
}
```

```
---
```

```
// Services provide reactive streams
export class ExampleService {
  private dataSubject = new BehaviorSubject<Data[]>([]);
  public data$ = this.dataSubject.asObservable();

  getData(): Observable<Data[]> {
    return this.http.get<Data[]>(this.apiUrl).pipe(
      map((data) => {
        this.dataSubject.next(data); // Update cache
        return data;
      })
    );
  }
}
```

```
---
```

```
// Container passes data to presentational
<app-user-card
  [data]="userData()"
  [disabled]="loading()"
  (actionTriggered)="onUserAction($event)"
  (itemClicked)="onUserSelect($event)">
</app-user-card>
```

// Multiple containers share data through service

```
export class UserListContainerComponent {
  private userService = inject(UserService);
  protected users = signal<User[]>([]);

  constructor() {
    this.userService.data$
      .pipe(takeUntilDestroyed())
      .subscribe((users) => this.users.set(users));
  }
}
```

```
export class UserDetailContainerComponent {
  private userService = inject(UserService);
  protected selectedUser = signal<User | null>(null);

  constructor() {
    this.userService.data$.pipe(takeUntilDestroyed()).subscribe((users) => {
      // Find selected user
      const user = users.find((u) => u.id === this.route.snapshot.params["id"]);
      this.selectedUser.set(user || null);
    });
  }
}
```

```
export class ExampleService {
  getData(): Observable<Data[]> {
    return this.http.get<Data[]>(this.apiUrl).pipe(
      catchError((error) => {
        console.error("Service error:", error);
        throw error;
      })
    );
  }
}
```

```
export class ExampleContainerComponent {
  protected error = signal<Error | null>(null);

  private loadData(): void {
    this.loading.set(true);
    this.error.set(null);

    this.exampleService
      .getData()
```

```

        .pipe(takeUntilDestroyed())
        .subscribe({
            next: (data) => {
                this.data.set(data);
                this.loading.set(false);
            },
            error: (error) => {
                this.error.set(error);
                this.loading.set(false);
            },
        });
    }

    protected retry(): void {
        this.loadData();
    }
}

---

@if (error(); as errorData) {
<div class="error-state" role="alert">
    <h2>Something went wrong</h2>
    <p>{{ errorData.message }}</p>
    <button (click)="retry()">Try Again</button>
</div>
}

---

@Component({
    changeDetection: ChangeDetectionStrategy.OnPush,
})
export class ExampleComponent {
    // Component only updates when inputs change
}

---

// Only updates when dependencies change
protected computedValue = computed(() =>
    this.data().filter(item => item.isActive).length
);

---

// Load data only when needed
export class LazyContainerComponent {
    private loaded = false;

```

```

protected loadData(): void {
  if (!this.loaded) {
    this.loaded = true;
    this.exampleService.getData().subscribe();
  }
}
}
}

```

```

describe("UserCardComponent", () => {
  let component: UserCardComponent;

  beforeEach(() => {
    component = new UserCardComponent();
  });

  it("should emit click event when interactive", () => {
    const spy = jasmine.createSpy();
    component.itemClicked.subscribe(spy);

    component.data.set({ id: "1", title: "Test", isActive: true });
    component.disabled.set(false);

    component.onClick();

    expect(spy).toHaveBeenCalled();
  });
});

```

```

describe("UserListContainerComponent", () => {
  let component: UserListContainerComponent;
  let userService: jasmine.SpyObj<UserService>;

  beforeEach(() => {
    const spy = jasmine.createSpyObj("UserService", ["getData"]);
    TestBed.configureTestingModule({
      providers: [{ provide: UserService, useValue: spy }],
    });

    component = TestBed.createComponent(
      UserListContainerComponent
    ).componentInstance;
    userService = TestBed.inject(UserService);
  });

  it("should load users on init", () => {
    const mockUsers = [{ id: "1", name: "John" }];
    userService.getData.and.returnValue(of(mockUsers));
  });
});

```

```

    component.ngOnInit();

    expect(component.users()).toEqual(mockUsers);
  });
});

---

describe("UserService", () => {
  let service: UserService;
  let httpMock: HttpTestingController;

  beforeEach(() => {
    TestBed.configureTestingModule({
      imports: [HttpClientTestingModule],
      providers: [UserService],
    });

    service = TestBed.inject(UserService);
    httpMock = TestBed.inject(HttpTestingController);
  });

  it("should fetch users", () => {
    const mockUsers = [{ id: "1", name: "John" }];

    service.getData().subscribe((users) => {
      expect(users).toEqual(mockUsers);
    });

    const req = httpMock.expectOne("/api/users");
    req.flush(mockUsers);
  });
});

```