

# Menu

Menu A flexible and feature-rich dropdown menu component for creating context menus, navigation dropdowns, and action menus. Supports icons, descriptions, multi-column layout, various positioning options, and full accessibility. How to use ■ `import { AavaMenuComponent } from "@aava/play-core"` ; Basic Usage ■ The Menu component provides a dropdown interface that can be positioned relative to a trigger element. It supports various menu items with different states and configurations. Default behavior: Bottom positioning, single column layout, with icons and titles. Usage: Pass an array of menu items to the items input and control visibility with the visible input. Angular Preview Code

```
<div class="menu-container"><button (click)="toggleMenu()">Open Menu</button><aava-menu [items]="menuItems" [visible]="showMenu" (itemSelected)="handleItemSelected($event)"></aava-menu></div>
```

`import { Component } from "@angular/core"; import { AavaMenuComponent } from "@aava/play-core"; @Component({ selector: "app-menu-basic", standalone: true, imports: [AavaMenuComponent], }) export class MenuBasicComponent { showMenu = false; menuItems = [{ label: "Dashboard", route: "/dashboard" }, { label: "Profile", route: "/profile" }, { label: "Settings", route: "/settings" }, { label: "Help", route: "/help" }, { label: "Logout", route: "/logout" }, ]; toggleMenu() { this.showMenu = !this.showMenu; } handleItemSelected(event: any) { console.log("Selected:", event.label); this.showMenu = false; } }` With Icons ■ Menu items can display icons alongside their labels for better visual recognition and user experience. How: Add an icon property to menu items with the icon name. When to use: For quick recognition, consistent visual language, or when space allows. Angular Preview Code

```
<div class="menu-container"><button (click)="toggleMenu()">Menu with Icons</button><aava-menu [items]="menuItems" [visible]="showMenu" [displayOptions]="{ showIcon: true, showTitle: true }" (itemSelected)="handleItemSelected($event)"></aava-menu></div>
```

`import { Component } from "@angular/core"; import { AavaMenuComponent } from "@aava/play-core"; @Component({ selector: "app-menu-with-icons", standalone: true, imports: [AavaMenuComponent], }) export class MenuWithIconsComponent { showMenu = false; menuItems = [{ label: "Dashboard", icon: "home", route: "/dashboard" }, { label: "Profile", icon: "user", route: "/profile" }, { label: "Settings", icon: "settings", route: "/settings" }, { label: "Notifications", icon: "bell", route: "/notifications" }, { label: "Help", icon: "help-circle", route: "/help" }, { label: "Logout", icon: "log-out", route: "/logout" }, ]; toggleMenu() { this.showMenu = !this.showMenu; } handleItemSelected(event: any) { console.log("Selected:", event.label); this.showMenu = false; } }` With Descriptions ■ Menu items can include descriptions to provide additional context or information about each option. How: Add a description property to menu items. When to use: For complex menus where items need additional explanation or context. Angular Preview Code

```
<div class="menu-container"><button (click)="toggleMenu()">Menu with Descriptions</button><aava-menu [items]="menuItems" [visible]="showMenu" [displayOptions]="{ showIcon:
```

```

true, showTitle: true, showDescription: true } " (itemSelected) = " handleItemSelected($event) " >
</ aava-menu > </ div > import { Component } from "@angular/core" ; import {
AavaMenuComponent } from "@aava/play-core" ; @ Component ( { selector :
"app-menu-with-descriptions" , standalone : true , imports : [ AavaMenuComponent ] , } ) export
class MenuWithDescriptionsComponent { showMenu = false ; menuItems = [ { label : "Dashboard"
, icon : "home" , description : "View your main dashboard and overview" , route : "/dashboard" , } ,
{ label : "Profile" , icon : "user" , description : "Manage your account settings and preferences" ,
route : "/profile" , } , { label : "Settings" , icon : "settings" , description : "Configure application
settings and options" , route : "/settings" , } , { label : "Help" , icon : "help-circle" , description : "Get
help and support documentation" , route : "/help" , } , ] ; toggleMenu ( ) { this . showMenu = ! this .
showMenu ; } handleItemSelected ( event : any ) { console . log ( "Selected:" , event . label ) ; this .
showMenu = false ; } } Disabled Items ■ Menu items can be disabled to indicate unavailable
options or actions that require certain conditions. How: Set disabled: true on menu items. When to
use: For conditional actions, permission-based menus, or unavailable features. Angular Preview
Code < div class = " menu-container " > < button (click) = " toggleMenu() " > Menu with Disabled
Items </ button > < aava-menu [items] = " menuItems " [visible] = " showMenu " [displayOptions] =
" { showIcon: true, showTitle: true, showDescription: true } " (itemSelected) = "
handleItemSelected($event) " > </ aava-menu > </ div > import { Component } from
"@angular/core" ; import { AavaMenuComponent } from "@aava/play-core" ; @ Component ( {
selector : "app-menu-disabled-items" , standalone : true , imports : [ AavaMenuComponent ] , } )
export class MenuDisabledItemsComponent { showMenu = false ; menuItems = [ { label :
"Dashboard" , icon : "home" , description : "View your main dashboard" , route : "/dashboard" , } , {
label : "Profile" , icon : "user" , description : "Manage your account settings" , route : "/profile" , } , {
label : "Premium Features" , icon : "star" , description : "Upgrade to access premium features" ,
disabled : true , } , { label : "Advanced Analytics" , icon : "bar-chart" , description : "Advanced
analytics (requires premium)" , disabled : true , } , { label : "Help" , icon : "help-circle" , description :
"Get help and support" , route : "/help" , } , ] ; toggleMenu ( ) { this . showMenu = ! this . showMenu
; } handleItemSelected ( event : any ) { console . log ( "Selected:" , event . label ) ; this . showMenu
= false ; } } Features ■ Flexible Positioning ■ 8 Position Options : top, bottom, left, right, and their
start/end variants Alignment Control : start, center, end alignment within positioned area Offset
Configuration : Customizable spacing from trigger element Auto Flip : Automatic position
adjustment when space is limited Rich Content Support ■ Icons : Lucide icons with customizable
size and colors Descriptions : Additional text for context and explanation Active States : Visual
indication of currently active/selected items Disabled States : Clear indication of unavailable
options Layout Options ■ Multi-Column : Configurable column layout for extensive menus
Responsive Design : Adapts to different screen sizes and orientations Flexible Sizing : Automatic
width adjustment based on content Custom Styling : Extensive CSS custom properties for theming
Accessibility ■ Keyboard Navigation : Full keyboard support with arrow keys Screen Reader :
Proper ARIA attributes and semantic structure Focus Management : Clear focus indicators and
logical tab order High Contrast : Support for high contrast mode and color preferences API

```

Reference ■ Inputs ■ Property Type Default Description items MenuItem[] [] Array of menu items to display visible boolean false Controls menu visibility itemsPerColumn number 3 Number of items per column in multi-column layout positionConfig MenuPositionConfig See default config below Configuration for menu positioning displayOptions MenuItemDisplayOptions See default options below Configuration for item display customStyles Record<string, string> {} Custom CSS styles to apply to the menu Outputs ■ Property Type Description itemSelected EventEmitter<{route?: string; label: string; item: MenuItem}> Emitted when a menu item is clicked

MenuItem Interface ■ interface MenuItem { label : string ; // Display text for the menu item description ? : string ; // Optional description text route ? : string ; // Optional route for navigation icon ? : string ; // Optional icon name (Lucide) disabled ? : boolean ; // Whether the item is disabled divider ? : boolean ; // Whether to show a divider line customData ? : Record < string , unknown > ; // Custom data for the item } MenuPositionConfig Interface ■ interface MenuPositionConfig { position ? : MenuPosition ; // Position relative to trigger alignment ? : MenuAlignment ; // Alignment within positioned area offset ? : number ; // Distance from trigger element autoFlip ? : boolean ; // Auto-adjust position if needed } type MenuPosition = | "top" | "bottom" | "left" | "right" | "top-start" | "top-end" | "bottom-start" | "bottom-end" ; type MenuAlignment = "start" | "center" | "end" ; MenuItemDisplayOptions Interface ■ interface MenuItemDisplayOptions { showIcon ? : boolean ; // Whether to show icons showTitle ? : boolean ; // Whether to show item titles showDescription ? : boolean ; // Whether to show descriptions iconSize ? : number ; // Size of icons in pixels titleWeight ? : "normal" | "medium" | "semibold" | "bold" ; // Font weight for titles descriptionSize ? : "xs" | "sm" | "md" | "lg" ; // Font size for descriptions } Default Configurations ■ // Default position config { position : 'bottom' , alignment : 'start' , offset : 8 , } // Default display options { showIcon : true , showTitle : true , showDescription : true , iconSize : 24 , titleWeight : 'medium' , descriptionSize : 'sm' , } CSS Custom Properties ■

The component uses CSS custom properties for theming: Property Description --menu-min-width Minimum width of the menu --menu-background Background color of the menu --menu-border-radius Border radius of the menu --menu-shadow Box shadow of the menu --menu-border Border of the menu --menu-padding Padding inside the menu --menu-margin-top Top margin for positioning --menu-transform-y Transform distance for animations --menu-transition Transition timing for animations --menu-z-index Z-index for layering --menu-columns-gap Gap between columns --menu-column-min-width Minimum width of each column --menu-item-gap Gap between icon and content --menu-item-padding Padding of menu items --menu-item-border-radius Border radius of menu items --menu-item-background Background of menu items --menu-item-color Text color of menu items --menu-item-hover-background Background on hover --menu-item-hover-color Text color on hover --menu-item-active-background Background when active --menu-item-active-color Text color when active --menu-item-disabled-background Background when disabled --menu-item-disabled-color Text color when disabled --menu-item-margin Margin of menu items --menu-item-first-margin-top Top margin of first item --menu-item-last-margin-bottom Bottom margin of last item --menu-item-transition Transition timing for items --menu-item-icon-size Size of

item icons --menu-item-icon-color Color of item icons --menu-item-icon-active-color Color of active item icons --menu-item-icon-transition Transition timing for icons --menu-item-hover-icon-filter Icon filter on hover --menu-item-active-icon-filter Icon filter when active --menu-item-content-gap Gap between title and description --menu-item-title-font-weight Font weight of titles --menu-item-title-font-size Font size of titles --menu-item-title-color Color of titles --menu-item-title-active-color Color of active titles --menu-item-title-active-font-weight Font weight of active titles --menu-item-title-line-height Line height of titles --menu-item-title-transition Transition timing for titles --menu-item-description-font-size Font size of descriptions --menu-item-description-color Color of descriptions --menu-item-description-active-color Color of active descriptions --menu-item-description-line-height Line height of descriptions --menu-item-description-transition Transition timing for descriptions

**Best Practices**

- **Content Guidelines**
  - **Clear Labels** : Use concise, descriptive labels for menu items
  - Consistent Icons** : Use consistent iconography throughout the menu
  - Helpful Descriptions** : Provide context when items need explanation
  - Logical Grouping** : Group related items together in the menu
- **Interaction Design**
  - **Trigger Elements** : Ensure trigger elements are clearly identifiable
  - Positioning** : Choose positioning that doesn't obscure important content
  - Keyboard Support** : Test keyboard navigation thoroughly
  - Touch Support** : Consider touch interactions on mobile devices
- **Accessibility**
  - **ARIA Labels** : Provide appropriate ARIA labels for screen readers
  - Focus Management** : Ensure proper focus handling when menu opens/closes
  - Color Contrast** : Maintain sufficient contrast for all text and icons
  - Motion Sensitivity** : Respect user motion preferences

**Performance**

- **Efficient Rendering** : Use OnPush change detection for better performance
- Event Handling** : Properly handle click events to prevent bubbling
- Memory Management** : Clean up event listeners and subscriptions
- Lazy Loading** : Consider lazy loading for large menus

**Use Cases**

- **Context Menus**
  - Right-click context menus for actions on selected items:
 

```
< aava - menu [ items ] = "contextMenuItems" [ visible ] = "showContextMenu" [ positionConfig ] = "{ position: 'bottom-start' }" ( itemSelected ) = "handleContextMenuAction($event)" > < / aava - menu
```
- **Navigation Dropdowns**
  - Dropdown navigation menus for main navigation:
 

```
< aava - menu [ items ] = "navigationItems" [ visible ] = "showNavMenu" [ positionConfig ] = "{ position: 'bottom', alignment: 'center' }" [ displayOptions ] = "{ showIcon: true, showDescription: false }" > < / aava - menu
```
- **Action Menus**
  - Action menus for buttons or toolbar items:
 

```
< aava - menu [ items ] = "actionItems" [ visible ] = "showActionMenu" [ positionConfig ] = "{ position: 'bottom-end' }" [ itemsPerColumn ] = "1" > < / aava - menu
```
- **Application Launchers**
  - Multi-column menus for application or feature launchers:
 

```
< aava - menu [ items ] = "applItems" [ visible ] = "showAppMenu" [ positionConfig ] = "{ position: 'bottom', alignment: 'center' }" [ itemsPerColumn ] = "4" [ displayOptions ] = "{ showIcon: true, showDescription: true }" > < / aava - menu
```

**Accessibility Guidelines**

- **Keyboard Navigation**
  - The menu supports full keyboard navigation:
    - Enter/Space : Activate the currently focused menu item
    - Arrow Keys : Navigate between menu items
    - Escape : Close the menu
    - Tab : Move focus to next focusable element
- **Screen Reader Support**
  - The component provides comprehensive screen reader support:
    - ARIA Labels : Proper labeling for menu and menu items
    - Role Attributes : Correct ARIA roles for menu structure
    - State Announcements : Clear announcements of menu

state changes Focus Indicators : Visible focus indicators for keyboard users Color and Contrast ■ WCAG Compliance : All text and icons meet WCAG AA contrast ratios High Contrast Mode : Component works with system high contrast settings Color Independence : Information is not conveyed by color alone Motion and Animation ■ Respects Preferences : Animation respects user motion preferences Reduced Motion : Provides alternative interaction for motion-sensitive users Clear Feedback : Visual feedback is immediate and clear

```
<div class="menu-container">
  <button (click)="toggleMenu()">Open Menu</button>

  <aava-menu
    [items]="menuItems"
    [visible]="showMenu"
    (itemSelected)="handleItemSelected($event)">
  </aava-menu>
</div>
```

---

```
import { Component } from "@angular/core";
import { AavaMenuComponent } from "@aava/play-core";

@Component({
  selector: "app-menu-basic",
  standalone: true,
  imports: [AavaMenuComponent],
})
export class MenuBasicComponent {
  showMenu = false;

  menuItems = [
    { label: "Dashboard", route: "/dashboard" },
    { label: "Profile", route: "/profile" },
    { label: "Settings", route: "/settings" },
    { label: "Help", route: "/help" },
    { label: "Logout", route: "/logout" },
  ];

  toggleMenu() {
    this.showMenu = !this.showMenu;
  }

  handleItemSelected(event: any) {
    console.log("Selected:", event.label);
    this.showMenu = false;
  }
}
```

```

<div class="menu-container">
  <button (click)="toggleMenu()">Menu with Icons</button>

  <aava-menu
    [items]="menuItems"
    [visible]="showMenu"
    [displayOptions]="{ showIcon: true, showTitle: true }"
    (itemSelected)="handleItemSelected($event)">
  </aava-menu>
</div>

```

---

```

import { Component } from "@angular/core";
import { AavaMenuComponent } from "@aava/play-core";

@Component({
  selector: "app-menu-with-icons",
  standalone: true,
  imports: [AavaMenuComponent],
})
export class MenuWithIconsComponent {
  showMenu = false;

  menuItems = [
    { label: "Dashboard", icon: "home", route: "/dashboard" },
    { label: "Profile", icon: "user", route: "/profile" },
    { label: "Settings", icon: "settings", route: "/settings" },
    { label: "Notifications", icon: "bell", route: "/notifications" },
    { label: "Help", icon: "help-circle", route: "/help" },
    { label: "Logout", icon: "log-out", route: "/logout" },
  ];

  toggleMenu() {
    this.showMenu = !this.showMenu;
  }

  handleItemSelected(event: any) {
    console.log("Selected:", event.label);
    this.showMenu = false;
  }
}

```

```

<div class="menu-container">
  <button (click)="toggleMenu()">Menu with Descriptions</button>

  <aava-menu
    [items]="menuItems"
    [visible]="showMenu"
    [displayOptions]="{ showIcon: true, showTitle: true, showDescription: true }"
    (itemSelected)="handleItemSelected($event)">
  </aava-menu>
</div>

```

---

```

import { Component } from "@angular/core";
import { AavaMenuComponent } from "@aava/play-core";

@Component({
  selector: "app-menu-with-descriptions",
  standalone: true,
  imports: [AavaMenuComponent],
})
export class MenuWithDescriptionsComponent {
  showMenu = false;

  menuItems = [
    {
      label: "Dashboard",
      icon: "home",
      description: "View your main dashboard and overview",
      route: "/dashboard",
    },
    {
      label: "Profile",
      icon: "user",
      description: "Manage your account settings and preferences",
      route: "/profile",
    },
    {
      label: "Settings",
      icon: "settings",
      description: "Configure application settings and options",
      route: "/settings",
    },
    {
      label: "Help",
      icon: "help-circle",
      description: "Get help and support documentation",
      route: "/help",
    },
  ];

  toggleMenu() {
    this.showMenu = !this.showMenu;
  }
}

```

```
handleItemSelected(event: any) {  
  console.log("Selected:", event.label);  
  this.showMenu = false;  
}  
}
```



```

<div class="menu-container">
  <button (click)="toggleMenu()">Menu with Disabled Items</button>

  <aava-menu
    [items]="menuItems"
    [visible]="showMenu"
    [displayOptions]={ showIcon: true, showTitle: true, showDescription: true }"
    (itemSelected)="handleItemSelected($event)">
  </aava-menu>
</div>

```

---

```

import { Component } from "@angular/core";
import { AavaMenuComponent } from "@aava/play-core";

@Component({
  selector: "app-menu-disabled-items",
  standalone: true,
  imports: [AavaMenuComponent],
})
export class MenuDisabledItemsComponent {
  showMenu = false;

  menuItems = [
    {
      label: "Dashboard",
      icon: "home",
      description: "View your main dashboard",
      route: "/dashboard",
    },
    {
      label: "Profile",
      icon: "user",
      description: "Manage your account settings",
      route: "/profile",
    },
    {
      label: "Premium Features",
      icon: "star",
      description: "Upgrade to access premium features",
      disabled: true,
    },
    {
      label: "Advanced Analytics",
      icon: "bar-chart",
      description: "Advanced analytics (requires premium)",
      disabled: true,
    },
    {
      label: "Help",
      icon: "help-circle",
      description: "Get help and support",
      route: "/help",
    },
  ],

```

```
];

toggleMenu() {
  this.showMenu = !this.showMenu;
}

handleItemSelected(event: any) {
  console.log("Selected:", event.label);
  this.showMenu = false;
}
}
```