

Performance

Play+ Performance Helper : playperf Introduction ■ In the Play+ ecosystem, performance is not a feature to be added later—it's a foundational commitment. We believe great design must feel fast. This helper is based on the concept of Performance by Default, where speed, responsiveness, and stability are architected and enforced from day one. A performant application builds user trust and delight. This directly supports our core design pillars by creating an Engaging experience that feels fluid and responsive, and an Adaptive interface that performs well across all devices and network conditions. By ensuring a fast, stable experience, we also make our products more Intuitive and less frustrating to use.

Package Info ■ The Play+ performance helper and its associated CI configurations are included by default in the Golden Path starter kit. **Description** ■ Package / Path Golden Path (Recommended) Pre-installed /system/play.perf.ts Uplift Path npm install

@playplus/perf Folder Reference ■ The performance helper and its configuration follow our standardized folder structure for core system logic. **File / Directory Purpose & Guidelines** system/play.perf.ts The core performance helper. It provides utilities for deferring tasks and monitoring real-world performance.

config/play.performance.config.json User-overridable configuration for performance budgets (Lighthouse) and monitoring settings. reports/performance/ The git-ignored directory where Lighthouse CI reports are saved for local inspection.

Helper - Pillars Alignment ■ The playperf helper is a direct implementation of our core design pillars,

focused on the user's perception of speed. **Pillar How This Helper Aligns Engaging** Primary Pillar: Ensures snappy interactions and fluid animations, which are key to a delightful and engaging user experience. Adaptive Enforces performance budgets that ensure the application is fast and responsive on a wide range of devices and networks.

Intuitive A fast and stable application feels more predictable and intuitive, as users aren't left waiting or dealing with layout shifts.

Helper Overview ■ The playperf toolchain is a combination of automated guardrails and developer-facing utilities designed to abstract the plumbing of performance management. Instead of manually configuring performance budgets or writing complex code to defer non-critical tasks, developers can rely on the Play+ system to handle it. It automates performance quality control in two key ways:

Preventative Guardrails : In the CI/CD pipeline, playperf automatically runs Lighthouse audits against every pull request. If key metrics (like LCP or CLS) exceed the configured

budgets, the build fails, preventing performance regressions from ever reaching production.

Developer Empowerment Utilities : It provides a simple runtime helper with methods like `defer()` and `monitor()` that make it trivial to implement common performance patterns without writing boilerplate code. The goal is to make high performance the default path, not an extra chore.

Config Options ■ Global performance budgets and settings are managed in `config/play.performance.config.json` . These values are consumed by the CI pipeline and runtime helpers.

Config Key Table ■

Config Key	Default Value	Description
<code>lighthouse.lcp</code>	2500	Lighthouse budget for Largest Contentful Paint (ms).
<code>lighthouse.cls</code>	0.1	Lighthouse budget for Cumulative Layout Shift.
<code>lighthouse.inp</code>	200	Lighthouse budget for Interaction to Next Paint (ms).
<code>lighthouse.maxBundleSize</code>	250	Lighthouse budget for initial JS bundle size (KB, gzipped).
<code>enforce.blockBuildOnFail</code>	true	If true, the CI build will fail if performance budgets are exceeded.
<code>enforce.enableBundleDiff</code>	true	If true, PRs will be flagged with any unexpected changes to bundle size.
<code>monitor.webVitals</code>	true	If true, enables the real-user monitoring of Core Web Vitals via <code>playperf.monitor</code> .
<code>monitor.sentry</code>	true	Enables integration with Sentry Performance for transaction tracking.
<code>assist.highlightHeavyComponents</code>	true	In dev mode, flags components that are computationally expensive or re-rendering unnecessarily.

Helper Methods ■

Core Methods ■

Method Name	Description	Signature
<code>defer</code>	Schedules non-critical tasks to run during browser idle time, preventing them from blocking critical rendering.	<code>defer(callback: () => void, options?: { priority: 'high' 'low', timeout: number }): void</code>
<code>monitor</code>	Initializes comprehensive performance monitoring including Core Web Vitals, long tasks, and bundle size tracking.	<code>monitor(options: { onReport: (metric) => void, enableWebVitals?: boolean, enableLongTasks?: boolean, enableBundleMonitoring?: boolean }): void</code>
<code>measure</code>	Measures the performance of synchronous functions.	<code>measure<T>(name: string, fn: () => T): T</code>
<code>measureAsync</code>	Measures the performance of asynchronous functions.	<code>measureAsync<T>(name: string, fn: () => Promise<T>): Promise<T></code>

Angular Integration ■

PlayPerfService ■ Angular service wrapper that integrates with Play+ logging and provides component-specific performance utilities.

```
import { PlayPerfService } from './services/playperf.service';
@Component({ ... })
export class MyComponent {
  constructor(private playperf: PlayPerfService) {}
  ngOnInit() { // Initialize monitoring this
    playperf.monitor();
  }
  processData() { // Measure expensive operations
    return this.playperf.measure('dataProcessing', () => {
      return this.heavyComputation();
    });
  }
}
```

Performance Directive ■ Automatically monitors component render times and highlights

heavy components. `<!-- Monitor component performance --> < div playPerf = " user-list " perfThreshold = " 16 " > < app-user-list [users] = " users " > </ app-user-list > </ div >`

Performance Pipe ■ Measures and reports template expression performance. `<!-- Monitor expensive template expressions --> < div > </ div >`

React: Deferring a Non-Critical Script ■ This example shows how to defer the initialization of an analytics script so it doesn't interfere with the initial page load.

```
import React , { useEffect } from 'react' ; import {
playperf } from '../system/play.perf' ; import { initializeAnalytics } from '../lib/analytics' ;
function App ( ) { useEffect ( ( ) => { // Defer the analytics script to run after the main thread
is free. playperf . defer ( ( ) => { initializeAnalytics ( { apiKey : '...' } ) ; } ) ; } , [ ] ) ; return ( //
... your application components ) ; }

```

Angular: Monitoring Real-World Performance ■ This example shows how to initialize Web Vitals monitoring in your main application component and log the results.

```
// app.component.ts import { Component , OnInit } from
"@angular/core" ; import { playperf } from "@playplus/core" ; // Assuming helper is
available import { playlog } from "@playplus/core" ; @ Component ( { selector : "app-root" ,
templateUrl : "../app.component.html" , } ) export class AppComponent implements OnInit {
ngOnInit ( ) { // Start monitoring real-user performance metrics. playperf . monitor ( {
onReport : ( metric ) => { // Send the collected metric to our logging service. playlog . info (
` Web Vitals Metric: ${ metric . name } ` , { value : metric . value , id : metric . id , } ) ; } ) ;
} } import { playperf } from "../system/play.perf" ; // Defer non-critical initialization
playperf . defer ( ( ) => { initializeAnalytics ( ) ; loadNonCriticalScripts ( ) ; } ) ; // High priority
defer (shorter timeout) playperf . defer ( ( ) => { updateUserPreferences ( ) ; } , { priority :
"high" , timeout : 100 } ) ; // Measure sync function const result = playperf . measure (
"dataProcessing" , ( ) => { return processLargeDataset ( data ) ; } ) ; // Measure async
function const result = await playperf . measureAsync ( "apiCall" , async ( ) => { return
await fetchUserData ( ) ; } ) ;

```

Additional Info ■ **Why We Created This Helper** ■ Web performance is critical, but its tooling is complex. Without a dedicated system, each team would need to: Manually set up, configure, and maintain Lighthouse CI for every project. Write custom logic to track bundle sizes. Implement their own utilities for deferring scripts or monitoring Web Vitals. This is inefficient and leads to inconsistent standards. The playperf helper automates the enforcement and simplifies the implementation of performance best practices. It provides a pre-configured safety net and easy-to-use tools so developers can build fast experiences by default.

Performance Budgets ■ All Play+ applications must meet these baseline performance standards: Metric Target Budget LCP (Largest Contentful Paint) < 2.5s 2500ms INP (Interaction to Next Paint) < 200ms 200ms

CLS (Cumulative Layout Shift) < 0.1 0.1 JS Bundle Size (gzipped) < 250KB 250KB Main Thread Long Tasks (>50ms) 0 0 Best Practices ■ Component Optimization ■ Change Detection Strategy ■ Use OnPush change detection for components that don't need frequent updates: @ Component ({ changeDetection : ChangeDetectionStrategy . OnPush , // ... }) export class OptimizedComponent { // Component logic } TrackBy Functions ■ Always provide trackBy functions for ngFor loops: @ Component ({ ... }) export class ListComponent { trackByFn (index : number , item : any) : any { return item . id || index ; } } < div = " let item of items; trackBy: trackByFn " > </ div > Lazy Loading ■ Use lazy loading for routes and components: const routes : Routes = [{ path : "dashboard" , loadComponent : () => import ("../dashboard/dashboard.component") . then ((m) => m . DashboardComponent) , } ,] ; Data Management ■ Caching Strategy ■ Use Play+ caching for expensive operations: import { PlayCacheService } from "../services/playcache.service" ; @ Injectable () export class DataService { constructor (private playcache : PlayCacheService) { } async getUsers () : Promise < User [] > { return this . playcache . get ("users" , async () => { return this . apiService . fetchUsers () ; } , { ttl : 300 }) ; // 5 minutes cache } } Virtual Scrolling ■ Use virtual scrolling for large lists: import { ScrollingModule } from "@angular/cdk/scrolling" ; @ Component ({ imports : [ScrollingModule] , // ... }) export class LargeListComponent { items = Array . from ({ length : 10000 } , (_ , i) => ` Item \${ i } `) ; } < cdk-virtual-scroll-viewport itemSize = " 50 " class = " list-container " > < div *cdkVirtualFor = " let item of items " > </ div > </ cdk-virtual-scroll-viewport > Image Optimization ■ Lazy Loading ■ Always lazy load images: < img [src] = " imageUrl " loading = " lazy " [alt] = " imageAlt " /> Modern Formats ■ Use WebP with fallbacks: < picture > < source [srcset] = " imageUrl + '.webp' " type = " image/webp " /> < img [src] = " imageUrl + '.jpg' " [alt] = " imageAlt " /> </ picture > Explicit Dimensions ■ Always specify width and height to prevent layout shifts: < img [src] = " imageUrl " width = " 300 " height = " 200 " [alt] = " imageAlt " /> Forbidden Patterns ■ Blocking Operations ■ // DON'T: Block main thread with heavy operations ngOnInit () { this . heavyComputation () ; // Blocks rendering } // DO: Defer non-critical operations ngOnInit () { this . playperf . defer (() => { this . heavyComputation () ; }) ; } Synchronous API Calls ■ // DON'T: Make synchronous API calls getData () { return this . http . get ('/api/data') . toPromise () ; // Blocks UI } // DO: Use async/await with proper error handling async getData () { return await this . playperf . measureAsync ('apiCall' , async () => { return this . http . get ('/api/data') . toPromise () ; }) ; } Expensive Template Expressions ■ <!-- DON'T: Expensive operations in templates --> < div > </ div > <!-- DO: Use pipes or

computed properties --> < div > </ div > Manual setTimeout/setInterval ■ // DON'T: Use setTimeout directly setTimeout (() => { this . updateData () ; } , 1000) ; // DO: Use playperf.defer() this . playperf . defer (() => { this . updateData () ; } , { timeout : 1000 }) ;

Required Patterns ■ Performance Monitoring ■ // Always initialize performance monitoring in app component ngOnInit () { this . playperf . monitor ({ onReport : (metric) => { // Handle metrics appropriately } }) ; } Component Performance Tracking ■ // Use performance directive for heavy components @ Component ({ ... }) export class HeavyComponent { constructor (private playperf : PlayPerfService) { } ngOnInit () { this . playperf . highlightHeavyComponent ('HeavyComponent' , 0) ; } } Async Data Loading ■ // Always use async patterns for data loading async loadData () { return await this . playperf . measureAsync ('dataLoading' , async () => { return this . apiService . getData () ; }) ; } } Testing Performance ■ Unit Testing ■ describe ("PerformanceService" , () => { it ("should measure function performance" , () => { const result = playperf . measure ("test" , () => { return "test result" ; }) ; expect (result) . toBe ("test result") ; }) ; }) ; Integration Testing ■ describe ("Component Performance" , () => { it ("should render within performance budget" , () => { const start = performance . now () ; fixture . detectChanges () ; const renderTime = performance . now () - start ; expect (renderTime) . toBeLessThan (16) ; // 60fps budget }) ; }) ; Monitoring and Analytics ■ Core Web Vitals ■ LCP : Largest Contentful Paint - measures loading performance FID : First Input Delay - measures interactivity CLS : Cumulative Layout Shift - measures visual stability Custom Metrics ■ Component render times API response times Bundle size changes Long task detection Reporting ■ Performance metrics are automatically logged and can be sent to: Play+ logging system Analytics platforms Monitoring dashboards CI/CD pipelines ### Lighthouse CI Configuration Example This is a sample of the configuration used by CI to assert performance budgets. It is managed by the `@playplus/perf` package. ``json { "ci": { "collect": { "numberOfRuns": 3 } , "assert": { "assertions": { "core-web-vitals": "error", "largest-contentful-paint": ["error", { "maxNumericValue": 2500 }] , "cumulative-layout-shift": ["error", { "maxNumericValue": 0.1 }] , "interactive": ["warn", { "maxNumericValue": 3800 }] } } } } } Developer Checklist ■ Are all non-critical third-party scripts or tasks wrapped in playperf.defer() ? Is the code for my route being dynamically imported (code-splitting)? Are all images lazy-loaded and served in modern formats (e.g., WebP) with explicit width and height attributes to prevent CLS? Have I used skeleton loaders for data-heavy components instead of spinners? For long lists, am I using a virtualized scrolling solution? Are pure components memoized using React.memo or Angular's OnPush change

detection strategy? Have I analyzed the bundle size impact of any new dependencies I've added? Does my feature pass the Lighthouse CI performance budget checks?

Performance Checklist ■ Development ■ All non-critical tasks use `playperf.defer()`

Components use `OnPush` change detection where appropriate All `ngFor` loops have `trackBy` functions Images are lazy loaded with explicit dimensions Routes are lazy loaded

Heavy computations are measured with `playperf.measure()` Testing ■ Performance monitoring is initialized in app component Component render times are within 16ms

budget Bundle size is under 250KB limit Lighthouse scores meet performance budgets

Long tasks are eliminated Production ■ Core Web Vitals are monitored Performance

metrics are logged Bundle analysis is performed CDN is configured for static assets Gzip

compression is enabled Recommended Monitoring Tools ■ For a full view of real-world

performance, we recommend integrating with: Web Vitals JS Library : To send Core Web Vitals from the browser to your analytics or logging provider. Sentry Performance : To track

slow transactions and identify main thread stalls. SpeedCurve or New Relic : For in-depth

Real User Monitoring (RUM) analysis over time, across geographies and devices.

Minimum Enforcement Thresholds ■ All Play+ applications in the Golden Path are held to these baseline standards, which are enforced automatically in the CI/CD pipeline. Metric

Target LCP (Largest Contentful Paint) < 2.5s INP (Interaction to Next Paint) < 200ms CLS

(Cumulative Layout Shift) < 0.1 JS Bundle Size (gzipped) < 250KB Main Thread Long

Tasks (>50ms) 0

```
import { PlayPerfService } from '../services/playperf.service';
```

```
@Component({...})
```

```
export class MyComponent {
```

```
  constructor(private playperf: PlayPerfService) {}
```

```
  ngOnInit() {
```

```
    // Initialize monitoring
```

```
    this.playperf.monitor();
```

```
  }
```

```
  processData() {
```

```
    // Measure expensive operations
```

```
    return this.playperf.measure('dataProcessing', () => {
```

```
      return this.heavyComputation();
```

```
    });
```

```
  }
```

```
}
```

```
---
```

```

<!-- Monitor component performance -->
<div playPerf="user-list" perfThreshold="16">
  <app-user-list [users]="users"></app-user-list>
</div>

---

<!-- Monitor expensive template expressions -->
<div>{{ expensiveComputation() | playPerf:'user-count' }}</div>

---

import React, { useEffect } from 'react';
import { playperf } from '../system/play.perf';
import { initializeAnalytics } from '../lib/analytics';

function App() {
  useEffect(() => {
    // Defer the analytics script to run after the main thread is free.
    playperf.defer(() => {
      initializeAnalytics({ apiKey: '...' });
    });
  }, []);

  return (
    // ... your application components
  );
}

---

// app.component.ts
import { Component, OnInit } from "@angular/core";
import { playperf } from "@playplus/core"; // Assuming helper is available
import { playlog } from "@playplus/core";

@Component({
  selector: "app-root",
  templateUrl: "./app.component.html",
})
export class AppComponent implements OnInit {
  ngOnInit() {
    // Start monitoring real-user performance metrics.
    playperf.monitor({
      onReport: (metric) => {
        // Send the collected metric to our logging service.
        playlog.info(`Web Vitals Metric: ${metric.name}`, {
          value: metric.value,
          id: metric.id,
        });
      }
    });
  }
}

```

```

        });
    },
    });
}
}

```

```
import { playperf } from "../../system/play.perf";
```

```
// Defer non-critical initialization
```

```
playperf.defer(() => {
    initializeAnalytics();
    loadNonCriticalScripts();
});
```

```
// High priority defer (shorter timeout)
```

```
playperf.defer(
    () => {
        updateUserPreferences();
    },
    { priority: "high", timeout: 100 }
);
```

```
// Measure sync function
```

```
const result = playperf.measure("dataProcessing", () => {
    return processLargeDataset(data);
});
```

```
// Measure async function
```

```
const result = await playperf.measureAsync("apiCall", async () => {
    return await fetchUserData();
});
```

```
@Component({
    changeDetection: ChangeDetectionStrategy.OnPush,
    // ...
})
export class OptimizedComponent {
    // Component logic
}
```

```
@Component({...})
export class ListComponent {
    trackByFn(index: number, item: any): any {
```

```

        return item.id || index;
    }
}

---

<div *ngFor="let item of items; trackBy: trackByFn">{{ item.name }}</div>

---

const routes: Routes = [
    {
        path: "dashboard",
        loadComponent: () =>
            import("../dashboard/dashboard.component").then(
                (m) => m.DashboardComponent
            ),
    },
];

---

import { PlayCacheService } from "../services/playcache.service";

@Injectable()
export class DataService {
    constructor(private playcache: PlayCacheService) {}

    async getUsers(): Promise<User[]> {
        return this.playcache.get(
            "users",
            async () => {
                return this.apiService.fetchUsers();
            },
            { ttl: 300 }
        ); // 5 minutes cache
    }
}

---

import { ScrollingModule } from "@angular/cdk/scrolling";

@Component({
    imports: [ScrollingModule],
    // ...
})
export class LargeListComponent {

```

```

    items = Array.from({ length: 10000 }, (_, i) => `Item ${i}`);
  }

---

<cdk-virtual-scroll-viewport itemSize="50" class="list-container">
  <div *cdkVirtualFor="let item of items">{{ item }}</div>
</cdk-virtual-scroll-viewport>

---

<img [src]="imageUrl" loading="lazy" [alt]="imageAlt" />

---

<picture>
  <source [srcset]="imageUrl + '.webp'" type="image/webp" />
  <img [src]="imageUrl + '.jpg'" [alt]="imageAlt" />
</picture>

---

<img [src]="imageUrl" width="300" height="200" [alt]="imageAlt" />

---

// DON'T: Block main thread with heavy operations
ngOnInit() {
  this.heavyComputation(); // Blocks rendering
}

// DO: Defer non-critical operations
ngOnInit() {
  this.playperf.defer(() => {
    this.heavyComputation();
  });
}

---

// DON'T: Make synchronous API calls
getData() {
  return this.http.get('/api/data').toPromise(); // Blocks UI
}

// DO: Use async/await with proper error handling

```

```

async getData() {
  return await this.playperf.measureAsync('apiCall', async () => {
    return this.http.get('/api/data').toPromise();
  });
}

```

```

<!-- DON'T: Expensive operations in templates -->
<div>{{ expensiveComputation() }}</div>

```

```

<!-- DO: Use pipes or computed properties -->
<div>{{ data | playPerf:'computation' }}</div>

```

```

// DON'T: Use setTimeout directly
setTimeout(() => {
  this.updateData();
}, 1000);

```

```

// DO: Use playperf.defer()
this.playperf.defer(
  () => {
    this.updateData();
  },
  { timeout: 1000 }
);

```

```

// Always initialize performance monitoring in app component
ngOnInit() {
  this.playperf.monitor({
    onReport: (metric) => {
      // Handle metrics appropriately
    }
  });
}

```

```

// Use performance directive for heavy components
@Component({...})
export class HeavyComponent {
  constructor(private playperf: PlayPerfService) {}

  ngOnInit() {

```

```

    this.playperf.highlightHeavyComponent('HeavyComponent', 0);
  }
}

```

```

// Always use async patterns for data loading
async loadData() {
  return await this.playperf.measureAsync('dataLoading', async () => {
    return this.apiService.getData();
  });
}

```

```

describe("PerformanceService", () => {
  it("should measure function performance", () => {
    const result = playperf.measure("test", () => {
      return "test result";
    });

    expect(result).toBe("test result");
  });
});

```

```

describe("Component Performance", () => {
  it("should render within performance budget", () => {
    const start = performance.now();
    fixture.detectChanges();
    const renderTime = performance.now() - start;

    expect(renderTime).toBeLessThan(16); // 60fps budget
  });
});

```

Lighthouse CI Configuration Example

This is a sample of the configuration used by CI to assert performance budgets. It is managed by the

```

```json
{
 "ci": {
 "collect": {

```

```
 "numberOfRuns": 3
 },
 "assert": {
 "assertions": {
 "core-web-vitals": "error",
 "largest-contentful-paint": ["error", { "maxNumericValue": 2500 }],
 "cumulative-layout-shift": ["error", { "maxNumericValue": 0.1 }],
 "interactive": ["warn", { "maxNumericValue": 3800 }]
 }
 }
}
```