WealthSei Stage 2 Report

WealthSei — Stage 2 Implementation Report

An AI Personal Finance Agent

Course: EECS3311 Software Design, Fall 2026 · **Stage:** 2 (Implementation) **Student:** Rishit Shah, *[219773050]* · **Repository:** github.com/Rishit-Shah/EECS-3311-Project---WealthSei

Contents

1. Project overview and implementation status
2. Feature to implementation mapping
3. Implemented design patterns (with updated UML class diagram, use-case and sequence diagram notes)
4. Changes and rationale
5. AI tools and collaboration log
6. Development and verification summary
7. Demonstration index

1. Project overview and implementation status

1.1 The application

WealthSei is a personal-finance assistant for people who manage a budget without financial expertise (students, early-career workers, freelancers). It imports bank and credit-card CSV statements, categorizes the spending, tracks budgets and savings goals, projects the balance for the next 30 days, and answers decision questions such as "Can I afford this laptop?" or "What changes if I cancel two subscriptions?". It runs as a Swing desktop application (GUI) and as an interactive command-line program (CLI); both call the same `WealthSeiFacade`, so the two interfaces behave identically. Data is stored in plain text files in a local folder (`~/.wealthsei`), nothing leaves the machine except the AI calls described below.

Technology: Java 17, Maven, JUnit 5 (the only dependency). The Claude API is called with the JDK's HTTP client; there is no third-party library in the application itself.

1.2 How the AI/LLM is integrated

All numbers (budget status, forecast, safe-to-spend, goal feasibility, health score, what-if results) are computed by ordinary code. The model is used for language and for deciding which tools to call, and every answer is checked against the numbers the tools returned.

Part	Model	What it does
F02 categorizer (`LLMCategorizationStrategy`)	`claude-haiku-5-5`	Last-resort category for a merchant that no learned rule or keyword recognizes; must answer with one allowed category.
F04 recurring review (`RecurringReviewer`)	`claude-haiku-5-5`	Writes 2–3 sentences about the detected recurring payments from the computed list only.
Tool-using agent (`AgentController`, `Planner`, `PromptBuilder`)	`claude-sonnet-5-5`	F08 affordability, F10 scenario parsing and explanation, F11 monthly review text, F12 chat; also explains F05–F07 and F09 results when asked in the chat (the model calls the tools, the tools return the numbers).

Safeguards: `GroundingChecker` compares every dollar amount, percentage, decimal and number of 100 or more in the model's answer with the tool results (one correction attempt, then the answer is flagged); `PurchaseAssessor` rules act as a floor for affordability (the model may be more cautious, never more optimistic); `PlainText` strips markdown from answers; the full trace of tool calls is kept and can be shown (`trace`, Assistant → trace button); `LoggingLLMProvider` writes model, token count and time of each call to `llm.log` (never the key, the questions or the data). Without an API key the app starts normally: categorization falls

back to rules, reviews and explanations use fixed templates, and the agent commands say the AI is unavailable (affordability is still answered from the rules).

1.3 Current working functionality

All 14 Stage 1 features (F01–F14) are implemented and work in both the GUI and the CLI, plus three supporting items that implement or extend parts of Stage 1 (plan setup from F03, saved data in place of SQLite, an AI call log built on the Stage 1 logging decorator). 596 unit tests pass (`mvn test`). Each feature has a recorded demonstration (Section 7).

ID	Feature	Type in Stage 1	Type as implemented	Status
F01	Import transactions (CSV or manual entry)	Deterministic	Deterministic	Implemented (modified: own CSV reader, extra card-statement layout; manual entry `NewTransaction` added at the end of Stage 2, see C17)
F02	Smart categorization and correction (with undo)	Hybrid	Hybrid	Implemented
F03	Budget and plan setup, tracking and alerts	Deterministic	Deterministic	Implemented
F04	Recurring payment and subscription detector	Hybrid	Hybrid	Implemented (AI review added as a button/command)
F05	Safe-to-spend coach	Hybrid	Deterministic + AI explanation on request	Implemented (modified)
F06	Spending habit detective	Hybrid	Deterministic + AI explanation on request	Implemented (modified)
F07	Financial health score	Hybrid	Deterministic + AI explanation on request	Implemented (modified; change from last month not computed)
F08	Purchase affordability check	AI (agent)	AI (agent)	Implemented
F09	Savings goal planner with replan	AI (agent)	Deterministic planner; the agent reads goals through a tool	Implemented (modified)
F10	What-if scenario simulator	AI (agent)	Hybrid (AI parses plain words; typed form needs no AI)	Implemented
F11	Monthly review and fix plan	AI (agent)	AI (agent) with numbers-only fallback	Implemented
F12	Natural-language chat with agent trace	AI (agent)	AI (agent)	Implemented
F13	Proposal approval queue	Hybrid	Deterministic queue; drafts come from the agent, what-if, goals	Implemented
F14	Report export	Deterministic	Deterministic	Implemented
N01	Financial plan setup (balance, buffer, income, bills, planned expenses): the plan part of Stage 1 F03	Stage 1 F03	Deterministic	Implemented (CLI command names differ, see Section 4)
N02	Saved data between sessions (text files): Stage 1 persistence behind the repository interfaces	Stage 1 (SQLite)	Deterministic	Implemented (modified: text files instead of SQLite, C3)
N03	AI call log and `aicalls` command: output of the Stage 1 `LoggingLLMProvider`	Stage 1 (logging decorator)	Deterministic	Implemented (extended: `llm.log` file and `aicalls` viewer)

1.4 Limitations and incomplete functionality (stated honestly)

- **Not saved between runs:** pending proposals, generated monthly reviews, agent traces, the undo/redo history and the chat memory window are kept for the session only. (Learned rules, protected categories, goals, budgets, the plan, transactions and recurring flags are saved.) After a restart a budget alert already shown can appear once more.
- **Explanations of F05–F07 are templates on the dashboard.** The AI explains them only when asked through the Assistant/`ask`; Stage 1 described an automatic AI explanation on each screen. The numbers are the same either way.

- **F09 planning is plain code.** Stage 1 had the agent plan and replan goals; in the implementation `GoalPlanner` does it and the agent can read and discuss goals. No automatic re-planning button beyond the goal screen's feasibility view and "suggest a fix".
- **CSV support is three layouts:** signed-amount, debit/credit columns, and the credit-card statement layout. A card export that shows purchases as positive numbers in the first two layouts would be read as income. An amount such as `12,50` is rejected rather than guessed. Currency is a single (dollar) currency.
- **F07 "change from last month" is not computed:** the score is not stored per month, so the Stage 1 comparison with the previous month is missing (the field exists and is always empty).
- **Month errors:** some commands show a raw parse message for an invalid month (`habits 2026-13`); the health score for a month with no data is shown without a clear "no data" notice. Duplicate goal names are allowed.
- **Needs a network and a key for AI features;** answers can vary between runs, which is why every figure is grounded against tool results.
- **Not done in Stage 2 (by design):** full deterministic test coverage of every rule and KUMA agent validation belong to Stage 3. The GUI is verified by logic tests (`GuiLogicTest`) and by the recorded demonstrations, not by automated screen tests.
- **Stage 1 design differences** (Swing instead of JavaFX, own HTTP/JSON/CSV code instead of LangChain4j and Apache Commons CSV, text files instead of SQLite, a hand-written CLI parser instead of picocli) are explained in Section 4.

---

2. Feature to implementation mapping

Package folders are under `src/main/java/wealthsei/`. "GUI" screens are in `presentation/gui`, the CLI is `presentation/cli/CliApp.java`, and every request goes through `facade/WealthSeiFacade.java` (Facade pattern), whose objects are wired by `facade/WealthSeiFactory.java`. Video links are filled in Section 7 (GUI and CLI recordings of every feature).

F01 — Import Transactions (CSV) · Deterministic

Field	Details
Feature ID and name	F01 — Import Transactions (CSV)
Stage 1 feature/reference	F01 (UC01, SD01)
Status or change	**Modified.** Same behaviour; the CSV is read by our own `CsvParser` instead of Apache Commons CSV; a third layout (credit-card statements) was added; card payments are skipped rather than imported as income.
Implemented classes/files and responsibilities	`importing/CsvImporter` reads the header and chooses the adapter. `importing/BankCsvAdapter` (interface) with `AbstractCsvAdapter` (reads rows, template), `SignedAmountCsvAdapter`, `DebitCreditCsvAdapter`, `CardStatementCsvAdapter` (+ `CardMerchantCleaner`: tidies merchant names, skips card payments) turn rows into `Transaction` objects. `CsvParser`/`CsvRecord`/`RowParsing` split lines, handle quotes and parse dates and amounts. `service/TransactionService` removes duplicates, calls the `Categorizer` (F02) and saves through `TransactionRepository`. `domain/ImportResult`, `ParseResult` report counts and rejected rows. GUI: `TransactionsView`/`ShellPanel` (Import button, file chooser, summary).
Key methods	`CsvImporter.parse(Path)`, `detectAdapter(header, parser)`, `AbstractCsvAdapter.readTransactions()`, `toTransaction(CsvRecord)`, `TransactionService.importFile(Path)`, `WealthSeiFacade.importTransactions(file, today)`, `CliApp.importFile`
Design patterns	Adapter (CSV layouts behind one interface), Template Method (`AbstractCsvAdapter.readTransactions()` is final, subclasses supply `toTransaction`), Facade, Decorator (`PersistentTransactionRepository`)
Video link/timestamp	GUI video · CLI video (both show CSV import, duplicate skipping, and manual entry)

How the classes collaborate. The user picks a file in the GUI (or types `import <file>`); the call reaches `WealthSeiFacade.importTransactions`, which gives the path to `TransactionService.importFile`. `CsvImporter` reads the header row and asks each adapter whether it matches (`detectAdapter`); the matching adapter's final `readTransactions()` loops over the rows and calls its own `toTransaction` for each, collecting bad rows as rejected with a reason. `TransactionService` drops transactions already stored (same date, amount, merchant; matched by count so two real identical purchases in one file are both kept), categorizes the new ones through `Categorizer` (F02), and saves them. Back in the facade, `BudgetService.refreshAlerts` re-checks only the months touched (F03) and `GoalService.evaluateAll` re-checks goals (F09). The Stage 1 diagrams also allow a second input, a hand-typed `NewTransaction` (date, amount, merchant, description, optional category, income flag): the GUI "Add transaction" button or the CLI `add` command calls `WealthSeiFacade.addTransaction`, which calls `TransactionService.addTransaction`; its private `validate` rejects a missing date, a zero amount or a blank merchant, the category

is the chosen one or the `Categorizer`'s answer, and the facade then refreshes that month's alerts and the goals the same way as for an import. The user sees "Imported n, skipped d duplicates, rejected r rows". This feature is deterministic: no model call.

F02 — Smart Categorization and Correction (with Undo) · Hybrid

Field	Details
Feature ID and name	F02 — Smart Categorization and Correction (with Undo)
Stage 1 feature/reference	F02 (UC02, SD02)
Status or change	**Implemented.** Command renamed as in Stage 1 (`RecategorizeCommand`); extra `CategoryCorrector` groups the undo/redo calls. The AI step runs only when an API key exists.
Implemented classes/files and responsibilities	`service/Categorizer` tries each `CategorizationStrategy` in order until one answers. `LearnedRuleStrategy` (merchant rules the user taught, stored by `RuleRepository`), `KeywordRuleStrategy` (built-in keywords), `LLMCategorizationStrategy` (Haiku, last resort, answer must be one allowed category). `command/RecategorizeCommand` changes the category and teaches (or forgets) the rule; `CommandHistory` runs it and keeps undo/redo; `CategoryCorrector` is the facade-side helper. GUI: category drop-down and Undo/Redo in `TransactionsView`.
Key methods	`Categorizer.categorize(Transaction)`, `CategorizationStrategy.categorize`, `LearnedRuleStrategy.learn/forget/ruleFor`, `LLMCategorizationStrategy.categorize`, `RecategorizeCommand.execute/undo`, `CommandHistory.execute/undo/redo`, `WealthSeiFacade.correctCategory/undoCorrection/redoCorrection`, `CliApp` `correct`, `undo`, `redo`
Design patterns	Strategy (chain of categorizers), Command (undoable correction), Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. *Automatic:* during import `Categorizer` asks `LearnedRuleStrategy` first, then `KeywordRuleStrategy`, and only if both return nothing and a key is configured, `LLMCategorizationStrategy` (a small Haiku request listing the allowed categories; an answer outside the list is rejected and the transaction stays `Uncategorized`). *Manual:* a correction in the GUI or `correct <txId> <category>` reaches the facade, which builds a `RecategorizeCommand` (through `CategoryCorrector`) and hands it to `CommandHistory.execute`. The command updates the transaction through `TransactionService.updateCategory` and calls `LearnedRuleStrategy.learn` so the next import of that merchant is correct; `undo` restores the old category and the old rule (or removes the new one). Income and "Uncategorized" corrections are not learned. Budget alerts for the affected month are then refreshed. Hybrid: rules and undo are deterministic; the model is only the last-resort strategy.

F03 — Budget Setup, Tracking and Alerts · Deterministic

Field	Details
Feature ID and name	F03 — Budget Setup, Tracking and Alerts
Stage 1 feature/reference	F03 (UC03, SD03)
Status or change	**Implemented.** Added `BudgetCalculator` (pure calculation); the plan part of F03 (`PlanService`, plan dialogs) is described under N01; alerts are not repeated at start-up (`primeAlerts`).
Implemented classes/files and responsibilities	`service/BudgetService` saves limits and returns the status; `BudgetCalculator.compute` counts the month's expenses against each limit (80% or more = warning, over 100% = over); `AlertMonitor` raises an `Alert` only when a category's level gets worse and tells its listeners; `BudgetRepository` (`InMemory…`, `PersistentBudgetRepository`); domain `Budget`, `BudgetLine`, `BudgetLimits`, `BudgetStatus`, `BudgetLineStatus`, `Alert`. GUI: dashboard budget card, `PlanDialogs`, toast alerts from `ShellPanel`.
Key methods	`BudgetService.setBudget/setLimit/getStatus/refreshAlerts/primeAlerts`, `BudgetCalculator.compute`, `AlertMonitor.attach/evaluate/publish`, `WealthSeiFacade.setBudget/getBudgetStatus/addAlertListener`, `SetBudgetLimitCommand` (used by F13)
Design patterns	Observer (`AlertMonitor` subject, `AlertListener` observers), Decorator (persistent repository), Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `budget set 2026-10 dining=450 …` (or the GUI form) calls `BudgetService.setBudget`, which stores the limits and immediately recomputes the status: `BudgetCalculator.compute` sums that month's expense transactions per

category and divides by the limit. `AlertMonitor.evaluate` compares the new level with the last level it published for that category and, only if it got worse (none → warning → over), builds an `Alert` and calls every attached `AlertListener`: the CLI prints it, the GUI `ShellPanel` shows a toast. Importing or correcting transactions calls `refreshAlerts` for the affected months. Deterministic.

F04 — Recurring Payment and Subscription Detector · Hybrid

Field	Details
Feature ID and name	F04 — Recurring Payment and Subscription Detector
Stage 1 feature/reference	F04 (UC04, SD04)
Status or change	**Modified.** The detection is as designed. The AI wording is a separate "AI review" button/command (`recurring review`) rather than part of every refresh, to limit cost and waiting time; a fixed template is the fallback.
Implemented classes/files and responsibilities	`analytics/RecurringDetector.detect` groups expenses by merchant and checks regular gaps and steady amounts; `RecurringPayment` (carries `priceIncrease`, `occurrences`); `AnalyticsService` (report, flags); `RecurringReport` + `RecurringSummaryTemplate` (total and template text); `RecurringReviewer` (Haiku: 2–3 sentences from the computed list; every number in the reply must appear in the facts, answers cached for identical facts) and `RecurringReview`; `RecurringRepository` (`PersistentRecurringRepository`) stores review flags. GUI: dashboard "Recurring" card with the AI-review button (runs in a background worker).
Key methods	`RecurringDetector.detect(txs, asOf)`, `AnalyticsService.recurringReport/reviewRecurring/flagRecurring`, `RecurringReviewer.review/facts/numbersComeFrom`, `WealthSeiFacade.recurringPayments/reviewRecurring/flagRecurring`, `CliApp recurring`, `recurring review`, `recurring flag
Design patterns	Strategy-like fallback (reviewer vs. template), Facade, Decorator (persistent flags)
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `recurring` → facade → `AnalyticsService.recurringReport(asOf)` loads transactions, runs `RecurringDetector.detect` (at least 3 payments, at least 75% regular gaps, at least 50% steady amounts; confidence = 0.6 × regular gaps + 0.4 × steady amounts; a pattern whose last payment is over two intervals old counts as cancelled), and adds the template summary. `recurring flag <merchant>` stores a flag through `RecurringRepository` (refused if the merchant is not a detected recurring payment). `recurring review` (or the GUI button) builds a facts list from the detected payments and asks `RecurringReviewer` (Haiku); if the reply contains a figure not in the facts, or the model is unavailable, the template summary is shown with the reason. Hybrid: detection and flags are deterministic; the sentence wording is AI.

F05 — Safe-to-Spend Coach · Hybrid (implemented: deterministic, AI explanation on request)

Field	Details
Feature ID and name	F05 — Safe-to-Spend Coach
Stage 1 feature/reference	F05 (UC05, SD04)
Status or change	**Modified.** Calculation and forecast as designed. The explanation on the dashboard/`safe` is a fixed template; the AI explains it only when asked in the Assistant.
Implemented classes/files and responsibilities	`analytics/ForecastEngine.project(inputs, days)` builds the daily balance from income, plan bills, recurring payments and planned expenses; `ForecastInputs` (with `deepCopy`, also used by F10); `SafeToSpendCalculator.calculate(forecast, goals, buffer)` returns `SafeToSpendResult`; `SafeToSpendSummaryTemplate` (text); `AlertMonitor.evaluateLowBalance`; domain `Forecast`, `DailyBalance`, `SafeToSpendResult`. GUI: dashboard hero card and balance chart (`HeroBalanceCard`, `LineChart`).
Key methods	`ForecastEngine.project/monthlySurplus`, `SafeToSpendCalculator.calculate`, `AnalyticsService.safeToSpend/forecast/baselineInputs`, `WealthSeiFacade.getSafeToSpend/getForecast`, `CliApp safe`, `forecast`
Design patterns	Prototype (`ForecastInputs.deepCopy`), Observer (low-balance alert), Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `safe` → facade → `AnalyticsService.safeToSpend(today)`: `baselineInputs` gathers the saved plan (balance, buffer, income, bills), recurring payments and planned expenses; `ForecastEngine.project` produces the day-by-day balance; `SafeToSpendCalculator.calculate` takes the balance plus income before month end, minus bills before month end, minus

the monthly amount reserved for open goals, minus the safety buffer, divided by the days left in the month. `AlertMonitor.evaluateLowBalance` raises a low-balance alert once if the lowest projected balance falls under the buffer. The template writes the sentence. Asking "why is it $208?" in the Assistant lets the agent call the forecast tool and explain the same figures (checked by `GroundingChecker`). Deterministic core.

F06 — Spending Habit Detective · Hybrid (implemented: deterministic, AI explanation on request)

Field	Details
Feature ID and name	F06 — Spending Habit Detective
Stage 1 feature/reference	F06 (UC06, SD04)
Status or change	**Modified** (explanation on request only, as F05).
Implemented classes/files and responsibilities	`analytics/HabitAnalyzer.analyze(txs, month)` applies five fixed-threshold rules (weekend spike, payday splurge, month-end crunch, small-purchase leak, unusual expense = above the category mean + 2 standard deviations) to non-essential spending only; `domain/Insight` + `InsightType`; `InsightTool` lets the agent read the findings. GUI: dashboard "Needs attention" card (up to 8 rows with caps).
Key methods	`HabitAnalyzer.analyze`, `AnalyticsService.habits`, `WealthSeiFacade.getHabits`, `CliApp habits <month>`, `InsightTool.execute`
Design patterns	Facade; (tool use through `ToolManager`, see F08)
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `habits 2026-10` → facade → `AnalyticsService.habits(month)` loads that month's (and history) transactions and passes them to `HabitAnalyzer`, which returns a list of `Insight` records (type, headline, numbers). Fewer than 30 days of history gives a "need more data" message; no findings gives "no notable patterns". The dashboard merges these findings with over-budget categories in one card. In the Assistant, a question about habits makes the agent call `InsightTool`, which returns the same insights as tool results. Deterministic core.

F07 — Financial Health Score · Hybrid (implemented: deterministic, AI explanation on request)

Field	Details
Feature ID and name	F07 — Financial Health Score
Stage 1 feature/reference	F07 (UC06, SD04)
Status or change	**Modified.** `ScoreComponent` gained a `detail` field and `HealthScore` an `excluded` list. **Not implemented:** the "change from last month" in the Stage 1 specification (`HealthScore` has the field `previousTotal` and `changeFromLastMonth()`, but there is no stored history of past scores, so it is always empty). The explanation is a template unless asked in the Assistant.
Implemented classes/files and responsibilities	`analytics/HealthScoreCalculator.calculate(status, forecast, goals)` scores budget adherence, savings rate, emergency buffer and goal progress with weights 30/25/25/20, re-scaled when a component has no data; `biggestGap` finds what would improve the score most; `domain/HealthScore`, `ScoreComponent`; `HealthScoreSummaryTemplate`. GUI: `ScoreRing` on the dashboard.
Key methods	`HealthScoreCalculator.calculate/biggestGap`, `AnalyticsService.healthScore`, `WealthSeiFacade.getHealthScore`, `CliApp score [month]`
Design patterns	Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `score 2026-10` → facade → `AnalyticsService.healthScore` gets that month's `BudgetStatus` from `BudgetService`, the 30-day forecast from `ForecastEngine`, and the goals, and calls `HealthScoreCalculator.calculate`; each component becomes a `ScoreComponent` (score, weight, detail); a component with no data is listed in `excluded` and the other weights are re-scaled. `HealthScoreSummaryTemplate` writes the text. Deterministic core; the AI can explain the components in the chat using the same numbers.

F08 — Purchase Affordability Check · AI (agent)

Field	Details
Feature ID and name	F08 — Purchase Affordability Check
Stage 1 feature/reference	F08 (UC07, SD05)
Status or change	**Implemented** (own HTTP client instead of LangChain4j; rules act as a floor, see below).
Implemented classes/files and responsibilities	`agent/AgentController.handle(AgentTask)` runs the loop; `Planner.nextStep` asks the model (via `PromptBuilder.build`, `ResponseParser.parse`) for the next step: a tool call or a final answer; `ToolManager` holds the tools (`ForecastTool`, `BudgetStatusTool`, `GoalTool`, `TransactionQueryTool`, `ScenarioTool`, `InsightTool`) and `execute(ToolCall)`; `analytics/PurchaseAssessor.assess` applies the fixed rules (Yes / Yes-but / Wait / No) from the lowest balance after the purchase, the buffer and the daily allowance; `AffordabilityFallback` writes the answer from the rules if the model cannot be reached; `GroundingChecker.verify` checks every figure; `AgentTrace`, `TraceRepository` record the steps; `llm/*` (`ClaudeProvider`, decorators). GUI: Assistant "Can I afford" tab (`AssistantView`) with `TraceDialog`.
Key methods	`AgentController.handle/latestTrace`, `Planner.nextStep/revise`, `PromptBuilder.build`, `ToolManager.execute`, `AnalyticsService.purchaseImpact`, `PurchaseAssessor.assess`, `GroundingChecker.verify`, `WealthSeiFacade.canIAfford`, `CliApp afford "<item>" <price> [date]`, `trace`
Design patterns	Facade, Adapter + Decorator (LLM layer); the rules-based fallback is a plain fallback, not a pattern
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `afford "laptop" 600` → `WealthSeiFacade.canIAfford` → `AgentController.handle`. The controller first runs the purchase-impact tool, so the deterministic result exists before any wording; `PurchaseAssessor` turns it into a verdict. `Planner` then sends the task, the conversation and the tool results to Sonnet (`PromptBuilder` states the rules: use tools for numbers, no markdown, say assumptions). The model may call more tools (`ToolManager.execute` returns a `ToolResult`) before it gives the final answer. `GroundingChecker.verify` compares each figure in the answer with the tool results; if one is unsupported, `Planner.revise` asks once for a corrected answer, otherwise the answer is flagged. The verdict can only be more cautious than the rules. If the model is unreachable the answer is written from the rules and says so. The trace (which tools, which figures) is stored and shown by `trace`. AI (agent) with a deterministic floor.

F09 — Savings Goal Planner with Replan · AI (agent) in Stage 1; deterministic planner + agent reads goals as implemented

Field	Details
Feature ID and name	F09 — Savings Goal Planner with Auto-Replan
Stage 1 feature/reference	F09 (UC08, SD06)
Status or change	**Modified.** Planning, feasibility and the options are plain code (`GoalPlanner`); the facade methods `planGoal/replanGoal` became `addGoal` + `getGoalFeasibility` + `proposeGoalFix`. The agent reads goals through `GoalTool` (for example in affordability and the monthly review). Goals are re-evaluated after every import and correction.
Implemented classes/files and responsibilities	`service/GoalService` (create, save money, set monthly contribution, evaluate, feasibility), `GoalPlanner` (months left, required monthly amount, projected completion, options), `MonthlySurplusProvider` (asks analytics for the monthly surplus), `GoalRepository` (+ `PersistentGoalRepository`); domain `SavingsGoal`, `GoalStatus`, `GoalRequest`, `FeasibilityReport`, `GoalOption`, `GoalOptionKind`; `AlertMonitor.evaluateGoal` (goal-risk alert); `UpdateGoalContributionCommand` (F13); `GoalTool`. GUI: `GoalsView`, `GoalRow`.
Key methods	`GoalService.createGoal/evaluateAll/feasibility/updateContribution/addSaved`, `GoalPlanner.requiredMonthly/projectedCompletion/isFeasible/buildOptions`, `WealthSeiFacade.addGoal/getGoals/getGoalFeasibility/setGoalMonthlyContribution/addToGoal/proposeGoalFix`, `CliApp` `goal add
Design patterns	Observer (goal-risk alert), Command (goal fixes through F13), Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `goal add "Laptop" 1400 2026-12-20 350` → facade → `GoalService.createGoal`, which stores the goal. `GoalPlanner` counts the months left (a part of a month counts as a whole month), the required monthly amount, and whether the plan surplus allows it. The surplus available to a goal is the plan surplus minus what the other open goals already take (`MonthlySurplusProvider`). Status: achieved (saved reaches target), on track (monthly contribution covers the requirement), at

risk (it does not, but the surplus could), behind (otherwise); a behind/at-risk status that gets worse raises a goal alert. `goal replan <id>` returns a `FeasibilityReport` with options (keep, save more, extend the deadline, reduce the target); `proposals from-goal <id>` turns the suggested monthly amount into a proposal (F13). Deterministic; the agent only reads and explains the numbers.

F10 — What-If Scenario Simulator · AI (agent) / hybrid

Field	Details
Feature ID and name	F10 — What-If Scenario Simulator
Stage 1 feature/reference	F10 (UC09, SD07)
Status or change	**Implemented.** Added a typed form that skips the model (`whatif cancel=Netflix caps=dining=150 income=200 buy=600@2026-12-01`); the tool takes four plain-text fields instead of a nested array.
Implemented classes/files and responsibilities	`agent/ScenarioTool` is the tool the model fills in; `analytics/ScenarioParser.parse(ToolArgs)` turns the fields into `ScenarioChange` objects (`CancelRecurringChange`, `CapCategoryChange`, `IncomeChange`, `OneTimeExpenseChange`) and refuses unknown names, more than 5 changes, non-positive values and dates outside six months; `ScenarioSimulator.simulate(scenario, today)` copies the baseline (`ForecastInputs.deepCopy`), applies the changes and compares six months with and without them (`ScenarioResult`); `agent/ScenarioDrafts` makes proposal drafts from a scenario. GUI: Assistant "What if" tab.
Key methods	`ScenarioParser.parse`, `ScenarioSimulator.simulate`, `ScenarioTool.execute`, `WealthSeiFacade.runWhatIf/simulateWhatIf/whatIfDrafts`, `CliApp whatif <text>` and `whatif key=value …`
Design patterns	Prototype (`deepCopy`), Factory-style parsing (`ScenarioParser` creates the right `ScenarioChange`), Strategy (`ScenarioChange.applyTo`), Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `whatif "cancel Spotify and cap dining at 150"` → `AgentController` → the model calls `ScenarioTool` with fields (`cancel`, `caps`, `income_increase`, `one_time_expenses`); `ScenarioParser` validates them and creates the change objects (a partial name such as "Netflix" matches `Netflix.com` when exactly one item matches; an ambiguous name is refused with a list). `ScenarioSimulator.simulate` deep-copies the baseline inputs so the real plan is not touched, applies each change (a cap is modelled as the average monthly spend of the last up to 3 full months minus the cap, counted as extra money each month), projects six months twice and returns the difference per month and in total. The model only words the result; `GroundingChecker` checks its figures. The typed form (`whatif cancel=… caps=…`) calls `simulateWhatIf` directly with no model. Hybrid: model parses plain words and explains; simulation is deterministic.

F11 — Monthly AI Review and Fix Plan · AI (agent)

Field	Details
Feature ID and name	F11 — Monthly AI Review and Fix Plan
Stage 1 feature/reference	F11 (UC10, SD08)
Status or change	**Implemented.** The (up to three) fixes are chosen by code rules so every suggestion is backed by numbers; the model writes the review text; the previous review's short summary is given to the model from memory. Reviews are kept for the session.
Implemented classes/files and responsibilities	`service/ReviewService.generate(month)` checks the month has transactions, gets the budget status and health score, runs the agent for the "what happened / went well / to fix" text, and builds fix drafts with plain rules (`candidateFixes`); `ReviewResult`; `domain/MonthlyReview`; `ReviewRepository`; `MemoryManager.rememberReview/pastReviewSummaries`; fix proposals use F13. GUI: `ReportsView` ("Generate review").
Key methods	`ReviewService.generate/find`, `MemoryManager.rememberReview`, `WealthSeiFacade.generateMonthlyReview/getMonthlyReview`, `CliApp review [month]`
Design patterns	Facade; (agent loop, see F08)
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `review 2026-10` → facade → `ReviewService.generate`. The service refuses a month that has not started or has no transactions, reads the month's budget status and health score, and runs the agent (`TaskType.MONTHLY_REVIEW`,

with short summaries of earlier reviews from memory) so the model gathers figures through the tools and writes the review; `GroundingChecker` checks them. Independently of the model, `candidateFixes` selects fix drafts with plain rules (goals behind schedule, subscriptions whose price rose), skips those already waiting as proposals, and keeps at most three. If the model is unavailable the review is a numbers-only version. The review is stored (`ReviewRepository`) and the drafts become proposals (F13). The Reports screen shows the review and can export it (F14). AI (agent) with a numbers-only fallback.

F12 — Natural-Language Finance Chat with Agent Trace · AI (agent)

Field	Details
Feature ID and name	F12 — Natural-Language Finance Chat with Agent Trace
Stage 1 feature/reference	F12 (UC11, SD09)
Status or change	**Modified.** `ConversationMemory` is our own bounded list of recent messages (not LangChain4j's); figures from earlier answers in the window are allowed in the grounding check; a failed model call is not remembered; `forget` command added.
Implemented classes/files and responsibilities	`agent/MemoryManager.buildContext/remember/forgetConversation` joins `ConversationMemory` (recent turns) and `UserProfileMemory` (preferences such as protected categories, stored by `MemoryRepository`/`PersistentMemoryRepository`); `AgentController` (`TaskType.CHAT`); `InsightTool`, `TransactionQueryTool`, `BudgetStatusTool` for answers; `PromptBuilder` (off-topic redirect, vague times assumed and stated); `GroundingChecker`; `AgentTrace`. GUI: `ChatPanel`/`ChatDock` and `AssistantView`; `TraceDialog` shows the trace.
Key methods	`WealthSeiFacade.ask/clearConversation/latestTrace`, `MemoryManager.buildContext/remember`, `ConversationMemory.append/recent`, `UserProfileMemory.setProtected`, `CliApp ask "<question>"`, `forget`, `trace`
Design patterns	Facade; Adapter/Decorator (LLM layer)
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `ask "How much did I spend on dining last month?"` → `WealthSeiFacade.ask` → `AgentController.handle(CHAT)`. `MemoryManager.buildContext` adds the last few turns and the saved preferences to the `AgentContext`. The model chooses tools (for example `TransactionQueryTool` for a category total); results come back as `ToolResult`s; the answer is checked by `GroundingChecker` and cleaned by `PlainText`; `MemoryManager.remember` stores the turn (a follow-up like "and on shopping?" is understood as the same month). Questions unrelated to finances are redirected. The trace lists every tool call with its inputs and output so each figure can be followed. AI (agent).

F13 — Proposal Approval Queue · Hybrid (implemented: deterministic queue)

Field	Details
Feature ID and name	F13 — Proposal Approval Queue
Stage 1 feature/reference	F13 (UC12, UC14, SD10)
Status or change	**Modified.** Added `UndoneState` (a fifth state so "Undone" is visible); pending proposals are kept for the session only; proposals come from what-if (`proposals from-whatif`), goals (`proposals from-goal`) and monthly reviews.
Implemented classes/files and responsibilities	`command/Proposal` holds the state and the `Command`; `ProposalState` with `PendingState`, `AppliedState`, `RejectedState`, `ExpiredState`, `UndoneState` (illegal moves throw `IllegalStateTransitionException`); `CommandFactory.create(ProposalDraft)` builds `SetBudgetLimitCommand`, `UpdateGoalContributionCommand` or `FlagSubscriptionCommand`; `service/ProposalService` creates, approves, rejects, undoes, expires old proposals and blocks drafts that touch a protected category (Groceries by default); `ProposalRepository`. GUI: `ProposalsView` (approve, reject, undo, protected-category toggles).
Key methods	`ProposalService.createFromDrafts/decide/undoLast/expireOld/setProtectedCategory`, `Proposal.approve/reject/expire/undo`, `CommandFactory.create`, `WealthSeiFacade.createProposals/decideProposal/undoLastProposal`, `CliApp` `proposals list`
Design patterns	State (proposal life cycle), Command (what an approval does, undoable through `CommandHistory`), Factory (`CommandFactory`), Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. A suggestion (from the monthly review, a what-if or a goal) arrives as a `ProposalDraft`. `ProposalService.createFromDrafts` discards drafts that touch a protected category and, for the rest, asks `CommandFactory.create` for the right `Command` and wraps it in a `Proposal` in the `PendingState`. `proposals approve <id>` → `ProposalService.decide` → `Proposal.approve(history)`; the state object checks the move is allowed, runs the command through `CommandHistory.execute` (for example `SetBudgetLimitCommand` changes the limit through `BudgetService`) and switches to `AppliedState`; a failing command leaves the proposal pending with a message. `proposals undo` calls the command's `undo` and moves the proposal to `UndoneState`; reject, and proposals for past months (`expireOld`), end in `RejectedState` / `ExpiredState`. Deterministic: the model never applies anything.

F14 — Report Export · Deterministic

Field	Details
Feature ID and name	F14 — Report Export
Stage 1 feature/reference	F14 (UC13, SD11)
Status or change	**Implemented.** CLI syntax is `export <md
Implemented classes/files and responsibilities	`service/ReportService.buildReportData/export` gathers the month's data into `ReportData` (summary, category table, goals, review if one exists) and chooses the exporter; `report/ReportExporter` (final `export` runs the fixed steps), `MarkdownExporter`, `CsvExporter`, `TextExporter` supply each part; `ExportException` for a file that already exists or cannot be written. GUI: `ReportsView` (format, save, overwrite confirmation).
Key methods	`ReportService.buildReportData/export`, `ReportExporter.export` (final), `writeHeader/writeSummary/writeCategoryTable/writeReviewSection/writeFooter`, `WealthSeiFacade.exportReport`, `CliApp export`
Design patterns	Template Method (`ReportExporter`), Factory (`ReportService` picks the exporter for the format), Facade
Video link/timestamp	GUI video · CLI video

How the classes collaborate. `export 2026-10 md ~/october.md` → facade → `ReportService.export(month, format, path, overwrite)`: `buildReportData` reads transactions, budget status, goals and the saved review for the month; the service picks the exporter for the format; `ReportExporter.export` (final) calls the abstract steps in a fixed order and writes the file (refusing to overwrite unless asked). A month with no review gets a note instead of a review section. Deterministic.

Supporting items (parts of Stage 1 that are implemented differently or extended)

These three were drawn in Stage 1 only as part of other features (plan inside F03, SQLite storage behind the repositories, the logging decorator). They are given their own IDs here because they have their own classes and videos.

N01 — Financial Plan Setup · Deterministic

Field	Details
Feature ID and name	N01 — Financial Plan Setup
Stage 1 feature/reference	F03 (UC03, SD03): "Budget and Plan Setup": income sources, current balance, fixed bills, planned one-off expenses, safety buffer; `FinancialPlan`, `IncomeSource`, `FixedBill`, `PlannedExpense`, `PlanService`, `PlanRepository`
Status or change	**Implemented as designed; command names differ.** Stage 1: `plan set-income`, `plan add-bill`, `plan add-expense`, `plan set-balance`; implemented: `plan income`, `plan bill`, `plan expense`, `plan balance`, plus `plan buffer`. GUI: plan dialogs (`PlanDialogs`) opened from the dashboard instead of a fixed Plan panel. Needed by F03, F05, F07, F08, F10.
Implemented classes/files and responsibilities	`service/PlanService` (balance with its date, safety buffer — default $200, income sources, fixed bills, planned expenses; a repeated name replaces the old entry); `domain/FinancialPlan`, `IncomeSource`, `FixedBill`, `PlannedExpense`, `Frequency` (weekly, biweekly, monthly, yearly); `PlanRepository` (+ persistent). GUI: `PlanDialogs`.
Key methods	`PlanService.setBalance/setSafetyBuffer/addIncome/addFixedBill/addPlannedExpense/getPlan`, `WealthSeiFacade` same names, `CliApp` `plan show
Design patterns	Facade, Decorator (persistent repository)
Video link/timestamp	Shown at the start of the F05 videos: GUI video, CLI video

How the classes collaborate. `plan income Paycheque 1685 biweekly 2026-11-13` → facade → `PlanService.addIncome` updates the saved `FinancialPlan` (immutable record, replaced), which `AnalyticsService.baselineInputs` reads for the forecast. The balance is the plan's balance plus transactions dated after the balance date.

N02 — Saved Data Between Sessions · Deterministic

Field	Details
Feature ID and name	N02 — Saved Data Between Sessions
Stage 1 feature/reference	Stage 1 stack and package table: "SQLite via JDBC", "repository interfaces and their `Sqlite…` implementations"
Status or change	**Modified (C3).** The repository interfaces are as designed; the `Sqlite…` implementations are replaced by `Persistent*Repository` classes that write text files.
Implemented classes/files and responsibilities	`repository/file/TsvFile` (tab-separated files, escaping, atomic replace), `FileCodec`, `StorageException`, and the `Persistent*Repository` classes (transactions, budgets, plan, rules, goals, recurring flags, memory) that wrap the in-memory repositories; `WealthSeiFactory.persistent(dir, …)`; `Main` (data folder `~/.wealthsei`, override `WEALTHSEI_HOME`).
Key methods	`TsvFile.read/write`, `Persistent*Repository.save/findAll`, `WealthSeiFactory.persistent`
Design patterns	Decorator (adds saving to the in-memory repository), Factory (`WealthSeiFactory`)
Video link/timestamp	Not a separate video: shown by restarting the app in the F03 and F09 videos (budget and goals still there). F03 GUI video, F09 GUI video

How the classes collaborate. Each `Persistent*Repository` implements the same interface as its `InMemory*` twin, delegates every call to it, and after a change writes the full list with `TsvFile` (temporary file then atomic replace). At start-up the factory loads the files into the in-memory repositories. A damaged file stops start-up with a message naming the file and line.

N03 — AI Call Log · Deterministic

Field	Details
Feature ID and name	N03 — AI Call Log
Stage 1 feature/reference	Fig 3.5 and pattern P7 (Decorator): `LoggingLLMProvider` does "logging and token counting"
Status or change	**Extended.** The Stage 1 decorator is implemented as designed; the `llm.log` file, the `aicalls` command and `scripts/ai-usage.sh` are additions that support the AI-use reporting required in Stage 2.
Implemented classes/files and responsibilities	`llm/LoggingLLMProvider` (decorator) writes one line per call to `llm.log` (call number, model, tokens, milliseconds; never the key, questions or data); `CliApp` `aicalls [n]` reads it; `scripts/ai-usage.sh` totals calls and tokens per model.
Key methods	`LoggingLLMProvider.complete`, `CliApp.aicalls/setCallLog`
Design patterns	Decorator
Video link/timestamp	Shown in the F05 and F07 CLI videos (`aicalls`): F05 CLI video, F07 CLI video

How the classes collaborate. Every `LLMProvider` call goes through `RetryingLLMProvider` and then `LoggingLLMProvider` before `ClaudeProvider` sends it; the logger records the response's token usage and the time taken; `aicalls` prints the last calls and the session totals per model.

---

3. Implemented design patterns

Ten patterns are implemented and used (Stage 1 required nine; Prototype was added). Source files are under `src/main/java/wealthsei/`.

P1 — Facade

Design problem	The GUI and the CLI both need import, budgets, goals, analytics, the agent, proposals and export. Letting each screen talk to a dozen services would duplicate logic and make the two interfaces drift apart.

Participants and roles	`facade/WealthSeiFacade` (the single entry point; coordinates services, e.g. refreshes alerts and goals after an import); clients `presentation/cli/CliApp` and the GUI (`ShellPanel`, `DashboardView`, `TransactionsView`, `GoalsView`, `ProposalsView`, `ReportsView`, `AssistantView`, `ChatPanel`); subsystems `TransactionService`, `BudgetService`, `PlanService`, `GoalService`, `AnalyticsService`, `ReviewService`, `ProposalService`, `ReportService`, `AgentController`. `WealthSeiFactory` builds the facade.
Source and methods	`WealthSeiFacade.importTransactions`, `correctCategory`, `getBudgetStatus`, `getSafeToSpend`, `addGoal`, `canIAfford`, `runWhatIf`, `ask`, `decideProposal`, `exportReport`.
How it follows the pattern and why it helps	Neither interface calls a service directly; they only use the facade, so a rule such as "after an import refresh only the affected months' budget alerts and re-check goals" exists once. The same behaviour is shown in both GUI and CLI videos.
Matches Stage 1?	Yes. Some method names differ (`canIAfford` for `checkAffordability`, `addGoal`/`getGoalFeasibility` for `planGoal`/`replanGoal`); see Section 4.

P2 — Strategy

Design problem	Choosing a category needs several interchangeable methods (what the user taught, built-in keywords, an AI guess) that must be tried in a fixed priority, and new ones must be addable without changing the caller.
Participants and roles	`service/CategorizationStrategy` (strategy interface, `Optional<Category> categorize(Transaction)`); `LearnedRuleStrategy`, `KeywordRuleStrategy`, `LLMCategorizationStrategy` (concrete strategies); `Categorizer` (context: holds the ordered list).
Source and methods	`Categorizer.categorize`, `CategorizationStrategy.categorize`, `LLMCategorizationStrategy.categorize`.
How it follows the pattern and why it helps	`Categorizer` knows only the interface; it returns the first strategy's answer. The AI strategy is added to the list only when an API key exists, so the same code works with and without AI.
Matches Stage 1?	Yes.

P3 — Adapter

Design problem	Banks export CSV in different layouts, and the Claude API has its own request/response format; the application wants one stable interface for each.
Participants and roles	*CSV:* `BankCsvAdapter` (target interface); `SignedAmountCsvAdapter`, `DebitCreditCsvAdapter`, `CardStatementCsvAdapter` (adapters, via `AbstractCsvAdapter`); `CsvParser`/`CsvRecord` (adaptee); `CsvImporter` (client, chooses the adapter). *LLM:* `LLMProvider` (target); `ClaudeProvider` (adapter); `HttpTransport`/`JdkHttpTransport` and `Json` (adaptee).
Source and methods	`CsvImporter.detectAdapter`, `AbstractCsvAdapter.readTransactions`, `ClaudeProvider.complete`.
How it follows the pattern and why it helps	Callers use `readTransactions()` and `complete(request)` and never see a bank column layout or JSON. Adding a new bank layout means one new adapter class; swapping the model vendor means one new provider.
Matches Stage 1?	**Differs in the adaptee.** Stage 1 wrapped Apache Commons CSV's `CSVParser` and LangChain4j's `ChatModel`. The implementation wraps our own `CsvParser` and a small JDK-based `HttpTransport`. Reason: neither library could be built or tested reliably in the development sandbox, and the code stays dependency-free (Section 4, C2). The roles and the problem solved are the same.

P4 — Observer

Design problem	Budget, low-balance and goal alerts arise deep inside services, but must reach whichever screen is open (a printed line in the CLI, a toast in the GUI) without the services knowing about screens.
Participants and roles	`service/AlertMonitor` (subject: `attach`, `detach`, `publish`); `service/AlertListener` (observer interface); observers `CliApp` (prints the alert) and `ShellPanel` (shows a toast); `Alert` (the event).
Source and methods	`AlertMonitor.evaluate`, `evaluateLowBalance`, `evaluateGoal`, `publish`; `WealthSeiFacade.addAlertListener`.
How it follows the pattern and why it helps	The monitor keeps the last level per category and notifies listeners only when it gets worse, so alerts are not repeated; a listener that throws is skipped so it cannot stop the others.
Matches Stage 1?	Yes in structure. The GUI observer is `ShellPanel` (toasts) instead of a dashboard-only listener (Section 4, C6).

P5 — Command

Design problem	Category corrections and approved proposals change data and must be undoable and redoable, and an approved proposal must carry "what to do" as an object.
Participants and roles	`command/Command` (`execute`, `undo`, `describe`); `RecategorizeCommand`, `SetBudgetLimitCommand`, `UpdateGoalContributionCommand`, `FlagSubscriptionCommand` (concrete commands holding their receivers' services); `CommandHistory` (invoker; keeps `done` and `undone` stacks, bounded to 100); `CommandFactory` and `Proposal` create/trigger commands.
Source and methods	`CommandHistory.execute/undo/redo`, `RecategorizeCommand.execute/undo`, `Proposal.approve`.
How it follows the pattern and why it helps	A command that throws while running is not recorded; running a new command clears the redo list; undo restores the old category and the old learned rule (or removes the new one). The invoker never knows what a command does.
Matches Stage 1?	Yes. The Stage 1 requirement that the undo stack be bounded was missing in the first implementation and was added (limit 100, with a test).

P6 — State

Design problem	A proposal's allowed actions depend on its stage (pending can be approved or rejected; applied can be undone; rejected and expired are final). Using flags and `if` chains would scatter the rules.
Participants and roles	`command/Proposal` (context); `ProposalState` (interface: `approve`, `reject`, `expire`, `undo`, `name`); `PendingState`, `AppliedState`, `RejectedState`, `ExpiredState`, `UndoneState` (concrete states); `IllegalStateTransitionException` for refused moves.
Source and methods	`Proposal.approve/reject/expire/undo/setState`, `PendingState.approve`, `ProposalService.decide/expireOld`.
How it follows the pattern and why it helps	The proposal delegates each action to its current state object, which either performs it and sets the next state or throws; every illegal move is refused in one place.
Matches Stage 1?	Yes, plus one extra state, `UndoneState`, so an undone proposal is visibly different from a rejected one (Section 4, C7).

P7 — Decorator

Design problem	Retrying failed model calls, logging them and saving repository data are extra behaviours that should be added without changing the classes they wrap.
Participants and roles	*LLM:* `LLMProvider` (component); `ClaudeProvider` (concrete component); `LLMProviderDecorator` (abstract); `RetryingLLMProvider`, `LoggingLLMProvider` (decorators). *Storage:* `TransactionRepository` etc. (component); `InMemory*Repository` (concrete components); `Persistent*Repository` (decorators that save to a text file after each change).
Source and methods	`RetryingLLMProvider.complete`, `LoggingLLMProvider.complete`, `PersistentTransactionRepository.save`, `WealthSeiFactory.persistent`.
How it follows the pattern and why it helps	Every decorator implements the same interface as what it wraps and delegates to it, so the chain `Logging(Retrying(Claude))` is built in the factory and callers see one `LLMProvider`. Persistence could later be replaced (for example by SQLite) without touching the services.
Matches Stage 1?	Yes for the LLM chain. The persistent repositories are an additional use of the same pattern (Stage 1 planned SQLite).

P8 — Template Method

Design problem	The three report formats share the same steps and order (header, summary, category table, review section, footer) and differ only in how each step is written; CSV adapters share row reading and differ only in how a row becomes a `Transaction`.
Participants and roles	`report/ReportExporter` (abstract class; `export` is final and calls the abstract steps in order); `MarkdownExporter`, `CsvExporter`, `TextExporter` (concrete). `importing/AbstractCsvAdapter` (`readTransactions` is final; subclasses supply `toTransaction`).
Source and methods	`ReportExporter.export`, `writeHeader/writeSummary/writeCategoryTable/writeReviewSection/writeFooter`, `AbstractCsvAdapter.readTransactions/toTransaction`.

How it follows the pattern and why it helps	The order and the file writing (including refusing to overwrite) are fixed in one place; a new format needs only the five step methods.
Matches Stage 1?	Yes (the CSV adapter use is additional).

P9 — Factory

Design problem	The right object depends on data: which `Command` for a proposal draft, which exporter for a format, which adapter for a CSV header; and the whole object graph must be wired in one place.
Participants and roles	`command/CommandFactory.create(ProposalDraft)` (returns a `SetBudgetLimitCommand`, `UpdateGoalContributionCommand` or `FlagSubscriptionCommand` by draft type); `service/ReportService.exporterFor(ExportFormat)`; `CsvImporter.detectAdapter`; `facade/WealthSeiFactory` (creates and wires all services, repositories, tools and the LLM chain).
Source and methods	`CommandFactory.create`, `ReportService.exporterFor`, `WealthSeiFactory.persistent/inMemory`.
How it follows the pattern and why it helps	Callers ask for a product by data (a draft type, a format) and get a subclass of the common type; adding a proposal type touches the factory only.
Matches Stage 1?	Yes (`WealthSeiFactory` is an additional wiring factory).

P10 — Prototype

Design problem	The what-if simulator must try changes on a copy of the forecast inputs without altering the user's real plan.
Participants and roles	`analytics/ForecastInputs` (prototype, `deepCopy()`); `ScenarioChange` implementations (`CancelRecurringChange`, `CapCategoryChange`, `IncomeChange`, `OneTimeExpenseChange`: `applyTo(inputs)`); `ScenarioSimulator` (client).
Source and methods	`ForecastInputs.deepCopy`, `ScenarioSimulator.simulate`, `ScenarioChange.applyTo`.
How it follows the pattern and why it helps	The simulator clones the baseline, applies each change to the clone and projects both; the original inputs are never modified, which a test checks.
Matches Stage 1?	Stage 1 named Prototype only as "also considered"; it was adopted in the implementation (Section 4, C8).

3.1 Updated UML class diagrams

The class diagrams were rebuilt from the submitted Stage 1 UXF files (Figures 3-1 to 3-7), so figure numbers, groupings and layout match Stage 1. All 136 Stage 1 class boxes are kept except three that were never built (`ExplanationService`, `ChatModel`, `AnthropicChatModel`); three keep their role under a new name (`CSVParser` → `CsvParser`, `ProposalView` → `ProposalsView`, `ReportView` → `ReportsView`). Colours: **orange** = changed in Stage 2 (renamed, new signature or fields, Stage 1 handler names or private fields not in the code), **green** = new class, **white** = unchanged. Each new (green) class is placed next to the class that uses it and joined by a dashed "uses" arrow, or by an inheritance/implements line; a blue note under each figure lists what each new class is used by. Old classes show the members they had in Stage 1 and still have; unchanged members are not repeated, so a class may not list every method. Every changed (orange) or new (green) class lists its current members in its own box. Every changed method is compared with the Java source; the full per-class list is in `docs/class-diagram-changes.md`. Stage 1's own Figure 3-2 contains `BudgetService` twice; that is kept as submitted.

Stage 2 figure	Content	Stage 1 classes	Changed	New	Removed (not built)
3.1 (S1 Fig 3-1)	Presentation and facade	10	9	4	—
3.2 (S1 Fig 3-2)	Import, categorization, plan, budgets, alerts	20	14	8	—
3.3 (S1 Fig 3-3)	Analytics, goals, scenarios, recurring	18	12	7	ExplanationService
3.4 (S1 Fig 3-4)	Agent subsystem	32	18	5	—
3.5 (S1 Fig 3-5)	LLM provider layer	10	4	5	ChatModel, AnthropicChatModel
3.6 (S1 Fig 3-6)	Proposals, commands, reviews, reports	25	17	1	—
3.7 (S1 Fig 3-7)	Domain model	24	16	2	—

Figure 3.1 — Presentation and facade. `MainWindow` and `CliApp` use `WealthSeiFacade`; `AlertMonitor` notifies the listeners. New: `ShellPanel`, `WealthSeiFactory`, `ArgTokenizer`, `Main`.




Figure 3.2 — Import, categorization, plan, budgets, alerts. Adapter (CSV adapters), Strategy (categorizers), Observer (`AlertMonitor`). New: `AbstractCsvAdapter`, `CardStatementCsvAdapter`, `CsvRecord`, `CategoryCorrector`, `BudgetCalculator`, the in-memory and persistent transaction repositories, `TsvFile`.




Figure 3.3 — Analytics, goals, scenarios, recurring. Template Method summaries and the deterministic goal planner. `ExplanationService` was not built and is removed (C4).




Figure 3.4 — Agent subsystem. `AgentController` loop with `Planner`, `ToolManager`, `GroundingChecker`, `MemoryManager`, trace. New: `PurchaseAssessor`, `Verdict`, `AffordabilityFallback`, `ScenarioDrafts`, `PlainText`.




Figure 3.5 — LLM provider layer. Adapter and Decorator. `ChatModel` / `AnthropicChatModel` were not built; `ClaudeProvider` calls `HttpTransport` (C2).




Figure 3.6 — Proposals, commands, reviews, reports. Command, State, Factory, Template Method. New: `UndoneState`.





Figure 3.7 — Domain model. Value classes and records. New: `PurchaseImpact`, `RecurringReview`.



Note on scope. The figures show the Stage 1 design plus the changes made in Stage 2. Classes that Stage 1 never drew (value records and enums such as `ImportResult` or `TxFilter`, exception classes, and `Account`) are in the code but are not added here.

Note on class members. Classes that exist only as Swing helper widgets, and the `Persistent*`/`InMemory*` repository pairs for plan, budgets, goals, proposals, rules and traces, are not drawn individually (they follow the pattern shown for transactions). The hand-entry operations of F01 are in Figure 3.1 (`addTransaction` on the facade) and Figure 3.2 (`NewTransaction` use in `TransactionService`) as in Stage 1; they were implemented late (C17). The Swing views no longer list Stage 1's button-handler names because the code uses anonymous listeners.

3.2 Use-case and sequence diagram updates

Stage 1 has one use-case diagram, fourteen use-case descriptions (UC01–UC14) and eleven sequence diagrams (SD01–SD11). Checking each against the implementation:

Stage 1 diagram	Still accurate?	What differs
Use-case diagram, actors (User, LLM Service, File System)	Yes	Same actors and system boundary.
UC01–UC03, UC05–UC07, UC09–UC14	Yes (wording of the user steps is unchanged)	Only names differ (see Section 4).
UC04 View recurring payments	Mostly	The AI review is a separate action (button/command) instead of part of the page load.
UC08 Plan and replan savings goal	**No**	The agent no longer plans or replans; the goal service does (C13). Replaced below (Figure 3.9).
SD01 Import or add transactions	Yes (naming only)	`CsvParser`, own reader instead of Commons CSV `CSVParser`. Part B (add by hand: `addTransaction`, `validate`) is implemented as drawn (C17).
SD02 Categorize and correct	Yes	`RecategorizeCommand` as in Stage 1.
SD03 Budget and alerts	Mostly	The GUI listener is `ShellPanel` (toasts) (C6).
SD04 Analytics with explanation (F04–F07)	**No**	It calls `ExplanationService`, which was not built (C4). Replaced by Figure 3.8 (F05–F07: templates, AI only on request) and Figure 3.10 (F04 AI review).
SD05 Affordability agent loop	Yes	Facade method is `canIAfford`; the deterministic purchase-impact step runs first.

Stage 1 diagram	Still accurate?	What differs
SD06 Goal planning and replanning (F09)	**No**	Replaced by Figure 3.9.
SD07 What-if	Yes	Tool takes four plain-text fields (C14); a typed form skips the model.
SD08 Monthly review	Yes	Fix drafts are chosen by code rules (C15).
SD09 Chat with memory	Yes	Own `ConversationMemory`.
SD10 Proposal approval	Yes	Extra `UndoneState`.
SD11 Export	Yes	None.

So **three** Stage 1 items were inaccurate (UC08, SD04, SD06) and are replaced by three new diagrams (Figures 3.8–3.10); UC04 gets a one-line note; the class diagrams were redrawn (Figures 3.1–3.7, same numbering as Stage 1); the others still describe the code, with the naming differences listed above.

Figure 3.8 — F05–F07 as implemented (replaces SD04 for F05–F07). The dashboard shows numbers and a fixed-template sentence; the AI is only involved when the user asks in the Assistant.




Figure 3.9 — Plan and replan a savings goal (replaces UC08 / SD06). The user need is unchanged (see how a goal is doing, find out if it is reachable, get a fix); the fix becomes a proposal the user approves (F13).





Figure 3.10 — Recurring payments with the AI review (replaces SD04 for F04). The review is a separate action, not part of each refresh.



4. Changes and rationale

Each entry follows **Original design → Implemented change → Reason → Impact**. IDs C1–C18 are used in other sections.

4.1 Architecture and class changes

C1 — GUI toolkit. *Original:* JavaFX screens (`DashboardView`, `TransactionsView`, ...). *Implemented:* the same screens in Swing (`javax.swing`), plus helper classes (`Card`, `Toast`, `ScoreRing`, `LineChart`, ...) and `ShellPanel`/`MainWindow`. *Reason:* Swing is part of the JDK, so the application needs no extra install and runs from one Maven command on any machine used for marking. *Impact:* screen names and responsibilities are the same; `ProposalView` and `ReportView` became `ProposalsView` and `ReportsView`; event handlers (`onApprove`, ...) are button actions inside the views.

C2 — No third-party libraries (LangChain4j, Apache Commons CSV, picocli). *Original:* LangChain4j `ChatModel`/`MessageWindowChatMemory`, Apache Commons CSV `CSVParser`, picocli for the CLI. *Implemented:* `ClaudeProvider` with `JdkHttpTransport` and our own `Json`; `CsvParser`; our own bounded `ConversationMemory`; a hand-written command reader (`CliApp`, `ArgTokenizer`). `ChatModel`/`AnthropicChatModel` are not built. *Reason:* the libraries could not be downloaded and tested in the environment where the code was drafted; code that cannot be run before delivery would not have been verifiable. The Claude Messages API is a plain HTTP/JSON interface. *Impact:* the only dependency is JUnit; all behaviour is covered by tests; the Adapter pattern keeps its roles with a different adaptee (P3); a library can still be added behind `LLMProvider`.

C3 — Storage. *Original:* SQLite. *Implemented:* tab-separated text files with atomic replace (`TsvFile`, `Persistent*Repository`). *Reason:* no extra library, data can be opened in a text editor, fully testable. *Impact:* repository interfaces are unchanged, so SQLite could be added later; undo history, proposals, reviews and traces are not saved between runs (Section 1.4).

C4 — Explanation layer. *Original:* `ExplanationService` and `AnalysisFacts` turn computed facts into an LLM explanation for F04–F07. *Implemented:* no such classes. Fixed summary templates (`RecurringSummaryTemplate`, `SafeToSpendSummaryTemplate`, `HealthScoreSummaryTemplate`, `AffordabilityFallback`), `RecurringReviewer` for F04, and the agent (`PromptBuilder`, tools, `GroundingChecker`) for explanations asked in the Assistant. *Reason:* a general explainer duplicated what the agent loop already

does with tool results, and templates are free, instant and always correct. *Impact:* F05–F07 are deterministic with AI explanation on request (the dashboard shows the template).

C5 — Facade method names and signatures. *Original:* `getRecurringPayments()`, `getHabitInsights(month)`, `checkAffordability(item, price)`, `planGoal(request)`, `replanGoal(id)` (the last two returned an `AgentResult`). *Implemented:* `recurringPayments(asOf)`, `getHabits(month)`, `canIAfford(item, price, date)`, `addGoal(request, today)`, `getGoalFeasibility(id, today)`, `proposeGoalFix(id, today)`. Many methods take today's date as a parameter. *Reason:* tests control the date; goal planning needs no model (F09). *Impact:* behaviour is as specified; see C9.

C6 — Observer: GUI observer. *Original:* `DashboardView` as the GUI listener. *Implemented:* `ShellPanel` registers the listener and shows toasts on any screen; `CliApp` registers `printAlert`. *Reason:* an alert should appear on whichever screen is open. *Impact:* same pattern, different observer class (P4).

C7 — State: extra state. *Original:* Pending, Applied, Rejected, Expired. *Implemented:* plus `UndoneState`. *Reason:* an undone proposal is neither rejected nor applied. *Impact:* five states; `proposals undo` moves to it.

C8 — Prototype adopted. *Original:* only "also considered". *Implemented:* `ForecastInputs.deepCopy` (P10). *Reason:* the simulator needs an independent copy. *Impact:* none on other patterns.

C9 — Added domain/service classes. `BudgetCalculator`, `CategoryCorrector`, `PurchaseAssessor`, `Verdict`, `PlainText`, `ScenarioDrafts`, `RecurringReviewer`, `RecurringReview`, `AbstractCsvAdapter`, `CardStatementCsvAdapter`, `CardMerchantCleaner`, `WealthSeiFactory`, `LlmConfig`, `HttpTransport`/`JdkHttpTransport`, `Json`, `UnavailableLLMProvider` and the Swing helper classes. *Reason:* each fills a gap found while implementing (the plan data the forecast needs; the fixed rules for affordability; markdown-free answers). *Impact:* more classes than Stage 1. Every class named in the final Stage 1 report exists under the same name, except the library classes (C2: `CSVParser`, `ChatModel`, `AnthropicChatModel`, `MessageWindowChatMemory` and the LangChain4j message types), `ExplanationService` and `AnalysisFacts` (C4), and the renamed `ProposalView`/`ReportView` (C1). The check compared the class names written in the Stage 1 text with the code; `docs/stage1-conformance.md` has the details.

4.2 Feature changes

C10 — F01. *Original:* two CSV layouts, rows read with Commons CSV. *Implemented:* a third layout (credit-card statements); card payments skipped; merchant names cleaned; own `CsvParser`. *Reason:* the project's own sample data is a card export where payments to the card would otherwise be counted as income. *Impact:* UC01 unchanged otherwise.

C11 — F04. *Original:* LLM summary through `ExplanationService`. *Implemented:* template summary on every refresh; `recurring review` / "AI review" button for the AI sentences (`RecurringReviewer`, Haiku). *Reason:* limit cost and waiting time; AI output only when asked. *Impact:* hybrid kept; the template is the fallback the design required.

C12 — F05, F06, F07. *Original:* hybrid, with an LLM explanation on each screen. *Implemented:* deterministic results with template text; AI explanation when asked in the Assistant; `ScoreComponent.detail` and `HealthScore.excluded` added. **Not implemented:** F07's "change from last month" (no stored history of past scores). *Reason:* C4. *Impact:* the numbers are identical; the explanation is generic until asked.

C13 — F09. *Original:* agent-driven `planGoal`/`replanGoal`. *Implemented:* `GoalService`/`GoalPlanner` plain code, goals re-checked after every import, correction and contribution change; `GoalTool` lets the agent read them; the fix is a proposal (F13). *Reason:* planning is arithmetic that must be exact and repeatable, so code is more reliable than a model. *Impact:* UC08/SD06 replaced (Section 3.2, Figure 3.9); the user need (see feasibility, get alternatives, approve a fix) is met.

C14 — F10. *Original:* the agent builds a nested list of changes. *Implemented:* the tool takes four plain-text fields; a typed `whatif key=value` form skips the model; caps are modelled as the average spend minus the cap. *Reason:* simpler for the model to fill correctly; code validates every value. *Impact:* fewer malformed requests; works without a key.

C15 — F11/F12/F13. F11 fixes are chosen by code rules so every suggestion has numbers behind it; F12 uses our own memory window and a `forget` command; F13 gains `from-whatif` / `from-goal` and `expireOld` for past months. *Impact:* proposals can come from three sources; pending proposals and reviews are session-only.

C16 — Supporting items N01–N03. *Original:* the plan is part of F03; persistence is SQLite behind repository interfaces; logging is the `LoggingLLMProvider` decorator. *Implemented:* these are given their own IDs and videos: N01 plan setup (as designed, command names differ), N02 text-file storage (C3), N03 `llm.log` and the `aicalls` command (an addition to the decorator). *Reason:* they have their own classes and are shown in their own videos; AI use must be reported. *Impact:* Section 2.

C17 — F01 manual entry. *Original:* F01 input is a CSV path or a `NewTransaction` (Stage 1 facade `addTransaction`, `TransactionService.addTransaction` and `validate`). *Implemented:* first Stage 2 builds covered CSV only; manual entry was found missing while comparing the submitted UXF files with the code and was added: `NewTransaction` record, `TransactionService.addTransaction`/`validate`, `WealthSeiFacade.addTransaction`, CLI `add`, GUI "Add transaction" dialog, 9 new tests. *Reason:* it was part of the Stage 1 design. *Impact:* none on other features; matches the Stage 1 diagrams.

C18 — Reshaped records and private members. *Original (Stage 1 UXF class diagrams):* `ForecastInputs` held `plan`, `startDate` and `startBalance`; `ReportData` held `status`; `RecurringPayment` had an `income` flag; each screen had a named handler (`onApprove`, `onAddClicked`, ...); services kept their repositories and helpers as private fields (`txRepo`, `forecastEngine`, `chatMemory`, `undoStack`, ...). *Implemented:* `ForecastInputs` holds `today`, `openingBalance`, the plan's three lists (`incomeSources`, `fixedBills`, `plannedExpenses`) and `typicalMonthlySpending`; `ReportData` holds the figures the report prints (`income`, `spending`, `transactionCount`, `categories`, `goals`, `review`); `RecurringPayment` has no `income` flag because the detector reads expenses only (income comes from the plan, N01); screen handlers are button actions inside the Swing views; private fields follow the changed design (our own memory window and storage, two deques `done`/`undone` in `CommandHistory`, dependencies passed as arguments). *Reason:* the forecast needs the plan items separately; the report needs its totals; the libraries behind the other fields were replaced (C2, C3). *Impact:* no change to what the features do, except that a regular paycheque is not listed as a recurring payment in F04. A check of all 432 members in the submitted Stage 1 class diagrams and all 178 calls in the sequence diagrams found no other missing names; the result is in `docs/stage1-conformance.md`.

Command-line differences from Stage 1 (not behaviour changes). Stage 1 sketched the CLI as `wealthsei <command>` (picocli). The implemented CLI is started through `Main` with Maven (`exec:java`): with no arguments it opens a prompt, and with arguments it runs that one command and exits. The commands keep the Stage 1 meaning; only the spelling of some differs:

Stage 1	Implemented	Note
`import <file.csv>`	`import <file.csv>`	same
`add-tx --date <d> --amount <a> --merchant <m> [--category <c>] [--income]`	`add <date> <amount> "<merchant>" [category=<id>] [income] [note="<text>"]`	positional instead of flags (C17)
`categorize <txId> <category>`	`correct <txId> <categoryId>`	renamed
`undo`, `redo`	`undo`, `redo`	same
`plan set-income`, `add-bill`, `add-expense`, `set-balance`	`plan income`, `bill`, `expense`, `balance`	shorter names; `plan buffer` added; `plan show` same
`budget set <month> <category> <amount>`	`budget set <month> <category>=<amount> ...`	several limits at once
`budget status <month>`	`budget status <month>`	same
`recurring`, `safe [date]`, `habits <month>`	same	`forecast`, `recurring review`, `recurring flag` added
`score <month>`, `review <month>`	`score [month]`, `review [month]`	month optional
`afford "<item>" <price>`	`afford "<item>" <price> [date]`	optional date
`goal add "<name>" <target> <deadline>`, `goal replan <id>`	same, `goal add` takes an optional saved amount	`goal list`, `save`, `monthly` added
`whatif "<text>"`	`whatif <text>`	also a typed form `whatif key=value` that needs no AI
`ask "<question>"`, `trace <id>`	`ask "<question>"`, `trace [id]`	id optional (latest by default)
`proposals list`, `approve <id>`, `reject <id>`	same	`all`, `from-whatif`, `from-goal`, `undo`, `why` added
`export <month> --format md --out report.md`	`export <month> <md|csv|txt> <file> [overwrite]`	positional
(not in Stage 1)	`transactions`, `categories`, `aicalls`, `forget`, `protect`/`unprotect`	helper commands

In the GUI the plan is edited in dialogs opened from the dashboard (`PlanDialogs`), where Stage 1 drew a Plan panel on `DashboardView`. The undo stack is bounded to 100 commands as Stage 1 required. Learned rules apply to future imports only, not to past transactions.

---

5. AI tools and collaboration log

5.1 Tools and models

Tool / platform	Model	Features, classes or tasks	Total token cost and money cost
Claude (chat with code tools)	Claude Sonnet 5.5 (`claude-sonnet-5-5`)	AI-assisted development of all Stage 2 code: domain classes, services, analytics, agent and LLM layers, CLI, Swing GUI, unit tests, build/editor debugging, demo data and scripts, report and README drafts. (Stage 1: design report, UML, use cases.)	Whole Stage 2 development, Oct 20 – Nov 7 (one continuous session, about 8.2 hours of model time): **248,485,938 tokens** in total = 43,138 plain input + 1,398,501 output + 240,720,798 cache-read + 6,323,501 cache-write tokens. **About $62.73** API-equivalent cost as computed by the tool (not necessarily what was billed; it depends on the plan). Stage 1 usage is not included.
Claude API inside WealthSei (runtime)	`claude-sonnet-5-5` (agent: F08, F10–F12, explanations)	Tool-using agent: `AgentController`, `Planner`, `PromptBuilder`.	**362,079 tokens** (338,620 input + 23,459 output; Nov 5–7 UTC). Cost: part of the **$0.92** total below (the Console dashboard does not split the cost by model). The kept call logs show 20 Sonnet calls and 44,589 tokens (`scripts/ai-usage.sh`); the Console figure is higher because it also counts testing and the demo folders whose logs were deleted.
Claude API inside WealthSei (runtime)	`claude-haiku-5-5` (categorizer F02, recurring review F04)	`LLMCategorizationStrategy`, `RecurringReviewer`.	**56,275 tokens** (46,674 input + 9,601 output; Nov 5–7 UTC). Cost: part of the **$0.92** total below. The kept call logs show 28 Haiku calls and 5,889 tokens.
VS Code + Java extension	n/a	Editing and running tests.	Free.

How the numbers were obtained: development usage from the chat tool's own running total for the session (tokens by type and a computed cost); runtime usage from the Anthropic Console and from `llm.log` (model, tokens and time per call, summed per model by `scripts/ai-usage.sh`; see `docs/ai-usage.md`). Money is the API price, so it is an estimate of cost, not an invoice. No API key appears in this report, the logs or the repository.

5.2 How the work was divided

I chose the project, features and stack, decided what to build next and how much, ran every build and test on my own machine, recorded the demonstrations, reviewed and committed all code, and kept the key out of the repository. The AI assistant drafted code and tests for the piece I asked for following the Stage 1 design, explained trade-offs, diagnosed errors from the output I pasted, and checked its drafts in its own sandbox (strict compile and a stand-in test runner) before handing them over. The complete dated log is in `docs/ai-log.md`.

5.3 Representative interactions

1. A test caught a startup bug (domain classes, Oct 20). *Ask:* build `Money`, `Category`, `Transaction` with tests. *AI output:* the classes and 17 tests; its own check showed 14 of 17 failing because `Money.ZERO` was created before the rounding constant was initialised. *Fix:* reorder the declarations. *My verification:* ran `mvn test` with real JUnit 5: 17 tests passing; committed and pushed.

2. Editor errors that were not code errors (Oct 20). *Problem:* VS Code showed 80 false errors ("record" not recognised, lambdas at source level 1.8). I pasted the output; the AI traced it to the Java engine needing JDK 21 and the project being imported as "J2SE-1.5" because `pom.xml` lacked `maven.compiler.source/target`. *My verification:* installed JDK 21 for the editor, applied the properties; all errors cleared; `mvn test` unchanged.

3. Library choice (Oct 27 – Nov 4). *AI proposal:* a small own CSV reader and own HTTP/JSON client instead of Apache Commons CSV and LangChain4j, because it could not download or test those libraries before handing code over. *My decision:* accepted; the consequence (Adapter adaptee changed) is documented in C2. *My verification:* `mvn test` passing after each piece (expected counts reported back in the log); live calls to the real API with my key worked (three calls, 5,051 tokens for the first `afford`).

4. A live run exposed a plan bug (Nov 4). *Observation:* the first real `afford` showed a safe-to-spend figure that did not match my hand calculation. *AI diagnosis:* 8,800 / 27 days = 325.93 matched income added twice to the saved plan. *Fix:* an income or bill with the same name replaces the old one, with a test. *My verification:* re-ran the same commands; the figure matched my hand calculation.

5. Missing AI step in F04 (Nov 6). *My direction:* F04 was designed as a hybrid feature but the first version only had the template, so the AI part was missing. The AI added `RecurringReviewer` (facts-only prompt, numbers must come from the facts, template fallback, button and command). *My verification:* ran `recurring review` with the key and compared every figure with `recurring`; checked the call in `aicalls` (model, tokens, time).

6. Grounding and honesty while recording (Nov 6). *Problems found while recording:* the grounding check flagged the harmless "100" in "out of 100"; the model added chatter when asked to correct itself; answers contained markdown asterisks; a whole-number health score was not checked. *Fixes:* ignore "out of 100", the revise prompt asks for the corrected answer only, `PlainText` strips markdown, the score before a "score" word is checked. *My verification:* re-ran the questions in the Assistant; and I caught that the AI had quoted a score from its sandbox data (58) that did not match my data (55); the AI withdrew the figure and the demo text was changed to avoid quoting numbers it had not seen on my screen.

7. Stage 1 audit before pushing (Nov 7). *My ask:* compare every class, pattern, feature and domain item with Stage 1. *AI work:* class and method comparison (`docs/stage1-conformance.md`); it found the undo stack was not bounded and the F07 "change from last month" was never computed; the first was fixed, the second is listed as a limitation. *My verification:* `mvn test`: 587 tests passing; pushed.

---

6. Development and verification summary

6.1 Weekly commit summary

Repository: https://github.com/Rishit-Shah/EECS-3311-Project---WealthSei · links are of the form `…/commit/<hash>`. Dates are Toronto local time.

Period 1 — October 20–26, 2026 (5 commits)

Commit	Message
a10be9f	first domaintest
64a4daa	second domain push
725906a	third domain push
b850c8a	test one
7a9ce76	second test set

Period 2 — October 27 – November 2, 2026 (21 commits)

Commit	Message
cc80d07	testing file for transactions
7151611	Add Maven project setup and Java .gitignore
bf7bdde	Add Frequency enum with monthly conversion and occurrence dates
f26584f	Add FinancialPlan with income, fixed bills and planned expenses
99cd482	Add Budget, BudgetLine and BudgetLimits
f738f52	Add BudgetStatus with 80% and 100% alert levels, and Alert
a990dd0	add parsing
2475690	Add Categories, ImportResult, ParseResult and TxFilter
1ea460a	Add CSV import: record, row parsing, bank adapters and CsvImporter
1b9fe1c	Add transaction repository
6a4d066	Add TransactionService for import, query and category updates
d6f2c7d	Add keyword categorization strategy and Categorizer
c243494	Add budget repository and BudgetCalculator
5670869	Add AlertMonitor (Observer) and BudgetService
a8779d8	Report affected months in ImportResult

Commit	Message
dd44b9d	Add PlanService and plan repository
7c33f6b	Add WealthSeiFacade
94d3657	Add learned merchant rules for categorization
24b2697	Add Command interface and undo/redo history
e3d0156	Add undoable category corrections that teach the app
cb4155c	Wire category undo and redo into the facade

Period 3 — November 3–9, 2026 (33 commits)

Commit	Message
0e6ef2a	Add TsvFile for saving records as text files
ccd6cc8	Add file-backed repositories (Decorator) and BudgetRepository.findAll
afff94f	Save data between sessions in the CLI
88da5a7	Add RecurringDetector to find repeating payments
61d8bb1	Add AnalyticsService, recurring summary and review flags
8b6e3fd	Align rule repository and commands with Stage 1 design
c354ae9	Add recurring command to the CLI and facade; add Stage 1 conformance table
b840f54	Add Forecast, DailyBalance, SafeToSpendResult and SavingsGoal
189c894	Add ForecastEngine and SafeToSpendCalculator
019df15	Add goal repository and align recurring repository with Stage 1
fca524f	Add safe-to-spend service, low-balance alert and CLI commands
91a649e	Add health score (F07), habits and score CLI commands, tests
12dc822	Add savings goals (F09): GoalService, GoalPlanner, feasibility and options
a423894	Persist goals, goal CLI commands, goal alerts, habit sample data, tests
f623e1d	Add LLM layer: provider interface, Claude adapter, retry and logging decorators
4b40d5d	Add F08 affordability agent: tools, planner, grounding check, traces
07e2ae0	Wire agent into facade and CLI; fix duplicate income and bill entries
ce6055a	Add F10 what-if scenario simulator and parser
1d18153	Support credit-card statement CSVs; skip card payments; clean merchant names
7b92c0d	Add Account domain class from Stage 1
08386bf	Add LLM categorization strategy; filter transactions by uncategorized; ignore private bank CSVs
c911548	Add F13 proposal approval queue: states, commands, factory, service
e4adc3b	Count typical everyday spending in what-if, affordability and goals; add proposals CLI
732b061	Add F14 report export: Markdown, CSV and text exporters
555a1b5	Do not repeat budget alerts after a restart: prime alert levels at startup
d79c159	F12: chat with memory (ConversationMemory, UserProfileMemory, MemoryManager, InsightTool)
7138f44	F11: monthly review (ReviewService, review command, numbers-only fallback, fix proposals)
d75829f	F04: AI recurring-payments review (RecurringReviewer, facts-only prompt, template fallback)
21dfb4a	Agent: strip markdown from answers, tighten grounding check for scores and scales
08d4bdf	CLI: recurring review and aicalls commands, expand ~ in export paths
aa4829f	Bound undo history to 100 commands, as Stage 1 requires
ea55fe6	Add Swing GUI: dashboard, transactions, goals, proposals, reports, assistant with trace view
fcbdf90	Add demo statements and load-demo script for reproducible demos

Commits that changed only documents (the AI log and the conformance table) are not counted above. The Period 3 list is in order of date; all of its commits change implementation or test code.

6.2 Checks performed to verify the implementation

- **Unit tests:** `mvn test` runs 596 JUnit 5 tests with 0 failures and 0 errors (test classes per package: domain, importing, repository, service, analytics, command, agent, llm, report, facade, CLI and GUI logic). The tests that involve the model use `MockLLMProvider` with scripted replies, so they are repeatable and cost nothing.
- **Strict compile:** the code is compiled for Java 17 with `-Xlint:all -Werror` before each delivery.
- **Hand arithmetic:** the safe-to-spend figure, goal months and budget percentages were recomputed by hand from the demo data and compared with the application (for example the safe-to-spend example in the F05 video: $208.17 per day on Nov 6).
- **Real API runs:** every AI feature was run against the real Claude API with my own key, and each model call was checked in `llm.log` / `aicalls` (model, tokens, time).
- **Grounding:** answers were compared with the trace (`trace`); unsupported figures are rejected by `GroundingChecker`, which has its own tests (13 cases).
- **Demo data:** all demonstrations use invented statements (`demo/`), loaded by `bash demo/load-demo.sh` into a separate data folder, so the recordings can be reproduced from a clean clone and contain no real data or keys.
- **Both interfaces:** every feature was demonstrated in the GUI and in the CLI.
- **Secrets:** `.env` is git-ignored and only `.env.example` (placeholders) is committed; the key is never printed, logged or recorded.

6.3 Important defects found and corrected

Defect	How it was found	Fix
`Money.ZERO` crashed the class at load (static initialisation order)	Unit tests (14 of 17 failing)	Reordered declarations
Same income and bills added twice to the saved plan, giving a wrong safe-to-spend figure	Live run did not match hand calculation	An income or bill with the same name now replaces the old one (test added)
A pattern with steady amounts half the time scored exactly 0.80 and was not reported	Unit test	Cut-off moved to 0.85
`cancel=Netflix` did not find "Netflix.com"	Real sample data	A partial name matches when exactly one item fits; an ambiguous name is refused with the list
Forecasts ignored everyday spending ("$3,887 left per month" on real data)	Real data	Typical monthly spending is counted in what-if, affordability and goals
Same budget alert printed again after each restart	Real use	`primeAlerts` loads the current levels at start-up
Grounding check flagged the harmless "100" in "out of 100"; whole-number scores were not checked	Recording the demos	Ignore "out of 100"; check the number after "score"
Model answers contained markdown asterisks and correction chatter	Recording the demos	`PlainText` strips markdown; revise prompt asks for the corrected answer only
Dashboard "needs attention" missed the weekend spike (5-row cap)	Demo recording	Cap raised to 8 rows with limits per kind
`export` did not expand `~` in a path	Demo recording	`expandHome` added (test added)
Undo history was not bounded (Stage 1 required it)	Stage 1 audit	Bounded to 100 (test added)
F04 had no AI step although designed as hybrid	Review against Stage 1	`RecurringReviewer` added

6.4 Remaining limitations

See Section 1.4 for the complete list. In short: pending proposals, reviews, traces, undo history and chat memory are session-only; F07's "change from last month" is not computed; F05–F07 explanations are templates unless asked in the Assistant; three CSV layouts only; a few commands show a raw message for an invalid month; duplicate goal names are allowed. Full deterministic testing of every rule and KUMA agent validation are Stage 3 work.

---

7. Demonstration index

Every feature has a GUI recording and a CLI recording using the invented demo data (`demo/`); no keys or real data appear. Each feature has its own video (one GUI, one CLI), so each link opens at the start of that feature's demonstration. Each video starts with a title card naming the feature ID.

Note on F01 manual entry. The F01 videos show both inputs: CSV import and adding a transaction by hand (GUI "Add transaction" button, CLI `add`). Manual entry was implemented on Nov 7, after the other feature videos were recorded. In those earlier videos the Transactions screen therefore has no "Add transaction" button and the CLI help has no `add` line. Nothing else in them is affected: the other features do not depend on how a transaction was entered.

ID	Feature	GUI demonstration	CLI demonstration	Where AI is shown
F01	Import transactions (CSV or manual entry)	GUI video	CLI video	none (deterministic)
F02	Categorization and correction (with undo)	GUI video	CLI video	Haiku fallback for an unknown merchant, call visible in `llm.log`
F03	Budgets and alerts	GUI video	CLI video	none; shows saved data after a restart (N02)
F04	Recurring payments	GUI video	CLI video	AI review (Haiku) and the template fallback
F05	Safe-to-spend and forecast	GUI video	CLI video	AI explanation in the Assistant; plan setup (N01) and `aicalls` (N03)
F06	Habit detective	GUI video	CLI video	AI explanation on request
F07	Financial health score	GUI video	CLI video	AI explanation on request; `aicalls`
F08	Affordability check	GUI video	CLI video	Agent loop, tools, grounding, trace
F09	Savings goals	GUI video	CLI video	none in planning; fix becomes a proposal
F10	What-if scenarios	GUI video	CLI video	AI parses plain words; typed form uses no AI
F11	Monthly review	GUI video	CLI video	AI writes the review; numbers-only fallback
F12	Chat with memory and trace	GUI video	CLI video	Agent chat, memory, trace
F13	Proposal approval queue	GUI video	CLI video	AI drafts the suggestions; approval is deterministic
F14	Report export	GUI video	CLI video	none
N01	Financial plan setup	in the F05 GUI video	in the F05 CLI video	none
N02	Saved data between sessions	in the F03 and F09 GUI videos (restart)	in the F03 and F09 CLI videos (restart)	none
N03	AI call log	n/a (CLI feature)	in the F05 and F07 CLI videos (`aicalls`)	shows model, tokens and time per call

Reproduce the demonstrations from a clean clone: `bash demo/load-demo.sh`, then start the GUI or the CLI on `~/.wealthsei-demo` as described in the README.