

PIZZA SALES SQL QUERIES

1. KPI's

1.1 Total Revenue:

```
SELECT SUM(total_price) AS Total_Revenue from pizza_sales_excel_file
```

Results		Messages	
Total_Revenue			
1	817860.05083847		

1.2 Average Order Value

```
SELECT (SUM(total_price) / COUNT(DISTINCT order_id)) AS Avg_order_Value FROM  
pizza_sales_excel_file
```

Results		Messages	
Avg_order_Value			
1	38.3072623343546		

1.3 Total Pizzas Sold

```
SELECT SUM(quantity) AS Total_Pizza_sold FROM pizza_sales_excel_file
```

Results		Messages	
Total_pizza_sold			
1	49574		

1.4 Total Orders

```
SELECT COUNT(DISTINCT order_id) AS Total_Orders FROM pizza_sales_excel_file
```

Results		Messages	
Total_Orders			
1	21350		

1.5 Average Pizzas Per Order

```
SELECT CAST(CAST(SUM(quantity) AS DECIMAL(10,2)) / CAST(COUNT(DISTINCT order_id) AS  
DECIMAL(10,2)) AS DECIMAL(10,2)) AS Avg_Pizza_Per_Order from pizza_sales_excel_file
```

Results		Messages	
Avg_Pizzas_per_order			
1	2.32		

2. Daily Trend for Total Orders

```
SELECT DATENAME(DW, order_date) AS order_day, COUNT(DISTINCT order_id) AS Total_orders
FROM pizza_sales_excel_file GROUP BY DATENAME(DW, order_date)
```

Output:

	order_day	total_orders
1	Saturday	3158
2	Wednesday	3024
3	Monday	2794
4	Sunday	2624
5	Friday	3538
6	Thursday	3239
7	Tuesday	2973

3. Monthly Trend for Orders

```
SELECT DATENAME(MONTH, order_date) AS Month_Name, COUNT(DISTINCT order_id) AS
Total_orders FROM pizza_sales_excel_file
GROUP BY DATENAME(MONTH, order_date)
```

Output

	Month_Name	Total_Orders
1	February	1685
2	June	1773
3	August	1841
4	April	1799
5	May	1853
6	December	1680
7	January	1845
8	September	1661
9	October	1646
10	July	1935
11	November	1792
12	March	1840

6. Total Pizzas Sold by Pizza Category

```
SELECT pizza_category, SUM(quantity) as Total_Quantity_Sold
FROM pizza_sales
WHERE MONTH(order_date) = 2
GROUP BY pizza_category
ORDER BY Total_Quantity_Sold DESC
```

Output

	Results	Messages
	pizza_category	Total_Quantity_Sold
1	Classic	14888
2	Supreme	11987
3	Veggie	11649
4	Chicken	11050

7. Top 5 Pizzas by Revenue

```
SELECT Top 5 pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Revenue DESC
```

	Results	Messages
	pizza_name	Total_Revenue
1	The Thai Chicken Pizza	43434.25
2	The Barbecue Chicken Pizza	42768
3	The California Chicken Pizza	41409.5
4	The Classic Deluxe Pizza	38180.5
5	The Spicy Italian Pizza	34831.25

8. Bottom 5 Pizzas by Revenue

```
SELECT Top 5 pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Revenue ASC
```

	pizza_name	Total_Revenue
1	The Brie Carre Pizza	11588.4998130798
2	The Green Garden Pizza	13955.75
3	The Spinach Supreme Pizza	15277.75
4	The Mediterranean Pizza	15360.5
5	The Spinach Pesto Pizza	15596

9. Top 5 Pizzas by Quantity

```
SELECT Top 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold DESC
```

Output

	pizza_name	Total_Pizza_Sold
1	The Classic Deluxe Pizza	2453
2	The Barbecue Chicken Pizza	2432
3	The Hawaiian Pizza	2422
4	The Pepperoni Pizza	2418
5	The Thai Chicken Pizza	2371

10. Bottom 5 Pizzas by Quantity

```
SELECT TOP 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold ASC
```

Output

	pizza_name	Total_Pizza_Sold
1	The Brie Carre Pizza	490
2	The Mediterranean Pizza	934
3	The Calabrese Pizza	937
4	The Spinach Supreme Pizza	950
5	The Soppressata Pizza	961

11. Top 5 Pizzas by Total Orders

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders DESC
```

	pizza_name	Total_Orders
1	The Classic Deluxe Pizza	2329
2	The Hawaiian Pizza	2280
3	The Pepperoni Pizza	2278
4	The Barbecue Chicken Pizza	2273
5	The Thai Chicken Pizza	2225

12. Bottom 5 Pizzas by Total Orders

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders ASC
```

	pizza_name	Total_Orders
1	The Brie Carre Pizza	480
2	The Mediterranean Pizza	912
3	The Spinach Supreme Pizza	918
4	The Calabrese Pizza	918
5	The Chicken Pesto Pizza	938

NOTE

If you want to apply the pizza_category or pizza_size filters to the above queries you can use WHERE clause. Follow some of below examples:

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
WHERE pizza_category = 'Classic'
GROUP BY pizza_name
ORDER BY Total_Orders ASC
```