

CME 252: Support Vector Machines

AJ Friend
ICME, Stanford University

Intro

Outline


Intro

Which Separator?

Maximum Margin Classifier

Support Vector Machines


- ▶ find a hyperplane to separate data points into two classes
- ▶ use hyperplane to classify new (unseen) points




Scenarios

- ▶ assume data falls into one of these categories:
 - ▶ strictly linearly separable
 - ▶ approximately (not strictly) linearly separable
 - ▶ approximately non-linearly separable (hyperplanes won't work)


Strictly Linearly Separable Data



Approximately Linearly Separable Data



Approximately Non-linearly Separable



Linearly Separable Problem

- ▶ data: $x_i \in \mathbf{R}^n$ with labels $y_i \in \{+1, -1\}$ for $i = 1, \dots, m$
- ▶ assume **strictly** linearly separable
- ▶ find hyperplane $\{x \mid a^T x = b\}$ that separates points by label

$$a^T x_i - b > 0 \text{ if } y_i = +1$$


$$a^T x_i - b < 0 \text{ if } y_i = -1$$

- ▶ **rescale** a, b so that

$$a^T x_i - b \geq +1 \text{ if } y_i = +1$$

$$a^T x_i - b \leq -1 \text{ if } y_i = -1$$

Linearly Separable Problem



Linearly Separable Problem

- ▶ for all i , rewrite constraints as

$$y_i (a^T x_i - b) \geq 1$$

- ▶ get **feasibility** problem

$$\begin{array}{ll} \text{minimize} & 0 \\ \text{subject to} & y_i (a^T x_i - b) \geq 1 \text{ for } i = 1, \dots, m \end{array}$$

with variables $a \in \mathbf{R}^n$, $b \in \mathbf{R}$

CVXPY for Separable Problem

```
a = Variable(n)
b = Variable()

obj = Minimize(0)
constr = [mul_elemwise(y, X*a - b) >= 1]
Problem(obj, constr).solve()
```

Which Separator?

Outline


Intro

Which Separator?

Maximum Margin Classifier


Which Separator?

Which Separator?




Which Separator?

Which Separator?




Which Separator?

Which Separator?



Which Separator?

Which Separator?



Which Separator?

Maximum Margin Classifier

Outline

Intro

Which Separator?


Maximum Margin Classifier

Maximum Margin Classifier

- ▶ infinitely many choices for separating hyperplane
- ▶ choose one which maximizes **width** of separating **slab**

$$\{x \mid -1 \leq a^T x - b \leq +1\}$$

- ▶ “maximum margin” or “robust linear” classifier



Maximum Margin Classifier

- ▶ width of separating slab

$$\{x \mid -1 \leq a^T x - b \leq +1\}$$

is $2/\|a\|_2$ (via linear algebra)

- ▶ suggests optimization problem

$$\begin{array}{ll} \text{maximize} & 2/\|a\|_2 \\ \text{subject to} & y_i (a^T x_i - b) \geq 1 \text{ for } i = 1, \dots, m \end{array}$$

- ▶ but not convex!

Maximum Margin Classifier

- reformulate:

$$\text{maximize } 2/\|a\|_2 \iff \text{minimize } \|a\|_2$$

gives

$$\begin{array}{ll} \text{minimize} & \|a\|_2 \\ \text{subject to} & y_i (a^T x_i - b) \geq 1 \text{ for } i = 1, \dots, m, \end{array}$$


the **maximum margin classifier** problem

Maximum Margin Classifier in CVXPY

```
a = Variable(n)
b = Variable()

obj = Minimize(norm(a))
constr = [mul_elemwise(y, X*a - b) >= 1]
Problem(obj, constr).solve()
```


Maximum Margin Classifier



Nonseparable linear classification

- ▶ relaxed feasibility problem
- ▶ l_1 penalty to minimize misclassification: pure LP
- ▶ tradeoff between classification and width of slab: SOCP

Hinge loss

- ▶ reformulate as hinge loss objective
- ▶ general loss function form. . . $l(Ax + b)$

logistic

- ▶ change loss function to get logistic loss
- ▶ other loss functions

regularization

- ▶ regularize to get sparse classifier. . .

nonlinear discrimination

- ▶ adding features
- ▶ polynomial discrimination any different?
- ▶ rbf kernel? radial basis function
- ▶ kernel methods and relationship with convex opt. . .

algorithms

- ▶ note that so far, we have said **nothing** about **how** to compute a supporting vector
- ▶ we have focused on modeling
- ▶ that's OK, we're focusing on modeling
- ▶ algorithms involve duality and optimality conditions

scikitlearn comparison

- ▶ make sure it matches up with python SVM formulation
- ▶ maybe even do a timing comparison. . .

data science perspective

- ▶ cleaning and centering data
- ▶ sparse predictors