Aiswarya Sanvin B
12-2 PM

1) what JS:

JS is the open source interpreted dynamic type programming language used to create dynamic web application.

*use of JS:

* To make web pages interactive
* To validate user input
* Single thread architecture
* API Access

2) Difference between var, let, const JS:

var	let	const
declare	declare	declare
redeclare	NO redeclared in same scope	NO redeclared
reassign	reassign	NO reassign

3) data types JS:

*Primitive datatype (String, Number, Boolean, Null undefined)

*Non primitive Datatype (array, object, array of object)

4) function in JS:

*A function is a block of code used to perform a particular task.

*Types:

* Function declaration
* Function expression
* Arrow function

5) Difference between == & === in JS:

*Both are comparison operators.

*== [Loose Equality]

* compares values
* Allows type conversion

*=== [Strict Equality]

* compares both value and data type
* does not allow automark type conversion

6) What is React.JS?

React.JS is a JS library used to build user interfaces.

*Use of React:

* To create dynamic web sites.
* To build single page application
* To develop fast application

7) Component in React?

A component is a reusable part of a React Application.

Types:

* Functional component (It is a JS function that returns JSX)
* Class component (It is component created using a JS class)

---

8) JSX in React:

* It is allow us to write HTML like code inside JS.
* JSX stands for JS XML

---

9) Difference between Props & State:

* Props & State are used to manage data in React
* Props:
  * Props means property
  * used to pass data from parent to child component.
  * Props are read only.
* State:

State stores component data.

State can be updated

updating state can change.

10) Real DOM Virtual DOM.

Real DOM	Virtual DOM
Actual web page structure	Light weight representation
update can be expensive	Helps optimize updates
Directly changes web page	React calculates necessary changes
can involve multiple updates.	updates only necessary parts.