

Name: Rishwan Batvin B

Batch: 12:00 - 2:00

Date: 03/10/2021

PART - A

Q1) What is variable?

Variable is the primary process holding a value or data's ~~edges~~ in the single name. Variables are process by or identified is keyword.

*var

*let

*const

*var:

var is keyword used to declare a variable.

*let:

let is keyword used to declare a variable.

*const:

const is a keyword used to declare a constant variable.

variable	declaration	redclaration	Reassign
var	✓	✓	✓
let	✓	✗	✓
const	✓	✗	✗

2) What are JS Data Types?

Data types is accept value for a programming process all value are data have a value. Based on the type process will change. Every data types have a free define types every data types equal and Boolean values. Data types & type.

* Primitive

* Non Primitive

* Primitive:

* String

* Number

* Boolean

* Undefined

Null

* String:

A String is a data type used to store text or characters in JS.

Identity (" ") Text, character

* Number:

A number is a data type used to store numeric values. 12 3 4 5 No "

* Boolean:

A Boolean is a data type that has only two values:

*undefined:

undefined is a data type that means a variable has been declared but no value has been assigned.

*null:

null is a data used to represent an empty or no value.

3) What is the difference between: == and ===

== (Loose Equality)

It compares only the value and can convert the data type.

$5 == '5'$ // true

=== (Strict Equality):

It compares both value and data type.

$5 === 5$ // true

4) Explain these operators with ex p l e:

* Arithmetic operators: (+, -, *, /)

Operators are symbols used to perform operations on value and variables in operators.

Example:

let a = 10;

* Assignment operators : =, +=, -=

Assignment operators are used to assign or update values in variables.

```
let a = 10;
```

```
a += 5;
```

```
console.log(a);
```

* Comparison operator:

Comparison operators are used to compare two values and return

```
let a = 10;
```

```
let b = 5;
```

```
console.log(a > b);
```

true.

* Logical:

Logical operators are used to combine two or more conditions.

```
let a a = 20;
```

```
let b = 15;
```

```
console.log(a > 5 && b < 10);
```

5) what is the difference between;

*Array:

An array stores multiple values in a single variable.

```
let fruit = ["apple", "Banana", "orange"];  
console.log(fruit[1]);
```

*Array object:

It stores multiple object inside an array

```
let students = [  
  { name: "Rishward", age: 20 },  
  { name: "Atrina", age: 18 }  
];
```

students();

*object:

```
let student = {  
  name: "gaf rosh",  
  age: 21  
};
```

student();

6) What is a function?

function is the block of reusable code. That performs some task. function always runs when called.

~~function~~ function greet () {

console.log ("Hello world")

}

greet();

* parameter :

parameter is also 1st listed variable inside a function. Different parameters are data storage for functions.

* argument :

an argument value parameter argument is input. parameter is used calling the function.

* Return :

Return sends a value back from the function.

function add (a, b) {

return a+b;

}

Part - B

7) EVEN OR ODD;

let number = 29;

if (number % 2 === 0) {

console.log('Even');

} else {

console.log('Odd');

}

8) FOR LOOP PRINT 1 TO 150

for (let i = 0; i <= 150; i++) {

if (i % 2 === 0) {

console.log(i);

}

}

9) Factorial

let number = 5;

let factorial = 1;

for (let i = 1; i <= number; i++) {

factorial = factorial * i;

}

console.log(factorial)

5! 5 × 4 × 3 × 2 × 1 = 120

10)

FIBONACCI

let a = 0;

let b = 1;

for (let i = 1; i <= 8; i++) {

console.log(a);

let c = a + b;

a = b;

b = c

}

PART-C

11)

Array

let numbers = [10, 15, 20, 25, 30, 35, 40];

for (let i = 0; i < numbers.length; i++) {

{

if (numbers[i] % 2 === 0) {

console.log(numbers[i]);

}

}

12)

Array Total

let marks = [80, 75, 90, 85, 70];

let total = 0;

for (let i = 0; i < marks.length; i++) {

total = total + marks[i];

}

console.log(total);

13) Object:

```
let student = {
```

```
  name: "Rishwan",
```

```
  age: 23;
```

```
  course: "FS
```

```
  mark: 95
```

```
};
```

```
console.log("Student Name:", student.name);
```

```
console.log("Course:", student.course);
```

```
console.log("Mark:", student.mark);
```

14) Array of Object:

```
let students = [
```

```
  { name: "Arun", mark: 80 },
```

```
  { name: "Kumar", mark: 45 },
```

```
  { name: "Priya", mark: 90 },
```

```
  { name: "Ram", mark: 35 },
```

```
];
```

```
for (let i = 0; i < students.length; i++) {
```

```
  if (students[i].mark >= 50) {
```

```
    console.log(students[i].name);
```

```
  }
```

```
}
```

15) Function - Largest Number

function findNumber(a,b) {

if (a > b) {

return a;

} else {

return b;

}

}

console.log(findNumber(20,30));

Output: 30

16) Largest of three numbers

function largest(a,b,c) {

if (a > b & a > c) {

return a;

if (b > a & b > c) {

return b;

}

if (c > a & c > b) {

return c;

} console.log(largest(20,30,40));

}

}