SHMS
QUICK USER GUIDE

Start the app. Find your role. Complete the everyday tasks.

1. Run it on Windows

From PowerShell, go to the project's `shms` folder, then run:

```
1.  py -3 -m venv .venv
2.  .\.venv\Scripts\python.exe -m pip install -r requirements.txt
3.  .\.venv\Scripts\python.exe manage.py migrate
4.  .\.venv\Scripts\python.exe manage.py createsuperuser
5.  .\.venv\Scripts\python.exe manage.py runserver
```

Open **http://127.0.0.1:8000/**. Keep the terminal open while using the app; press Ctrl+C to stop the server.

Database: SQLite is used when no database settings are configured. If your local .env specifies PostgreSQL, make sure that database is reachable before running migrations.

Optional demo accounts

After migrations, load sample records with `.\.venv\Scripts\python.exe manage.py shell -c "exec(open('demo-data.py', encoding='utf-8').read())"`. Demo password: **Demo@12345**. Emails are numbered, e.g. `demo.patient1@shms.test`. The seed does not create an admin. Use createsuperuser; SHMS assigns it the Admin role. Development only; demo prescriptions are placeholders.

2. Choose your role

After sign-in, use your dashboard and navigation links. Access is limited by role and, where applicable, by the user's own or assigned records.

Appointments, prescriptions & billing

Booking an appointment

- Choose the patient and doctor, then select an offered date/time and enter the visit reason.
- Availability depends on doctor schedules, leave, existing bookings, and the 60-day booking window. Slots are 30 minutes; active slots cannot be double-booked.
- If a slot is unavailable, choose another offered time. Confirm the appointment details before saving.

Appointment statuses

Status	Next step
Scheduled	Confirm or cancel
Confirmed	Complete after visit or cancel
Completed	Visit finished; no further status change
Cancelled	Cancelled; no further status change

Prescriptions

- Doctors create one prescription per appointment, with diagnosis, remarks, and medicine details.
- Check the patient and appointment before saving. Patients can view their own prescriptions.

Bills and payments

- Bills are created for completed appointments. The total is the charge plus tax.
- Authorized staff record payments (Cash, Card, UPI, or Online); SHMS does not contact a payment gateway.
- Download or print the bill/receipt from its detail page. Patients can see their own bills and receipts.

Payment status	Meaning
Pending	No payment recorded
Partial	Some amount recorded; balance remains
Paid	Bill settled

Clinical safety: This guide explains app navigation only; it is not medical advice. Confirm all real clinical information under your organization's policies.

Quick help

If you see…	Try this
Login failed	Check credentials and account access; ask an administrator or use password reset.
Permission denied	Confirm the correct account role. Ask an administrator if access should be granted.
Slot unavailable	Choose another offered date/time; check schedule and leave constraints.
Database error at startup	Check .env/database settings and confirm the configured database is running.
Missing tables	Run manage.py migrate, then restart the server.
Demo records absent	Run the demo seed after migrations on a development database.

Role permissions at a glance

Role	Main access
Admin	Manage accounts, patients, doctors, appointments, reports, audit, and billing.
Doctor	Own appointments, patient clinical summaries, schedules, prescriptions, and permitted billing.
Receptionist	Patient registration/lookup, appointment desk, check-in, and billing view.
Patient	Own profile, appointments, prescriptions, bills, and receipts.

Need help? Tell your administrator which screen you were using and the error message. Do not send passwords or unnecessary patient/medical details.

Safe use

- Use only your assigned account; log out when finished.
- Protect patient information and printed documents. Use HTTPS and a secured database in production.
- Demo accounts and the local development server are for testing—not production.

Project: Django 6.0.8 • Python 3.12+ • Local address: http://127.0.0.1:8000/