

THE GR GROUP

MS PROP JACK & GI SHUTTERING

MS PROP JACK

MS PROP JACK

High-strength adjustable jack made from MS steel. Used in slab support and shuttering work. Durable, corrosion-resistant and available in multiple configurations.

Outer x Inner	Weight	Inner Tube	Outer Tube
1.50 x 1.50 Mtr.	15.00 KG	48mm (2.9mm)	60mm (3.2mm)
2.00 x 2.00 Mtr.	18.20 KG	48mm (2.9mm)	60mm (3.2mm)
2.00 x 2.50 Mtr.	20.50 KG	48mm (2.9mm)	60mm (3.2mm)
2.00 x 3.00 Mtr.	22.15 KG	48mm (2.9mm)	60mm (3.2mm)
2.50 x 2.50 Mtr.	22.80 KG	48mm (2.9mm)	60mm (3.2mm)
2.50 x 3.00 Mtr.	22.50 KG	48mm (2.9mm)	60mm (3.2mm)

MS SHUTTERING PLATE & ACRO PLATE



MS SHUTTERING PLATE

Made from galvanized steel (GI), these plates offer reliable slab support. Lightweight, rust-resistant, and widely used in construction shuttering.

WELDED SHUTTERING PLATE			
SIZE IN FT.	~WEIGHT		
3.0 x 0.9	08.00 kg		
3.0 x 1.0	10.00 kg		
3.0 x 1.3	11.00 kg		
3.0 x 1.6	12.00 kg		

RIVETTED SHUTTERING			
SIZE IN FT.	~WEIGHT		
3.0 x 0.9	06.00 kg		
3.0 x 1.0	07.00 kg		
3.0 x 1.3	08.00 kg		
3.0 x 1.6	10.00 kg		
3.0 x 2.0	12.50 kg		



ACRO PLATE

Premium TATA steel plates used for shuttering edge alignment. Their rigidity helps ensure precise formwork and prevent leakage.

Size in MM	Weight
651250 x 200 mm	14.30 KG
1250 x 230 mm	15.25
1250 x 300	19.00 KG
1250 x 350	22.00 KG
1250 x 400	24.00 KG
1250 x 450	25.25 KG
1250 x 500	27.00 KG
1250 x 600	34.00 KG
1250 x 750	40.00 KG