

Q1

```
mysql> use sales_db;
Database changed
mysql> show tables;
+-----+
| Tables_in_sales_db |
+-----+
| customers           |
| orders              |
| salespeople         |
+-----+
3 rows in set (0.00 sec)

mysql> select * from customers;
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100    | 1001 |
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin | 300    | 1002 |
| 2006 | Clemens  | London | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome   | 100    | 1004 |
+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)

mysql> SELECT cnum,cname,snum from customers WHERE snum = 101;
Empty set (0.00 sec)

mysql> SELECT cnum,cname,snum from customers WHERE snum = 1001;
+-----+-----+-----+
| cnum | cname   | snum |
+-----+-----+-----+
| 2001 | Hoffman | 1001 |
| 2006 | Clemens | 1001 |
+-----+-----+-----+
2 rows in set (0.00 sec)

mysql> |
```

Q2

```
mysql> SELECT rating,cname from customers WHERE city = "San Jose";
+-----+-----+
| rating | cname |
+-----+-----+
|    200 | Liu   |
|    300 | Cisneros |
+-----+-----+
2 rows in set (0.00 sec)

mysql> |
```

Q3

```
mysql> SELECT DISTINCT snum FROM ORDERS;
+-----+
| snum |
+-----+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+-----+
5 rows in set (0.00 sec)
```

Q4

```
mysql> SELECT onum,amt,odate,cnum,snum FROM Orders WHERE amt > 1000;
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

Q5

```
mysql> SELECT sname,city FROM salespeople WHERE city = 'London' AND comm > 0.10;
+-----+-----+
| sname | city |
+-----+-----+
| Peel  | London |
| Motika | London |
+-----+-----+
2 rows in set (0.00 sec)
```

Q6

```
mysql> SELECT cname,city,rating from customers WHERE rating > 100 OR city = 'Rome';
+-----+-----+-----+
| cname | city | rating |
+-----+-----+-----+
| Giovanni | Rome | 200 |
| Liu | San Jose | 200 |
| Grass | Berlin | 300 |
| Cisneros | San Jose | 300 |
| Pereira | Rome | 100 |
+-----+-----+-----+
5 rows in set (0.01 sec)
```

Q7

```
mysql> Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
+-----+-----+-----+-----+-----+
| onum | amt | odate | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

Q8

```
mysql> Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
```

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3005	5160.45	1990-10-03	2003	1002
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.00 sec)
```

Q9

```
mysql> SELECT snum,sname,city,comm from salespeople WHERE comm BETWEEN .12 AND .14;
```

snum	sname	city	comm
1001	Peel	London	0.12
1002	Serres	San Jose	0.13

```
2 rows in set (0.01 sec)
```

Q10

```
mysql> select onum,amt,odate,cnum,snum from orders WHERE amt > 100;
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.00 sec)
```