
```
Date Name - Ritesh Anil Badhe
04/01/2025 Roll No. 115 std -SY Bsc(CS) Batch - F
Practical no
2 - 3D Graph Plotting
```

Q.1)Using python, generate 3D surface Plot for the functioni) a)  $f(x) = \sin(x^2 + y^2)$  in the interval [-6,6]. b)  $f(x) = \sin(x^2 + y^2)$  in the interval [0,10]. a)  $f(x) = \sin(x^2 + y^2)$  in the interval [-6,6].


# $sin(x^2+y^2)$



b)  $f(x) = \sin(x^2 + y^2)$  in the interval [0,10].

```
In [13]: from mpl_toolkits import mplot3d
import numpy as np from pylab
import* def f(x,y):
    return np.sin(x**2+y**2)
x=np.linspace(0,10,30) y=np.linspace(0,10,30)
X,Y=np.meshgrid(x,y)
Z=f(X,Y)
ax=axes(projection='3d')
ax.contour3D(X,Y,Z,50)
xlabel('x') ylabel('y')
title('sin(x^2+y^2)')
show()
```


## $sin(x^2+y^2)$



ii)  $z = \sin x + \cos y$  in -10 < x, y < 10

```
In [11]: from mpl_toolkits import mplot3d
import numpy as np from pylab
import* def f(x,y):
    return np.sin(x) + np.cos(y) x=np.linspace(-
10,10,30) y=np.linspace(-10,10,30)
X,Y=np.meshgrid(x,y)
Z=f(X,Y)
ax=axes(projection='3d')
ax.contour3D(X,Y,Z,50)
xlabel('x') ylabel('y')
title('sinx + cosy')
show()
```

#### sinx + cosy




iii)  $f(x) = \sin(x) - e^x + 3x^2 - \log 10(x)$  on the Interval  $[0,2\pi]$ .

```
In [17]:
    from mpl_toolkits import mplot3d
    import numpy as np from pylab
    import* def f(x,y):
        return np.sin(x)-e**x+3*x**2-log10(x)
        x=np.linspace(0,2*pi,30) y=np.linspace(0,2*pi,30)
        X,Y=np.meshgrid(x,y)
        Z=f(X,Y)
        ax=axes(projection='3d')
        ax.contour3D(X,Y,Z,50)
        xlabel('x') ylabel('y')
        title('sin(x)-e^x+3x^2-log10(x)')
        show()
```

C:\Users\Student\AppData\Local\Temp\ipykernel\_9852\4294359593.py:5: RuntimeWarnin
g: divide by zero encountered in log10 return np.sin(x)-e\*\*x+3\*x\*\*2-log10(x)


# $sin(x)-e^x+3x^2-log10(x)$



iv) f(x,y) = -x2 -y2 when  $-10 \le x, y \le 10$ .


```
In [19]: from mpl_toolkits import mplot3d
import numpy as np from pylab
import* def f(x,y):
    return -x**2-y**2 x=np.linspace(-10,10,30)
y=np.linspace(-10,10,30)
X,Y=np.meshgrid(x,y)
Z=f(X,Y)
ax=axes(projection='3d')
ax.contour3D(X,Y,Z,50)
xlabel('x') ylabel('y')
title('-x2-y2') show()
```

#### -x2-y2



v) z = x2 + y2 in -6 < x, y < 6 using surface plot.


## x2 + y2



#### vi) z = x2 + y2 in -5 < x, y < 5.

```
In [23]: from mpl_toolkits import mplot3d
    import numpy as np from pylab
    import* def f(x,y):
        return x**2+y**2 x=np.linspace(-5,5,30)
    y=np.linspace(-5,5,30)
    X,Y=np.meshgrid(x,y)
    Z=f(X,Y)
    ax=axes(projection='3d')
    ax.contour3D(X,Y,Z,50)
    xlabel('x') ylabel('y')
    title('x2 + y2 ')
    show()
```


## x2 + y2



vii) z = cos(|x|+|y|) in -1 < x,y < 1.

```
In [27]:
    from mpl_toolkits import mplot3d
    import numpy as np from pylab
    import* def f(x,y):
        return np.cos(abs(x)+abs(y))
    x=np.linspace(-1,1,30) y=np.linspace(-1,1,30)
    X,Y=np.meshgrid(x,y)
    Z=f(X,Y)
    ax=axes(projection='3d')
    ax.contour3D(X,Y,Z,50)
    xlabel('x') ylabel('y')
    title('cos(|x|+|y|)')
    show()
```


## cos(|x|+|y|)



viii) z = cos(x2 + y2 - 0.5) in the interval from -1 < x, y < 1.


```
In [35]: from mpl_toolkits import mplot3d
import numpy as np from pylab
import* def f(x,y):
          return np.cos(x**2+y**2-0.5) x=np.linspace(-
1,1,1000) y=np.linspace(-1,1,1000)
X,Y=np.meshgrid(x,y)
Z=f(X,Y)
ax=axes(projection='3d')
ax.contour3D(X,Y,Z,50)
xlabel('x') ylabel('y')
title('cos(x2 + y2 -0.5)')
show()
```

# cos(x2 + y2 - 0.5)




Q.2) Write a Python program to plot 2D graph of the function f(x) = e-x2 in [-5,5] with green dashed points line with upwardpointing triangle.

```
In [49]: from pylab import* import numpy as np
x=np.linspace(-5,5,100) y=np.exp(-
x**2) plot(x,y,"-.^g",label="$y=e^{-x^2}$") xlabel('x') ylabel('y')
title('y=e^{-x^2}') legend() show()
```



Q.3) Write a python program to plot 3D axes with labels as X-axis, Y-axis and Z-axis and also plot following point with given coordinates in the same graph: (70,-25,15) as a diamond in black color.


```
In [53]: from mpl_toolkits import mplot3d import
matplotlib.pyplot as plt import numpy as
np fig=plt.figure(figsize=(4,4))
ax=fig.add_subplot(111,projection='3d')
ax.scatter(70,-25,15,c='k',marker='d')
plt.show()
```



Q.4) Write a python program to plot the 3D line graph whose parametric equation is  $(\cos(2x), \sin(2x), x)$  for  $10 \le x \le 20$  (in redcolor), with title to the graph.

```
In [57]: from mpl_toolkits import mplot3d
    import numpy as np from pylab
    import* fig=plt.figure()
    ax=plt.axes(projection='3d')
    z=np.linspace(10,20,100)
    x=np.cos(2*z) y=np.sin(2*z)
    ax.plot3D(x,y,z,'red')
    ax.set_title('3D Line Plot')
    show()
```


#### 3D Line Plot



Q.5) Write a Python program to plot the 3D graph of the function  $f(x) = ex^2 + y^2$  for  $x, y \in [0, 2\pi]$  using wireframe.

```
In [61]: from mpl_toolkits import mplot3d
    import numpy as np from pylab
    import* def f(x,y):
        return np.exp(x**2+y**2)
    x=np.linspace(0,2*pi,30) y=np.linspace(0,2*pi,30)
    X,Y=np.meshgrid(x,y)
    Z=f(X,Y)
    ax=axes(projection='3d')
    ax.plot_wireframe(X,Y,Z,rstride=2,cstride=2)
    xlabel('x') ylabel('y')
    title('exp(x**2+y**2)') show()
```


## exp(x\*\*2+y\*\*2)



Q.6) Write a Python program to plot the 3D graph of the function  $f(x) = xe-x^2-y^2$  for  $x,y \in [0,2\pi]$  using

```
In [69]:
    from mpl_toolkits import mplot3d
    import numpy as np from pylab
    import* def f(x,y):
        return np.exp(x*e-x**2-y**2)
    x=np.linspace(0,2*pi,30) y=np.linspace(0,2*pi,30)
    X,Y=np.meshgrid(x,y)
    Z=f(X,Y)
    ax=axes(projection='3d')
    ax.plot_wireframe(X,Y,Z,rstride=2,cstride=2)
    xlabel('x') ylabel('y') title('exp(x*e-x**2-y**2)') show()
```

# exp(x\*e-x\*\*2-y\*\*2)



In [ ]: