

Rajalakshmi Engineering College

Name: Ritesh Sivakumar
Email: 240701427@rajalakshmi.edu.in
Roll no: 240701427
Phone: 9342061449
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 0_Arrays and Functions

Attempt : 1
Total Mark : 5
Marks Obtained : 5

Section 1 : Coding

1. Problem Statement

Tim is creating a program to track and analyze student attendance. The program requires two inputs: the total number of students (n) and the total number of class sessions (m). The task is to design and populate an attendance matrix, 'matrix', representing the attendance record of each student for each session.

The program's specific objective is to determine whether the last student on the list attended an even or odd number of classes. This functionality will aid teachers in quickly evaluating the attendance habits of individual students.

Input Format

The first line of input consists of a positive integer n, representing the number of students.

The second line consists of a positive integer m , representing the number of class sessions.

The next n lines consist of m space-separated positive integers representing the number of classes attended by the student.

Output Format

The output displays one of the following results:

If the last session is even the output prints "[LastSession] is even".

If the last session is odd the output prints "[LastSession] is odd".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 2

2

1 2

3 100

Output: 100 is even

Answer

```
#include<stdio.h>
int main()
{
    int n;
    scanf("%d",&n);
    int m;
    scanf("%d",&m);
    int matrix[n][m];
    for(int i=0;i<n;i++)
    {
        for(int j=0;j<m;j++)
        {
            scanf("%d",&matrix[i][j]);
        }
    }
}
```

```
int Lastsession=matrix[n-1][m-1];
if(Lastsession%2==0)
{
    printf("%d is even",Lastsession);
}else
{
    printf("%d is odd",Lastsession);
}
return 0;
}
```

Status : Correct

Marks : 1/1

2. Problem Statement

Saurabh is the manager of a growing tech company. He needs a program to record and analyze the monthly salaries of his employees. The program will take the number of employees and their respective salaries as input and then calculate the average salary, and find the highest and lowest salary among them.

Help Saurabh automate this task efficiently.

Input Format

The first line of input consists of an integer n , representing the number of employees.

The second line consists of n integers, where each integer represents the salary of an employee.

Output Format

The output prints n lines, where each line will display: "Employee i : "Salary

Where i is the employee number (starting from 1) and salary is the respective salary of that employee.

After that, print the average salary in the following format: "Average Salary: "average_salary

Where average_salary is the average salary of all employees, rounded to two decimal places.

Next, print the highest salary in the following format: "Highest Salary: "max_salary

Where max_salary is the highest salary among all employees.

Finally, print the lowest salary in the following format: "Lowest Salary: "min_salary

Where min_salary is the lowest salary among all employees.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

4000

3500

6000

2500

4500

Output: Employee 1: 4000

Employee 2: 3500

Employee 3: 6000

Employee 4: 2500

Employee 5: 4500

Average Salary: 4100.00

Highest Salary: 6000

Lowest Salary: 2500

Answer

```

// You are using GCC
#include<stdio.h>
int main()
{
    int n;
    float avg=0;
    scanf("%d",&n);
    int arr[n];
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
    }
    for(int j=0;j<n;j++)
    {
        printf("Employee %d: %d\n",j+1,arr[j]);
        avg+=arr[j];
    }
    printf("\n\nAverage Salary: %.2f\n",avg/n);
    int high,low;
    high=low=arr[0];
    for(int i=0;i<n;i++)
    {
        if(high<arr[i])
            high=arr[i];

        if(low>arr[i])
            low=arr[i];
    }
    printf("Highest Salary: %d\n",high);
    printf("Lowest Salary: %d",low);
}

```

Status : Correct

Marks : 1/1

3. Problem Statement

Alex, a budding programmer, is tasked with writing a menu-driven program to perform operations on an array of integers. The operations include finding the smallest number, the largest number, the sum of all numbers, and their average. The program must repeatedly display the menu until

Alex chooses to exit.

Write a program to ensure the specified tasks are implemented based on Alex's choices.

Input Format

The first line contains an integer n , representing the number of elements in the array.

The second line contains n space-separated integers representing the array elements.

The subsequent lines contain integers representing the menu choices:

Choice 1: Find and display the smallest number.

Choice 2: Find and display the largest number.

Choice 3: Calculate and display the sum of all numbers.

Choice 4: Calculate and display the average of all numbers as double.

Choice 5: Exit the program.

Output Format

For each valid menu choice, print the corresponding result:

For choice 1, print "The smallest number is: X", where X is the smallest number in the array.

For choice 2, print "The largest number is: X", where X is the largest number in the array.

For choice 3, print "The sum of the numbers is: X", where X is the sum of all numbers in the array.

For choice 4, print "The average of the numbers is: X. XX", where X.XX is the double value representing an average of all numbers in the array, rounded to two decimal places.

For choice 5, print "Exiting the program".

If an invalid choice is made, print "Invalid choice! Please enter a valid option (1-5)."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

10 20 30

1

5

Output: The smallest number is: 10

Exiting the program

Answer

```
// You are using GCC
```

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int n,b,sum=0;
```

```
    scanf("%d",&n);
```

```
    int a[n];
```

```
    for (int i=0;i<n;i++)
```

```
    {
```

```
        scanf("%d",&a[i]);
```

```
        sum+=a[i];
```

```
    }
```

```
    do
```

```
    {
```

```
        scanf("%d",&b);
```

```
    if(b==1)
```

```
    {
```

```
        int min;
```

```
        min=a[0];
```

```
        for(int i=0;i<n;i++)
```

```
        {
```

```
            if(min>a[i])
```

```
            min=a[i];
```

```

    }
    printf("the smallest number is: %d\n",min);
}
else if(b==2)
{
    int max;
    max=a[0];
    for (int i=0;i<n;i++)
    {
        if(max<a[i])
            max=a[i];
    }
    printf("the largest number is: %d\n",max);
}
else if(b==3)
{
    printf("The sum of the numbers is: %d\n",sum);
}
else if(b==4)
{
    printf("The average of the numbers is: %.2f\n",(float)sum/n);
}
else if(b==5)
{
    printf("Exiting the program\n");
}
else
    printf("Invalid choice! Please enter a valid option (1-5).\n");
}while(b!=5);
}

```

Status : Correct

Marks : 1/1

4. Problem Statement

Write a program that reads an integer 'n' and a square matrix of size 'n x n' from the user. The program should then set all the elements in the lower triangular part of the matrix (including the main diagonal) to zero using a function and display the resulting matrix.

Function Signature: void setZeros(int [][], int)

Input Format

The first line consists of an integer M representing the number of rows & columns.

The next M lines consist of M space-separated integers in each line representing the elements of the matrix.

Output Format

The output displays the matrix containing M space-separated elements in M lines where the lower triangular elements are replaced with zero.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
10 20 30
40 50 60
70 80 90

Output: 0 20 30
0 0 60
0 0 0

Answer

```
#include <stdio.h>

// You are using GCC
void setZeros(int arr[10][10], int n) {
    for(int i=0;i<n;i++)
    {
        for(int j=0;j<n;j++)
        {
            if(i==j || i>=j)
            {
                arr[i][j]=0;
            }
        }
    }
}
```

```

    }
    //Type your code here
}

int main() {
    int arr1[10][10];
    int n;

    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &arr1[i][j]);
        }
    }

    setZeros(arr1, n);

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            printf("%d ", arr1[i][j]);
        }
        printf("\n");
    }

    return 0;
}

```

Status : Correct

Marks : 1/1

5. Problem Statement

Write a program that will read a Matrix (two-dimensional arrays) and print the sum of all elements of each row by passing the matrix to a function.

Function Signature: void calculateRowSum(int [][], int, int)

Input Format

The first line consists of an integer M representing the number of rows.

The second line consists of an integer N representing the number of columns.

The next M lines consist of N space-separated integers in each line representing the elements of the matrix.

Output Format

The output displays the sum of all elements of each row separated by a space.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

3

1 2 3

4 5 6

7 8 9

Output: 6 15 24

Answer

```
#include <stdio.h>
```

```
// You are using GCC
```

```
void calculateRowSum(int matrix[20][20], int rows, int cols) {
```

```
    int sum=0;
```

```
    for(int i=0;i<rows;i++)
```

```
    {
```

```
        for(int j=0;j<cols;j++)
```

```
        {
```

```
            sum+=matrix[i][j];
```

```
            if(j==(cols-1))
```

```
            {
```

```
                printf("%d ",sum);
```

```
                sum=0;
```

```
            }
```

```
        }
```

```
    }
```

```
    //Type your code here
```

```
}
```

```
int main() {
```

```
int matrix[20][20];  
int r, c;
```

```
scanf("%d", &r);  
scanf("%d", &c);
```

```
for (int i = 0; i < r; i++) {  
    for (int j = 0; j < c; j++) {  
        scanf("%d", &matrix[i][j]);  
    }  
}
```

```
calculateRowSum(matrix, r, c);  
return 0;  
}
```

Status : Correct

Marks : 1/1