Customer Behavior Analysis

Loading the Data set

```
from google.colab import drive
drive.mount('/content/drive')
```

```
Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True).
```

```
import pandas as pd

df = pd.read_csv('add your drive details')

df.head()
```

	Customer ID	Age	Gender	Item Purchased	Category	Purchase Amount (USD)	Location	Size	Color	Season	Review Rating	Subscription Status	Shipping Type	Discount Applied	Promo Code Used	Previous Purchases	Payment Method	Fre Pur
0	1	55	Male	Blouse	Clothing	53	Kentucky	L	Gray	Winter	3.1	Yes	Express	Yes	Yes	14	Venmo	F
1	2	19	Male	Sweater	Clothing	64	Maine	L	Maroon	Winter	3.1	Yes	Express	Yes	Yes	2	Cash	F
2	3	50	Male	Jeans	Clothing	73	Massachusetts	S	Maroon	Spring	3.1	Yes	Free Shipping	Yes	Yes	23	Credit Card	
3	4	21	Male	Sandals	Footwear	90	Rhode Island	M	Maroon	Spring	3.5	Yes	Next Day Air	Yes	Yes	49	PayPal	
4	5	45	Male	Blouse	Clothing	49	Oregon	M	Turquoise	Spring	2.7	Yes	Free Shipping	Yes	Yes	31	PayPal	

Next steps: Generate code with df New interactive sheet

Exploratory Data Analysis (EDA)

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 3900 entries, 0 to 3899
Data columns (total 18 columns):
 #   Column                  Non-Null Count  Dtype
---  ------                  --------------  -----
 0   Customer ID             3900 non-null   int64
 1   Age                     3900 non-null   int64
 2   Gender                  3900 non-null   object
 3   Item Purchased          3900 non-null   object
 4   Category                3900 non-null   object
 5   Purchase Amount (USD)   3900 non-null   int64
 6   Location                3900 non-null   object
 7   Size                    3900 non-null   object
 8   Color                   3900 non-null   object
 9   Season                  3900 non-null   object
 10  Review Rating           3863 non-null   float64
```

```
 11  Subscription Status     3900 non-null   object
 12  Shipping Type           3900 non-null   object
 13  Discount Applied        3900 non-null   object
 14  Promo Code Used         3900 non-null   object
 15  Previous Purchases      3900 non-null   int64
 16  Payment Method          3900 non-null   object
 17  Frequency of Purchases  3900 non-null   object
dtypes: float64(1), int64(4), object(13)
memory usage: 548.6+ KB
```

Summary statistics using .describe()

```
df.describe(include='all')
```

	Customer ID	Age	Gender	Item Purchased	Category	Purchase Amount (USD)	Location	Size	Color	Season	Review Rating	Subscription Status	Shipping Type	Discount Applied	Promo Code Used	Previou Purchase
count	3900.000000	3900.000000	3900	3900	3900	3900.000000	3900	3900	3900	3900	3863.000000	3900	3900	3900	3900	3900.00000
unique	NaN	NaN	2	25	4	NaN	50	4	25	4	NaN	2	6	2	2	Nal
top	NaN	NaN	Male	Blouse	Clothing	NaN	Montana	M	Olive	Spring	NaN	No	Free Shipping	No	No	Nal
freq	NaN	NaN	2652	171	1737	NaN	96	1755	177	999	NaN	2847	675	2223	2223	Nal
mean	1950.500000	44.068462	NaN	NaN	NaN	59.764359	NaN	NaN	NaN	NaN	3.750065	NaN	NaN	NaN	NaN	25.35153
std	1125.977353	15.207589	NaN	NaN	NaN	23.685392	NaN	NaN	NaN	NaN	0.716983	NaN	NaN	NaN	NaN	14.44712
min	1.000000	18.000000	NaN	NaN	NaN	20.000000	NaN	NaN	NaN	NaN	2.500000	NaN	NaN	NaN	NaN	1.00000
25%	975.750000	31.000000	NaN	NaN	NaN	39.000000	NaN	NaN	NaN	NaN	3.100000	NaN	NaN	NaN	NaN	13.00000
50%	1950.500000	44.000000	NaN	NaN	NaN	60.000000	NaN	NaN	NaN	NaN	3.800000	NaN	NaN	NaN	NaN	25.00000
75%	2925.250000	57.000000	NaN	NaN	NaN	81.000000	NaN	NaN	NaN	NaN	4.400000	NaN	NaN	NaN	NaN	38.00000
max	3900.000000	70.000000	NaN	NaN	NaN	100.000000	NaN	NaN	NaN	NaN	5.000000	NaN	NaN	NaN	NaN	50.00000

Checking if missing data or null values are present in the dataset

```
df.isnull().sum()
```

	0
Customer ID	0
Age	0
Gender	0
Item Purchased	0
Category	0
Purchase Amount (USD)	0
Location	0
Size	0
Color	0
Season	0
Review Rating	37
Subscription Status	0
Shipping Type	0
Discount Applied	0
Promo Code Used	0
Previous Purchases	0
Payment Method	0
Frequency of Purchases	0

dtype: int64

Replacing the null values with the median of the product catogory that they belong to, because to maintain relevence among the products.

```
df['Review Rating'] = df.groupby('Category')['Review Rating'].transform(lambda x: x.fillna(x.median()))
```

```
df.isnull().sum()
```

	0
Customer ID	0
Age	0
Gender	0
Item Purchased	0
Category	0
Purchase Amount (USD)	0
Location	0
Size	0
Color	0
Season	0
Review Rating	0
Subscription Status	0
Shipping Type	0
Discount Applied	0
Promo Code Used	0
Previous Purchases	0
Payment Method	0
Frequency of Purchases	0

dtype: int64

Snake Casing the column names to be easy to use them

```
df.columns = df.columns.str.lower()
df.columns = df.columns.str.replace(' ','_')
df = df.rename(columns={'purchase_amount_(usd)':'purchase_amount'})
```

```
df.columns
```

```
Index(['customer_id', 'age', 'gender', 'item_purchased', 'category',
       'purchase_amount', 'location', 'size', 'color', 'season',
       'review_rating', 'subscription_status', 'shipping_type',
       'discount_applied', 'promo_code_used', 'previous_purchases',
       'payment_method', 'frequency_of_purchases'],
      dtype='object')
```

Creating a new column age_group to catogories age

```
labels = ['Young Adult', 'Adult', 'Middle-aged', 'Senior']
df['age_group'] = pd.qcut(df['age'], q=4, labels = labels)
```

```
df[['age','age_group']].head(10)
```

	age	age_group
0	55	Middle-aged
1	19	Young Adult
2	50	Middle-aged
3	21	Young Adult
4	45	Middle-aged
5	46	Middle-aged
6	63	Senior
7	27	Young Adult
8	26	Young Adult
9	57	Middle-aged

Create new column purchase_frequency_days

```
frequency_mapping = {
    'Fortnightly': 14,
    'Weekly': 7,
    'Monthly': 30,
    'Quarterly': 90,
    'Bi-Weekly': 14,
    'Annually': 365,
    'Every 3 Months': 90
}

df['purchase_frequency_days'] = df['frequency_of_purchases'].map(frequency_mapping)
```

```
df[['purchase_frequency_days','frequency_of_purchases']].head(10)
```

	purchase_frequency_days	frequency_of_purchases
1	14	Fortnightly
2	7	Weekly
4	365	Annually
6	90	Quarterly
8	365	Annually

```
df[['discount_applied','promo_code_used']].head(10)
```

	discount_applied	promo_code_used
0	Yes	Yes
1	Yes	Yes
2	Yes	Yes
3	Yes	Yes
4	Yes	Yes
5	Yes	Yes
6	Yes	Yes
7	Yes	Yes
8	Yes	Yes
9	Yes	Yes

```
(df['discount_applied'] == df['promo_code_used']).all()
```

```
np.True_
```

Dropping promo code used column

```
df = df.drop('promo_code_used', axis=1)
```

```
df.columns
```

```
Index(['customer_id', 'age', 'gender', 'item_purchased', 'category',
       'purchase_amount', 'location', 'size', 'color', 'season',
       'review_rating', 'subscription_status', 'shipping_type',
       'discount_applied', 'previous_purchases', 'payment_method',
       'frequency_of_purchases', 'age_group', 'purchase_frequency_days'],
      dtype='object')
```