

DATE:5/9/24

EXP NO 8

NMAP LIVE HOST

DISCOVERY AIM:

To use NMAP to discover live hosts using

- ARP scan
- ICMP scan
- TCP/UDP
- Reverse DNS-lookup in the tryhackme platform.

TASK 2:SUBNETWORKS

Answer the questions below.

Send a packet with the following:

Send Packet

From:
computer

To:
computer

Packet Type:
arp_request

Data:
computer

Send Packet

- From computer 1
- To computer 2 (to indicate it is broadcast)
- Packet Type: "ARP Request"
- Data: computer6 (because we are asking for computer6 MAC address using ARP Request)

How many devices can see the ARP Request?

4

✓ Correct Answer

🔍 Hint

Did computer6 receive the ARP Request? (Y/N)

N

✓ Correct Answer

Send a packet with the following:

Send Packet

From:
computer

To:
computer

Packet Type:
arp_request

Data:
computer6

Send Packet

- From computer 4
- To computer 4 (to indicate it is broadcast)
- Packet Type: "ARP Request"
- Data: computer6 (because we are asking for computer6 MAC address using ARP Request)

How many devices can see the ARP Request?

4

✓ Correct Answer

🔍 Hint

Did computer6 reply to the ARP Request? (Y/N)

Y

✓ Correct Answer

TASK 3:ENUMERATING TARGETS

Task 3 Enumerating Targets

We mentioned the different techniques we can use for scanning in Task 1. Before we explain each in detail and put it into use against a live target, we need to specify the targets we want to scan. Generally speaking, you can provide a list, a range, or a subnet. Examples of target specification are:

- list: `MACHINE_IP -s scanme.nmap.org -o example.com` will scan 3 IP addresses.
- range: `10.11.12.15-20` will scan 6 IP addresses: `10.11.12.15`, `10.11.12.16`, ..., and `10.11.12.20`.
- subnet: `MACHINE_IP/30` will scan 4 IP addresses.

You can also provide a file as input for your list of targets, `nmap -iL list_of_hosts.txt`.

If you want to check the list of hosts that Nmap will scan, you can use `nmap -sT TARGETS`. This option will give you a detailed list of the hosts that Nmap will scan without scanning them; however, Nmap will attempt a reverse-DNS resolution on all the targets to obtain their names. Names might reveal various information to the pentester. (If you don't want Nmap to the DNS server, you can add `-n`.)

Launch the AttackBox using the Start AttackBox button, open the terminal when the AttackBox is ready, and use Nmap to answer the following.

Answer the questions below

What is the first IP address Nmap would scan if you provided `10.10.12.13/29` as your target?

✓ Correct Answer

🔍 Hint

How many IP addresses will Nmap scan if you provide the following range `10.10.6-255.101-125`?

✓ Correct Answer


🔍 Hint

TASK 4:DISCOVERING LIVE HOSTS

Task 4 Discovering Live Hosts

Let's revisit the TCP/IP layers shown in the figure next. We will leverage the protocols to discover the live hosts. Starting from bottom to top, we can use:

- ARP from Link Layer
- ICMP from Network Layer
- TCP from Transport Layer
- UDP from Transport Layer



Before we discuss how scanners can use each in detail, we will briefly review these four protocols. ARP has one purpose: sending a frame to the broadcast address on the network segment and asking the computer with a specific IP address to respond by providing its MAC (hardware) address.

ICMP has many types. ICMP ping uses Type 8 (Echo) and Type 0 (Echo Reply).

If you want to ping a system on the same subnet, an ARP query should precede the ICMP Echo.

Although TCP and UDP are transport layers, for network scanning purposes, a scanner can send a specially-crafted packet to common TCP or UDP ports to check whether the target will respond. This method is efficient, especially when ICMP Echo is blocked.

If you have closed the network simulator, click on the "View Site" button in Task 2 to display it again.

Answer the questions below

Send a packet with the following:

- From computer1
- To computer3
- Packet Type: "Ping Request"

What is the type of packet that computer1 sent before the ping?

✓ Correct Answer

What is the type of packet that computer1 received before being able to send the ping?

✓ Correct Answer

How many computers responded to the ping request?

✓ Correct Answer

Send a packet with the following:

- From computer2
- To computer5
- Packet Type: "Ping Request"

What is the name of the first device that responded to the first ARP Request?

✓ Correct Answer

What is the name of the first device that responded to the second ARP Request?

✓ Correct Answer

Send another Ping Request. Did it require new ARP Requests? (Y/N)

✓ Correct Answer

TASK 5:NMAP DISCOVERY USING ARP

Answer the questions below

We will be sending broadcast ARP Requests packets with the following options:

- From computer1
- To computer1 (to indicate it is broadcast)
- Packet Type: "ARP Request"
- Data: try all the possible eight devices (other than computer1) in the network: computer2, computer3, computer4, computer5, computer6, switch1, switch2, and router.

How many devices are you able to discover using ARP requests?

✓ Correct Answer

TASK6:NMAP DISCOVERY USING ICMP NMAP

Answer the questions below

What is the option required to tell Nmap to use ICMP Timestamp to discover live hosts?

✓ Correct Answer

What is the option required to tell Nmap to use ICMP Address Mask to discover live hosts?

✓ Correct Answer

What is the option required to tell Nmap to use ICMP Echo to discover live hosts?

✓ Correct Answer

TASK7 NMAP HOST DISCOVERY USING TCP AND UDP

Answer the questions below

Which TCP ping scan does not require a privileged account?

✓ Correct Answer

Which TCP ping scan requires a privileged account?

✓ Correct Answer

What option do you need to add to Nmap to run a TCP SYN ping scan on the telnet port?

✓ Correct Answer

🔍 Hint

TASK 8:USING REVERSE -DNS LOOKUP

Task 8 Using Reverse-DNS Lookup

Nmap's default behaviour is to use reverse-DNS online hosts. Because the hostnames can reveal a lot, this can be a helpful step. However, if you don't want to send such DNS queries, you use `-n` to skip this step.

By default, Nmap will look up online hosts; however, you can use the option `-R` to query the DNS server even for offline hosts. If you want to use a specific DNS server, you can add the `-dns-servers DNS_SERVER` option.

Answer the questions below

We want Nmap to issue a reverse DNS lookup for all the possible hosts on a subnet, hoping to get some insights from the names. What option should we add?

✓ Correct Answer

RESULT: Nmap to discover live host using ARP Scan ,ICMP Scan and TCP/UDP ping scan in tryhackme platform has been studied.