PROMPTSHIELD: AI-BASED PROMPT INJECTION AND RECOVERY SYSTEM

A PROJECT REPORT

Submitted by

RITHIKA BASKAR 2116231901042

KALIYARASI M 2116231901503

in partial fulfillment for the award of the degree

of

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING (CYBER SECURITY)





RAJALAKSHMI ENGINEERING COLLEGE

ANNA UNIVERSITY: CHENNAI 600 025

OCTOBER 2026

RAJALAKSHMI ENGINEERING COLLEGE

CHENNAI

BONAFIDE CERTIFICATE

Certified that this Project report titled **"PROMPT SHIELD: AI-BASED PROMPT INJECTION AND RECOVERY SYSTEM"** is the Bonafide work of **"RITHIKA BASKAR (2116231901042), KALAIYARASI M (2116231901503)"** who carried out the work under my supervision. Certified further that to the best of my knowledge the work reported herein does not form part of any other project report or dissertation on the basis of which a degree or award was conferred on an earlier occasion on this or any other candidate



SIGNATURE

Dr. P. Tamilselvi, Ph.D.,

HEAD OF THE DEPARTMENT

PROFESSOR

Department of Computer Science and Engineering (Cyber Security)

Rajalakshmi Engineering College

Chennai – 602 105



SIGNATURE

Mrs. R. Divya,

SUPERVISOR

ASSISTANT PROFESSOR

Department of Computer Science and Engineering (Cyber Security)

Rajalakshmi Engineering College

Chennai – 602 105

Submitted to Project Viva-Voce Examination held on 7/10/2026



Internal Examiner



External Examiner

ABSTRACT

Large Language Models (LLMs) such as ChatGPT, Gemini, and Llama have become widely used in various applications, but they are vulnerable to prompt injection attacks, where malicious prompts manipulate the model to ignore system instructions, reveal sensitive information, or generate unintended responses. Existing solutions primarily focus on detecting and blocking these attacks, which can also prevent legitimate user requests from being processed.

To address this limitation, this project proposes Prompt Shield: AI-Based Prompt Injection and Recovery System, a secure framework that not only detects prompt injection attacks but also recovers safe user prompts. The system uses DeBERTa-v3 to detect malicious prompts, Regular Expressions (Regex) to sanitize harmful instructions, FLAN-T5 to repair the prompt while preserving its original meaning, and Sentence-BERT (SBERT) to verify semantic similarity between the original and repaired prompts.

A rule-based risk scoring mechanism further classifies the severity of detected attacks before forwarding the sanitized prompt to the LLM. By combining detection, sanitization, repair, and intent verification, the proposed system enhances the security, reliability, and usability of LLM-based applications while ensuring that genuine user intent is preserved.

ACKNOWLEDGEMENT

First, we thank the almighty God for the successful completion of the project. Our sincere thanks to our Chairman **Mr. S. Meganathan B.E., F.I.E.,** for his sincere endeavor in educating us in his premier institution. We would like to express our deep gratitude to our beloved Chairperson **Dr. Thangam Meganathan Ph.D.,** for her enthusiastic motivation which inspired us a lot in completing this project and Vice Chairman **Mr. Abhay Shankar Meganathan B.E., M.S.,** for providing us with the requisite infrastructure.

We also express our sincere gratitude to our college Principal **Dr. S. N. Murugesan M.E., Ph.D.,** and **Dr. P. Tamilselvi Ph.D., Professor and Head, Department of Computer Science and Engineering (Cyber Security)** and our project guide **Mrs. R. Divya**., **Assistant Professor** for encouragement and guiding us throughout the project. We would like to thank our project coordinator **Mr. Benedict J.N., M.E., Assistant Professor (SG),** for his encouragement and guidance towards successful completion of this project and to our parents, friends, all faculty members and supporting staffs for their direct and indirect involvement in successful completion of the project for their encouragement and support.

RITHIKA BASKAR (2116231901042)

KALAIYARASI M (2116231901503)

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	iii
	LIST OF TABLES	vii
	LIST OF FIGURES	viii
1	**INTRODUCTION**	**1**
	1.1 BACKGROUND	1
	1.2 PROBLEM STATEMENT	2
	1.3 OBJECTIVES	2
	1.4 SCOPE	3
	1.5 SECURITY REQUIREMENTS	4
	1.6 SDG ALIGNMENT	5
2	**LITERATURE REVIEW**	**6**
	2.1 EXISTING SYSTEM WITH SECURITY APPROACHES	7
	2.2 RESEARCH GAPS	8
	2.3 PROPOSED SYSTEM	10
	2.3.1 OVERVIEW	11
	2.3.2 OBJECTIVES	12
	2.3.3 ADVANTAGES	12
3	**SYSTEM DESIGN**	**13**
	3.1 SYSTEM ARCHITECTURE	13
	3.2 MODULE DESIGN	15
	3.3 DATA FLOW DIAGRAM	16
	3.4 THREAT MODEL AND ATTACK SURFACE	17
	3.5 SECURITY CONTROLS	18
4	**SYSTEM DESCRIPTION**	**19**
	4.1 DATA COLLECTION	19
	4.2 DATA PREPROCESSING	19

	4.2.1 METHODOLOGY	23
	4.2.2 RESULTS AND DISCUSSION	24
5	**CONCLUSION**	29
6	**REFERENCES**	30

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
1.1	SDG MAPPING	5
2.1	EXISTING SYSTEMS	7
2.2	RESEARCH GAPS	9

LIST OF FIGURES

FIGURE	TITLE	PAGE NO.
3.1	ARICHITECTURE DIAGRAM	14
3.2	DATAFLOW DIAGRAM	16
4.1	PROMPTSHIELD PROMPT INPUT INTERFACE	25
4.2	DETECTED MALICIOUS CONTENT AND ATTACK CATEGORIES	25
4.3	PROMPT SANITIZATION AND INTENT VERIFICATION	26
4.4	CLASSIFICATION REPORT RISK ASSESSMENT AND ADAPTIVE DECISION	27

CHAPTER 1
INTRODUCTION

1.1 BACKGROUND

Large Language Models have become an important component of modern artificial intelligence applications. Models such as ChatGPT, Gemini, and Llama are capable of understanding natural language instructions and generating responses for applications including chatbots, coding assistants, information retrieval, customer support, and automated decision-support systems.

However, the increasing use of LLMs introduces new security challenges. One important threat is prompt injection, where an attacker crafts a malicious input intended to influence the behaviour of an LLM. Such an input may attempt to override system instructions, manipulate the model into following unintended commands, expose sensitive information, or generate responses outside the intended application policy.

A major limitation of conventional prompt-injection protection mechanisms is that they primarily concentrate on identifying and blocking suspicious inputs. Although blocking can prevent malicious prompts from reaching the LLM, it may also reject legitimate prompts that contain words or patterns that resemble malicious instructions.

The proposed Prompt Shield system addresses this limitation by introducing a prompt recovery approach. Instead of only rejecting a suspicious prompt, the system analyses the input, identifies potentially malicious instructions, sanitizes harmful content, and attempts to reconstruct a safe version of the prompt.

The proposed system uses DeBERTa-v3 for malicious-prompt detection, Regex for sanitization, FLAN-T5 for prompt repair, and SBERT for semantic similarity verification. A rule-based risk-scoring mechanism is used to determine the severity of the detected prompt before the final prompt is forwarded to the LLM.

1.2 PROBLEM STATEMENT

The increasing adoption of LLM-based applications has created a need for effective protection against prompt injection attacks. Malicious prompts can attempt to manipulate the model's instruction-following behaviour and may result in unintended responses or disclosure of information.

Traditional approaches generally treat detected prompt injections as inputs that should be blocked. However, such approaches may result in legitimate user requests being rejected when they contain suspicious words, instructions, or patterns.

Therefore, there is a need for a security framework that can:

- Detect malicious prompt injections.
- Identify potentially harmful instructions.
- Sanitize malicious content.
- Recover a safe version of the user's prompt.
- Preserve the original user intent.
- Verify whether the repaired prompt retains the meaning of the original.
- Assess the severity of the detected attack.
- Forward only the verified safe prompt to the LLM.

1.3 OBJECTIVES

The major objectives of Prompt Shield are:

- To identify malicious prompt injection attempts in user inputs.
- To develop a DeBERTa-v3 based prompt classification mechanism.
- To identify and remove harmful instruction patterns using Regular Expressions.
- To repair sanitized prompts using FLAN-T5.
- To compare the original and repaired prompts using SBERT.
- To calculate a rule-based risk score for detected prompt injections.
- To classify prompt injection severity based on the calculated risk.
- To prevent unsafe prompts from being directly forwarded to the LLM.
- To provide a secure prompt-processing pipeline for LLM-based applications.

1.4 SCOPE

The scope of Prompt Shield includes:

- **Prompt Injection Detection**

  The system analyses incoming user prompts and determines whether they contain potentially malicious prompt-injection behaviour.

- **Prompt Sanitization**

  Potentially harmful instructions identified in the prompt are processed using predefined Regular Expression rules.

- **Prompt Recovery**

  Instead of simply rejecting a suspicious prompt, the system attempts to reconstruct a safe version using FLAN-T5.

- **Semantic Verification**

  SBERT is used to compare the original prompt with the repaired prompt and determine whether the intended meaning has been retained.

- **Risk Assessment**

  A rule-based scoring mechanism evaluates the detected prompt and determines the severity of the potential attack.

- **Secure LLM Interaction**

  Only a sanitized and verified prompt is forwarded to the downstream LLM.

- **Legitimate Intent Preservation**

  The system attempts to maintain the user's original request while eliminating malicious instructions.

1.5 SECURITY REQUIREMENTS

The proposed architecture should satisfy the following security requirements:

1. Input Validation

All incoming prompts should be validated before being passed to the LLM.

2. Prompt Integrity

The original and processed versions of the prompt should be maintained securely to prevent unauthorized modification.

3. Malicious Prompt Detection

The system should identify prompt-injection patterns using the trained detection model.

4. Secure Sanitization

Harmful instructions identified during preprocessing should be removed or neutralized.

5. Intent Preservation

Prompt repair should not significantly change the legitimate meaning of the original request.

6. Semantic Verification

The repaired prompt should be compared with the original prompt before being forwarded to the LLM.

7. Risk-Based Processing

Prompts should be assigned an appropriate risk level based on detected characteristics.

8. Secure LLM Communication

Only the final verified prompt should be sent to the LLM.

9. Logging and Monitoring

Relevant detection, sanitization, repair, and verification events should be recorded for security analysis.

10. Availability

The security pipeline should process legitimate requests without unnecessarily preventing access to the LLM.

1.6 SDG ALIGNMENT

TABLE 1.1 SDG MAPPING

S.No	SDG No. & Goal	Relevant Target	Project Contribution
1	**SDG 9 – Industry, Innovation and Infrastructure**	Target 9.1 – Develop reliable, sustainable and resilient infrastructure	Prompt Shield improves the security and reliability of AI-based digital infrastructure by protecting LLM applications against prompt injection attacks.
2	**SDG 16 – Peace, Justice and Strong Institutions**	Target 16.6 – Develop effective, accountable and transparent institutions	The system supports secure and trustworthy AI operations through automated prompt analysis, risk assessment, sanitization, and verification.

CHAPTER 2

LITERATURE REVIEW

2.1 EXISTING SYSTEM WITH SECURITY APROACHES

The literature review focus specifically on:

1. Prompt injection attacks.
2. LLM security.
3. Prompt classification.
4. NLP-based malicious-input detection.
5. LLM guardrails.
6. Prompt sanitization.
7. Prompt rewriting.
8. Semantic similarity.
9. LLM security frameworks.
10. AI-based prompt injection detection.

TABLE 2.1 EXISTING SYSTEMS

S.No	Research Paper	Tools and Techniques Used	Application	Advantages and Disadvantages	Dataset Used	Inference
1	Paper on prompt injection detection	ML/NLP classification	LLM security	Improved malicious prompt detection; may require training data	Prompt injection dataset	Supports automated detection
2	Paper on LLM guardrails	Input filtering and policy rules	LLM protection	Simple filtering; may block legitimate requests	Prompt dataset	Supports input filtering
3	Paper on prompt injection defense	Detection and sanitization	LLM applications	Reduces malicious instructions; rule dependency	Security prompts	Supports sanitization
4	Paper on LLM security	NLP/LLM analysis	AI security	Provides security analysis; computational overhead	Security benchmark	Supports LLM protection
5	Paper on semantic prompt analysis	Transformer/SBERT	Intent preservation	Measures semantic similarity	Text datasets	Supports prompt verification

2.2 RESEARCH GAPS

The literature indicates that prompt-injection protection mechanisms commonly concentrate on detection, filtering, blocking, or restricting malicious prompts.

However, the following gaps can be identified for the proposed approach:

1. Limited Prompt Recovery

Many security approaches focus on identifying malicious prompts rather than recovering a safe version of a legitimate user request.

2. Excessive Blocking

Strict filtering may reject legitimate requests containing suspicious words or instruction patterns.

3. Limited Intent Preservation

A sanitized prompt may lose part of the original user intent if harmful and legitimate instructions are not properly separated.

4. Lack of Semantic Verification

Prompt rewriting without semantic verification may change the meaning of the original request.

5. Limited Risk-Based Processing

Binary classification into safe and malicious categories may not adequately represent different levels of prompt-injection severity.

6. Lack of Integrated Recovery Pipeline

Detection, sanitization, repair, semantic verification, and risk assessment are often treated as separate security mechanisms.

7. Need for Human-Meaning Preservation

A practical system should protect the LLM while still allowing legitimate user interaction.

TABLE 2.2 RESEARCH GAPS

S.NO	RESEARCH GAPS	REQUIREMENT IN PROPOSED SYSTEM
1	Limited Automated Security Recommendations	The proposed system plans to generate security recommendations based on detected attacks, attack-chain information, and risk.
2	Limited Detection of Rare Attacks	The proposed system should use suitable network-flow features for reliable attack classification.
3	Lack of Attack Explainability and Response	The proposed system aims to extend attack classification with threat analysis and security recommendations.
4	High Cost and Inconsistency of LLM-Based IDS	A machine-learning-based approach can provide an efficient initial attack classification before advanced security analysis.
5	Limited Attack-to-Attack Relationship Analysis	The proposed system includes attack-chain prediction to analyse possible subsequent attack stages.
6	Need for an Integrated Security Analysis Framework	The proposed system aims to integrate attack classification, MITRE ATT&CK analysis, attack-chain prediction, risk assessment, and security recommendations.
7	Limited Risk-Based Decision Support	The proposed system aims to incorporate attack information and risk assessment for security decision support.

2.3 PROPOSED SYSTEM

The proposed Prompt Shield: AI-Based Prompt Injection and Recovery System is a multi-stage security framework designed to protect Large Language Model (LLM) applications from prompt injection attacks while preserving legitimate user intent. Unlike conventional approaches that primarily detect and block suspicious prompts, the proposed system performs detection, risk assessment, sanitization, prompt recovery, and semantic verification before allowing the processed prompt to reach the LLM.

The system receives the user's prompt as input and first analyses it using DeBERTa-v3, which is responsible for identifying whether the prompt contains characteristics associated with prompt injection attacks. The detection result is then combined with a rule-based risk scoring mechanism to determine the severity of the identified threat.

For suspicious prompts, the system applies Regular Expression (Regex)-based sanitization to identify and remove or neutralize harmful instruction patterns. The sanitized prompt is then passed to FLAN-T5, which generates a repaired version of the prompt while attempting to retain the legitimate meaning and purpose of the original request.

Since prompt repair can unintentionally alter the user's intended meaning, the proposed system introduces an additional semantic verification layer using Sentence-BERT (SBERT). SBERT generates semantic representations of both the original prompt and the repaired prompt, and their similarity is evaluated. This enables the system to determine whether the recovered prompt sufficiently preserves the original user intent.

Based on the detection result, risk level, sanitization outcome, and semantic verification result, the system determines whether the prompt can safely proceed to the LLM. A verified prompt is forwarded to the LLM for response generation, whereas prompts that fail the security or semantic verification conditions can be rejected or subjected to further processing.

Key Features of the Proposed System

- **AI-Based Detection:** Uses DeBERTa-v3 to identify potentially malicious prompts.
- **Risk-Based Analysis:** Assigns a risk level to detected prompt-injection attempts.
- **Prompt Sanitization:** Uses Regex rules to remove or neutralize harmful instructions.
- **Prompt Recovery:** Uses FLAN-T5 to reconstruct a safer version of the prompt.
- **Intent Preservation:** Attempts to retain the legitimate purpose of the user's
- original request.
- **Semantic Verification:** Uses SBERT to compare the original and repaired prompts.
- **Secure LLM Interaction:** Forwards only the verified prompt to the LLM.
- **Reduced False Blocking:** Provides an opportunity to recover legitimate requests instead of immediately rejecting suspicious inputs.
- **Layered Protection:** Combines multiple security mechanisms to provide stronger protection against prompt injection.

2.3.1 OVERVIEW

The proposed system operates as follows:

1. The user submits a prompt.
2. The input prompt is passed to the prompt detection module.
3. DeBERTa-v3 analyses the prompt for malicious characteristics.
4. A risk-scoring mechanism evaluates the severity.
5. Suspicious instructions are identified for sanitization.
6. Regex rules remove or neutralize known harmful patterns.
7. FLAN-T5 generates a repaired version of the prompt.
8. SBERT compares the original and repaired prompts.
9. If semantic similarity satisfies the required threshold, the repaired prompt is considered to preserve the user's intent.
10. The verified prompt is forwarded to the LLM.
11. The processing result can be logged for security monitoring.

2.3.2 OBJECTIVES

The proposed system aims to:

- Detect prompt injection attacks.
- Identify suspicious instruction patterns.
- Sanitize malicious instructions.
- Recover safe prompts.
- Preserve legitimate user intent.
- Verify semantic similarity.
- Assign risk levels.
- Reduce unnecessary prompt blocking.
- Provide secure interaction with LLM applications.

2.3.3 ADVANTAGES

Advantages of the proposed system include the following:

- **Automated Detection**
  DeBERTa-v3 enables automated identification of potentially malicious prompts.
- **Prompt Recovery**
  Instead of simply rejecting a suspicious prompt, the system attempts to generate a safe alternative.
- **Intent Preservation**
  The repair mechanism aims to retain the original purpose of the user's request.
- **Semantic Verification**
  SBERT provides a semantic comparison between the original and repaired prompts.
- **Risk-Based Security**
  A rule-based risk score allows the system to distinguish different levels of prompt-injection severity.
- **Multi-Layer Protection**
  The system combines detection, sanitization, repair, verification, and risk assessment.
- **Improved Usability**
  Legitimate requests can potentially be recovered instead of being unnecessarily blocked.

CHAPTER 3

SYSTEM DESIGN

3.1 SYSTEM ARCHITECTRURE

The proposed Prompt Shield: AI-Based Prompt Injection and Recovery System is designed as a multi-stage security framework for protecting Large Language Model (LLM) applications from prompt injection attacks. The architecture integrates prompt detection, risk assessment, sanitization, prompt recovery, semantic verification, and secure LLM interaction into a unified processing pipeline.

The system begins when a user submits a natural-language prompt. The input is first passed through an input validation stage to ensure that the prompt is in an acceptable format. The validated prompt is then analysed using DeBERTa-v3, which identifies whether the input contains characteristics associated with prompt injection attacks.

The detection output is passed to a rule-based risk scoring module, which evaluates the severity of the detected threat. Suspicious prompts are subsequently processed by the Regex-based sanitization module, which identifies and removes or neutralizes potentially harmful instruction patterns.

The sanitized prompt is then passed to FLAN-T5, which performs prompt recovery by generating a safer version of the input while attempting to preserve the legitimate intent of the original user request. Since prompt repair may potentially alter the meaning of the original input, the repaired prompt is passed to Sentence-BERT (SBERT) for semantic verification.

SBERT generates semantic representations of the original and repaired prompts and calculates their similarity. If the repaired prompt maintains the required level of semantic similarity and satisfies the security conditions, it is considered a verified safe prompt and is forwarded to the LLM. If the verification fails, the prompt can be rejected or subjected to further processing.




Figure 3.1 Architecture Diagram of Prompt Shield

FIGURE 3.1 ARCHITECTURE DIAGRAM

3.2 MODULE DESIGN

The PromptShield: AI-Based Prompt Injection Detection and Sanitization Framework is composed of five major modules. Each module performs a specific task in the security pipeline so that the overall process transforms a user prompt into prompt injection detection, malicious-content identification, prompt sanitization, intent verification, risk assessment, and an appropriate security decision.

1. Prompt Input and Preprocessing

This module accepts the user prompt and performs basic preprocessing and normalization. The processed prompt is then forwarded for security analysis.

2. Hybrid Prompt Injection Detection

This module combines the DeBERTa machine learning model with rule-based pattern matching to identify prompt injection attacks. It detects malicious content and categorizes attacks such as instruction override, system prompt extraction, jailbreak, and role manipulation.

3. Prompt Sanitization and Intent Verification

The detected malicious instructions are removed from the prompt while preserving the legitimate user request. SBERT compares the original and sanitized prompts to verify whether the user's intended meaning has been maintained.

4. Risk Assessment and Adaptive Decision

This module calculates a risk score and risk level based on detected attack indicators and semantic similarity. The Adaptive Decision Engine then determines the appropriate action: ALLOW, SANITIZE, or BLOCK.

5. Security Audit and Analysis

This module presents the complete analysis results, including detected malicious content, attack category, sanitized prompt, similarity score, risk assessment, and final security decision for monitoring and analysis.

3.3 DATA FLOW DIAGRAM




FIGURE 3.2 DATAFLOW DIAGRAM

3.4 THREAT MODEL AND ATTACK SURFACE

This is because the PromptShield: AI-Based Prompt Injection Detection and Sanitization Framework analyzes user prompts, detection results, malicious content, sanitized prompts, semantic similarity, risk scores, and security decisions. Hence, various parts of the system may be vulnerable to attacks from adversaries. The threat model describes the major assets, potential threats, attack surfaces, and security measures for the proposed system.

Assets

The major assets of the proposed PromptShield framework include the user prompts, preprocessed prompts, DeBERTa detection model, rule-based detection patterns, attack categories, detected malicious content, sanitized prompts, SBERT intent verification results, risk scores, and adaptive security decisions.

Potential Threats

- **Prompt Injection:** Malicious instructions may be inserted into user prompts to manipulate the AI system or override its intended instructions.
- **System Prompt Extraction:** Attackers may attempt to reveal system prompts, hidden instructions, or confidential information.
- **Jailbreak and Safety Bypass:** Attackers may use carefully crafted prompts to bypass safety restrictions and security controls.
- **Role Manipulation:** An attacker may force the system to behave as an unrestricted or unauthorized role.
- **Adversarial Input:** Carefully modified prompts may attempt to bypass the DeBERTa model or rule-based detection mechanism.
- **Sanitization Manipulation:** Malicious content may be designed so that its removal changes the original meaning or leaves harmful instructions in the prompt.
- **Unauthorized Access:** Unregistered users may attempt to access detection rules, models, analysis results, or security information.
- **Denial of Service:** Excessive or very large prompts may affect the processing capability and availability of the system.

Attack Surfaces

The important attack surfaces are the user prompt input, preprocessing and normalization, hybrid detection module, DeBERTa model, rule-based patterns, sanitization process, SBERT intent verification, risk assessment, and adaptive decision engine.

The user prompt may contain malicious or obfuscated instructions designed to bypass detection. The detection model and rule-based patterns may be targeted using adversarial inputs. The sanitization and intent verification modules may also be manipulated to produce an unsafe result or incorrectly preserve malicious instructions. The risk assessment and adaptive decision engine may provide an incorrect decision if the input detection or verification results are manipulated.

3.5 SECURITY CONTROLS

The PromptShield: AI-Based Prompt Injection Detection and Sanitization Framework needs proper security measures to protect the user prompts, detection model, attack analysis, sanitized prompts, and security decisions created by the system. The user prompts and processed data need to be protected from unauthorized access or manipulation. Input data must be validated and normalized before analysis to minimize the risk of malicious or malformed prompts entering the system. Users who have access to the detection models, rules, configurations, and security results must be authorized users. The model files, detection rules, analysis results, and configurations must be protected from unauthorized modification or tampering.

The trained DeBERTa model and rule-based detection patterns must be secured against unauthorized alterations. Prompts and detected features should be validated before being processed by the detection and sanitization modules. Important system activities such as detected attacks, malicious content, sanitization results, similarity scores, risk levels, and final decisions should be recorded for security analysis. The SBERT intent verification results must be used to ensure that sanitization preserves the legitimate user intention. The risk assessment and adaptive decision mechanism should use the detection and verification results to determine whether the prompt should be ALLOWED, SANITIZED, or BLOCKED. These measures help in improving the security and reliability of the proposed PromptShield framework.

CHAPTER 4
SYSTEM DESCRIPTION

4.1 DATA COLLECTION

The PromptShield: AI-Based Prompt Injection Detection and Sanitization Framework uses a collection of normal and malicious user prompts as the main source of data for detecting prompt injection attacks. The collected prompts represent different types of user requests, including normal queries and malicious instructions such as instruction override, system prompt extraction, safety bypass, jailbreak attempts, developer mode manipulation, and role manipulation.

The prompt data is organized into a standard format containing the original prompt, attack category, and corresponding classification information where available. The collected prompts are used for testing the hybrid detection mechanism and evaluating the ability of the system to identify malicious content.

The prepared prompt data is further provided to the Prompt Preprocessing stage for normalization and input preparation. The processed prompts are then passed to the Hybrid Prompt Injection Detection stage, where the DeBERTa model and rule-based patterns are used to identify possible attacks. The detection output is further used by the Prompt Sanitization and Intent Verification stage, followed by Risk Assessment and Adaptive Decision.

4.2 DATA PREPROCESSING

The data preprocessing stage prepares the collected prompts for prompt injection detection and security analysis. The preprocessing process includes receiving the user prompt, removing unnecessary formatting, normalizing the input, and preparing the prompt for the machine-learning and rule-based detection mechanisms.The collected data contains both benign prompts and malicious prompts. Benign prompts represent legitimate user requests, while malicious prompts contain instructions intended to manipulate or bypass the intended behavior of an AI system.The input prompt can be represented as:

$$P = \{p_1, p_2, p_3, \dots, p_n\}$$

where Prepresents the prompt and $p_i$represents the individual elements of the prompt.

The normalized prompt is represented as:

$$P' = N(P)$$

where Nrepresents the preprocessing and normalization function.

The processed prompt is then provided to the hybrid detection model.

Prompt Normalization

The input prompt is normalized before detection to provide a consistent representation for analysis. Unnecessary spaces, formatting variations, and inconsistent text representations can be handled during this stage.

The normalization process can be represented as:

$$P' = N(P)$$

where Prepresents the original prompt and P'represents the normalized prompt.

Detection Data Preparation

After preprocessing, the normalized prompt is provided to both the DeBERTa-based classification model and the rule-based pattern matching mechanism. The machine-learning model provides a classification result and confidence score, while the rule-based mechanism searches for known malicious patterns.

The detection process can be represented as

$$D(P') \rightarrow \{L, S, M, C\}$$

where:

- L= Detection Label
- S= Detection Confidence Score
- M= Detected Malicious Content
- C= Attack Category

Attack Category Preparation

The detected malicious content is categorized according to the identified attack type. The major categories considered by PromptShield include:

- Instruction Override
- System Prompt Extraction
- Safety Bypass
- Developer Mode Manipulation

- Jailbreak Attempt
- Role Manipulation
- Confidential Information Extraction

This categorization helps the system explain why a prompt has been identified as potentially malicious.

Prompt Sanitization

After detecting malicious content, the identified malicious instructions are removed from the prompt. The sanitization process attempts to preserve the legitimate portion of the user's request.

The sanitized prompt can be represented as:

$$P_s = S(P', M)$$

where Srepresents the sanitization function, P'represents the normalized prompt, Mrepresents the detected malicious content, and $P_s$represents the sanitized prompt.

Intent Verification

The original prompt and sanitized prompt are compared using SBERT-based semantic similarity to determine whether the user's intended meaning has been preserved.

The similarity can be represented as:

$$Sim(P, P_s) = \cos(E, (P)E(P_s))$$

where E represents the sentence embedding generated by SBERT.

A higher similarity indicates that the sanitized prompt is closer in meaning to the original prompt, while a lower similarity may indicate that important information or intent has been changed during sanitization.

Risk Assessment

The risk assessment stage combines the detected attack information, detection confidence, and semantic similarity to calculate a risk score.

The risk score can be represented as:

$$R = f(D, S, Sim)$$

where:

- R= Risk Score
- D= Detected attack indicators
- S= Detection confidence
- Sim= Semantic similarity

The resulting risk score is used to determine the corresponding risk level.

Adaptive Decision

The final processed information is provided to the Adaptive Decision Engine. Based on the risk assessment and intent verification results, the system determines the appropriate action:

$$Decision = f(R, Sim)$$

The possible decisions are:

- **ALLOW** – The prompt is considered safe.
- **SANITIZE** – Malicious content is removed while preserving the intended request.
- **BLOCK** – The prompt is considered sufficiently risky and is prevented from further process

4.2.1 METHODOLOGY

The preprocessing and analysis process is conducted to transform the collected user prompts into a clean and consistent format suitable for prompt injection detection and security analysis. In this process, user prompts are received, normalized, and prepared for the hybrid detection mechanism. The processed prompts are then analyzed using the DeBERTa model and rule-based detection patterns.

The following activities are performed during the preprocessing and analysis process:

- **Prompt Input:** User prompts are received through the PromptShield interface for security analysis.
- **Prompt Normalization:** The input prompt is normalized by handling unnecessary spaces, formatting variations, and other inconsistencies.
- **Input Preparation:** The normalized prompt is prepared for both the machine-learning model and rule-based pattern matching.
- **Hybrid Detection:** The DeBERTa model and predefined security patterns are used together to identify possible prompt injection attacks.
- **Malicious Content Identification:** The exact malicious portion of the prompt is identified and extracted for further analysis.
- **Attack Categorization:** The detected content is classified into categories such as Instruction Override, System Prompt Extraction, Safety Bypass, Jailbreak Attempt, and Role Manipulation.
- **Prompt Sanitization:** The identified malicious instructions are removed while attempting to preserve the legitimate user request.
- **Intent Verification:** The original and sanitized prompts are compared using SBERT to determine whether the user's intended meaning has been preserved.
- **Risk Assessment:** Detection results and semantic similarity are used to calculate the risk score and corresponding risk level.
- **Adaptive Decision:** Based on the risk assessment and intent verification, the system determines whether the prompt should be ALLOWED, SANITIZED, or BLOCKED.

4.2.2 RESULTS AND DISCUSSION

The implementation of the proposed PromptShield: AI-Based Prompt Injection Detection and Sanitization Framework was carried out using a web-based security application. The system was developed to analyze user prompts and identify possible prompt injection attacks before the prompts reach an AI system. The implemented framework combines prompt preprocessing, rule-based pattern matching, ProtectAI-based prompt injection classification, prompt sanitization, semantic intent verification, risk assessment, and adaptive decision-making.

The PromptShield application provides a prompt analysis interface where the user can enter the required prompt and submit it for security analysis. The input prompt is processed locally by the application and forwarded to the different security analysis stages.

PROMPTSHIELD PROMPT INPUT INTERFACE

The submitted prompt is then analyzed using the hybrid prompt injection detection mechanism. The system combines the machine-learning detector with predefined rule-based patterns to identify malicious instructions. The detection result provides the hybrid classification, combined confidence, rule-engine result, and machine-learning detector result. In the demonstrated test case, the system classified the input as INJECTION with a high confidence score.

The detected malicious content is then extracted from the submitted prompt. Each identified instruction is displayed along with its corresponding attack category, detection source, machine-learning confidence, and risk contribution. In the tested prompt, the system identified System Prompt Extraction, Instruction Override, Developer Mode Manipulation, and Safety Bypass as the major attack categories.




Fig 4.1

DETECTED MALICIOUS CONTENT AND ATTACK CATEGORIES

After detecting the malicious instructions, the PromptShield framework performs prompt sanitization. The identified malicious portions are removed from the original prompt while attempting to preserve the legitimate part of the user's request. The system also displays the content removed during the sanitization process.

The sanitized prompt is then passed to the intent verification stage. SBERT-based semantic comparison is used to compare the original prompt with the sanitized prompt. The resulting similarity score is compared with the predefined intent-preservation threshold. In the demonstrated test case, the similarity score was 0.0%, which was below the 80.0% threshold, and therefore the prompt was marked as not verified .




Fig 4.2

PROMPT SANITIZATION AND INTENT VERIFICATION

The result obtained from the detection and intent verification stages is then used for risk assessment. PromptShield calculates a risk score based on the detected attack categories, machine-learning classification, rule matches, and semantic verification result. The risk score is represented using different severity levels such as LOW, MEDIUM, HIGH, and CRITICAL.

In the demonstrated test case, the prompt received a 100/100 CRITICAL risk score. Since the sanitized prompt did not satisfy the required intent-preservation threshold, the Adaptive Decision Engine generated a BLOCK decision. This demonstrates that the final decision is not based only on the initial detection result but also considers the risk and semantic verification results.




Fig 4.3

RISK ASSESSMENT AND ADAPTIVE DECISION

The PromptShield framework also maintains an Analysis Audit Log containing the previously analyzed prompts and their corresponding security results. The audit log records information such as the analyzed prompt, detected attack categories, risk level, risk score, and final decision. The recorded results show that different prompts can produce different security decisions, including ALLOW, SANITIZE, and BLOCK.




Fig 4.4




Fig 4.5

PROMPTSHIELD ANALYSIS DASHBOARD

Overall, the results demonstrate the working of the proposed PromptShield framework from prompt input and detection to sanitization, intent verification, risk assessment, adaptive decision-making, and security auditing. The implementation shows that the system can identify different types of prompt injection attacks, display the specific malicious content, remove detected malicious instructions, verify semantic similarity, calculate security risk, and generate an appropriate ALLOW, SANITIZE, or BLOCK decision. The audit log and analysis dashboard further support the monitoring and analysis of the security results produced by the framework.



LOCAL SECURITY OVERVIEW
Analysis dashboard
Summary statistics are calculated from locally stored audit records.
Prompts analyzed
15
Injections detected
7
Safe prompts
8
Sanitized
2
Blocked
5
Average risk
32.0
Average similarity
0.7976
Attack categories
Developer Mode Manipulation
3
Instruction Override
3
Safety Bypass
3
System Prompt Extraction
5
Confidential Information Extraction
1
Role Manipulation
1
ML-only signal
1

Fig 4.6

CHAPTER 6

CONCLUSION

The PromptShield: AI-Based Prompt Injection Detection and Sanitization Framework was developed to identify and mitigate prompt injection attacks in AI-based systems. The framework combines prompt preprocessing, DeBERTa-based detection, rule-based pattern matching, prompt sanitization, SBERT-based intent verification, risk assessment, and adaptive decision-making.

The hybrid detection mechanism helps identify malicious instructions and categorize attacks such as instruction override, system prompt extraction, safety bypass, jailbreak attempts, and role manipulation. The sanitization process removes the detected malicious content while attempting to preserve the legitimate user intention. SBERT-based semantic verification is used to measure the similarity between the original and sanitized prompts.

The framework further calculates a risk score and determines an appropriate security action based on the analysis. The Adaptive Decision Engine provides three possible actions: ALLOW, SANITIZE, or BLOCK. This provides a systematic approach for handling potentially malicious prompts.

Overall, the proposed PromptShield framework provides a practical and explainable approach for improving the security of AI-based applications against prompt injection attacks. Future development can focus on larger benchmark datasets, advanced obfuscation detection, improved sanitization techniques, detailed audit logging, and comprehensive performance evaluation.

REFERENCES

1. **Devlin, J.**, Chang, M.-W., Lee, K., and Toutanova, K., "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding," *Proceedings of NAACL-HLT*, 2019.
2. **Hugging Face**, "Transformers Documentation," Hugging Face.
3. **OWASP Foundation**, "OWASP Top 10 for Large Language Model Applications," OWASP, 2025.
4. **OWASP Foundation**, "OWASP Top 10 Web Application Security Risks," OWASP.
5. **ProtectAI**, "DeBERTa-v3-base Prompt Injection v2," Hugging Face Model Repository.
6. **Reimers, N.**, and Gurevych, I., "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks," *Proceedings of EMNLP-IJCNLP*, 2019.
7. **Vaswani, A.**, Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I., "Attention Is All You Need," *Advances in Neural Information Processing Systems*, 2017.
8. **UK National Cyber Security Centre (NCSC)**, "Guidelines for Secure AI System Development," NCSC.
9. **Vaswani, A.**, Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I., "Attention Is All You Need," *Advances in Neural Information Processing Systems*, 2017.
10. **Wei, A.**, Wang, B., and others, "Jailbroken: How Does LLM Safety Training Fail?" *NeurIPS Workshop*, 2023.
11. **Zou, A.**, Wang, Z., Kolter, J. Z., and Fredrikson, M., "Universal and Transferable Adversarial Attacks on Aligned Language Models," *arXiv preprint arXiv:2307.15043*, 2023.