

Rajalakshmi Engineering College

Name: RITHIKA L
Email: 240701430@rajalakshmi.edu.in
Roll no: 240701430
Phone: 9360758246
Branch: REC
Department: CSE - Section 3
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 10_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. Which method removes all elements from a Set?

Answer

clear()

Status : Correct

Marks : 1/1

2. How does HashSet check for duplicate elements?

Answer

Using equals() and hashCode()

Status : Correct

Marks : 1/1

3. Which statement is true about HashSet and TreeSet?

Answer

TreeSet provides sorted elements

Status : Correct

Marks : 1/1

4. What happens when you add duplicate elements to a HashSet?

Answer

The duplicate is ignored

Status : Correct

Marks : 1/1

5. Which method retrieves the lowest key in a TreeMap?

Answer

firstKey()

Status : Correct

Marks : 1/1

6. Which of the following allows null keys in Java?

Answer

HashMap

Status : Correct

Marks : 1/1

7. Which of the following is true about HashMap?

Answer

It is not synchronized

Status : Correct

Marks : 1/1

8. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("A", 1);
        map.put("B", 2);
        map.put("C", 3);
        System.out.println(map.containsKey("B"));
    }
}
```

Answer

true

Status : Correct

Marks : 1/1

9. Which of the following is true about TreeMap?

Answer

It maintains natural ordering

Status : Correct

Marks : 1/1

10. What is the time complexity of retrieving an element from a HashSet?

Answer

$O(1)$

Status : Correct

Marks : 1/1

11. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, String> map = new HashMap<>();
        map.put("A", "Apple");
    }
}
```

```
map.put("B", "Banana");
map.put("C", "Cherry");
map.replace("B", "Blueberry");
System.out.println(map);
}
```

Answer

{A=Apple, B=Blueberry, C=Cherry}

Status : Correct

Marks : 1/1

12. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("X", 10);
        map.put("Y", 20);
        map.put("Z", 30);
        map.remove("Y");
        System.out.println(map);
    }
}
```

Answer

{X=10, Z=30}

Status : Correct

Marks : 1/1

13. What happens if two keys have the same hash code in a HashMap?

Answer

A linked list is used to store values with the same hash

Status : Correct

Marks : 1/1

14. What will happen if you add a null element to a TreeSet?

Answer

An exception occurs

Status : Correct

Marks : 1/1

15. What will happen if you add elements in descending order in a TreeSet?

Answer

They are sorted in ascending order

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: RITHIKA L
Email: 240701430@rajalakshmi.edu.in
Roll no: 240701430
Phone: 9360758246
Branch: REC
Department: CSE - Section 3
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

A city traffic management system needs to track vehicles entering a toll booth. Each vehicle is uniquely identified by its registration number. The system should allow adding vehicles to a record, ensuring that no duplicate registration numbers exist. The vehicles should be stored in a HashSet, which does not guarantee any specific order.

Your task is to implement a program using a HashSet that allows adding vehicle details and displaying the records.

Input Format

The first line of input contains an integer N - the number of vehicles.

The next N lines contain details of each vehicle in the format: "RegNumber

OwnerName VehicleType"

1. RegNumber (String) - A unique registration number (Alphanumeric).
2. OwnerName (String) - The name of the vehicle owner.
3. VehicleType (String, Car, Bike, or Truck) - The type of vehicle.

If a vehicle with the same registration number is already present, ignore the duplicate entry.

Output Format

The output prints the unique vehicle records in any order (since HashSet does not maintain order).

Output format: "RegNumber OwnerName VehicleType"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

KA01AB1234 John Car

MH02CD5678 Alice Bike

DL03EF9012 Bob Truck

TN04GH3456 Mike Car

KA01AB1234 John Car

Output: TN04GH3456 Mike Car

KA01AB1234 John Car

MH02CD5678 Alice Bike

DL03EF9012 Bob Truck

Answer

```
import java.util.*;
```

```
class Vehicle {
```

```
    String regNumber;
```

```
    String ownerName;
```

```
    String vehicleType;
```

```
    Vehicle(String regNumber, String ownerName, String vehicleType) {
```

```
        this.regNumber = regNumber;
```

```

        this.ownerName = ownerName;
        this.vehicleType = vehicleType;
    }

    // Override equals() to compare vehicles by registration number only
    @Override
    public boolean equals(Object obj) {
        if (this == obj)
            return true;
        if (obj == null || getClass() != obj.getClass())
            return false;
        Vehicle v = (Vehicle) obj;
        return regNumber.equals(v.regNumber);
    }

    // Override hashCode() to ensure unique regNumbers
    @Override
    public int hashCode() {
        return regNumber.hashCode();
    }

    @Override
    public String toString() {
        return regNumber + " " + ownerName + " " + vehicleType;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine(); // consume newline

        HashSet<Vehicle> vehicleSet = new HashSet<>();

        for (int i = 0; i < n; i++) {
            String regNumber = sc.next();
            String ownerName = sc.next();
            String vehicleType = sc.next();

            Vehicle v = new Vehicle(regNumber, ownerName, vehicleType);
            vehicleSet.add(v);
        }
    }
}

```



```
}  
    // Display unique vehicle records  
    for (Vehicle v : vehicleSet) {  
        System.out.println(v);  
    }  
  
    sc.close();  
}  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: RITHIKA L
Email: 240701430@rajalakshmi.edu.in
Roll no: 240701430
Phone: 9360758246
Branch: REC
Department: CSE - Section 3
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

John is organizing a fruit festival, and the quantities of various fruits are stored in a HashMap where fruit names are keys and quantities are values.

Help him develop a program to find the total quantity of fruits for the festival by summing up the values in the HashMap.

Input Format

The input consists of fruit quantities in the format 'fruitName:quantity', where fruitName is the name of the fruit(a string), and quantity is a double value representing the quantity.

The input is terminated by entering "done".

Output Format

The output prints a double value, representing the sum of values in the HashMap, rounded off to two decimal places.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are entered, print "Invalid format".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Banana:15.2

Orange:56.3

Mango:47.3

done

Output: 118.80

Answer

// You are using Java

import java.util.*;

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        HashMap<String, Double> fruits = new HashMap<>();
        double total = 0.0;
        boolean invalidInput = false;
        boolean invalidFormat = false;

        while (sc.hasNext()) {
            String input = sc.next();
            if (input.equalsIgnoreCase("done")) {
                break;
            }

            // check if ':' is present
            if (!input.contains(":")) {
                invalidFormat = true;
                break;
            }
        }
    }
}
```

```

// check for invalid characters (only letters, digits, '.', and '-')
if (!input.matches("[A-Za-z]+:[0-9]*\\.?[0-9]+")) {
    // if it has letters in quantity or other special chars
    if (input.matches("[A-Za-z]+:[A-Za-z]+")) {
        invalidInput = true;
    } else {
        invalidFormat = true;
    }
    break;
}

// split into key and value
String[] parts = input.split(":");
String fruit = parts[0];
String value = parts[1];

try {
    double quantity = Double.parseDouble(value);
    fruits.put(fruit, quantity);
} catch (NumberFormatException e) {
    invalidInput = true;
    break;
}

}

sc.close();

if (invalidInput) {
    System.out.print("Invalid input");
} else if (invalidFormat) {
    System.out.print("Invalid format");
} else {
    for (double qty : fruits.values()) {
        total += qty;
    }
    System.out.printf("%.2f", total);
}
}
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: RITHIKA L
Email: 240701430@rajalakshmi.edu.in
Roll no: 240701430
Phone: 9360758246
Branch: REC
Department: CSE - Section 3
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

Priya is analyzing encrypted messages in a research project. She wants to analyze the frequency of each character in a given paragraph. The characters should be stored in a TreeMap so that the output is sorted in ascending order of characters automatically.

You are required to build a Java program that:

Uses a `TreeMap<Character, Integer>` to count how many times each character appears in the message. Ignores spaces and considers only alphabets (case-sensitive). Outputs the frequencies of characters in sorted order.

You must use a TreeMap in the class named MessageAnalyzer.

Input Format

The first line of input contains an integer n, the number of lines in the message.

The next n lines each contain a string (the encrypted message line).

Output Format

The first line of output prints: "Character Frequency:"

Then print each character and its frequency in the format: "<character>: <count>"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2
Hello World
Java

Output: Character Frequency:

H: 1

J: 1

W: 1

a: 2

d: 1

e: 1

l: 3

o: 2

r: 1

v: 1

Answer

```
import java.util.*;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        sc.nextLine(); // consume newline after integer  
        TreeMap<Character, Integer> freqMap = new TreeMap<>();  
        for (int i = 0; i < n; i++) {
```

```
String line = sc.nextLine();

for (int j = 0; j < line.length(); j++) {
    char ch = line.charAt(j);

    // Consider only alphabets (case-sensitive) and ignore spaces
    if (Character.isLetter(ch)) {
        freqMap.put(ch, freqMap.getDefault(ch, 0) + 1);
    }
}

sc.close();

System.out.print("Character Frequency: ");
for (Map.Entry<Character, Integer> entry : freqMap.entrySet()) {
    System.out.print(entry.getKey() + ": " + entry.getValue() + " ");
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: RITHIKA L
Email: 240701430@rajalakshmi.edu.in
Roll no: 240701430
Phone: 9360758246
Branch: REC
Department: CSE - Section 3
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

In a ticket reservation system, you store the available seat numbers in a TreeSet. Users input their desired seat number, and the program checks whether the chosen seat is available.

Using a TreeSet ensures quick and efficient verification of seat availability, ensuring a smooth and organized ticket booking process.

Input Format

The first line of input contains a single integer n , representing the number of available seats.

The second line contains n space-separated integers, representing the available seat numbers.

The third line contains an integer m , representing the seat number that needs to be searched.

Output Format

The output displays "[m] is present!" if the given seat is available. Otherwise, it displays "[m] is not present!"

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

2 4 5 6

5

Output: 5 is present!

Answer

// You are using Java

import java.util.*;

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt(); // number of available seats
        TreeSet<Integer> seats = new TreeSet<>();

        // Read n seat numbers
        for (int i = 0; i < n; i++) {
            seats.add(sc.nextInt());
        }

        int m = sc.nextInt(); // seat to be searched

        if (seats.contains(m)) {
            System.out.print(m + " is present!");
        } else {
            System.out.print(m + " is not present!");
        }
    }
}
```

```
    sc.close();  
  }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: RITHIKA L
Email: 240701430@rajalakshmi.edu.in
Roll no: 240701430
Phone: 9360758246
Branch: REC
Department: CSE - Section 3
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 10_PAH

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

A university maintains a list of student records and wants to store them in a sorted manner based on their GPA. If two students have the same GPA, they should be further sorted by their name in lexicographical order. Implement a program that uses a TreeSet to store student records and ensures unique student IDs.

Input Format

The first line contains an integer N - the number of students.

The next N lines contain details of each student in the format: "StudentID Name GPA"

- StudentID (Integer) - A unique identifier.
- Name (String) - The student's name (can contain spaces).

- GPA (Double) - The Grade Point Average.

Output Format

The output prints the list of students in ascending order of GPA.

If two students have the same GPA, sort them by name.

Print details in the format: "StudentID Name GPA" in the output, GPA is rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

101 John 8.5

102 Alice 9.1

103 Bob 8.5

104 Zoe 7.3

105 Charlie 9.1

Output: 104 Zoe 7.30

103 Bob 8.50

101 John 8.50

102 Alice 9.10

105 Charlie 9.10

Answer

```
// You are using Java
import java.util.*;
```

```
class Student implements Comparable<Student> {
    int id;
    String name;
    double gpa;
```

```
    Student(int id, String name, double gpa) {
        this.id = id;
        this.name = name;
        this.gpa = gpa;
    }
}
```

```

@Override
public int compareTo(Student other) {
    // Sort by GPA first
    if (this.gpa != other.gpa) {
        return Double.compare(this.gpa, other.gpa);
    }
    // If GPA is the same, sort by name lexicographically
    int nameCompare = this.name.compareTo(other.name);
    if (nameCompare != 0) return nameCompare;

    // Ensure uniqueness by Student ID
    return Integer.compare(this.id, other.id);
}

@Override
public String toString() {
    return id + " " + name + " " + String.format("%.2f", gpa);
}
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        TreeSet<Student> students = new TreeSet<>();

        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            String name = sc.next();
            double gpa = sc.nextDouble();

            students.add(new Student(id, name, gpa));
        }

        sc.close();

        for (Student s : students) {
            System.out.print(s + " ");
        }
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Sarah is working on a spam detection system that analyzes incoming messages for unique patterns. Spammers often use repetitive character sequences, making it important to identify the first non-repeating character in a message.

Given a string, Sarah needs to determine the first character that appears only once. If all characters repeat, the system should return -1.

She decides to use a HashMap to efficiently track character frequencies and find the solution.

Input Format

The first line contains an integer N representing , the length of the string.

The second line contains a string of N lowercase English letters (a-z).

Output Format

The output prints a character representing the first non-repeating character. If none exist, print -1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10
abacabadac

Output: d

Answer

```
// You are using Java
import java.util.*;

public class Main {
```

```

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);
    int n = sc.nextInt();
    String str = sc.next();

    HashMap<Character, Integer> map = new HashMap<>();

    // Count frequency of each character
    for (int i = 0; i < n; i++) {
        char ch = str.charAt(i);
        map.put(ch, map.getDefault(ch, 0) + 1);
    }

    // Find first non-repeating character
    char result = '-';
    for (int i = 0; i < n; i++) {
        char ch = str.charAt(i);
        if (map.get(ch) == 1) {
            result = ch;
            break;
        }
    }

    if (result == '-') {
        System.out.print("-1");
    } else {
        System.out.print(result);
    }

    sc.close();
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Riya is building a calendar event scheduler where each event is stored in chronological order using a TreeMap. The key represents the event time in 24-hour format (HH:MM), and the value is the event description.

She wants the system to:

Automatically sort events by time. Avoid duplicate time entries — if a duplicate time is entered, ignore the new entry. Print all scheduled events in order.

Implement this logic using a class named EventManager.

Input Format

The first line of the input contains an integer n , representing the number of events.

The next n lines each contain a string in the format: "HH:MM Description"

(Example: 09:00 TeamMeeting).

Output Format

The first line of the output prints "Scheduled Events:"

The next k lines print each event in the format: "HH:MM - Description"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

09:00 TeamMeeting

13:30 LunchBreak

11:00 ProjectUpdate

09:00 Standup

15:00 ClientCall

Output: Scheduled Events:

09:00 - TeamMeeting

11:00 - ProjectUpdate

13:30 - LunchBreak

15:00 - ClientCall

Answer

// You are using Java


```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();

        TreeMap<String, String> events = new TreeMap<>();

        for (int i = 0; i < n; i++) {
            String time = sc.next();
            String desc = sc.next();

            // If time already exists, ignore duplicate
            if (!events.containsKey(time)) {
                events.put(time, desc);
            }
        }

        sc.close();

        System.out.print("Scheduled Events: ");
        for (Map.Entry<String, String> entry : events.entrySet()) {
            System.out.print(entry.getKey() + " - " + entry.getValue() + " ");
        }
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: RITHIKA L
Email: 240701430@rajalakshmi.edu.in
Roll no: 240701430
Phone: 9360758246
Branch: REC
Department: CSE - Section 3
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 10_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : COD

1. Problem Statement

Arjun is working on a program that checks if one set of numbers is a subset of another. If Set B is a subset of Set A, the program should print "YES" followed by the sorted elements of Set B. If Set B is not a subset of Set A, the program should print "NO" followed by the average of all elements from both sets combined, rounded to two decimal places.

Implement a class Solution with the required method to perform the subset check using TreeSet in Java.

Input Format

The first line contains an integer n - the number of elements in Set A.

The second line contains n space-separated integers - the elements of Set A.

The third line contains an integer m - the number of elements in Set B.

The fourth line contains m space-separated integers - the elements of Set B.

Output Format

If Set B is a subset of Set A, print "YES" followed by the sorted values of Set B.

Otherwise, print "NO" followed by the average of all numbers in both sets (rounded to two decimal places).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

1 2 3 4 5

3

2 3 5

Output: YES 2 3 5

Answer

```
import java.util.*;
```

```
class Solution {
    public static void checkSubset(TreeSet<Integer> setA, TreeSet<Integer> setB,
int totalCount, long sum) {
        if (setA.containsAll(setB)) {
            System.out.print("YES ");
            for (int num : setB) {
                System.out.print(num + " ");
            }
        } else {
            double avg = (double) sum / totalCount;
            System.out.printf("NO %.2f", avg);
        }
    }
}
```

```

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        TreeSet<Integer> setA = new TreeSet<>();
        long sum = 0;
        for (int i = 0; i < n; i++) {
            int num = sc.nextInt();
            setA.add(num);
            sum += num;
        }
        int m = sc.nextInt();
        TreeSet<Integer> setB = new TreeSet<>();
        for (int i = 0; i < m; i++) {
            int num = sc.nextInt();
            setB.add(num);
            sum += num;
        }
        Solution.checkSubset(setA, setB, n + m, sum);
        sc.close();
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

The city library maintains a record of books available for lending. Each book is uniquely identified by its ISBN number, along with its title and author. The librarian wants to efficiently store and manage these records, ensuring books can be listed in the order they were added.

Your task is to implement a Library Management System using HashSet where:

The librarian adds books with ISBN, title, and author. The librarian can remove books by providing an ISBN. Finally, the librarian displays the available books in the order they were added.

Implement a class Library that will handle these operations. The main function should manage user input and interact with the Library class accordingly.

Input Format

The first line contains an integer n – the number of books to be added.

The next n lines contain three values: ISBN (integer), Title (string without spaces), and Author (string without spaces).

1. An integer employee_id
2. A string title
3. A string author name

The next line contains an integer m – the number of books to be removed.

The next m lines follow, each contains an ISBN number to remove.

Output Format

The output prints a list of books available in the library after performing all operations in the format:

"ISBN: <isbn>, Title: <title>, Author: <author>"

If no books remain, print: "No books available"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

1234 JavaCompleteGuide JohnDoe

5678 PythonBasics JaneDoe

9012 DataStructures AliceSmith

1

5679

Output: ISBN: 1234, Title: JavaCompleteGuide, Author: JohnDoe

ISBN: 9012, Title: DataStructures, Author: AliceSmith

ISBN: 5678, Title: PythonBasics, Author: JaneDoe

Answer

```
import java.util.*;
```

```
class Book {  
    int isbn;  
    String title;  
    String author;
```

```
    Book(int isbn, String title, String author) {  
        this.isbn = isbn;  
        this.title = title;  
        this.author = author;  
    }
```

```
    @Override  
    public boolean equals(Object o) {  
        if (this == o) return true;  
        if (!(o instanceof Book)) return false;  
        Book b = (Book) o;  
        return this.isbn == b.isbn;  
    }
```

```
    @Override  
    public int hashCode() {  
        return Objects.hash(isbn);  
    }  
}
```

```
class Library {  
    LinkedHashSet<Book> books = new LinkedHashSet<>();
```

```
    void addBook(int isbn, String title, String author) {  
        books.add(new Book(isbn, title, author));  
    }
```

```

void removeBook(int isbn) {
    books.removeIf(b -> b.isbn == isbn);
}

void displayBooks() {
    if (books.isEmpty()) {
        System.out.println("No books available");
    } else {
        for (Book b : books) {
            System.out.println("ISBN: " + b.isbn + ", Title: " + b.title + ", Author: " +
b.author);
        }
    }
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        Library library = new Library();
        int n = sc.nextInt();
        for (int i = 0; i < n; i++) {
            int isbn = sc.nextInt();
            String title = sc.next();
            String author = sc.next();
            library.addBook(isbn, title, author);
        }
        int m = sc.nextInt();
        for (int i = 0; i < m; i++) {
            int isbn = sc.nextInt();
            library.removeBook(isbn);
        }
        library.displayBooks();
        sc.close();
    }
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Aryan is developing a voting system for a college election. Each vote is recorded as an entry in an array, where every student's vote is represented by a candidate's ID. Since it's a majority-rule election, the winner is the candidate who receives more than $n/2$ votes, where n is the total number of votes cast.

To quickly determine the winner, Aryan decides to use a HashMap to count the occurrences of each vote and identify the candidate who has received more than half of the total votes.

Example

Input

7

2 2 1 2 2 3

Output

2

Explanation

The votes are: 2, 2, 1, 2, 2, 3, 2

Count of each candidate:

2 appears 5 times 1 appears once 3 appears once

The majority element is the one that appears more than $N/2$ times. Since $7/2 = 3.5$, a number must appear at least 4 times to be the majority.

The number 2 appears 5 times, which is greater than 3.5, so the output is 2.

Input Format

The first line contains an integer N representing the number of votes cast.

The second line contains N space-separated integers representing the votes, where each integer corresponds to a candidate.

Output Format

The output prints an integer representing the majority element (the candidate who received more than $N/2$ votes).

If no such candidate exists, print -1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7

2 2 1 2 2 2 3

Output: 2

Answer

```
import java.util.HashMap;  
import java.util.Scanner;
```

```
class MajorityElementFinder {  
    public static int findMajorityElement(int[] arr) {  
        HashMap<Integer, Integer> map = new HashMap<>();  
        int n = arr.length;  
  
        // Count frequency of each element  
        for (int num : arr) {  
            map.put(num, map.getDefault(num, 0) + 1);  
        }  
  
        // Find majority element  
        for (int key : map.keySet()) {  
            if (map.get(key) > n / 2) {  
                return key;  
            }  
        }  
  
        return -1; // No majority element found  
    }  
}
```

```
class Main {  
    public static void main(String[] args) {
```

```

Scanner scanner = new Scanner(System.in);
int N = scanner.nextInt();
int[] arr = new int[N];

for (int i = 0; i < N; i++) {
    arr[i] = scanner.nextInt();
}

int result = MajorityElementFinder.findMajorityElement(arr);
System.out.println(result);

scanner.close();
}
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

Bob wants to develop a score-tracking application for a gaming tournament. Each player's score is stored in a HashMap with the player's name as the key and the score as the value.

Write a program to assist Bob that takes user input to enter player scores, calculates the maximum score from the HashMap, and prints the player with the highest score.

Input Format

The input consists of strings representing player details in the format "playerName:score".

The input is terminated by entering "done".

Output Format

The output displays a string, representing the player's name who scored the maximum.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are given, print "Invalid format".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Alice:15

Bob:56

done

Output: Bob

Answer

```
import java.util.*;

class ScoreTracker {
    HashMap<String, Integer> scoreMap = new HashMap<>();

    // Method to process each line of input
    public boolean processInput(String input) {
        input = input.trim();

        // Check if format contains exactly one ':'
        if (!input.contains(":") || input.indexOf(':') != input.lastIndexOf(':')) {
            System.out.println("Invalid format");
            return false;
        }

        String[] parts = input.split(":");
        if (parts.length != 2) {
            System.out.println("Invalid format");
            return false;
        }

        String player = parts[0].trim();
        String scoreStr = parts[1].trim();

        // Validate player name (alphabets only)
        if (!player.matches("[A-Za-z]+")) {
            System.out.println("Invalid format");
            return false;
        }
    }
}
```

```

    }

    // Validate score (digits only)
    if (!scoreStr.matches("\\d+")) {
        System.out.println("Invalid input");
        return false;
    }

    int score = Integer.parseInt(scoreStr);
    if (score < 1 || score > 100) {
        System.out.println("Invalid input");
        return false;
    }

    // Store valid input
    scoreMap.put(player, score);
    return true;
}

// Method to find player with top score
public String findTopPlayer() {
    String topPlayer = "";
    int maxScore = -1;
    for (Map.Entry<String, Integer> entry : scoreMap.entrySet()) {
        if (entry.getValue() > maxScore) {
            maxScore = entry.getValue();
            topPlayer = entry.getKey();
        }
    }
    return topPlayer;
}
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        ScoreTracker tracker = new ScoreTracker();
        boolean validInput = true;

        while (true) {
            String input = scanner.nextLine();

```

```
    if (input.toLowerCase().equals("done")) {  
        break;  
    }  
  
    if (!tracker.processInput(input)) {  
        validInput = false;  
        break;  
    }  
}  
  
if (validInput && !tracker.scoreMap.isEmpty()) {  
    System.out.println(tracker.findTopPlayer());  
}  
scanner.close();  
}  
}
```

Status : Correct

Marks : 10/10