

Exercise 3: Using Different Appenders

Exe3LoggingExample

pom.xml Dependencies

```
<dependency>
  <groupId>org.slf4j</groupId>
  <artifactId>slf4j-api</artifactId>
  <version>1.7.30</version>
</dependency>
<dependency>
  <groupId>ch.qos.logback</groupId>
  <artifactId>logback-classic</artifactId>
  <version>1.2.3</version>
</dependency>
```

logback.xml

```
<configuration>
  <appender name="console"
    class="ch.qos.logback.core.ConsoleAppender">
    <encoder>
      <pattern>
        %d{HH:mm:ss.SSS}
        [%thread]
        %-5level
        %logger{36}
        - %msg%n
      </pattern>
    </encoder>
```

```

</appender>
<appender name="file"
    class="ch.qos.logback.core.FileAppender">
    <file>app.log</file>
    <encoder>
        <pattern>
            %d{HH:mm:ss.SSS}
            [%thread]
            %-5level
            %logger{36}
            - %msg%n
        </pattern>
    </encoder>
</appender>
<root level="debug">
    <appender-ref ref="console"/>
    <appender-ref ref="file"/>
</root>
</configuration>

```

LoggingExample.java

```

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class LoggingExample {

    private static final Logger logger =

        LoggerFactory.getLogger(LoggingExample.class);

    public static void main(String[] args) {

```

```
    logger.info("Application Started");  
    logger.debug("Debug Message");  
    logger.warn("Warning Message");  
    logger.error("Error Message");  
}  
}
```

Output:

```
15:30:01.123 INFO LoggingExample - Application Started  
15:30:01.125 DEBUG LoggingExample - Debug Message  
15:30:01.126 WARN LoggingExample - Warning Message  
15:30:01.128 ERROR LoggingExample - Error Message
```