LAB PRACTICALS (JAN-JUN, 2025)

~	WEDY	NAME OF PRACTICAL	Date	Signature
S. No.	WEEK No.			

Task - 01:

1.Radix sort:

```
#include <iostream>
#include <vector>
#include <algorithm>
using namespace std;
int maximum(const vector<int>& arr) {
    int maxi = 0;
    for(int i : arr){
        maxi = max(maxi,i);
    return maxi;
}
void countingSort(vector<int>& arr, int exp) {
    int n = arr.size();
    vector<int> output(n);
    int count[10] = {0};
    for (int i = 0; i < n; i++)
        count[(arr[i] / exp) % 10]++;
    for (int i = 1; i < 10; i++)
        count[i] += count[i - 1];
    for (int i = n - 1; i >= 0; i--) {
        output[count[(arr[i] / exp) % 10] - 1] = arr[i];
        count[(arr[i] / exp) % 10]--;
    for (int i = 0; i < n; i++)
        arr[i] = output[i];
void radixSort(vector<int>& arr) {
    int maxNum = maximum(arr);
    for (int exp = 1; maxNum / exp > 0; exp *= 10)
        countingSort(arr, exp);
void printArray(const vector<int>& arr) {
    for (int num : arr)
        cout << num << " ";</pre>
    cout << endl;</pre>
}
int main() {
    vector<int> arr = {170, 45, 75, 90, 802, 24, 2, 66};
    cout << "Original array: ";</pre>
    printArray(arr);
    radixSort(arr);
```

```
cout << "Sorted array: ";</pre>
    printArray(arr);
    return 0;
}
 PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3> cd "c:\Users\Ritik gupta\Desktop\
  }
 Original array: 170 45 75 90 802 24 2 66
 Sorted array: 2 24 45 66 75 90 170 802
 PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3>
2.Bucket Sort:
#include <iostream>
#include <vector>
#include <algorithm>
using namespace std;
void bucketSort(vector<float>& arr) {
    int n = arr.size();
    vector<vector<float>> buckets(n);
    for (float num : arr) {
        int index = n * num;
        buckets[index].push_back(num);
    for (auto& bucket : buckets)
        sort(bucket.begin(), bucket.end());
    int idx = 0;
    for (auto& bucket : buckets)
        for (float num : bucket)
            arr[idx++] = num;
void printArray(const vector<float>& arr) {
    for (float num : arr)
        cout << num << " ";
    cout << endl;</pre>
}
int main() {
    vector<float> arr = {0.78, 0.17, 0.39, 0.26, 0.72, 0.94, 0.21, 0.12, 0.23, 0.68};
    cout << "Original array: ";</pre>
    printArray(arr);
    bucketSort(arr);
    cout << "Sorted array: ";</pre>
    printArray(arr);
    return 0;
}
 PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3> cd "c:\Users\Ritik gupta\Desktop\Lab\D.
 Original array: 0.78 0.17 0.39 0.26 0.72 0.94 0.21 0.12 0.23 0.68
 Sorted array: 0.12 0.17 0.21 0.23 0.26 0.39 0.68 0.72 0.78 0.94
```

Task-02

1.Kth Largest element in array:

#include<bits/stdc++.h>

```
using namespace std;
int findk(int arr[] , int size , int k){
    for(int i = 0; i<k; i++){
        int maxi = INT_MIN;
        int max_idx = -1;
        for(int j = 0; j < size; j++){
            if(arr[j] > maxi){
                maxi = arr[j];
                max_idx = j;}
            if(i == k-1){
                return maxi;
            }}
        arr[max_idx] = INT_MIN;}
    return -1;}
int main(){
    int arr[6] = \{2,5,6,3,8,1\};
    int n = 6;
    int k;
    cout<<"Enter value for k: ";</pre>
    cin>>k;
    int ans = findk(arr,n,k);
    cout<<"The Kth largest element is: "<<ans;}</pre>
 PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3> cd "c:\Users\Ritik gupta\Desktop\L
  }
 Enter value for k: 3
 The Kth largest element is: 2
2. Split linked list from middle:
#include<bits/stdc++.h>
using namespace std;
class Node{
    public:
    int data;
    Node* next;
    Node(int data){
        this->data = data;
        next = NULL;
    }};
void insert(Node* &head,int data){
   Node* temp= new Node(data);
   if(head == NULL){
   head = temp;
   return;
   }
   Node* curr = head;
  while(curr->next!=NULL){
   curr = curr->next;
   curr->next = temp;
}
```

```
void print(Node* head){
    while(head!=NULL){
        cout<<head->data<<" ";</pre>
        head = head->next;
    }
    cout<<endl;</pre>
}
void split(Node* head){
    Node* slow = head;
    Node* fast = head->next;
    while(fast!=NULL && fast->next!=NULL){
        slow = slow ->next;
        fast = fast ->next->next;
    Node* head2 = slow->next;
    slow->next = NULL;
    cout<<"First split is: ";</pre>
    print(head);
    cout<<"Second split is: ";</pre>
    print(head2);
int main(){
    Node* head = new Node(10);
    insert(head, 20);
    insert(head, 30);
    insert(head,40);
    insert(head,50);
    insert(head,60);
    insert(head,70);
    cout<<"original Linked list: "<<endl;</pre>
    print(head);
    split(head);
}
 PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3> cd "c:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3\";
 original Linked list:
 10 20 30 40 50 60 70
 First split is: 10 20 30 40
 Second split is: 50 60 70
 PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3>
3. Remove consecutive node with sum zero:
#include<bits/stdc++.h>
using namespace std;
class Node{
    public:
    int data;
    Node* next;
    Node(int data){
        this->data = data;
        next = NULL;
    }
};
```

```
void insert(Node* &head,int data){
   Node* temp= new Node(data);
   if(head == NULL){
   head = temp;
   return;
   }
   Node* curr = head;
   while(curr->next!=NULL){
    curr = curr->next;
   }
   curr->next = temp;
void print(Node* head){
    while(head!=NULL){
        cout<<head->data<<" ";</pre>
        head = head->next;
    }
    cout<<endl;</pre>
}
Node* remove_zero(Node* head){
    int sum = 0;
    Node* ans = head;
    while(head!=NULL){
        sum = sum + head->data;
        if(sum == 0){
            ans = head->next;
        }
        head = head->next;
    return ans;
}
int main(){
    Node* head = new Node(10);
    insert(head, 20);
    insert(head, -30);
    insert(head,40);
    insert(head,70);
    cout<<"original array: ";</pre>
    print(head);
    Node* ans = remove_zero(head);
    cout<<"After removing zero sum: ";</pre>
    print(ans);
}
  PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3> cd "c:\Users\Ritik gupta\Desktop\Lab\DAA
   }
  original array: 10 20 -30 40 70
  After removing zero sum: 40 70
  PS C:\Users\Ritik gupta\Desktop\Lab\DAA\Lab 3>
```