

Program – 7

AIM: To implement 3-Phase Commit client-server.

Introduction and Theory

Three-Phase Commit (3PC) Protocol is an extension of the Two-Phase Commit (2PC) Protocol that avoids blocking problem under certain assumptions. In particular, it is assumed that no network partition occurs, and not more than k sites fail, where we assume ' k ' is predetermined number. With the mentioned assumptions, protocol avoids blocking by introducing an extra third phase where multiple sites are involved in the decision to commit.

Instead of directly noting the commit decision in its persistent storage, the coordinator first ensures that at least ' k ' other sites know that it intended to commit transaction.




Fig-2 the Three-Phase Control Protocol

In a situation where coordinator fails, remaining sites are bound to first select new coordinator. This new coordinator checks status of the protocol from the remaining sites. If the coordinator had decided to commit, at least one of other ' k ' sites that it informed will be up and will ensure that commit decision is respected. The new coordinator restarts third phase of protocol if any of rest sites knew that old coordinator intended to commit transaction. Otherwise, new coordinator aborts the transaction.

Drawback of the Three-Phase Commit Protocol :

- While 3PC protocol has desired property of not blocking unless ' k ' sites fail, it has drawback that partitioning of network may appear to be same as more than ' k ' sites failing, which would lead to blocking.
- The protocol also has to be implemented carefully to ensure that network partitioning does not result in inconsistencies,
- Where transaction is committed in one partition and aborted in another. Because of its overhead, 3PC protocol is not widely used.

Dissemination Phase :

- It is introduced above helps the user to deal with the cases as when either a participant failure or both coordinator and participant node failure during the commit phase.
- The recovery coordinator when it takes over after coordinator failure during Phase-2 of the previous Two-Phase Commit Protocol the new additional phase comes handy as follows.
- On querying participants, if it learns that some nodes are in the commit phase, it then assumes that previous coordinator before crashing has made decision to commit. Hence it can shepherd the protocol to commit.
- Similarly, if a participant responds that it doesn't receive prepare to commit, then new coordinator can assume that previous coordinator failed even before it started the preparation to commit phase.

Program – 7

Code

Server

```
1  #include <sys/socket.h>
2  #include <netinet/in.h>
3  #include <arpa/inet.h>
4  #include <stdio.h>
5  #include <stdlib.h>
6  #include <unistd.h>
7  #include <errno.h>
8  #include <string.h>
9  #include <sys/types.h>
10 #include <time.h>
11 #include <string.h>
12 #define MSG_CONFIRM 0
13
14
15 #define TRUE 1
16 #define FALSE 0
17 #define ML 1024
18 #define MPROC 32
19
20 typedef struct wireless_node
21 {
22     int priority;
23     int parent;
24 } wireless_node;
25
26 wireless_node w;
27
28 int max(int a, int b)
29 {
30     return a >= b? a:b;
31 }
32
33 int connect_to_port(int connect_to)
34 {
35     int sock_id;
36     int opt = 1;
37     struct sockaddr_in server;
38     if ((sock_id = socket(AF_INET, SOCK_DGRAM, 0)) < 0)
39     {
40         perror("unable to create a socket");
41         exit(EXIT_FAILURE);
42     }
43     setsockopt(sock_id, SOL_SOCKET, SO_REUSEADDR, (const void
44 *)&opt, sizeof(int));
45     memset(&server, 0, sizeof(server));
46     server.sin_family = AF_INET;
47     server.sin_addr.s_addr = INADDR_ANY;
48     server.sin_port = htons(connect_to);
49
50     if (bind(sock_id, (const struct sockaddr *)&server,
51 sizeof(server)) < 0)
52     {
53         perror("unable to bind to port");
```

Program – 7

```

54         exit(EXIT_FAILURE);
55     }
56     return sock_id;
57 }
58
59 void send_to_id(int to, int from, char message[ML])
60 {
61     struct sockaddr_in cl;
62     memset(&cl, 0, sizeof(cl));
63
64     cl.sin_family = AF_INET;
65     cl.sin_addr.s_addr = INADDR_ANY;
66     cl.sin_port = htons(to);
67
68     sendto(
69         from, \
70         (const char *)message, \
71         strlen(message), \
72         MSG_CONFIRM, \
73         (const struct sockaddr *)&cl, \
74         sizeof(cl));
75 }
76
77 void begin_commit(int id, int *procs, int num_procs)
78 {
79     int itr;
80     char message[ML];
81     sprintf(message, "%s", "SCMT");
82     for (itr = 0; itr < num_procs; itr++)
83     {
84         printf("Sending begin commit to: %d\n", procs[itr]);
85         send_to_id(procs[itr], id, message);
86     }
87 }
88
89 void announce_action(int self, int *procs, int num_procs, char
90 msg[ML])
91 {
92     int itr;
93
94     for (itr = 0; itr < num_procs; itr++)
95     {
96         send_to_id(procs[itr], self, msg);
97     }
98 }
99
100
101 int main(int argc, char* argv[])
102 {
103     int self = atoi(argv[1]);
104     int n_procs = atoi(argv[2]);
105     int procs[MPROC];
106     int sender, okcnt = 0, nocnt = 0, dncnt = 0;
107     int sock_id, coord_id;
108     int itr, len, n, start, ix;
109
110     char buffer[ML], flag[ML], p_id[ML], msg[256];

```

Program – 7

```

111
112     struct sockaddr_in from;
113
114     for(itr = 0; itr < n_procs; itr += 1)
115         procs[itr] = atoi(argv[3 + itr]);
116     printf("Creating node at %d\n", self);
117     sock_id = connect_to_port(self);
118     begin_commit(sock_id, procs, n_procs);
119     while(TRUE)
120     {
121         sleep(2);
122         memset(&from, 0, sizeof(from));
123         // printf("Tring read\n");
124         n = recvfrom(sock_id, (char *)buffer, ML, MSG_WAITALL,
125 (struct sockaddr *)&from, &len);
126         buffer[n] = '\0';
127         printf("Recieved: %s\n", buffer);
128
129         if (strcmp(buffer, "CMOK") == 0)
130         {
131             okcnt += 1;
132         }
133         else if (strcmp(buffer, "CMNO") == 0)
134         {
135             nocnt += 1;
136         }
137         if ((nocnt + okcnt) == n_procs)
138         {
139             printf("Recieved replies from all clients\n");
140             if (okcnt == n_procs)
141             {
142                 printf("Announcing complete commit\n");
143                 announce_action(sock_id, procs, n_procs, "CDON");
144             }
145             else
146             {
147                 printf("Announcing abort commit\n");
148                 announce_action(sock_id, procs, n_procs, "CABT");
149             }
150         }
151         if (strcmp(buffer, "DONE") == 0)
152         {
153             dncnt += 1;
154             printf("clients confirmed commit\n");
155             if (dncnt == n_procs)
156             {
157                 printf("All process announced commit action\n");
158                 exit(EXIT_SUCCESS);
159             }
160         }
161         // printf("Waiting\n");
162     }
163     return 0;
164 }

```

Program – 7

Client

```
1  #include <sys/socket.h>
2  #include <netinet/in.h>
3  #include <arpa/inet.h>
4  #include <stdio.h>
5  #include <stdlib.h>
6  #include <unistd.h>
7  #include <errno.h>
8  #include <string.h>
9  #include <sys/types.h>
10 #include <time.h>
11 #include <string.h>
12 #define MSG_CONFIRM 0
13
14
15 #define TRUE 1
16 #define FALSE 0
17 #define ML 1024
18 #define MPROC 32
19
20 typedef struct wireless_node
21 {
22     int priority;
23     int parent;
24 } wireless_node;
25
26 wireless_node w;
27
28 int max(int a, int b)
29 {
30     return a >= b? a:b;
31 }
32
33 int connect_to_port(int connect_to)
34 {
35     int sock_id;
36     int opt = 1;
37     struct sockaddr_in server;
38     if ((sock_id = socket(AF_INET, SOCK_DGRAM, 0)) < 0)
39     {
40         perror("unable to create a socket");
41         exit(EXIT_FAILURE);
42     }
43     setsockopt(sock_id, SOL_SOCKET, SO_REUSEADDR, (const void
44 *)&opt, sizeof(int));
45     memset(&server, 0, sizeof(server));
46     server.sin_family = AF_INET;
47     server.sin_addr.s_addr = INADDR_ANY;
48     server.sin_port = htons(connect_to);
49
50     if (bind(sock_id, (const struct sockaddr *)&server,
51 sizeof(server)) < 0)
52     {
53         perror("unable to bind to port");
54         exit(EXIT_FAILURE);
55     }
```

Program – 7

```

56     return sock_id;
57 }
58
59 void send_to_id(int to, int from, char message[ML])
60 {
61     struct sockaddr_in cl;
62     memset(&cl, 0, sizeof(cl));
63
64     cl.sin_family = AF_INET;
65     cl.sin_addr.s_addr = INADDR_ANY;
66     cl.sin_port = htons(to);
67
68     sendto(
69         from, \
70         (const char *)message, \
71         strlen(message), \
72         MSG_CONFIRM, \
73         (const struct sockaddr *)&cl, \
74         sizeof(cl));
75 }
76
77 void begin_commit(int id, int *procs, int num_procs)
78 {
79     int itr;
80     char message[ML];
81     sprintf(message, "%s", "SCMT");
82     for (itr = 0; itr < num_procs; itr++)
83     {
84         printf("Sending begin commit to: %d\n", procs[itr]);
85         send_to_id(procs[itr], id, message);
86     }
87 }
88
89 void announce_action(int self, int *procs, int num_procs, char
90 msg[ML])
91 {
92     int itr;
93
94     for (itr = 0; itr < num_procs; itr++)
95     {
96         send_to_id(procs[itr], self, msg);
97     }
98 }
99
100
101 int main(int argc, char* argv[])
102 {
103     int self = atoi(argv[1]);
104     int server = atoi(argv[2]);
105     char *action = argv[3];
106     int sender, okcnt = 0, nocnt = 0, dncnt = 0;
107     int sock_id, coord_id;
108     int itr, len, n, start, ix;
109     char buffer[ML], flag[ML], p_id[ML], msg[256];
110     struct sockaddr_in from;
111     printf("Creating node at %d\n", self);
112     sock_id = connect_to_port(self);


```

Program – 7

```
113     while(TRUE)
114     {
115         sleep(2);
116         memset(&from, 0, sizeof(from));
117         // printf("Tring read\n");
118         n = recvfrom(sock_id, (char *)buffer, ML, MSG_WAITALL,
119 (struct sockaddr *)&from, &len);
120         buffer[n] = '\0';
121         printf("Recieved: %s\n", buffer);
122         if (strcmp(buffer, "SCMT") == 0)
123         {
124             printf("Sending %s to server\n", action);
125             send_to_id(server, sock_id, action);
126         }
127         else if (strcmp(buffer, "CDON") == 0)
128         {
129             printf("Got complete commit, committing to logs\n");
130             send_to_id(server, sock_id, "DONE");
131             exit(EXIT_FAILURE);
132         }
133         else if (strcmp(buffer, "CABT") == 0)
134         {
135             printf("Got abort commit, deleting updates\n");
136             send_to_id(server, sock_id, "DONE");
137             exit(EXIT_FAILURE);
138         }
139         // printf("Waiting\n");
140     }
141     return 0;
142 }
143
```

Program – 7

Results and Outputs:



```
(ml) Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10s 8000 4 8001 8002 8003 8004
Creating node at 8000
Sending begin commit to: 8001
Sending begin commit to: 8002
Sending begin commit to: 8003
Sending begin commit to: 8004
Received: CMOK
Received: CMOK
Received: CMOK
Received: CMOK
Received replies from all clients
Announcing complete commit
Received: DONE
Received replies from all clients
Announcing complete commit
147996507 clients confirmed commit
Received: DONE
Received replies from all clients
Announcing complete commit
147996507 clients confirmed commit
Received: DONE
Received replies from all clients
Announcing complete commit
147996507 clients confirmed commit
Received: DONE
Received replies from all clients
Announcing complete commit
147996507 clients confirmed commit
All process announced commit action
(ml) Anurags-MacBook-Air:DiSLAB jarvis$

Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8001 8000 CMOK
Creating node at 8001
Received: SCMT
Sending CMOK to server
Received: CDON
Got complete commit, committing to logs
Anurags-MacBook-Air:DiSLAB jarvis$

Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8002 8000 CMOK
Creating node at 8002
Received: SCMT
Sending CMOK to server
Received: CDON
Got complete commit, committing to logs
Anurags-MacBook-Air:DiSLAB jarvis$

Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8004 8000 CMOK
Creating node at 8004
Received: SCMT
Sending CMOK to server
Received: CDON
Got complete commit, committing to logs
Anurags-MacBook-Air:DiSLAB jarvis$

Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8003 8000 CMOK
Creating node at 8003
Received: SCMT
Sending CMOK to server
Received: CDON
Got complete commit, committing to logs
Anurags-MacBook-Air:DiSLAB jarvis$
```

Figure 1 Normal Operation

Program – 7

```
[[ml] Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10s 8000 4 8001 8002 8003 8004 ]
Creating node at 8000
Sending begin commit to: 8001
Sending begin commit to: 8002
Sending begin commit to: 8003
Sending begin commit to: 8004
Receieved: CMOK
Receieved: CMOK
Receieved: CMOK
Receieved: CMNO
Receieved replies from all clients
Announcing abort commit
Receieved: DONE
Receieved replies from all clients
Announcing abort commit
42020699 clients confirmed commit
Receieved: DONE
Receieved replies from all clients
Announcing abort commit
42020699 clients confirmed commit
Receieved: DONE
Receieved replies from all clients
Announcing abort commit
42020699 clients confirmed commit
All process announced commit action
(ml) Anurags-MacBook-Air:DiSLAB jarvis$

[Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8001 8000 CMOK ]
Creating node at 8001
Receieved: SCMT
Sending CMOK to server
Receieved: CABT
Got abort commit, deleting updates
Anurags-MacBook-Air:DiSLAB jarvis$

[Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8002 8000 CMOK ]
Creating node at 8002
Receieved: SCMT
Sending CMOK to server
Receieved: CABT
Got abort commit, deleting updates
Anurags-MacBook-Air:DiSLAB jarvis$

[Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8004 8000 CMNO ]
Creating node at 8004
Receieved: SCMT
Sending CMNO to server
Receieved: CABT
Got abort commit, deleting updates
Anurags-MacBook-Air:DiSLAB jarvis$

[Anurags-MacBook-Air:DiSLAB jarvis$ ./outs/l10c 8003 8000 CMOK ]
Creating node at 8003
Receieved: SCMT
Sending CMOK to server
Receieved: CABT
Got abort commit, deleting updates
Anurags-MacBook-Air:DiSLAB jarvis$
```

Figure 2 Abort Operation

Findings and Learnings:

1. We successfully implemented 3-phase commit.