```
Dt: 18/11/2024(Day-43)
*imp
=>The following are the implicit Objects generated in JSP:
 1.application - jakarta.servlet.ServletContext
 2.config
            - jakarta.servlet.ServletConfig
 3.request - jakarta.servlet.http.HttpServletRequest
 4.response - jakarta.servlet.http.HttpServletResponse
 5.out
           - jakarta.servlet.jsp.JspWriter
             - jakarta.servlet.http.HttpSession
 6.session
 7.exception - java.lang.Exception
 8.page
            - java.lang.Object
 9.pageContext - jakarta.servlet.jsp.PageContext
Ex-2:
(Construct JSP Application to demonstrate < isp:include>,
<jsp:forward> and <jsp:param>
Layout:
ProjectName: JSP_App_
input.html
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
```

</head>

```
<body>
<form action="Choice.jsp" method="post">
Enter the value-1:<input type="text" name="v1"><br>
Enter the value-2:<input type="text" name="v2"><br>
<input type="submit" value="Add" name="s1">
<input type="submit" value="Sub" name="s1">
</form>
</body>
</html>
web.xml
<?xml version="1.0" encoding="UTF-8"?>
<web-app>
   <welcome-file-list>
        <welcome-file>input.html</welcome-file>
   </welcome-file-list>
</web-app>
Choice.jsp
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"</pre>
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<%
String s1 = request.getParameter("s1");
if(s1.equals("Add")){
<jsp:forward page="Addition.jsp">
   <jsp:param value="<%=100 %>" name="k"/>
</jsp:forward>
<%
}else{
%>
   <jsp:forward page="Subtraction.jsp">
       <jsp:param value="<%=200 %>" name="z"/>
   </jsp:forward>
 <%
}
%>
```

```
</body>
</html>
Addition.jsp
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"</pre>
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<%
int v1 = Integer.parseInt(request.getParameter("v1"));
int v2 = Integer.parseInt(request.getParameter("v2"));
int k = Integer.parseInt(request.getParameter("k"));
int v3 = v1+v2;
out.println("Sum:"+v3+"<br>");
out.println("Parameter Value:"+k+"<br>");
<jsp:include page="input.html"/>
</body>
</html>
Subtraction.jsp
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"</pre>
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<%
int v1 = Integer.parseInt(request.getParameter("v1"));
int v2 = Integer.parseInt(request.getParameter("v2"));
int z = Integer.parseInt(request.getParameter("z"));
int v3 = v1 - v2;
out.println("Sum:"+v3+"<br>");
out.println("Parameter value:"+z+"<br>");
<jsp:include page="input.html"/>
</body>
</html>
```

ssignment:
pdate above application to handle exception for NonInteger values.
•
40,3