```
Dt: 9/11/2024(Day-38)
EditProduct.jsp(Edited Code)
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"</pre>
    pageEncoding="ISO-8859-1"
    import="test.*"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<%
AdminBean ab = (AdminBean)session.getAttribute("abean");
ProductBean pb = (ProductBean)request.getAttribute("pbean");
out.println("Page belongs to Admin:"+ab.getfName()+"<br>");
%>
<form action="update" method="post">
<input type="hidden" name="pcode" value=<%=pb.getCode() %>>
ProductPrice:<input type="text" name="price" value=<%=pb.getPrice() %>><br>
ProductQty:<input type="text" name="qty" value=<%=pb.getQty() %>><br>
<input type="submit" value="UpdateProduct">
</form>
</body>
</html>
UpdateProductDAO.java
package test;
import java.sql.*;
public class UpdateProductDAO {
    public int k=0;
    public int updateProduct(ProductBean pb) {
      try {
            Connection con = DBConnection.getCon();
            PreparedStatement ps = con.prepareStatement
                        ("update Product67 set price=?,qty=? where code=?");
            ps.setFloat(1, pb.getPrice());
            ps.setInt(2, pb.getQty());
            ps.setString(3, pb.getCode());
            k = ps.executeUpdate();
      }catch(Exception e) {
            e.printStackTrace();
      return k;
    }
}
```

```
UpdateProductServlet.java
package test;
import java.io.*;
import java.util.*;
import jakarta.servlet.*;
import jakarta.servlet.http.*;
import jakarta.servlet.annotation.*;
@SuppressWarnings("serial")
@WebServlet("/update")
public class UpdateProductServlet extends HttpServlet
{
       @SuppressWarnings("unchecked")
       @Override
 protected void doPost(HttpServletRequest req,HttpServletResponse res)throws ServletException,
 IOException
         HttpSession hs = req.getSession(false);//Accessing Existing Session
         if(hs==null) {
                 req.setAttribute("msg","Session Expired...<br>");
                 req.getRequestDispatcher("Msg.jsp").forward(req, res);
         }else {
                ArrayList<ProductBean> al = (ArrayList<ProductBean>)hs.getAttribute("alist");
                 String pCode = req.getParameter("pcode");
                 Iterator<ProductBean> it = al.iterator();
```

```
while(it.hasNext()) {
                      ProductBean pb = (ProductBean)it.next();
                      if(pCode.equals(pb.getCode())) {
                            pb.setPrice(Float.parseFloat(req.getParameter("price")));
                            pb.setQty(Integer.parseInt(req.getParameter("qty")));
                            int k = new UpdateProductDAO().updateProduct(pb);
                            if(k>0) {
                                   req.setAttribute("msg","Product Updated
Successfully...<br>");
                                   req.getRequestDispatcher("UpdateProduct.jsp").forward(req,
res);
                            }//end of if
                            break;
                      }//end of if
               }//end of loop
        }
 }
}
UpdateProduct.jsp
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"</pre>
    pageEncoding="ISO-8859-1"
    import="test.*"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
AdminBean ab = (AdminBean)session.getAttribute("abean");
String msg = (String)request.getAttribute("msg");
out.println("Page belongs to Admin:"+ab.getfName()+"<br>");
```

```
out.println(msg);
%>
<a href="Product.html">AddProduct</a>
<a href="view">ViewAllProducts</a>
<a href="logout">Logout</a>
</body>
</html>
LogoutServlet.java
package test;
import java.io.*;
import jakarta.servlet.*;
import jakarta.servlet.http.*;
import jakarta.servlet.annotation.*;
@SuppressWarnings("serial")
@WebServlet("/logout")
public class LogoutServlet extends HttpServlet{
       @Override
protected void doGet(HttpServletRequest req, HttpServletResponse res)throws ServletException,
IOException
{
        HttpSession hs = req.getSession(false);//Accessing Existing Session
        if(hs==null) {
                req.setAttribute("msg","Session Expired...<br>");
                req.getRequestDispatcher("Msg.jsp").forward(req, res);
        }else {
                hs.removeAttribute("abean");
                hs.removeAttribute("alist");
                hs.invalidate();
```

```
req.getRequestDispatcher("Logout.jsp").forward(req, res);
       }
}
}
Logout.jsp
<%@ page Language="java" contentType="text/html; charset=ISO-8859-1"</pre>
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<%
out.println("Logged out Successfully...<br>");
<%@include file="home.html"%>
</body>
</html>
```