

In Log4J 3 important objects are there

(a) Logger object

(b) Appender Object

(c) Layout object

Logger object

=>Appender and Layout Objs must be linked with Logger obj directly or indirectly

=> Enables the logging on given class

=> allows to generate log message having different categories

=> Allows to specify logger level towards retrieving the log messages

Appender object

eg:: `Logger logger= Logger.getLogger(SelectTest.class);`

=> Will be linked with Logger object to specify the destination place to write/record log messages eg::

FileAppender, ConsoleAppender, Rolling FileAppender, DailyRollingFileAppender, JdbcAppender, IMapAppender and etc..

(best)

(assume max size is 30 MB)

info.log.1

info.log. 2

info.log.3

Rolling FileAppender

info.log

The class on which we want to enable the Logging

=>IMapAppender writes the log messages to email accounts as email messages =>JdbcAppender writes the log messages to DB s/w

(30MB) (30MB)

(30MB)

DailyRollingFileAppender

info.log_22-04-2025

(The log files will be created on hourly/daily/monthly/ /.../... in other ways) info.log_21-04-2025

info.log_20-04-2025

info.log_19-04-202:5

J

localhost.2023-06-27

localhost.2023-06-28

localhost.2023-06-29

localhost.2023-07-03

localhost.2023-07-04

localhost.2023-08-09

localhost.2023-09-09

localhost.2023-09-19 localhost.2023-09-21

Layout object

=====

=>This object specifies the format to be used while writing the log messages specifies

=> This object the content and the order content that should come in the log messages

eg:: SimpleLayout, HTMLLayout, XMLLayout, PatternLayout

Application

--> we can customize the format and content of the log messages

Layout objec

log messages

Logger object

Appender obj

Log destinations(file/console/...)

...

log messages

The log messages given to Logger obj will be written to destination Log files through appender obj according the format specified by the Layout object

SLF4J

(Simple Logging Façade for Java)

on

=>To work with different logging tools, we need to use different apis.. So moving from 1 logging tool to another logging tool becomes very difficult to overcome this problem SLF4J is given which provides abstraction multiple logging tools or api and provides unified api to work any logging tool/api

Log4J (TV remote)

SLF4

(universal remote)

logback apache common-logging (AC remote)

(DTH Remote)

High level architecture of SLF4J

SLF4J unbound application

SLF4J bound to logback-classic

application

SLF4J bound to

log4j (best)

application

SLF4J bound to java.util.logging

application

SLF4J bound to simple application

SLF4J bound to no-operation

application

SLF4J API slf4j-api.jar

SLF4J API slf4j-api.jar

SLF4J API slf4j-api.jar

SLF4J API slf4j-api.jar

SLF4J API slf4j-api.jar

SLF4J API slf4j-api.jar

/dev/null

Underlying logging

Adaptation layer

Adaptation layer

Underlying

framework

logback-classic.jar logback-core.jar

bridge jar file slf4j-log4j12.jar

bridge jar file slf4j-jdk14.jar

Underlying logging framework

A

A invoking

software located

in B

B

x.jar

artifact available in classpath

x.jar SLF4J binding artifact available in classpath

Underlying logging framework

Underlying logging framework

log4j.jar

JVM runtime

non-native implementation

abstract logging api

native implementation

of slf4j-api (Given by SLESJ itself)

adaptation layer (Bridge Layer)

of slf4j-api

Binding with a logging framework at deployment time

logging framework slf4j-simple.jar

(slf4j itself providing the implementation)

slf4j-nop.jar

/dev/null

- SLF4J NOP binding is essentially a dummy or no-op implementation - meaning when you use this binding, all log calls will effectively do nothing. No logs will be written anywhere.

SLF4J Simple is a very lightweight logging backend that comes with SLF4J. Unlike NOP (which does

(Given by third party APIs) nothing), Simple actually prints log messages to the console (stdout).

It's useful when you want basic logging without adding bigger frameworks like Logback or Log4j.

As mentioned previously, SLF4J supports various logging frameworks. The SLF4J distribution ships with several jar files referred to as "SLF4J bindings", with each binding corresponding to a supported framework.

slf4j-log4j12-1.7.28.jar

Binding for log4j version 1.2, a widely used logging framework. You also need to place log4j.jar on your class path.

slf4j-jdk14-1.7.28.jar

Binding for java.util.logging, also referred to as JDK 1.4 logging

slf4j-nop-1.7.28.jar

Binding for NOP, silently discarding all logging.

slf4j-simple-1.7.28.jar

(kills all the log messages)

Binding for Simple implementation, which outputs all events to System.err. Only messages of level INFO and higher are printed. This binding may be useful in the context of small applications.

slf4j-jcl-1.7.28.jar

Binding for Jakarta Commons Logging. This binding will delegate all SLF4J logging to JCL.

logback-classic-1.2.3.jar (requires logback-core-1.2.3.jar)

NATIVE IMPLEMENTATION There are also SLF4J bindings external to the SLF4J project, e.g. logback which implements SLF4J natively.

Logback's `ch.qos.logback.classic.Logger` class is a direct implementation of SLF4J's `org.slf4j.Logger` interface.

if no logging api/tool is

specified for slf4j then internally uses logback by default

we can give instructions to slf4j and slf4j integrated with

log4j either using properties file(best) or using

xml file (not so recommended)

=> Log4j Logger object is useful for

a) To enable logging on particular class

b) To categorize log messages

c) To filter log messages

=> Log4j Appender object is useful to write/record the log messages to different destinations

=> Log4j Layout object is useful to format the log messages

The logger levels of SLF4J are

debug<info<trace<warn<error

(no fatal here)

=>for user activity related event handling based code execution will be logged with the support of "trace" log message (Auditing activities) Button is clicked --> actionPerformed(-) method executed --> this can be logged through "trace" level

=> The code execution related to user signedIn and user signed out can be kept tracked /logged using trace logger level

Logger class that is given in SLF4J and in other logging apis is singleton java class i.e it allows us to create single object per JVM singleton ==> single (one) ton(object), So singleton means single object

Procedure to add SLF4J with log4j 1.x support to Java App for logging

=====

step1) Add the following jar files to the CLASSPATH or build path

> 010 slf4j-api-1.7.30.jar - C:\Us

>log4j-1.2.17 (1).jar - C:\Us

> l slf4j-log4j12-1.7.30.jar - C

> ojdbc6.jar

we can add in pom.xml

as maven dependencies

<https://mvnrepository.com/artifact/org.slf4j/slf4j-log4j12/1.7.31>

<https://mvnrepository.com/artifact/log4j/log4j/1.2.17>

<https://mvnrepository.com/artifact/org.slf4j/slf4j-api/1.7.31>

step2) place log4j.properties file in "src" folder..

log4j.properties

=====

(src/main/java folder)

#For HTMLLaout and FileAppender

#specify Logger level to retrieve the log messages

log4j.rootLogger=DEBUG,R

#specify appender

log4j.appender.R=org.apache.log4j.FileAppender

#Specify file name

log4j.appender.R.File=info.html

#Disabling append mode on file

log4j.appender.R.append=true

#sepcify layaout

log4j.appender.R.layout=org.apache.log4j.HTMLLayout

step3) Develop any Java app having SLF4J based log messages

//SelectTest2.java

package com.nt.jdbc;

import java.sql.Connection;

import java.sql.DriverManager;

import java.sql.ResultSet;

import java.sql.SQLException;

import java.sql.Statement;

import org.slf4j.Logger;

ojdbc8.jar

SLF4JWithLog41.xProj

✓ src

✓ com.nt.jdbc

=>In any Logging api or Logging framework based Logging activities we need to work with Logger object

> Select Test2.java

log4j.properties

object

This Logger can be used in multiple ways

a) To enable Logging on certain class

b) To write the log messages having different categories /priorities

> JRE System Library [JavaSE-15] Referenced Libraries >log4j-1.2.17 (2).jar - C:\Users\Nareshit\Do

>slf4j-log4j12-1.7.31.jar - C:\Users\Nareshit >slf4j-api-1.7.31.jar - C:\Users\Nareshit\Do > I ojdbc6.jar -

C:\oraclexe\app\oracle\produ info.html

logger.info(".

logger.debug(".

."); .")

logger.trace("..");

logger.error(".....") and etc..

In pom.xml (the dependencies are)

<!-- https://mvnrepository.com/artifact/org.slf4j/slf4j-log4j12 --> <dependency>

<groupId>org.slf4j</groupId>

<artifactId>slf4j-log4j12</artifactId>

```

<version>1.7.30</version>
</dependency>
<!-- https://mvnrepository.com/artifact/log4j/log4j -->
<dependency>
<groupId>log4j</groupId>
<artifactId>log4j</artifactId>
<version>1.2.17</version>
</dependency>
<!-- https://mvnrepository.com/artifact/com.oracle.jdbc/ojdbc8 --> <dependency>
<groupId>com.oracle.jdbc</groupId>
<artifactId>ojdbc8</artifactId>
<version>19.3.0.0</version>
</dependency>
<!-- https://mvnrepository.com/artifact/org.slf4j/slf4j-api -->
<dependency>
<groupId>org.slf4j</groupId>
<artifactId>slf4j-api</artifactId>
<version>1.7.30</version>
</dependency>
import org.slf4j.LoggerFactory;
public class SelectTest2
{
It is built-in property
of type java.lang.Class
private static Logger logger=LoggerFactory.getLogger(SelectTest2.class);
public static void main(String args[]){
logger.debug("SelectTest:: start of main(-) method");
Current Class name
giving the object
of the java.lang.Class holding the class name
given
Connection con=null;
Statement st=null;
ResultSet rs=null;
try {
//Load jdbc driver class
//establish the connection (Road)

```

```

Class.forName("oracle.jdbc.driver.Oracle Driver");
logger.debug("com.nt.jdbc.SelectTest:: JDBC driver driver class loaded");
con=DriverManager.getConnection("jdbc:oracle:thin:@localhost:1521:xe",
"system", "manager");
logger.info("com.nt.jdbc.SelectTest:: Connection is established with DB s/w"); //create JDBC Statement
object (vechicle)
if(con!=null) {
st=con.createStatement();
logger.debug("com.nt.jdbc.SelectTest: JDBC Statement object is created");
}
//Send and execute SQL SELECT Query in Db s/w and get JDBC ResultSet object
if(st!=null) {
rs= st.executeQuery("SELECT * FROM STUDENT");
logger.debug("com.nt.jdbc.SelectTest: SQL query is send to Db s/w for execution and ResultSet obj is
generated");
}
if(rs!=null) {
//process the ResultSet object
while(rs.next()!=false){ // while(rs.next()==true)
// System.out.println(rs.getInt(1)+" "+rs.getString(2)+" "+ rs.getString(3)+" "+rs.getFloat(4));
//System.out.println(rs.getInt("SNO")+" "+rs.getString("SNAME")+" "+ rs.getString("SADD")+"
"+rs.getFloat("AVG"));
//System.out.println(rs.getString("SNO")+" "+rs.getString("SNAME")+" "+rs.getString("SADD")+"
"+rs.getString("AVG"));
System.out.println(rs.getString(1)+" "+rs.getString(2)+" "+ rs.getString(3)+" "+rs.getString(4));
} //while
logger.warn("com.nt.jdbc.SelectTest:: The records are ResultSet obj are retrived using getStrting(-) for all
cols ..change them accordingly"); logger.debug("com.nt.jdbc.SelectTest::ResultSet obj is processed");
} //if
} //try
catch(SQLException se) {
}
se.printStackTrace();
logger.error("com.nt.jdbc.SelectTest:: known DB Problem ::"+se.getMessage()+" SQL error
code"+se.getErrorCode());
catch (Exception e) {
e.printStackTrace();
logger.error("com.nt.jdbc.SelectTest:: unknown Problem "+e.getMessage());
}
}

```



```

finally {
logger.debug("com.nt.jdbc.SelectTest: Closing JDBC objs");
//close jdbc objs
try {
if(rs!=null)
rs.close();
logger.debug("com.nt.jdbc.SelectTest: ResultSet obj is closed");
}
catch(SQLException se) {
se.printStackTrace();
logger.error("com.nt.jdbc.SelectTest: Problem in closing ResultSet obj "+se.getMessage());
}
try {
if(st!=null)
st.close();
logger.debug("com.nt.jdbc.SelectTest: Statement obj is closed");
}
catch(SQLException se) {
se.printStackTrace();
logger.error("com.nt.jdbc.SelectTest: Problem in closing Statement obj "+se.getMessage());
}
try {
if(con!=null)
con.close();
logger.debug("com.nt.jdbc.SelectTest: Connection obj is closed");
}
catch(SQLException se) {
se.printStackTrace();
logger.error("com.nt.jdbc.SelectTest: Problem in closing Connection obj "+se.getMessage());
}
}finally
logger.debug("com.nt.jdbc.SelectTest: end of main(-) method");
}main
}///class

```

note:: Here SLFJ generated the log messages by using log4j setup internally based on the instructions collected from the log4j.properties file.

uses

note: spring boot internally slf4j with log4j to generate log messages.. we can control these log messages through application.properties file..

=>Built-in reference variables in Java are "this","super".

=>Built-in threads in java are "main","gc" (garbage collector) =>Built-in streams in java are "System.in","System.out","System.err"

=>Built-in properties in java are "class","length"

length (useful to get the length of the array)

```
int a[]=new int[]{10,20,30};
```

```
int size=a.length; //gives the size of the array
```

class (gives the object of java.lang.Class)

```
Class c1=Test.class; Class c2=java.util.Date.class; obj of java.lang.Class
```

Test class info

--> class name,

-->super class name

"class" is the static property that will be

added by the java compiler in every java class automatically and dynamically.. this property gives object of java.lang.Class having the meta data of the given class object of java.lang.Class java.util.Date class info

-->class name -->super class name

|-->method details

MetaData about Test class

|--->constructor details

|--->

|-->

In a running java app,

=> we use numeric variables (int,long,short and etc..) to hold the numeric values

=> we use floating variables(float,double) to hold floating point values

=> we use String variables to hold text content

=> Similarly we can use the object of java.lang.Class to hold java class/interface/Enum/annotation/.. and its metadata

In LoggerFactory.getLogger(-) method,we are passing SelectTest.class that means

we are passing the object of java.lang.Class having SelectTest class and its meta data..

Project using maven

```
SL4FJProj01-SL4FJWithLog4J
```

```
src/main/java
```

```
com.nt.service
```

```
> SelectTest.java
```

```
log4j.properties
```

```
> src/test/java
```

> JRE System Library [JavaSE-17]

Maven Dependencies

> junit-4.11.jar - C:\Users\NATARAJ\.m2\repository\junit\junit\4.1

> hamcrest-core-1.3.jar - C:\Users\NATARAJ\.m2\repository\org\

> slf4j-log4j12-1.7.30.jar - C:\Users\NATARAJ\.m2\repository\org\

> log4j-1.2.17.jar - C:\Users\NATARAJ\.m2\repository\log4j\log4j

> ojdbc8-19.3.0.0.jar - C:\Users\NATARAJ\.m2\repository\com\or

>

>

ucp-19.3.0.0.jar - C:\Users\NATARAJ\.m2\repository\com\orac

oraclepki-19.3.0.0.jar - C:\Users\NATARAJ\.m2\repository\com\

> osdt_cert-19.3.0.0.jar - C:\Users\NATARAJ\.m2\repository\com\

> osdt_core-19.3.0.0.jar - C:\Users\NATARAJ\.m2\repository\com'

> simplefan-19.3.0.0.jar - C:\Users\NATARAJ\.m2\repository\com'

> ons-19.3.0.0.jar - C:\Users\NATARAJ\.m2\repository\com\oracle

> slf4j-api-1.7.30.jar - C:\Users\NATARAJ\.m2\repository\org\slf4j

> src

> target

info_log.html

pom.xml

sample info_log.html

Log session start time Sat Sep 23 10:10:07 IST 2023

Category

com.nt.service.SelectTest com.nt.service.SelectTest com.nt.service.SelectTest

Time

Thread

Level

0

main

DEBUG

2

main

DEBUG

160

main

INFO

440

main

INFO

509

main

INFO

com.nt.service.SelectTest

540

main

INFO

com.nt.service.SelectTest

543

main

INFO

com.nt.service.SelectTest

543

main

DEBUG

com.nt.service.SelectTest

com.nt.service.SelectTest

Message

start of main(-) method

start of try block

JDBC driver class is loaded Connection is established PreparedStatement obj is created

JDBC ResultSet object is created JDBC ResultSEt object processed

end of try block

log4j.rootLogger=ALL,R

log4j.appender.R=org.apache.log4j.FileAppender

Entries in log4.properties (For writing the log messages to XML file)

To work with XMLLayout and FileAppender

#Specify the logger level to retrieve the log messages

log4j.appender.R.File=info_log1.xml

Log output

Conversion

Performance

Character

log4j.appender.R.append=true

Priority (level)

P

Fast

log4j.appender.R.layout=org.apache.log4j.xml.XMLLayout

New line separator Thread name

n

Fast

t

Fast

Time elapsed (milliseconds)

Γ

Fast

Thread's nested diagnostic context

X

Fast

log4j.properties (For ConsoleAppender and PatternLayout)

Thread's mapped diagnostic context

x

Fast

Percent sign

%%

Fast

To work with PatternLayout and ConsoleAppender

Category name (or logger name)

c

Fast

log4j.rootLogger=ALL,R

Log message

m

Fast

log4j.appender.R=org.apache.log4j.ConsoleAppender

Fully qualified class name

C

Slow

Date and time

d

Slow if using JDK's formatters.

log4j.appender.R.Target=System.out

log4j.appender.R.layout=org.apache.log4j.PatternLayout

d{format}

Fast if using log4j's formatters.

log4j.appender.R.layout.Conversion Pattern=%p-%t-%r-%c-%m-%d-%n

File name of Java class

F

Extremely slow

Location (class, method and line number)

Extremely slow

note:: Pattern Layout allows to specify the order of content that we want to see in log message.

Line number only Method name

L

Extremely slow

M

Extremely slow

popular log4j layout is :: PatternLayout

log4j.properties (For Working with RollingFileAppender and PatternLayout)

RollingFileAppender allows us to specify max size for the log file .. once that max file size is reached, the backup files will be recreated..

To work with PatternLayout and RollingFileAppender

log4j.rootLogger=ALL,R

log4j.appender.R=org.apache.log4j.RollingFileAppender

log4j.appender.R.File=roll_info_log.txt

log4j.appender.R.Append=true

note:: Any Layout can be used with any Appender by applying basic common sense

roll_info_log.txt

roll_info_log.txt .1

roll_info_log.txt.2

... ..

log4j.appender.R.Immediate Flush=true

log4j.appender.R.MaxFileSize=5KB

log4j.appender.R.MaxBackupIndex=3

log4j.appender.R.layout=org.apache.log4j.PatternLayout

log4j.appender.R.layout.ConversionPattern=%p-%-%-%-%-m-%d-%n

current file

...

...
... ..

5KB

roll_info_log.txt .3

.....

...

5KB

5KB

Example on DailyRollingFileAppender and PatternLayout

=====

Using DailyRollingFileAppender and PatternLayout

specify the Logger Level to retrieve the Log message

log4j.rootLogger=DEBUG,R

###specify the appender name

log4j.appender.R=org.apache.log4j.Daily RollingFileAppender

###specify the file name

log4j.appender.R.File=d_roll_log_info.txt

enable the append mode

log4j.appender.R.File.Append=true

#Date pattern

log4j.appender.R.Date Pattern='yyyy-MM-dd-HH-mm

#enable the immediateFlush

log4j.appender.R.immediate Flush=true

###Specify the Layout

log4j.appender.R.layout=org.apache.log4j.PatternLayout

###Specify the Conversion Pattern

log4j.appender.R.layout.Conversion Pattern=%p - %t - %c -% -%d-%m%n

-yyyy-MM -->gives every month one log file

- "yyyy-MM-dd ---->gives every day one log file

· "yyyy-MM-dd-HH -->gives every hour one log file

- "yyyy-MM-dd-HH-mm

----> gives every minute one log file

--.'yyyy-ww---> gives every week one log file

-- '.'yyyy-MM-dd-a---> gives log file every midday

and midnight

In Real Projects, we generally deal with two log files

a) Common Log file1 ---- To record all the log messages of all the levels (Logger Level is:: DEBUG)

b) Error Log file2 ----->To record only Exception/Error related log messages (Logger Level is :: ERROR)

Log4j.properties (To deal with multiple log files)

#Working with multiple log files and Loggers in one Application

log4j.rootLogger=ALL,R

log4j.logger.com.nt.main

For All log messages

=ERROR, E

log4j.appender.R=org.apache.log4j.FileAppender

log4j.appender.R.File=droll_info_log.txt

log4j.appender.R.Append=true

log4j.appender.R.Immediate Flush=true

log4j.appender.R.layout=org.apache.log4j.PatternLayout

R ---> For all log messages to a common Log file (Logger Level is DEBUG)

E ---> For Error log messages to a Error Log file (Logger Level is ERROR)

log4j.appender.R.layout.Conversion Pattern=%p- %t-%r-%c-%m-%d-% -%n

For Exception log messages

log4j.appender.E=org.apache.log4j.DailyRollingFileAppender

log4j.appender.E.File=droll_info_log_errors.txt

log4j.appender.E.DatePattern='.' yyyy-MM-dd-HH-mm

log4j.appender.E.Append=true

log4j.appender.E.Immediate Flush=true

log4j.appender.E.layout=org.apache.log4j.PatternLayout

log4j.appender.E.layout.Conversion Pattern-%-%%-%%-%%m-%d-% -%n

FAQS

Q) What is Logging?

Q) what is the difference b/w logging and auditing?

Q) What are problems with System.out.println(-) based logging operations?

Q) List out various Logging APIs/Tools/Frameworks?

Q) How SLF4J is different from regular Log4j and other Logging tools

Q) What is the default Logging API that is linked with SLF4J

Logger Levels and their usecases?

Q) Explain different

Q)

Explain Different Appenders

Q) Explain different Layouts

Q) Explain Logger Object

Q) Advantages

of doing Logging using various logging tools over System.out.println(-)?

Q) What is the need of two different logging files in Realtime Projects Development?

Q) What is difference b/w Rolling FileAppender and DailyRolling FileAppender?

Q) List out various details about PatternLayout

Q) Explain the format specifiers of the PatternLayout

Q) While integrating log4j with SLF4J what is file that we need to use to provide configurations?
(log4j.properties or log4j.xml)

Q) What is the popular Appender and Layout that will be used in Logging operations?
(DailyRollingFileAppender and PatternLayout)

Q) What is HtmlLayout and PatternLayout?

Example App on using SL4j and Log4j2

=====

log4j2.properties

=====

Root logger

rootLogger.level=debug

rootLogger.appenderRefs = R

>

>

SL4FProj-WithLog4J2

V

src/main/java

#com.nt.service

> SelectTest.java

log4j2.properties

src/test/java

JRE System Library [JavaSE-21]

> Maven Dependencies

>

src

rootLogger.appenderRef.R.ref = File

> target

app_log2.html

Mpom.xml

File Appender with HtmlLayout

appender.File.type = File

appender.File.name = File

appender.File.fileName = app_log2.html

appender.File.append = true

appender.File.layout.type = HtmlLayout

SelectTest.java

=====

```
//SelectTest.java package com.nt.service;
```

```
import java.sql.Connection;
```

```
import java.sql.DriverManager;
```

```
import java.sql.PreparedStatement;
```

```
import java.sql.ResultSet;
```

```
import java.sql.SQLException;
```

```
import org.slf4j.Logger;
```

```
import org.slf4j.LoggerFactory;
```

```
public class SelectTest {
```

```
//Logger object
```

```
private static Logger logger=LoggerFactory.getLogger(SelectTest.class); //static factory method giving  
Logger class (singleton class) object
```

```
//Query
```

```
private static final String GET_EMPS="SELECT EMPNO,ENAME,JOB,SAL FROM EMP";
```

```
public static void main(String[] args) {
```

```
logger.debug("start of main(-) method, application");
```

```
try( //establish the connection
```

```
Connection con=DriverManager.getConnection("jdbc:oracle:thin:@localhost:1521:xe", "system", "tiger"); ){
```

```
logger.info(" Connection with Db s/w is established");
```

```
try( //create PreparedStatement object
```

```
PreparedStatement ps=con.prepareStatement(GET_EMPS)){
```

```
logger.debug(" PreparedStatement obj is created");
```

```
try // execute the Query
```

```
ResultSet rs=ps.executeQuery(); ){
```

```
logger.debug(" ResultSet obj is created");
```

```
//the process the ResultSet oobject
```

```
while(rs.next()) {
```

```
System.out.println(rs.getInt(1)+" "+rs.getString(2)+" "+rs.getString(3)+" "+rs.getString(4));
```

```
}//while
```

```
logger.warn(" Its better to process the ResultSet data directly with getXxx() methods, not as String values");
```

```
logger.debug("ResultSet obj is processed");
```

```
}//try3
```

```

} //try2
} //try1
catch(SQLException se) { //To handle known exceptions
logger.error("DB problem ::"+se.getMessage());
se.printStackTrace();
}
catch (Exception e) { // To handle unknowns Exceptions
}
logger.error("Unknown DB Problem:"+e.getMessage());
e.printStackTrace();
logger.debug("end of main(-) method ");
} //main
} //class

```

note:: Slf4j with log4j we can not work with Simple Layout using properties file configuration ..but possible in log4j 1.x

Official Log4j2 layouts supported in .properties:

Works in properties file

PatternLayout

JsonLayout

HtmlLayout

XmlLayout

X Doesn't work

SimpleLayout

SimpleLayout

In pom.xml

=====

```

<dependency>
<groupId>org.apache.logging.log4j</groupId>
<artifactId>log4j-slf4j-impl</artifactId>
<version>2.20.0</version>
</dependency>
<!-- Log4j2 Core -->
<dependency>
<groupId>org.apache.logging.log4j</groupId>
<artifactId>log4j-core</artifactId> <version>2.20.0</version>
</dependency>
<!-- SLF4J API -->

```

```

<dependency>
<groupId>org.slf4j</groupId> <artifactId>slf4j-api</artifactId> <version>1.7.36</version>
</dependency>
<!-- Log4j2 API -->
<dependency>
<groupId>org.apache.logging.log4j</groupId>
<artifactId>log4j-api</artifactId> <version>2.20.0</version>
</dependency>
<dependency>
<groupId>com.oracle.database.jdbc</groupId>
<artifactId>ojdbc11</artifactId> <version>23.7.0.25.01</version>
</dependency>

```

For working with FileAppender and XmlLayout in log4j2 setup

=====

Root logger

rootLogger.level=debug rootLogger.appenderRef.file.ref = FileAppender

File Appender

logical name

appender.file.type = File appender.file.name = FileAppender

appender.file.fileName = app_log2.xml

appender.file.append = true

XML Layout

appender.file.layout.type = XmlLayout

=====

additional jar files to add in the pom.xml

=====

```

<dependency>
=====
<groupId>com.fasterxml.jackson.core</groupId>
<artifactId>jackson-core</artifactId>
<version>2.15.2</version>
</dependency>
<dependency>
<groupId>com.fasterxml.jackson.dataformat</groupId>
<artifactId>jackson-dataformat-xml</artifactId>
<version>2.15.2</version>
</dependency>

```

<dependency>

<groupId>com.fasterxml.jackson.core</groupId>

<artifactId>jackson-databind</artifactId>

<version>2.15.2</version>

</dependency>

<dependency>

<groupId>com.fasterxml.jackson.core</groupId>

<artifactId>jackson-annotations</artifactId>

<version>2.15.2</version>

</dependency>

log4j2.properties for FileAppender and PatternLayout

#FileAppender and PatternLayout

rootLogger.level=debug

rootLogger.appenderRef.file.ref = LogFile

appender.LogFile.type = File

appender.LogFile.name = LogFile

appender.LogFile.fileName = app_log3.txt

appender.LogFile.append = true

appender.LogFile.layout.type = PatternLayout

=====

note:: No Additional jar files are required

appender.LogFile.layout.pattern = %d{yyyy-MM-dd HH:mm:ss} [%t] %-5level %logger{36} - %msg - %M %n

%level --> gives thread priority level

%msg --> gives log message

%M --> gives Method name

RollingFileAppenders in log4j2 can be implemented in two ways

a) Size based (it is like log4j1.x RollingFileAppender)

b) Time based (it is like log4j1.x DailyRollingFileAppender)

For RollingFileAppender and PAtternLayout

rootLogger.level=debug rootLogger.appenderRef.rolling.ref = RollingFile appender.rolling.type = RollingFile

appender.rolling.name = RollingFile

appender.rolling.fileName = app_log4.txt

appender.rolling.filePattern = app_log4-%d{yyyy-MM-dd}-%i.txt

appender.rolling.append = true

appender.rolling.layout.type = PatternLayout

appender.rolling.layout.pattern

= [%d{yyyy-MM-dd HH:mm:ss} [%t] %-5level %logger{36} - %msg%n

```
appender.rolling.policies.type = Policies
appender.rolling.policies.size.type = SizeBased TriggeringPolicy
appender.rolling.policies.size.size = 5KB
log4j2.properties for Daily RollingFileAppender and PatternLayout
```

For Daily RollingFileAppender and PatternLayout

```
rootLogger.level=debug appender.rolling.type = RollingFile
rootLogger.appenderRef.rolling.ref = RollingFile
appender.rolling.name = RollingFile
appender.rolling.fileName = app_log5.txt
=====
appender.rolling.filePattern = app_log4-%d{yyyy-MM-dd-HH-mm}-%i.txt
appender.rolling.append = true
appender.rolling.layout.type = PatternLayout
appender.rolling.layout.pattern = [%d{yyyy-MM-dd HH:mm:ss}] [%t] %-5level %logger{36} - %msg%n
appender.rolling.policies.type = Policies
appender.rolling.policies.time.type = TimeBased TriggeringPolicy
appender.rolling.policies.time.interval
= 1
appender.rolling.policies.time.modulate = true
```