

[GET A QUOTE](#)[INDUSTRIES](#) ▾[SUSTAINABILITY](#) ▾[MEDIA
CENTRE](#) ▾[TECHNOLOGY](#)[FAQ](#)[VIDEO](#)[GALLERY](#)[BL](#)

Suggested Products



GS 20 HSI

High-precision machine for StandUp Zipper, Both Side Gusset, Three Side Seal, and Side...

Speed: 140/min



GSC 14 PLUS 300

Compact, high-speed machine delivering up to 300 pouches per minute efficiently.

Speed: 300/min



GS 24 TSG

Specialized for flat bottom and gusset pouches with precise sealing technology.

Speed: 70 shots/min



GS 24 PLUS 200

Versatile machine for stand-up, zipper, and shaped pouches

Speed: 200/min

[Home](#) / [Products](#) / [GS 20 PLUS](#)

GS 20 PLUS

Automatic Pouch Making Machine

Versatile Machine for Stand-Up, Gusset, and Zipper Pouches

 GS 20 PLUS

[GET A QUOTE](#)[INDUSTRIES](#) ▾[SUSTAINABILITY](#) ▾[MEDIA
CENTRE](#) ▾[TECHNOLOGY](#)[FAQ](#)[VIDEO](#)[GALLERY](#)[BL](#)[Materials](#)[Mono-family](#)[Web Speed](#)[30 m/min](#)

Application Industries

[Food](#)[Pharmaceuticals](#)[Personal Care](#)[Pet Food](#)[Request Quote](#)

Key Features

- ✓ Max web: 1000mm width
- ✓ Speed: Up to 160 shots/min
- ✓ Recyclable film compatible
- ✓ Quick setup with job recall
- ✓ Precision web handling

Performance

Supported Pouch Types

- ✓ Three Side Seal
- ✓ Zipper Pouch
- ✓ Stand-Up Pouch (Folded & Inserted Gusset)
- ✓ Both Side Gusset Pouch

[Product Details](#)[Request Information](#)

GS 20 PLUS Automatic Pouch Making Machine

Performance

Pouch Types: Three Side Seal, Zipper Pouch, Stand-Up Pouch (Folded & Inserted Gusset), Both Side Gusset Pouch

Max Web Size: 1000 mm with Ø600 mm Diameter

Linear Speed: Up to 30 m/min web speed

Three Side Seal: Up to 160 shots/min

Stand-Up Pouch (Folded & Inserted): Single Line or Double Line (with Multi Skip Function)

Suitable Materials: PET/PE, PET/METPET/PE, PET/AL Foil/PE, Paper-Based Laminates, MDO PE + PE, PA-based Films, and other recyclable mono-family structures

Advantages

- **Multi-Format Versatility:** Capable of producing 3-side seal, stand-up, zipper, and gusset pouches
- **Recyclable Film Compatible:** Runs mono-materials including MDO PE + PE with precision
- **Quick Setup & Job Recall:** Servo-driven automation with recipe-based format switching
- **Stable Pouch Forming:** Designed for consistent forming of thick and thin laminates
- **Live Monitoring Ready:** Remote LAN access for diagnostics and machine analytics
- **Precision Web Handling:** Smart skip cutting with adjustable cut lengths
- **Efficient Layout:** Compact footprint ideal for mid- to high-output plants



[GET A QUOTE](#)

- INDUSTRIES ▾
- SUSTAINABILITY ▾
- MEDIA
CENTRE ▾
- TECHNOLOGY
- FAQ
- VIDEO
- GALLERY
- BL

Max Web Size	1000 mm width, Ø600 mm
Speed	Up to 160 shots/min
Material Speed	Up to 30 Meters/min
Width of Bag	Up to 450 mm (Multi-format Range)
Height of Bag	Up to 490 mm (Single Line) / Up to 245 mm (Double Line)

Technical Specifications

Parameter	Specification
Pouch Formats	Three Side Seal, Zipper Pouch, Stand-Up (Folded & Inserted), Both Side Gusset
Max Web Size	1000 mm width, Ø600 mm
Linear Speed	Up to 30 Meters/min
Three Side Seal	Up to 160 shots/min
Stand Up Pouch	Single or Double Line (with Multi Skip Function)
Materials	PET/PE, PET/METPET/PE, PET/AL Foil/PE, Paper-Based Laminates, MDO PE + PE, PA-based Films
Bag Width	Up to 450 mm (Multi-format Range)

[GET A QUOTE](#)[INDUSTRIES](#) ▾[SUSTAINABILITY](#) ▾[MEDIA
CENTRE](#) ▾[TECHNOLOGY](#)[FAQ](#)[VIDEO](#)[GALLERY](#)[BL](#)

Gusset Size

Up to 200 mm

Key Advantages

- ✓ Multi-format versatility across pouch types
- ✓ Compatible with recyclable mono-materials
- ✓ Quick setup with recipe-based switching
- ✓ Stable pouch forming for various laminates
- ✓ Live monitoring ready via LAN
- ✓ Precision web handling with smart skip cutting
- ✓ Compact footprint for efficient production



SOCIAL MEDIA LINK

