

RITTVIK S 2024-CSE

2116240701616

Week-12-User-Defined Functions

Coding

Question 1

Correct

Marked out of
1.00

A binary number is a combination of 1s and 0s. Its n^{th} least significant digit is the n^{th} digit starting from the right starting with 1. Given a decimal number, convert it to binary and determine the value of the the 4th least significant digit.

Source code

```
1  /*
2  * Complete the 'fourthBit' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER number as parameter.
6  */
7
8  int fourthBit(int number)
9  {
10     int i =4,sum;
11     while(i-->0)
12     {
13         if(number%2==0)
14             sum =0;
15         else
16             sum =1;
17         number = number /2;
18     }
19     return sum;
20 }
21 }
```

Output

	Test	Expected	Got	
✓	<code>printf("%d", fourthBit(32))</code>	0	0	✓
✓	<code>printf("%d", fourthBit(77))</code>	1	1	✓

Passed all tests! ✓

Result

The above program is executed successfully and provides the above output.

Question **2**

Correct

Marked out of
1.00

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the list, sorted ascending. If there is no p^{th} element, return 0.

Source code

```

1  /*
2  * Complete the 'pthFactor' function below.
3  *
4  * The function is expected to return a LONG_INTEGER.
5  * The function accepts following parameters:
6  * 1. LONG_INTEGER n
7  * 2. LONG_INTEGER p
8  */
9
10 long pthFactor(long n, long p)
11 {
12     int count=0,i=1;
13     while(count!=p)
14     {
15         if(n%i==0)
16             count++;
17         else if (i>n)
18             return 0;
19         i++;
20     }
21     return i-1;
22 }

```

Output

	Test	Expected	Got	
✓	printf("%ld", pthFactor(10, 3))	5	5	✓
✓	printf("%ld", pthFactor(10, 5))	0	0	✓
✓	printf("%ld", pthFactor(1, 1))	1	1	✓

Passed all tests! ✓

Result

The above program is executed successfully and provides the above output.