


## Our Cluster



\*\*\*

## Hadoop Pieces

The major software components of a Hadoop cluster, and understanding the way our work get distributed among them requires a little background...

## HDFS

The problem: store (GB, TB, PB of) data in the cluster.

HDFS stores (blocks of) files on different nodes, replicated to make the data more available and to handle disk failure.

The **NameNode** coordinates everything and keeps track of who has what data.

The **DataNodes** actually store the data blocks (with each block on multiple nodes).

## YARN

The problem: use the compute resources (processors, memory) in the cluster to do work.

The **ResourceManager** tracks resources and jobs in the cluster.


The **NodeManagers** do actual compute work (and are also HDFS DataNodes).

The idea is that YARN will move a compute task to the data it's operating on: that's easier than moving the (possibly TB of) data to another node.

“Moving Computation is Cheaper than Moving Data” ([HDFS Architecture Guide](#))

That's why DataNodes and NodeManagers are typically on the same computers: to get the compute happening beside the data.

## (Simplified) Cluster Overview



## Work on Hadoop

A program you write to run on Hadoop is an **application** which could send multiple **jobs** to the cluster.

Different types of tasks can run on YARN and first we will see...

## MapReduce

The **MapReduce** model is a way to describe distributed parallel computation in a way that we can use for lots of problems, without having to do the message passing ourselves.

The MapReduce tool will be responsible for getting the computation done, as long as we express it in a way that fits the model.

Apache Hadoop provides an implementation of the MapReduce model that it can run on a YARN cluster.

From now on “MapReduce” will mean Hadoop MapReduce...

## MapReduce Stages

1. Map: apply a `map()` function to each piece of input. Output key/value pairs.
2. Shuffle: collect map output **with the same keys** together on a node so we can...
3. Reduce: call a `reduce()` function on each key and **each value** that a mapper produced for that key. Produce the final output for that key.

There can also be a step 1.5 Combiner: do reducer-like work on the data (on each node separately) to reduce the amount of data sent to the (expensive) shuffle.

## Example: word count

Everybody's first example: count the number of times each word occurs in a collection of text files.

1. Map: for each “word” in the input, output the key/value pair (“word”, 1).
2. Shuffle: move all of the (“word”, *n*) pairs to the same node, and (“other”, *n*) to the same node, ...
3. Reduce: Sum the values (the numbers) for each key (the words) to get a count of each word like: (“word”, 74), (“other”, 18), ...

## MapReduce Anatomy

```
public class WordCount extends Configured implements Tool {
    public static class TokenizerMapper
        extends Mapper<LongWritable, Text, Text, IntWritable> {
        private final static IntWritable one = new IntWritable(1);
        private Text word = new Text();

        @Override
        public void map(LongWritable key, Text value, Context context
            ) throws IOException, InterruptedException {
            StringTokenizer itr = new StringTokenizer(value.toString());
            while (itr.hasMoreTokens()) {
                word.set(itr.nextToken());
                context.write(word, one);
            }
        }
    }
}
```

```
public class WordCount extends Configured implements Tool {
    public static class IntSumReducer
        extends Reducer<Text, IntWritable, Text, IntWritable> {
        private IntWritable result = new IntWritable();

        @Override
        public void reduce(Text key, Iterable<IntWritable> values,
            Context context) throws IOException, InterruptedException {
            int sum = 0;
            for (IntWritable val : values) {
                sum += val.get();
            }
            result.set(sum);
            context.write(key, result);
        }
    }
}
```

```
public class WordCount extends Configured implements Tool {
    ...@Override
    public int run(String[] args) throws Exception {
        Configuration conf = this.getConf();
        Job job = Job.getInstance(conf, "word count");
        job.setJarByClass(WordCount.class);
        job.setInputFormatClass(TextInputFormat.class);

        job.setMapperClass(TokenizerMapper.class);
        job.setCombinerClass(IntSumReducer.class);
        job.setReducerClass(IntSumReducer.class);

        job.setOutputKeyClass(Text.class);
        job.setOutputValueClass(IntWritable.class);
        job.setOutputFormatClass(TextOutputFormat.class);
        TextInputFormat.addInputPath(job, new Path(args[0]));
        TextOutputFormat.setOutputPath(job, new Path(args[1]));

        return job.waitForCompletion(true) ? 0 : 1;
    } ...
}
```

```
public class WordCount extends Configured implements Tool {
    public static void main(String[] args) throws Exception {
        int res = ToolRunner.run(new Configuration(), new WordCount(),
            args);
        System.exit(res);
    }
}
```

## Hadoop MapReduce Details

There are a bunch of moving pieces in a Hadoop MapReduce job to make this work

## InputFormat

Get the data we need, split it up and process it into key/value pairs for the Mapper.

## Mapper

Processes each key/value input pair. Output key/value pairs to...

## Combiner

An instance of Reducer that works as part of the mapper process.

## Partitioner

Which keys go to which reducer? Default usually okay.

## Reducer

Take a key and an iterable of values; combine all of the values for the key and output result key/value pairs. Can also be plugged in as a combiner.

## OutputFormat

Output the key/values from the reducer to... wherever it goes.

## Summary Output

A MapReduce task produces some summary stats at the bottom of its output. e.g. WordCount running on the **wordcount-2** data set and with `-D mapreduce.job.reduces=3`:

```
File System Counters
  FILE: Number of bytes read=92807462
  FILE: Number of bytes written=82173142
  FILE: Number of read operations=0
  FILE: Number of large read operations=0
  FILE: Number of write operations=0
```

```
Map-Reduce Framework
  Map input records=257115
  Map output records=2136725
  Map output bytes=20178489
  Map output materialized bytes=3469320
  Input split bytes=2307
  Combine input records=2136725
  Combine output records=242404
  Reduce input groups=124601
  Reduce shuffle bytes=3469320
  Reduce input records=242404
  Reduce output records=124601
  Spilled Records=484808
  Shuffled Maps =57
  Failed Shuffles=0
  Merged Map outputs=57
  GC time elapsed (ms)=31
  Total committed heap usage (bytes)=15070134272
```

```
Shuffle Errors
  BAD_ID=0
  CONNECTION=0
  IO_ERROR=0
  WRONG_LENGTH=0
  WRONG_MAP=0
  WRONG_REDUCE=0
```

```
File Input Format Counters
  Bytes Read=4254260
File Output Format Counters
  Bytes Written=1399398
```

## MapReduce Parallelism

The goal of all of this structure is to *do work in parallel* across all of the cores available.

The `InputFormat` decides how to split the input, and thus how many map processes there will be.

YARN is responsible for running the map tasks: it does this in parallel as much as possible, and tries to run them locally to the inputs.

With the `TextInputFormat` we have been using:

- Every file goes to at least one separate mapper.
- If the file is uncompressed (or uses a splittable compression method) and large enough, it will be split to multiple map tasks.

Each mapper can do its job in parallel, and send its output to the shuffle. If the amount of parallelism isn't right for the problem/cluster, then things are going to be slow.

Too few parallel tasks: few cores used.

Too many tasks: they get queued and the overhead of starting/stopping them dominates.

How can you change the number of mappers to make it “right”?

Option 1: override the `InputFormat` to change the way the input is split.

Option 2: change the input files to make the size/number you want.

I would almost certainly choose 2. **Fix your input**, then start working with it. (And similar advice with Spark.)

We had to explicitly set the number of reducers: there's nothing the framework can do to guess the “correct” number.

The `Partitioner` decides which key goes to which reducer.

Then each reducer can work in parallel and produces a separate output file. Again, YARN runs them.

## Writables

All of the keys and values we have been using are wrapped in a `Writable` implementation.

Basically, the `Writable` implementations know how to (efficiently) serialize/deserialize their wrapped type for passing around the cluster.

The `WritableComparable` adds the ability to compare (for the shuffle).

Hadoop includes implementations for basic Java types:

- `int` → `IntWritable`
- `long` → `LongWritable`
- `float` → `FloatWritable`
- `double` → `DoubleWritable`
- `boolean` → `BooleanWritable`
- `String` → `Text` (should have been called `StringWritable` but it wasn't)

Implementing your own `Writable` (or `WritableComparable`) is easy if you have a more complex key or value.

e.g. the `LongPairWritable` from Assignment 1.

## Example: word count

1. InputFormat: the default `TextInputFormat` splits files into lines (with byte-offset as key): (241, “one text line”).
2. Mapper: Break the line up into words, and count one occurrence of each: (“one”, 1), (“text”, 1), (“line”, 1).
3. Combiner: Sum the values for each word on this node: (“line”, 3), (“one”, 32), (“text”, 2).

4. Shuffle: Move equal keys to same reducer, as decided by `HashPartitioner`.
5. Reducer: Sum the values for each word: (“line”, 12), (“one”, 76), (“text”, 6).
6. OutputFormat: the default `TextOutputFormat` outputs tab-separated keys and values:

```
line    12
one     76
text    6
```

## About MapReduce

Many problems can be expressed as a MapReduce task (or maybe multiple chained MapReduce tasks).


... but it's a little limiting. We'll see more flexibility in Spark.

## MapReduce: One more way

[\* meaning zero-or-more]

1. InputFormat: input → (k1, v1)\*
2. Mapper: (k1, v1) → (k2, v2)\*
3. Combiner: (k2, iterable(v2)) → (k2, v3)\*
4. Shuffle: move (k2, v2) to get equal k2 together (RawComparator decides what “equal” means)
5. Reducer: (k2, iterable(v2)) → (k3, v3)\*
6. OutputFormat: (k3, v3) → output

## MapReduce Data Flow



\*\*