

```
//Created By Ritwik Chandra Pandey on 24/03/21
//183215
//Preorder Traversal in n-ary tree
```

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct node
{
    int data;
    struct node *first;
    struct node *next_sibling;
};
```

```
/* frunction prototypes */
```

```
void Preorder(struct node* n)
{
    struct node *c;
    if(n!=NULL){
        printf("%d ", n->data);
    }
    c = n->first;
    while(c!=NULL){
        Preorder(c);
        c=c->next_sibling;
    }

}
```

```
struct node* newNode(int k){
    struct node* temp = (struct node*)malloc(sizeof(struct node));
```

```

temp->data = k;
temp->first = NULL;
temp->next_sibling = NULL;
return temp;
}
/* Driver program to test above functions*/
int main()
{
    struct node *root = newNode(01);
    root->first = newNode(12);
    root->first->next_sibling = newNode(13);
    root->first->next_sibling->next_sibling = newNode(14);
    root->first->next_sibling->next_sibling->first = newNode(25);
    root->first->next_sibling->next_sibling->next_sibling = newNode(15);
    root->first->first = newNode(26);
    root->first->first->next_sibling = newNode(27);
    root->first->first->first = newNode(38);
    printf("Pre Order traversal of the tree is \n");
    Preorder(root);

    printf("\n");
    return 0;
}

```