

```
//Created By Ritwik Chandra Pandey
//On 4th Nov
//Collision Resolution Techniques: Quadratic Probing
```

```
#include <stdio.h>
#include <stdlib.h>
#define SIZE 13
```

```
int HashTable[SIZE];
int hash(int x) {
    return x % SIZE;
}
void insert(int x) {
    int i, index, start;
    i=1;
    index = hash(x);
    start = index;
    while(HashTable[index]!=-1){
        if(HashTable[index]==-1){
            break;
        }
        index = (start+i*i)%SIZE;
        i++;
        if(index==start){
            printf("Hash table is full.\n");
            return;
        }
    }
    HashTable[index] = x;
    printf("Successfully inserted.\n");
}
void delete(int x) {
    int i, index, start;
    i=1;
    index = hash(x);
    start = index;
    while(HashTable[index]!=x){
        if(HashTable[index]==x){
            break;
        }
    }
}
```

```

        }
        index = (start+ i*1)%SIZE;
        i++;
        if(index==start){
            printf("Element not found. So cannot delete the element.\n");
            return;
        }
    }
    HashTable[index] = -1;
    printf("Successfully deleted.\n");
}

void search(int x) {
    int i,index,start;
    i =1;
    index = hash(x);
    start= index;
    while(HashTable[index]!=x){
        if(HashTable[index]==x){
            break;
        }
        index = (start+i*1)%SIZE;
        i++;
        if(index==start){
            printf("Element not found.\n");
            return;
        }
    }
    printf("Element found.\n");
}

void print() {
    int i;
    for(i=0;i<SIZE;i++){
        if(HashTable[i]!=-1){
            printf("[%d]=>%d ",i,HashTable[i]);
        }
    }
    printf("\n");
}
}

```

```

int main() {
    int x, op, i = 0;
    for (i = 0; i < SIZE; i++)
        HashTable[i] = -1;
    while (1) {
        printf("1.Insert 2.Delete 3.Search 4.Print 5.Exit\n");
        printf("Enter your option : ");
        scanf("%d", &op);
        switch (op) {
            case 1:printf("Enter an element to be inserted : ");
                    scanf("%d", &x);
                    insert(x);
                    break;

            case 2:
                    printf("Enter an element to be deleted : ");
                    scanf("%d", &x);
                    delete(x);
                    break;

            case 3:
                    printf("Enter an element to be searched : ");
                    scanf("%d", &x);
                    search(x);
                    break;

            case 4:
                    print();
                    break;

            case 5:exit(0);
        }
    }
}

```