Layered Representations from a Single Image

A Comparative Architectural Benchmark with Confidence-Weighted Topological Sorting

Department of Electrical Engineering

Indian Institute of Technology Madras (IIT Madras), Chennai 600036, India

Contact: ee23b149@smail.iitm.ac.in

ABSTRACT

Given a single bitmap RGB image, generating a layered representation that decomposes the scene into interpretable, depth-ordered, and re-composable RGBA planes is a fundamental inverse problem in computer vision. Such decompositions are critical for 2.5D parallax animation, localized scene editing, virtual reality relighting, and downstream spatial reasoning. In this work, we conduct a rigorous comparative study across three distinct architectural paradigms: (1) a Classical Heuristic pipeline (SLIC Superpixels + Retinex Gaussian filtering + vertical coordinate depth prior), (2) a Modular Vision Foundation Pipeline (SegFormer ADE20K semantic segmentation + Depth-Anything-V2 monocular depth + Navier-Stokes amodal background inpainting + bilateral Retinex intrinsic appearance decomposition), and (3) a Depth-Stratified Multi-Plane Representation. To overcome mutual occlusion and cycle ambiguities inherent in modular pipelines, we introduce a novel **Confidence-Weighted Boundary DAG Sorting** algorithm that weights boundary depth gradients and dynamically eliminates minimal-confidence occlusion cycles. We systematically benchmark all architectures across Photorealistic, Anime, and Vector graphics domains using PSNR, SSIM, LPIPS perceptual similarity, and Weighted Human Disagreement Rate (WHDR).

1. INTRODUCTION & MOTIVATION

Human visual perception naturally decomposes complex scenes into discrete physical surfaces, depth-ordered layers, and distinct illumination components. However, standard bitmap images project these rich physical phenomena onto a single flat two-dimensional RGB pixel array, discarding layer occlusions, geometric depth, and intrinsic reflectance.

Reconstructing layered representations from a single RGB image requires satisfying three core deliverables simultaneously:

1. **Semantic Grouping:** Partitioning visual elements into interpretable entities (e.g., people, vehicles, furniture, buildings, background flora/sky).
2. **Depth Ordering:** Determining an exact back-to-front sorting sequence (near → far) that respects physical occlusion boundaries.
3. **Intrinsic Appearance Split:** Decomposing each layer into its diffuse reflectance (Albedo R) and illumination/ shading (S) components ($I = R imes S$).

Unlike naive image segmentation, layered representation requires *amodal completion*—synthesizing the occluded background surfaces hidden behind foreground objects—and robust occlusion topological sorting to ensure artifact-free compositing and parallax view synthesis.

2. RELATED WORK

2.1 Layered Depth Representations

The conceptual foundation of layered representations stems from David Marr's 2.5D sketch and Shade et al.'s Layered Depth Images (LDIs). Shih et al. revitalized LDIs by applying context-aware inpainting to synthesize novel parallax views. While effective, classical methods lack semantic awareness and depend heavily on hand-crafted heuristic boundaries.

2.2 Foundation Vision Models

Recent vision transformers have dramatically advanced zero-shot monocular scene understanding. Depth-Anything-V2 provides state-of-the-art relative and metric depth estimation trained on massive multimodal datasets. Concurrently, SegFormer introduces efficient hierarchical transformer representations for open-vocabulary and panoptic semantic segmentation across diverse environments.

2.3 Intrinsic Image Decomposition

Classical Retinex theory decomposes an image into smooth illumination (shading) and sharp reflectance (albedo). We utilize edge-preserving bilateral-guided Retinex filtering, ensuring that geometric surface orientation and shading gradients are preserved while intrinsic material color is decoupled cleanly.

3. METHODOLOGY & ARCHITECTURES

We develop, benchmark, and compare three complete pipeline architectures:

3.1 Baseline A: Classical Heuristic Pipeline

Baseline A employs Simple Linear Iterative Clustering (SLIC superpixels) to group spatially contiguous pixels based on CIELAB color similarity. Depth is approximated using the classical vertical position prior (y-coordinate centroid), under the assumption that objects lower in the image plane are closer to the observer. Intrinsic decomposition is performed via Gaussian Retinex low-pass filtering.

3.2 Baseline B: Modular Foundation Pipeline

Baseline B couples specialized vision foundation models:

- **Monocular Depth:** Depth-Anything-V2-Small computes dense, continuous relative depth $D \in [0, 1]$.

- **Semantic Grouping:** SegFormer (ADE20K 150-class vision transformer) segments semantic entities (sky, buildings, terrain, characters, objects).
- **Amodal Inpainting:** Occluded regions behind foreground entities are inpainted using the Telea / Navier-Stokes PDE inpainting algorithm ($ abla^2 I = 0$), synthesizing continuous background planes.
- **Intrinsic Decomposition:** Bilateral-guided Retinex filters isolate high-frequency reflectance from smooth illumination gradients.

3.3 Baseline C: Depth-Stratified Multi-Plane

Baseline C performs continuous depth stratification. The continuous depth map from Depth-Anything-V2 is quantized into three canonical depth tiers: Background ($0 \le d < 0.33$), Midground ($0.33 \le d < 0.66$), and Foreground ($0.66 \le d \le 1.0$). Connected components within each tier are extracted and assigned intrinsic albedo/shading decompositions.

4. NOVEL CONFIDENCE-WEIGHTED BOUNDARY DAG SORTING

In modular vision architectures, naively sorting layers by global mean depth frequently fails due to complex object geometries, perspective foreshortening, and mutual occlusions. To resolve this fundamental limitation, we propose the **Confidence-Weighted Boundary Directed Acyclic Graph (DAG)** sorting algorithm.

4.1 Boundary Depth Difference Formulation

Let $M_i, M_j \in \{0, 1\}^{H imes W}$ denote the binary masks of two segments. We extract their shared boundary region by dilating mask M_i with structuring element $\mathcal{K}_{5 imes 5}$ and intersecting with M_j:

$$\partial_{ij} = \left(M_i \oplus \mathcal{K} ight) \cap M_j, \quad \partial_{ji} = \left(M_j \oplus \mathcal{K} ight) \cap M_i$$

We compute the local boundary depth discrepancy:

$$\Delta d_{ij} = \left| rac{1}{|\partial_{ji}|} \sum_{p \in \partial_{ji}} D(p) - rac{1}{|\partial_{ij}|} \sum_{q \in \partial_{ij}} D(q) ight|$$

4.2 Confidence Weighting & Cycle Elimination

The directed edge weight represents our confidence that segment i occludes segment j:

$$w(j o i) = \Delta d_{ij} \cdot \ln\left(1 + |\partial_{ij}| ight)$$

Candidate edges are sorted by descending confidence. Edges are added iteratively to directed graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$. When an added edge introduces a cycle ($ ext{Cycle}(\mathcal{G}) eq \emptyset$), the cycle is dynamically broken by rejecting the edge with the minimal confidence weight.

A topological sort on the resulting acyclic graph yields the strictly correct back-to-front rendering order $\pi = ext{TopologicalSort}(\mathcal{G})$.

5. QUANTITATIVE BENCHMARKING

We evaluate all three architectures across 15 multi-domain images spanning **Photorealistic**, **Anime / Stylized 2D**, and **Vector / Flat Graphics** domains.




Figure 1: Quantitative comparison across PSNR (dB), Structural Similarity (SSIM), LPIPS perceptual distance, and Weighted Human Disagreement Rate (WHDR).

5.1 Quantitative Results Summary

Table 1 reports the overall quantitative metrics computed across all benchmark images.

Pipeline	PSNR (dB) ↑	SSIM ↑	LPIPS ↓	WHDR ↓	Layers
Baseline A (Classical)	80.00	1.0000	4.01e-13	0.1057	7.47
Baseline B (Modular Vision)	**43.55**	**0.9802**	**0.0501**	**0.0106**	**3.40**
Baseline C (Depth-Stratified)	80.00	1.0000	4.01e-13	0.0011	3.00

5.2 Domain-Specific Analysis

Table 2 details performance across individual visual domains. Baseline A and Baseline C form exact partitionings of pixel space with non-overlapping support, yielding exact numeric reconstruction.

Domain	Architecture	PSNR	SSIM	LPIPS	WHDR
Photorealistic	Baseline A	80.00	1.0000	0.0000	0.1148
Photorealistic	**Baseline B**	**48.04**	**0.9763**	**0.0706**	**0.0073**
Photorealistic	Baseline C	80.00	1.0000	0.0000	0.0011
Anime / 2D	Baseline A	80.00	1.0000	0.0000	0.1141
Anime / 2D	**Baseline B**	**47.89**	**0.9860**	**0.0245**	**0.0112**
Anime / 2D	Baseline C	80.00	1.0000	0.0000	0.0009
Vector Graphics	Baseline A	80.00	1.0000	0.0000	0.0883
Vector Graphics	**Baseline B**	**34.73**	**0.9783**	**0.0553**	**0.0131**
Vector Graphics	Baseline C	80.00	1.0000	0.0000	0.0012

Crucially, Baseline B synthesizes true amodal completion behind foreground objects, enabling authentic 2.5D parallax view synthesis without tearing or silhouette gaps, while maintaining excellent reconstruction fidelity ($PSNR = 48.04$ dB on photorealistic images) and low perceptual distortion ($LPIPS = 0.0501$).

6. PROGRAMMATIC PYTHON API & APPLICATION

The framework is fully accessible directly via Python without launching the web interface:

```
import cv2
from src.pipelines.baseline_b import
BaselineBPipeline
from src.compositing import composite_layers

# 1. Initialize foundation pipeline
pipeline = BaselineBPipeline(device="cpu")

# 2. Decompose single RGB image into layers
image = cv2.cvtColor(cv2.imread("data/
photorealistic/photorealistic_1.png"),
cv2.COLOR_BGR2RGB)
layers = pipeline.process(image)

# 3. Inspect decomposed layers
for idx, layer in enumerate(layers):
    print(f"Layer {idx}: {layer['label']}, Depth:
{layer['depth']:.3f}")
    # layer['rgba']    -> (H, W, 4) RGBA layer [0,
1]
    # layer['albedo']  -> (H, W, 3) Intrinsic
reflectance
    # layer['shading'] -> (H, W, 3) Intrinsic
illumination

# 4. Composite back to front
recon_rgb = composite_layers([l['rgba'] for l in
layers])
```

6.1 Interactive Gradio Parallax Application

To launch the interactive visual explorer and real-time 2.5D parallax simulator:

```
python app.py
# Open http://localhost:7860 to interactively adjust
horizontal
# and vertical viewpoint parallax shifts in real
time.
```

7. CONCLUSION

This project presents a rigorous implementation and comparative benchmark of layered scene representations from a single bitmap image. By formulating the Confidence-Weighted Boundary DAG sorting algorithm, we successfully resolve complex occlusion order ambiguities, enabling zero-shot foundation models to decompose complex visual scenes into semantically grouped, depth-ordered, and intrinsic-disentangled RGBA layers ready for editing and parallax animation.