



Information on data access in accordance with Regulation (EU) 2023/2854 ('Data Act') for connected products

EU Data Act

Connected products and related services from Robert Bosch Smart Home GmbH generate various data and information during use. Below you will find information about the data available in the product, data access, and your data rights.

[Bosch Smart Home System](#)

[Bosch Smart Home Cameras](#)

[Bosch/Buderus Energiemanager](#)

Bosch Smart Home System

You can access the data generated and potentially stored in the product as follows:

App

The following mobile application is required for access:

Bosch Smart Home: [Google Play Store](#) [Apple App Store](#)

The terms of use required for use can be viewed at the following link:

[General Terms and Conditions of the Bosch Smart Home App](#)

Machine-readable local interface (of the Smart Home Controller to which the products are connected)

[To the interface documentation \(GitHub\)](#)

Technical means and requirements for data access:

A mobile device that is compatible with the [Bosch Smart Home App] application

A computer with the associated software (**only valid for local interface**)

Type, format and estimated volume of product data

The following data may be generated during the operation and use of the product. The data actually generated varies depending on the specific use of the product.

Types of product data

Physical data: Current data (e.g. temperature, pressure, power, energy)

Device identification data: (e.g. serial number, hardware and software version)

Status data: (e.g. on/off, present/absent)

Error messages

Setting values/user configurations: (e.g. room target temperature, time programmes)

Storage location and storage duration

The data is stored in the product

and transferred to the Smart Home Controller II/Smart Home Controller.

Depending on the type, the data is either overwritten cyclically or stored permanently.

A factory reset of the product deletes the data.



Product name	Item number	Data	Subcategory / Details	Example	How often is the data updated?	Measured data volume
Smart Home Controller II / Smart Home Controller	8750002101	MAC Adress Controller		64-da-a0-40-00-c5	static	- Public information: 1 - 5KB - Device information: 10 - 150KB*
	8750000001					
	8750000163					
		Name of the system	Name		B	
		Room	Which rooms were created in this home	Living room Bathroom	B	500Byte - 1.5KB
		Location		Exact location: City, Street	B	40 - 100Byte
		Time Zone		Timezone (MEZ Berlin)	B	30Byte
		Name of the device		Heating living room right	B	*
		Device Category		Radiator thermostat	B	*

		Room	Living room	B	*
		Device ID	50325FFFFF E72B074	B	*
		Error	BATTERY_DEFECT TROUBLE	S	*
		signal strength (result)	High/Low/not Available	S	*
		RCC	Time Schedules	B	2 - 15KB
		operation mode	manual/automatic	B	2 - 15KB
		Current temperature	18°	Typical every 120-180s.	2 - 15KB
		Target temperature	22°	B	2 - 15KB
		Boost	on/off	B	2 - 15KB
Radiator Thermostat	8750000002 8750000270	Child Protection	on/off	B	1.5 - 2KB Services + 515Byte general Device information
		Whisper mode	on/off	B	1.5 - 2KB Services + 515Byte general Device information
		Temperature adaption	+ 3C	B	1.5 - 2KB Services + 515Byte general Device information
		Current temperature	21°C	Typical every 120-180s.	1.5 - 2KB Services + 515Byte general Device information
		Time Schedules	Name/Days of the Week/ Times/Degree Shift Work Monday 0-8	B	1.5 - 2KB Services + 515Byte general Device information

		18° Monday 8-12 22°			
		operation mode	manual/automatic	B	1.5 - 2KB Services + 515Byte general Device information
		Target temperature	22°	B	1.5 - 2KB Services + 515Byte general Device information
		Battery State		S	1.5 - 2KB Services + 515Byte general Device information
		Boost	on/off		1.5 - 2KB Services + 515Byte general Device information
Light Control	8750000396	Schedules	Name/Weekdays/Times/ON/OFF	B	1.79KB Services + 500Byte general Device information
		switch off automatically (never / in x - 60 min.)	on/off	B	1.79KB Services + 500Byte general Device information
		Child protection	on/off	B	1.79KB Services + 500Byte general Device information
		Status	on/off	B	1.79KB Services + 500Byte general Device information
Shutter Control	8750000402	Calibration - Position; time for closing / opening in sec. / automatic	value in sec.	B	564Byte Services + 388Byte general Device information

		calibration			
		Calibration - Reaction; compensation time in sec. / automatically detect compensation value in sec.	value in sec.	B	564Byte Services + 388Byte general Device information
		Calibration - automatic end position detection; disable	value in sec.	B	564Byte Services + 388Byte general Device information
		Child protection	on/off	B	564Byte Services + 388Byte general Device information
		Current Shutter position	Closed/open/30%	B Typical 1800- 3600s	564Byte Services + 388Byte general Device information
Smoke detector	8750000287	Status: Detected smoke	yes/no	S	663Byte Services + 403Byte general Device information
		Battery State		S	663Byte Services + 403Byte general Device information
		Status: Sirene	on/off	3	663Byte Services + 403Byte general Device information
Room thermostat	8750001259	Child lock	on/off	B	4.35KB Services + 523Byte general Device information
		Temperatur- angleichung	+ 3C	B	4.35KB Services + 523Byte general Device information
		Controlled	3	B	4.35KB

		Devices (quantity)			Services + 523Byte general Device information
		Time Schedules	Name/Days of the Week/ Times/ Degree Shift Work Monday 0-8 18° Monday 8-12 22°	B	4.35KB Services + 523Byte general Device information
		operation mode	manual/automatic	B	4.35KB Services + 523Byte general Device information
		Current temperature	18°	Typical every 120-180s.	4.35KB Services + 523Byte general Device information
		Target temperature	22°	B	4.35KB Services + 523Byte general Device information
		Boost	on/off	B	4.35KB Services + 523Byte general Device information
Battery State		Battery State		S	4.35KB Services + 523Byte general Device information
		Humidity		Every 540s or on every 2% change	4.35KB Services + 523Byte general Device information
Room thermostat underfloor 24 / und 230	8750001003 8750001004	Calibration of measured temperature	+ 3C	B	1.70KB Services + 523Byte general Device information
		Child lock	on/off	B	1.70KB Services + 523Byte general Device information

	Valve Type	(normally open / normally closed)	B	1.70KB Services + 523Byte general Device information
	Heater Type	Underfloor Heating / Underfloor Heating low energy / Radiator / Passive Convector (without fan) / active Convector (with fan)	B	1.70KB Services + 523Byte general Device information
	Cooling mode	On/Off	B	1.70KB Services + 523Byte general Device information
	Time Schedules	Name/Days of the Week/ Times/ Degree Shift Work Monday 0-8 18° Monday 8-12 22°	B	1.70KB Services + 523Byte general Device information
	operation mode	manual/automatic	B	1.70KB Services + 523Byte general Device information
	Current temperature	18°	Typical every 120-180s.	1.70KB Services + 523Byte general Device information
	Target temperature	22°	B	1.70KB Services + 523Byte general Device information
	Boost	on/off	B	1.70KB Services

					+ 523Byte general Device information
		Humidity			Every 540s or on every 2% change
					1.70KB Services + 523Byte general Device information
Door Window Contact	8750000003	Profile	Entrance door, Window, Balcony/ Terrace door, Other	B	430Byte Services + 407Byte general Device information
		Battery State			S
					430Byte Services + 407Byte general Device information
		Status	Open/Closed	S	430Byte Services + 407Byte general Device information
Plug	8750000004 8750000286 8750000165	Status	on/off	B	2.54KB Services + 510Byte general Device information
		Mode	(manual / automatic)	B	2.54KB Services + 510Byte general Device information
		Range extension	on/off	B	2.54KB Services + 510Byte general Device information
		Profil	(Light, heater, standard)	B	2.54KB Services + 510Byte general Device information
		Status after powercut	on/off	B	2.54KB Services + 510Byte general Device information

		energy consumption level (Wh)	23 WH	Typically between 60 and 120s.	2.54KB Services + 510Byte general Device information
		power consumption level (W)	400 W	Typically between 60 and 120s.	2.54KB Services + 510Byte general Device information
		Schedules	Name/Weekdays/Times/ON/OFF	B	2.54KB Services + 510Byte general Device information
		Timer (switch on)		B	2.54KB Services + 510Byte general Device information
Universal Switch	8750000372 8750000373	Key assignment 1 long	Operation function (Alarm system, dimmable lamps, devices, scenario, shutters/blinds)	B	651Byte Services + 408Byte general Device information
		Key assignment 1 short	dito	B	651Byte Services + 408Byte general Device information
		Key press 1	yes/no	B	651Byte Services + 408Byte general Device information
		Key assignment 2 long		B	651Byte Services + 408Byte general Device information
		Key assignment 2 short		B	651Byte Services + 408Byte general Device information
		Battery State		S	651Byte Services

					+ 408Byte general Device information
		Key press 2		B	651Byte Services + 408Byte general Device information
Outdoor Sirene	8750001471	Alarm status	Sirene on/ Sirene of	S	1.64KB Services + 460Byte general Device information
		Volume	Reduced Medium Loud	B	1.64KB Services + 460Byte general Device information
		Power Supply	Solar Panel only 230 Volt Connection 5-28 (DC) Connection	B	1.64KB Services + 460Byte general Device information
		Siren alarm Duration	value in sec.	B	1.64KB Services + 460Byte general Device information
		Flashing Light Alarm duration	value in sec.	B	1.64KB Services + 460Byte general Device information
		Siren Alarm delay	value in sec.	B	1.64KB Services + 460Byte general Device information
		Flashing ligh alarm delay	value in sec.	B	1.64KB Services + 460Byte general Device information
		Battery State		S	1.64KB Services + 460Byte general Device information
		Classical	on / off	B	1.64KB

		Alarmsystem integration				Services + 460Byte general Device information
Motion detector	8750000018	Read detected last motion (When) / occupancy sensing	Date, Time	3		1.26KB Services + 440Byte general Device information
		Sensitivity setting	Small animal detection OR creep zone protection	B		1.26KB Services + 440Byte general Device information
		Battery State		S		1.26KB Services + 440Byte general Device information
		Brightness Value	value in Lumen	3		1.26KB Services + 440Byte general Device information
Motion detector II	8750002812	Read detected last motion (When) / occupancy sensing	Date, Time	S		2.99KB Services + 595Byte general Device information
		Sensitivity setting	high / middle / low	B		2.99KB Services + 595Byte general Device information
		Battery State				2.99KB Services + 595Byte general Device information
		Brightness Value	value in Lumen	S		2.99KB Services + 595Byte general Device information
		Temperature Value	value in °C	15min or +/-0,5°		2.99KB Services + 595Byte general Device information

		occupancy-state	present / not present	20sec	2.99KB Services + 595Byte general Device information
		Orientation-light status	on/off/%	3	2.99KB Services + 595Byte general Device information
		Tamper-protection	on/off	B	2.99KB Services + 595Byte general Device information
		area of application	indoor/outdoor	B	2.99KB Services + 595Byte general Device information
Dimmer	8750002080	Status	on /off	B	1.97KB Services + 539Byte general Device information
		Target Brightness	0-100 brightness	B	1.97KB Services + 539Byte general Device information
		Child lock	on/off	B	1.97KB Services + 539Byte general Device information
		Dimmer type	- Trailing edge phase cut (LEDs, energy-saving bulbs, low-voltage incandescent bulbs) - Leading edge phase cut (Traditional incandescent bulbs (230V, halogen incandescent bulbs)	B	1.97KB Services + 539Byte general Device information
		Brightness calibration	0-100%	B	1.97KB Services

		Set brightness range			+ 539Byte general Device information
		Brightness calibration - minimum brightness	percent value	B	1.97KB Services + 539Byte general Device information
		Electrical faults		S	1.97KB Services + 539Byte general Device information
Smartes Relais	8750002082	Configuration	On off switch / Pulse control	B	2.60KB Services + 534Byte general Device information
		Child lock	on/off	B	2.60KB Services + 534Byte general Device information
		Button	Switch Button/ push Button	B	2.60KB Services + 534Byte general Device information
		Schedule	Schedule manual / automatic	B	2.60KB Services + 534Byte general Device information
		Create Schedule	Name/Weekdays/ Times/ON/OFF	B	2.60KB Services + 534Byte general Device information
		switch off automatically	(never/ in min.)	B	2.60KB Services + 534Byte general Device information
		Profile	Standard, Lamp, Electric Heater, Boiler	B	2.60KB Services + 534Byte general Device information
	Relais Pulse Mode	last impuls (When)	Date/Time	B	2.60KB Services

					+ 534Byte general Device information
		impulse length	value in sec.	B	2.60KB Services + 534Byte general Device information
		Electrical faults		S	2.60KB Services + 534Byte general Device information
Smoke Alarm II	8750002142	Status: Detected smoke	yes/no	3	823Byte Services + 425Byte general Device information
		Battery State		S	823Byte Services + 425Byte general Device information
		Status: Sirene	on/off	S	823Byte Services + 425Byte general Device information
Water Sensor	8750001291	Movement Sound	on/off	S	984Byte Services + 449Byte general Device information
		Movement Notification	on/off	S	984Byte Services + 449Byte general Device information
		Water detection	last detected	S	984Byte Services + 449Byte general Device information
		movement detection	last detected	S	984Byte Services + 449Byte general Device information
		Battery State			984Byte Services

					+ 449Byte general Device information
		Sirene	Sounding/muted/ not sounding	S	984Byte Services + 449Byte general Device information
Plug compact	8750001300 8750001301 8750001302	Status	on/off	B	2.32KB Services + 504Byte general Device information
		Mode	(manual / automatic)	B	2.32KB Services + 504Byte general Device information
		Profil	(Lighting, heating, Standard)	B	2.32KB Services + 504Byte general Device information
		Status after powercut	Off / On / Status before powe cut)	B	2.32KB Services + 504Byte general Device information
		energy consumption level (Wh)	23 WH	Min: 30s Max. 3600s	2.32KB Services + 504Byte general Device information
		power consumption level (W)	400 W	Min: 30s Max. 3600s	2.32KB Services + 504Byte general Device information
		Schedules	Name/Weekdays/ Times/ON/OFF	B	2.32KB Services + 504Byte general Device information
		Timer (switch on)		B	2.32KB Services + 504Byte general Device information
		Reseted consumption	Date/ time	B	2.32KB Services

		value				+ 504Byte general Device information
Twist	8750000328	Twist configuration (32 spaces) 1	Device/Scenario	B		21.17KB Services + 444Byte general Device information
		Button Press		B		21.17KB Services + 444Byte general Device information
		Battery State		S		21.17KB Services + 444Byte general Device information
		Language	DE/FR usw	B		21.17KB Services + 444Byte general Device information
Twinguard	8750001213 8750001214	Status: Detected smoke	yes/no	S		1.65KB Services + 465Byte general Device information
		Status: Sirene	on/off	S		1.65KB Services + 465Byte general Device information
		Current temperature		S		1.65KB Services + 465Byte general Device information
		Current Humidity		S		1.65KB Services + 465Byte general Device information
		Current Air Quality		S		1.65KB Services + 465Byte general Device information

		Smoke sensitivity	(high - medium - low)	B	1.65KB Services + 465Byte general Device information
		Pre-alarm	on/off	B	1.65KB Services + 465Byte general Device information
		Air quality profile - Temperature limits	Range in degree	B	1.65KB Services + 465Byte general Device information
		Air quality profile - Humidity limits	Range in Percent	B	1.65KB Services + 465Byte general Device information
		Air quality profile - Air purity limits	Range in VOC	B	1.65KB Services + 465Byte general Device information
		Data history	Hour - Day - Week - List (DB)	S	1.65KB Services + 465Byte general Device information
		Battery State		S	1.65KB Services + 465Byte general Device information
		Heartbeat	on/off	B	1.65KB Services + 465Byte general Device information
Door Window contact II	8750002090 8750002094	Profile	Entrance door, Window, Balcony/ Terrace door,	B	1.12KB Services + 445Byte general

		Other			Device information
		Status	Open/Closed	S	1.12KB Services + 445Byte general Device information
		Break function	on/off	B	1.12KB Services + 445Byte general Device information
		Current Break function	Currently Active	B	1.12KB Services + 445Byte general Device information
		Break function	automatic timelimit	B	1.12KB Services + 445Byte general Device information
		Break function	Short press/ long press	B	1.12KB Services + 445Byte general Device information
		Battery State		S	1.12KB Services + 445Byte general Device information
		Button pressed Status		B	1.12KB Services + 445Byte general Device information
Door Window contact II plus	8750002092 8750002096	Profile	Entrance door, Window, Balcony/ Terrace door, Other	B	1.12KB Services + 448Byte general Device information
		Status	Open/Closed	S	1.12KB

Services
+ 448Byte
general
Device
information

		Battery State		S	1.12KB Services + 448Byte general Device information
		Vibration detected	Status ja/nein	S	1.12KB Services + 448Byte general Device information
Shutter / Light Controll II	8750002078	Profile	Shutter Venetian Blind Awning	B	
	Shutter Controll II as Shutter	Calibration - Position; time for closing / opening in sec. / automatic calibration	value in sec.	B	564Byte Services + 500Byte general Device information
		Calibration - Reaction; compensation time in sec. / automatically detect compensation value in sec.	value in sec.	B	564Byte Services + 500Byte general Device information
		Calibration - automatic end position detection; disable	value in sec.	B	564Byte Services + 500Byte general Device information
		Child protection	on/off	B	564Byte Services + 500Byte general Device information
		Current Shutter position	Closed/open/30%	1s when in motion	564Byte Services + 500Byte general Device information
	Shutter Controll II as venetian	Calibration - Position; time for	value in sec.	B	2.29KB Services + 500Byte

Blind	closing / opening in sec. / automatic calibration			general Device information
	Calibration - Reaction; compensation time in sec. / automatically detect compensation value in sec.	value in sec.	B	2.29KB Services + 500Byte general Device information
	Calibration - automatic end position detection; disable	value in sec.	B	2.29KB Services + 500Byte general Device information
	Child protection	on/off	B	2.29KB Services + 500Byte general Device information
	Current Shutter position	Closed/open/30%	1s when in motion	2.29KB Services + 500Byte general Device information
	tilt	in °	1s	2.29KB Services + 500Byte general Device information
Shutter Controll II as Awning	Calibration - Position; time for closing / opening in sec. / automatic calibration	value in sec.	B	1.72KB Services + 500Byte general Device information
	Calibration - Reaction; compensation time in sec. / automatically detect compensation	value in sec.	B	1.72KB Services + 500Byte general Device information

		value in sec.			
		Calibration - automatic end position detection; disable	value in sec.	B	1.72KB Services + 500Byte general Device information
		Child protection	on/off	B	1.72KB Services + 500Byte general Device information
		Current Awning position	Closed/open/30%	1s when in motion	1.72KB Services + 500Byte general Device information
	Light Control II	Schedules	Name/Weekdays/ Times/ON/OFF	B	1KB Services + 500Byte general Device information
		switch off automatically (never / in x - 60 min.)	on/off	B	1KB Services + 500Byte general Device information
		Child protection	on/off	B	1KB Services + 500Byte general Device information
		Status	on/off	B	1KB Services + 500Byte general Device information
		Read energy consumption level (Wh)	value in Wh	Min: 30s Max: 300s	1KB Services + 500Byte general Device information
		Read current power consumption level (W)	value in Wh	Min: 30s Max: 300s	1KB Services + 500Byte general Device information

Radiator Thermostat II	8750002330	Resetted consumption level	Date Time	B	1KB Services + 500Byte general Device information
		Electrical faults		S	1KB Services + 500Byte general Device information
		Child Protection	on off	B	2.60KB Services + 592Byte general Device information
		Temperature adaption	value in degree	B	2.60KB Services + 592Byte general Device information
		Boost	on/off	B	2.60KB Services + 592Byte general Device information
		Display orientation	(vertical / horizontal)	B	2.60KB Services + 592Byte general Device information
		Display brightness	(in %)	B	2.60KB Services + 592Byte general Device information
		Display switch- on duration	(in sec)	B	2.60KB Services + 592Byte general Device information
		Displayed Temperature	(measured / set temperature)	B	2.60KB Services + 592Byte general Device information

		Current temperature	21C	Between <1s and never (if no change happened). Typical every 120-180s.	2.60KB Services + 592Byte general Device information
		Valve Position		Between 30s and 43200s (if no change happened). Typical every 30s.	2.60KB Services + 592Byte general Device information
		Time Schedules	Name/Days of the Week/ Times/ Degrees Shift work Monday 0-8 18° Monday 8-12 22°	B	2.60KB Services + 592Byte general Device information
		operation mode	manual/automatic	B	2.60KB Services + 592Byte general Device information
		Target temperature	22°	B	2.60KB Services + 592Byte general Device information
		Battery State		S	2.60KB Services + 592Byte general Device information
		Boost	on/off	B	2.60KB Services + 592Byte general Device information
Room thermostat II	8750002414	Child lock	on/off	B	2.36KB Services + 556Byte general Device information
		Temperatur-	+ 3C	B	2.36KB

angleichung				Services + 556Byte general Device information
	Controlled Devices (quantity)	3	B	2.36KB Services + 556Byte general Device information
	Sensor Connection	(not used/ Temperature sensor / potential-free contact)	B	2.36KB Services + 556Byte general Device information
	Display switch- on duration	(in sec)	B	2.36KB Services + 556Byte general Device information
	Display brightness	(in %)	B	2.36KB Services + 556Byte general Device information
	Time Schedules	Name/Days of the Week/ Times/ Degree Shift Work Monday 0-8 18° Monday 8-12 22°	B	2.36KB Services + 556Byte general Device information
	operation mode	manual/automatic	B	2.36KB Services + 556Byte general Device information
	Current temperature	18°	Between <1s and never (if no change happened). Typical every 120-180s.	2.36KB Services + 556Byte general Device information
	Target temperature	22°	B	2.36KB Services

					+ 556Byte general Device information
		Battery State		S	2.36KB Services + 556Byte general Device information
		Boost	on/off	B	2.36KB Services + 556Byte general Device information
Roomthermostat II 230 V	8750002388	Calibration of measured temperature	+ 3C	B	2.43KB Services + 572Byte general Device information
		Child lock	on/off	B	2.43KB Services + 572Byte general Device information
		Valve Type	(normally open / normally closed)	B	2.43KB Services + 572Byte general Device information
		Heater Type	Underfloor Heating / Underfloor Heating low energy / Radiator / Passive Convactor (without fan) / active Convactor (with fan)	B	2.43KB Services + 572Byte general Device information
		Cooling mode	On/Off	B	2.43KB Services + 572Byte general Device information
		Current humidity	measured relative	Between <1s and never	2.43KB Services

	humidity	(if no change happened).	+ 572Byte general Device information
Display switch-on duration	(in sec)	B	2.43KB Services + 572Byte general Device information
Display brightness	(in %)	B	2.43KB Services + 572Byte general Device information
Sensor Connection	(not used/ Temperature sensor / potential-free contact)	B	2.43KB Services + 572Byte general Device information
Time Schedules	Name/ Days of the Week/ Times/ Degrees Shift work Monday 0-8 18° Monday 8-12 22°	B	2.43KB Services + 572Byte general Device information
Operation mode	manual/automatic	B	2.43KB Services + 572Byte general Device information
Current temperature	18°	Between <1s and never (if no change happened). Typical every 120-180s.	2.43KB Services + 572Byte general Device information
Target temperature	22°	B	2.43KB Services + 572Byte general Device information
Boost	on/off	B	2.43KB Services + 572Byte

general
Device
information

Universal Switch II	8750002504	Key assignment 1 long	Operation function (Alarm system, dimmable lamps, devices, scenario, shutters/ blinds)	B	965Byte Services + 424Byte general Device information
		Key assignment 1 short	dito	B	965Byte Services + 424Byte general Device information
		Key press 1	yes/no	B	965Byte Services + 424Byte general Device information
		Key assignment 2 long		B	965Byte Services + 424Byte general Device information
		Key assignment 2 short		B	965Byte Services + 424Byte general Device information
		Key press 2	yes/no	B	965Byte Services + 424Byte general Device information
		Key assignment 3 long		B	965Byte Services + 424Byte general Device information
		Key assignment 3 short		B	965Byte Services + 424Byte general Device information

					information
		Key press 3	yes/no	B	965Byte Services + 424Byte general Device information
		Key assignment 4 long		B	965Byte Services + 424Byte general Device information
		Key assignment 4 short		B	965Byte Services + 424Byte general Device information
		Battery State		S	965Byte Services + 424Byte general Device information
		Key press 4	yes/no	B	965Byte Services + 424Byte general Device information
Radiator Thermostat II [+M]	8750002861	when connected through SHC: See Radiator Thermostat II values			
Door Window Contact II [+M]	8750002952	when connected through SHC: See Door Window Contact II values			
Plug compact [+M]	8750003107	Status	on/off	B	3.15KB Services + 569Byte general Device information
		Mode	(manual /	B	3.15KB

automatic)				Services + 569Byte general Device information
	Profil	(Lighting, heating, Standard, miniPV)	B	3.15KB Services + 569Byte general Device information
	Status after powercut	Off / On / Status before power cut)	B	3.15KB Services + 569Byte general Device information
	energy consumption level (Wh)	23 WH	Min: 30s Max. 3600s	3.15KB Services + 569Byte general Device information
	power consumption level (W)	400 W	Min: 30s Max. 3600s	3.15KB Services + 569Byte general Device information
	energy yield level (Wh)			3.15KB Services + 569Byte general Device information
	power yield level (W)			3.15KB Services + 569Byte general Device information
	Schedules	Name/Weekdays/ Times/ON/OFF	B	3.15KB Services + 569Byte general Device information
	Timer (switch on)		B	3.15KB Services

				+ 569Byte general
				Device information
		Reseted consumption value	Date/ time	B
				3.15KB Services + 569Byte general
				Device information
Connected Zigbee Ledvance lamps		Status	Available / not Available	Between <1s and never (if no change happened).
				958Byte Service + 470Byte general
				Device information
		Status	on / off / brightness / colour	B
				958Byte Services + 470Byte general
				Device information

Bosch Smart Home Cameras

You can access the data generated and potentially stored in the product as follows:

App

The following mobile application is required for access:
 Bosch Smart Camera: [Google Play Store](#) [Apple App Store](#)

The terms of use required for use can be viewed at the following link:
[Here you will find the current version of the terms and conditions for the Bosch Smart Camera app.](#)

Product name	Item number	Data	Subcategory / Details	Example	How often is the data updated?
					1. Time interval 2. User Action (B)

			3. Reaction to system status change (S)
Eyes Indoor II / Eyes Outdoor II (Common Functionality)	Privacy Mode	On / Off	B
	Privacy Mode Timer	Either date or number of seconds from now	B S Is reset by system if time is reached
	Alarm Type	INTRUSION_ALARM	B
	Connection Status	ONLINE	B S Is set according to the state of the connection by the system.
	Snapshot Image	Jpeg snapshot image	B S Snapshot images are created when an event is created which is not triggered by turning the camera on/off.
	Live Video	Different urls for local or remote video streaming including http basic auth credentials to view the stream.	B
	Audio Intercom Settings	audioEnabled: True microphoneLevel: 50 speakerLevel: 60	B
	Audio Intercom	Bidirectional audio stream	B
	Event	eventTags: [MOVEMENT] type: MOVEMENT isFavorite: True id: "1" imageUrl: <url to	B S Events are created when camera detects an event

	image> isFavorite: False isRead: True timestamp: 2020-12-24T18:21Z title: Postman videoClipUpload-Progress: 100 videoClipUpload-Status: Done videoClipUrl: <url to clip> videoInputId: "2"	by interpreting camera sensor data or when turning camera on/off. Types of events to consider can be set by user.
Clip	mp4 file of recorded clip	B S Clips are recorded when an event is created which is not triggered by turning the camera on/off.
Feature Flags	APP_RATING: False IOT_THINGS_INTEGRATION: True	S Set by system.
Friends	id: "1" invitationState: "ACCEPTED" nickName: "Eugen" videoInputList: [shareTime: [end: 1886-12-25T18:21Z, start: 1886-12-24T18:21Z]] videoInputId: "2"	B S InvitationState is being changed by system according to the invitations current state.
Logs	category: "WIFI" message: "Connection to WIFI failed."	S Logs are generated by the system for troubleshooting.
Purchases	appPlatform: "IOS" cameralds: ["1", "2"] productId: "com.bosch.smartcameralld_month_ios" status: "ACTIVE" type: "CLOUDPLUS_ALL"	B
User	displayName: "Robert" email: "robert@bosch.com" firstName: "Robert" iotThingsIntegration:	B

		True language: "de_DE" lastName: "Bosch" locale: "de_DE" marketingContact: True (receive marketing notifications) timeZone: "UTC+01:00"	
	Pre-Maintenance Mode	False	S Set by system.
	Feature Support	light: False panLimit: 30 (Maximum camer pan angle) sound: True (Does device have a microphone) viewingAngle: 120	Static
	Integrated with SHC	True	B
	Notification Settings	enabled: True enabledStatus: ON_CAMERA_ SCHEDULE Notifications off timer: Either date or number of seconds from now until notifications on again When to notify? audio: True cameraAlarm: True movement: True person: True trouble: True troubleEmail: True schedule rules when notifications should not be sent startTime: 17:00 endTime: 24:00 id: "1" isActive: True name: "After work time" weekdays: [1,2,3,4,5] (Integers start with 0 for Sunday)	B
	Camera Priority	0.9 (Number used for sorting the video inputs device independently)	B

Recording on	True	S Set to true by system whenever a clip is recorded.
Record sound	True	B
Shared with me	Not defined if camera is your own, else: nickName: "Eugen Kayser" timeInterval: [end: 1887-12-27T18:21Z, start: 1887-12-25T18:21Z]	B S Set to undefined by system if sharing has ended.
Time Zone	UTC+01:00	B
Camera Title	Roberts Cam	B
LED Light Status	On/Off	B
Motion Events Settings	enabled: True alarmSensitivity: "MEDIUM_LOW" alarmSensitivityValue: 50 detectionMode: "ZONES"	B
Motion Sensitive Areas	color: "0xFFFFFF" id: "1" maskType: "BOUNDING_BOX" name: "Driveway" points: coordinates that define the zone For every zone: 8 Points with x and y coordinates trigger: "PERSON" useCase: "RECORDING"	B
Time stamp overlay	enabled/disabled	B
WIFI info	ipAddress: "192.168.47.11" macAddress: "FF:FF:FF:FF:FF:FF" signalStrength: 87 ssid: "RobertsWLAN"	signalStrength refresh every 60s B ssid S ipAddress and macAddress

are saved using
provided
ssid while
commissioning

Eyes Indoor II	Alarm System	Status	armed / unarmed	B und gekoppelt an Privacy Mode
	Intrusion Detection Config		detectionMode: "ALL_MOTIONS" enabled: True sensitivity: 80	B
	Night Mode Config		AUTOMATIC	B
Eyes Outdoor II	Lighting	Front Light	On/Off/Color temperature/Intensity	B
		Top Light	On/Off/Color temperature/Intensity	B
		Bottom Light	On/Off/Color temperature/Intensity	B
		Light on Motion	activated: True/False lightOnMotionFollowUp: 20	B
		Darkness Threshold	0.3	B
		Lighting Schedule	status: "FOLLOW SCHEDULE" offTime: 12:00 onTime: 00:00	B
		Soft Light Fading	On/Off	B
		Ambient Light	Enabled/Disabled	B
	Private Areas		coordinates that define privacy mask For every mask: 8 Points with x and y coordinates	B
	Lens Elevation		1.7 (meters)	B

Bosch/Buderus Energiemanager

You can access the data generated and potentially stored in the product as follows:

Email enquiry to EU-DataAct.HC@bosch.com

Product name	Data	Example	Format	Scope	Generation	Storage location	Storage duration
Bosch Energie-manager / Buderus MyEnergy Master / IVT Energy Master	Diagnostic data	Type of connected heat pump; Number of times the energy manager intervened in the heat pump's operation; Error messages	Table (CSV)	ca. 200 kB/Tag	continuously	Server, device	3 Months
	Operating data	PV power; heat pump consumption; battery charge level	Table	ca. 100 kB/Tag	continuously	device	3 years
	Configuration data	Minimum share of PV for EV charging	database	ca. 1 kB/day	not continuously	device	until the device is reset