pi — Cheat Sheet

AI coding assistant · CLI, slash commands & hotkeys

CLI — GETTING STARTED

`pi`	Start interactive session
`pi "msg"`	Start with a prompt
`pi @file.js "fix"`	Attach file(s) to prompt
`pi -p "msg"`	Non-interactive, print & exit
`pi -c`	Continue previous session
`pi -r`	Resume: pick a session
`pi -v`	Show version
`pi -h`	Show help

CLI — SESSIONS

`--session <id>`	Use specific session file/UUID
`--fork <id>`	Fork session into new one
`--no-session`	Ephemeral (don't save)
`-n <name>`	Set session display name
`--export <f>`	Export session to HTML

CLI — MODELS & THINKING

`--provider <n>`	Provider (default google)
`--model <pat>`	Model pattern or ID
`--models <p,p>`	Patterns for Ctrl+P cycling
`--thinking <lvl>`	off/low/medium/high/max
`--list-models`	List available models
`--api-key <k>`	API key (else env vars)

CLI — TOOLS & EXTENSIONS

`-t <tools>`	Allowlist of tools to enable
`-xt <tools>`	Denylist of tools to disable
`-nt`	Disable all tools
`-e <path>`	Load an extension
`--skill <path>`	Load a skill
`--theme <path>`	Load a theme
`-a`	Trust project-local files

CLI — SUBCOMMANDS

`pi install <src>`	Install extension
`pi remove <src>`	Remove extension
`pi update`	Update pi / extensions
`pi list`	List installed extensions
`pi config`	Enable/disable resources
`pi auth <cmd>`	Print credentials

SLASH — SESSIONS

`/new`	Start a new session
`/resume`	Pick a previous session
`/session`	Info: file, ID, tokens, cost
`/name <n>`	Set display name
`/tree`	Jump to any point, continue
`/fork`	New session from a message
`/clone`	Duplicate active branch
`/trust`	Save project trust decision

SLASH — CONTEXT & EXPORT

`/compact [p]`	Compact context, opt. prompt
`/copy`	Copy last reply to clipboard
`/export [f]`	Export to HTML or JSONL
`/import <f>`	Import & resume from JSONL
`/share`	Upload as private gist link
`/reload`	Reload config & extensions

SLASH — CONFIG

`/model`	Switch models
`/scoped-models`	Models for Ctrl+P cycling
`/settings`	Thinking, theme, delivery
`/login /logout`	Manage credentials
`/hotkeys`	Show all shortcuts
`/changelog`	Version history
`/quit`	Quit pi
`/skill:name`	Invoke a skill

HOTKEYS — APPLICATION

`Esc`	Cancel / abort
`Ctrl+C`	Clear editor / copy selection
`Ctrl+D`	Exit (editor empty)
`Ctrl+Z`	Suspend to background
`Ctrl+G`	Open external editor
`Ctrl+V`	Paste image from clipboard
`Enter`	Submit input
`Shift+Enter`	New line

HOTKEYS — MODELS & VIEW

`Ctrl+L`	Open model selector
`Ctrl+P`	Cycle to next model
`Shift+Ctrl+P`	Cycle to previous model
`Shift+Tab`	Cycle thinking level
`Ctrl+T`	Collapse/expand thinking
`Ctrl+O`	Collapse/expand tool output
`Ctrl+X`	Copy last assistant message

HOTKEYS — QUEUE & EDITING

`Alt+Enter`	Queue follow-up message
`Alt+Up`	Restore queued to editor
`Ctrl+W`	Delete word backward
`Ctrl+U`	Delete to line start
`Ctrl+K`	Delete to line end
`Ctrl+Y`	Yank (paste deleted)
`Ctrl+A / Ctrl+E`	Line start / end
`Ctrl+-`	Undo last edit

BUILT-IN TOOLS

`read`	Read file contents
`bash`	Execute bash commands
`edit`	Edit files (find/replace)
`write`	Write / overwrite files
`grep`	Search contents (off default)
`find`	Find files by glob (off def.)
`ls`	List directory (off default)

KEY ENV VARS

`PI_CODING_AGENT_DIR`	Config dir (~/.pi/agent)
`..._SESSION_DIR`	Session storage dir
`PI_OFFLINE`	Disable startup network ops
`PI_TELEMETRY`	Toggle install telemetry
`EDITOR / VISUAL`	External editor (Ctrl+G)

Customize keybindings in `~/.pi/agent/keybindings.json` · run `/reload` to apply · Type `/` in editor for commands