Q07: Why Does Scaling Work, and What Are Its Limits?

DLS 2026 — module author: Kukla

October 2026

Learning objectives

- State the empirical scaling laws and what they predict.
- Explain compute-optimal (Chinchilla) training and why it changed practice.
- Reason about the known limits of scaling and whether theory can explain it.

> **Companion video (5:38):** *Understanding LLM Chinchilla Scaling Laws* — Cloudvala. https://www.youtube.com/watch?v=TYCw8QSNT9w

1 The empirical finding

Student responses #21, #22, #39 ask why scaling works, whether there is a "science of scaling," and what its limits are. The surprising empirical fact: test loss of language models falls as a smooth *power law* in model size N, dataset size D, and compute C, over many orders of magnitude [2]. Concretely, loss $L(N) \approx L_\infty + (N_0/N)^\alpha$ with small exponent α; doubling parameters cuts the *reducible* loss by a fixed fraction. That such a noisy, high-dimensional system obeys a clean low-parameter curve is the empirical backbone of the whole scaling program, and it is what lets labs *predict* the loss of a model before training it.

2 Compute-optimal training (Chinchilla)

Kaplan et al. emphasized model size; Hoffmann et al. ("Chinchilla") corrected the recipe: for a fixed compute budget $C \approx 6ND$, loss is minimized by scaling N and D *together*, roughly equally [1]. Many earlier models were badly over-parameterized and under-trained—too many weights, too few tokens. The practical upshot that reshaped the field: a smaller model trained on more data can beat a larger model trained on less, at equal cost. This is the clearest example of scaling laws being not just descriptive but *prescriptive*.

3 Why would scaling work at all?

There is no complete theory, but several partial accounts. (1) **Prediction as compression**: lower loss means a better model of the data-generating process, and richer structure must be learned to predict better. (2) **Manifold / data-distribution** arguments relate the power-law exponent to the intrinsic dimension of the data. (3) **Over-parameterization** lets gradient descent find generalizing solutions (ties to module Q06's double descent). None of these yet predicts the exponents from first principles, so "science of scaling" today means *reliable empirical laws with partial theoretical understanding*, not a closed theory.

4 Reading a scaling law, concretely

It helps to put numbers to the power law. Suppose the reducible loss follows $(N_0/N)^\alpha$ with $\alpha \approx 0.08$ (a representative value for the parameter axis). Then a $10\times$ increase in parameters multiplies the reducible loss by $10^{-0.08} \approx 0.83$—a 17% cut. To halve the reducible loss you need $0.5 = (1/f)^{0.08}$, i.e. $f = 2^{1/0.08} \approx 5{,}700\times$ more parameters. That single calculation explains three things at once: why progress looked smooth and reliable (the curve is stable), why it is so *expensive* (halving loss costs thousands-fold compute), and why labs obsess over the exponent (a small change in α swings the economics enormously). The companion code fits exactly this kind of curve and shows the fit extrapolating cleanly in-regime but drifting if the exponent estimate is slightly off—a caution that applies to every published forecast built on a scaling law.

5 Loss curves vs. what people actually care about

Students should not confuse the thing that scales smoothly (next-token loss, in bits/token) with the thing they care about (can it pass the bar exam, write correct code, avoid hallucinating). The mapping from loss to downstream capability is itself nonlinear and task-dependent: large regions of loss improvement produce little visible change, then a threshold is crossed and a benchmark jumps. Whether those jumps are genuine phase transitions or artifacts of hard-edged metrics is the "emergence" debate (module Q06). The practical takeaway: a confident loss forecast is *not* a confident capability forecast, and responsible planning tracks both.

6 The limits

- **The data wall**: compute-optimal scaling demands more tokens, but high-quality human text is finite; this is a binding constraint and drives work on data quality, synthetic data, and multi-epoch training.
- **Diminishing returns**: the exponent is small, so each new capability costs exponentially more compute; naive loss-scaling eventually becomes uneconomic.
- **Loss is not capability**: a smooth loss curve can hide abrupt, uneven changes in downstream task performance, and whether such "emergence" is real or a measurement artifact is debated (module Q06).
- **New axes**: recent gains come increasingly from *post-training* and *inference-time* compute (modules Q04, Q05), not just bigger pre-training—evidence the pre-training power law alone is not the whole story.

7 Can learning theory model it?

Classical statistical learning theory (VC dimension, uniform convergence) predicts over-parameterized models should overfit—yet they scale gracefully, so classical bounds are too loose to explain scaling. Newer approaches (data-manifold dimension arguments, solvable models in simplified settings) recover power laws under assumptions, but a predictive theory matching real exponents across architectures does not yet exist. The companion code (`code/scaling_fit.py`) fits a power law to synthetic loss-vs-compute data and extrapolates, illustrating both the method and its fragility.

8 Summary

Scaling works empirically: loss follows clean power laws in N, D, C, enabling pre-training outcome prediction. Chinchilla showed N and D should grow together. Partial theories (compression, data-manifold, over-parameterization) explain *that* it works but not the exponents. Limits are real (data wall, diminishing returns, loss≠capability), and the frontier is shifting toward post-training and inference-time compute.

References

[1] Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, et al. Training compute-optimal large language models. *arXiv:2203.15556*, 2022.

[2] Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv:2001.08361*, 2020.