Q25: Can AI Agents Fine-Tune and Improve Other Models?

DLS 2026 — module author: Kukla

October 2026

Learning objectives

- Enumerate the concrete ways AI agents already help build and improve models.
- Distinguish genuine capability gains from circular self-evaluation traps.
- Assess the limits and risks of AI-improving-AI loops.

> **Companion video (19:01):** *Knowledge Distillation Explained: AI Model Compression Tutorial* — Richard Aragon.
> https://www.youtube.com/watch?v=C52ArSpB_9I

1 The question

Student response #40 asks whether AI agents can be used to fine-tune and improve other models efficiently. The answer is a qualified yes: AI systems are already deeply embedded in the pipeline that produces other AI systems—but the useful cases are specific, and there are real traps where the loop only *appears* to improve things.

2 Where AI already improves AI

- **Synthetic data generation.** Strong models generate training examples, instructions, and solutions to fine-tune smaller or newer models—the engine behind much modern post-training and **distillation**, where a student learns from a teacher's outputs [**?**].
- **AI feedback for alignment. RLAIF** and Constitutional AI replace much of the human preference labeling in RLHF with model-generated preferences against a written set of principles [**?**], cutting labeling cost.
- **LLM-as-judge.** Models evaluate other models' outputs at scale, powering automatic benchmarks and reward signals [**?**]—useful but bias-prone (next section).
- **Data curation and filtering.** Models score, deduplicate, and filter pre-training corpora, and strong data filtering is now one of the highest-leverage ways to improve a model.
- **Agentic engineering loops.** Coding agents propose architecture/hyperparameter changes, run experiments, and iterate—automating parts of the ML research loop itself.

3 The traps

Efficiency is real, but three failure modes recur. (1) **Circularity**: if a model both generates and judges, biases are self-reinforcing—LLM judges favor their own style, longer answers, and first-listed options, so "improvement" measured by a related judge can be illusory. (2) **Model collapse**: training repeatedly on model-generated data can degrade quality and diversity over generations as the data distribution narrows toward the model's own tendencies [**?**]. (3) **Reward hacking**: an agent optimizing against an automatic signal will exploit its flaws rather than achieve the intended goal. These are why AI-improving-AI is a powerful accelerant but not a free lunch—human-grounded evaluation and fresh real data remain load-bearing.

4 A concrete loop: distillation done right

Take the most mature case—distillation—and trace it end to end. A strong, expensive "teacher" model generates answers (and often full reasoning traces) for a large set of prompts; a smaller "student" is then fine-tuned to reproduce the teacher's outputs. The efficiency win is real and large: the student can approach a sizable fraction of the teacher's task performance at a fraction of the inference cost, which is why many deployed small models are distilled from bigger ones. But notice what is and is not transferred. The student inherits the teacher's *behavior on the covered distribution*, including the teacher's mistakes and blind spots; it does not acquire capability the teacher lacked, and it can amplify the teacher's biases if its outputs are taken uncritically. A well-run distillation therefore filters teacher outputs (reject low-quality or incorrect ones, ideally with an *independent* check), mixes in real ground-truth data where available, and evaluates the student on held-out human-labeled tasks rather than on agreement with the teacher. The same discipline generalizes to synthetic-data and RLAIF pipelines.

5 Why efficiency and rigor are not in tension

It is tempting to read the traps as a reason to avoid AI-improving-AI, but that is the wrong lesson. The efficiency gains—orders of magnitude cheaper labeling, data generation, and evaluation—are exactly why the technique is ubiquitous, and abandoning them is not competitive. The right framing is that the automatic loop must be *anchored*: a comparatively small amount of independent, human-grounded signal (a held-out labeled set, a periodic human audit, fresh real data) is enough to catch circularity, collapse, and reward hacking before they compound. The expensive human effort moves from doing all the labeling to *auditing the loop*, which is a far better use of it. Students should leave seeing AI-improving-AI as a powerful tool that demands a specific, affordable form of oversight—not as either a panacea or a trap.

6 Doing it safely and efficiently

The responsible pattern keeps an independent, human-grounded check in the loop: use AI feedback for scale but validate on held-out human-labeled data; mix synthetic with fresh real data to resist collapse; ensure the generator and the judge are not the same model optimizing the same signal; and treat automatic metrics as proxies to be audited, not ground truth. Done this way, agents genuinely compress the cost of data generation, preference labeling, evaluation, and experimentation—often by large factors—without the loop quietly drifting.

7 Summary

Yes—agents already improve other models via synthetic data, distillation, RLAIF/constitutional feedback, LLM-as-judge, data curation, and agentic experiment loops, often with big efficiency gains. But circularity, model collapse, and reward hacking mean AI-improving-AI must be anchored by independent human-grounded evaluation and fresh real data to produce genuine, not illusory, improvement.

References

[] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv:2212.08073*, 2022.

[] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv:1503.02531*, 2015.

[] Ilia Shumailov, Zakhar Shumaylov, Yiren Zhao, Nicolas Papernot, Ross Anderson, and Yarin Gal. Ai models collapse when trained on recursively generated data. *Nature*, 631, 2024.

[] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, et al. Judging llm-as-a-judge with mt-bench and chatbot arena. In *NeurIPS*, 2023.