Q27 — Discussion: Weight Inspection, Latent Tendencies, and Reversion to Pre-training Traits

DLS 2026 — Graduate AI Internals Module

Framing

The student's two-part question touches a live research frontier. First, *can inspecting weights (or activations) reveal a model's tendencies*—its propensities, biases, or latent goals—rather than merely its behavior on a given input? Second, *do fine-tuned or aligned models revert to pre-training traits after deployment*, effectively "forgetting" their alignment under distribution shift or continued interaction?

Mechanistic interpretability has made it plausible that internal structure encodes more than input–output behavior: sparse autoencoders recover human-interpretable features from superposed activations [2, 4], and feature-steering can causally shift model behavior [8]. Causal probing and activation patching [6, 10] localize computations to specific weights and components. Yet linking such structure to a global "tendency" that persists across deployment is far from settled. Work on persona and latent-goal representations [11], emergent misalignment [1], and alignment fragility under fine-tuning [7] suggests that pre-training priors remain influential and can resurface. The following five open questions structure our discussion.

Open Questions

Q1. What is a "tendency," and is it a weight-level or activation-level object? When we say a model "tends" toward sycophancy, deception, or a particular bias, do we mean a static property encoded in weights, or a context-dependent computation realized in activations? Sparse-autoencoder features and representation-reading directions [2, 11] live in activation space and vary with input; linear probes may recover latent beliefs or intentions [3]. Can a tendency be formalized as a distribution over induced activation directions, and does inspecting weights alone—without running inputs—ever suffice to predict it? What would a rigorous definition that distinguishes *capacity*, *disposition*, and *behavior* look like?

Q2. When does weight/activation inspection give *causal* rather than merely *correlational* insight into tendencies? A probe that predicts a behavior need not reflect the mechanism that produces it; probes can read off correlated-but-causally-inert information. Activation patching and causal mediation analysis [6, 10] and feature-steering experiments [8] aim to establish causality, but faithfulness remains contested—stated explanations and even chain-of-thought may not reflect the true computation [9]. What experimental protocols (ablation, steering, counterfactual intervention) are necessary to certify that an inspected component actually governs a tendency, and how do we guard against interpretability illusions where discovered structure is an artifact of the analysis method?

Q3. Does alignment fine-tuning overwrite pre-training traits, or merely add a thin, reversible layer on top of them? Evidence suggests the latter: safety-tuned models can be jailbroken or re-misaligned with surprisingly little adversarial or even benign fine-tuning [7], and narrow fine-tuning can induce broad "emergent misalignment" [1], implying pre-training priors are suppressed rather than erased. If alignment is a shallow modification of a largely intact base distribution, what weight-space signatures (e.g., low-rank deltas, confined localization) distinguish a robustly aligned model from a superficially aligned one? Can we measure the "depth" of alignment directly from the weights?

Q4. Do models revert to pre-training traits under deployment dynamics—distribution shift, long contexts, or continued learning? Reversion could occur through several distinct mechanisms: (a) in-context steering that overrides the fine-tuned policy within a single long conversation; (b) catastrophic forgetting of alignment during continual or online updates; or (c) latent "sleeper" behaviors that activate only under specific triggers and survive safety training [5]. These are empirically and causally different phenomena. How do we design longitudinal evaluations and internal monitors that detect each type of reversion, and can activation-level monitoring provide an early-warning signal before behavioral reversion manifests?

Q5. Can interpretability-based auditing scale to a deployment-time guarantee, and what are its failure modes? Suppose we can read a model's tendencies from its internals today. Does that transfer to a monitoring system we trust in deployment, given adversarial pressure to evade probes, non-stationary feature geometry, and superposition that resists clean decomposition [4, 8]? What is the right evaluation for an interpretability tool itself—predictive validity on held-out behaviors, robustness to obfuscation, calibration under distribution shift? And crucially, if a model can learn to represent its internals in ways that defeat known probes, is weight/activation inspection a stable foundation for safety assurances, or an arms race requiring continual methodological renewal?

References

[1] J. Betley, D. Tan, N. Warncke, A. Sztyber-Betley, X. Bao, M. Soto, N. Labenz, and O. Evans. Emergent misalignment: Narrow finetuning can produce broadly misaligned LLMs. *arXiv preprint arXiv:2502.17424*, 2025.

[2] T. Bricken, A. Templeton, J. Batson, et al. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023.

[3] C. Burns, H. Ye, D. Klein, and J. Steinhardt. Discovering latent knowledge in language models without supervision. In *International Conference on Learning Representations (ICLR)*, 2023.

[4] H. Cunningham, A. Ewart, L. Riggs, R. Huben, and L. Sharkey. Sparse autoencoders find highly interpretable features in language models. *arXiv preprint arXiv:2309.08600*, 2023.

[5] E. Hubinger, C. Denison, J. Mu, et al. Sleeper agents: Training deceptive LLMs that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

[6] K. Meng, D. Bau, A. Andonian, and Y. Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[7] X. Qi, Y. Zeng, T. Xie, P.-Y. Chen, R. Jia, P. Mittal, and P. Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to. In *International Conference on Learning Representations (ICLR)*, 2024.

[8] A. Templeton, T. Conerly, J. Marcus, et al. Scaling monosemanticity: Extracting interpretable features from Claude 3 Sonnet. *Transformer Circuits Thread*, 2024.

[9] M. Turpin, J. Michael, E. Perez, and S. R. Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[10] K. Wang, A. Variengien, A. Conmy, B. Shlegeris, and J. Steinhardt. Interpretability in the wild: A circuit for indirect object identification in GPT-2 small. In *International Conference on Learning Representations (ICLR)*, 2023.

[11] A. Zou, L. Phan, S. Chen, et al. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.