Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

Autonomous Systems Lab
Prof. Roland Siegwart

Master Thesis

Use of a DVS for High Speed Applications

Autumn Term 2018

Supervised by:
Florian Tschopp
Ignacio Alzugaray

Author:
Weizhen Huang

Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

Declaration of originality

The signed declaration of originality is a component of every semester paper, Bachelor's thesis, Master's thesis and any other degree paper undertaken during the course of studies, including the respective electronic versions.

Lecturers may also require a declaration of originality for other written papers compiled for their courses.

I hereby confirm that I am the sole author of the written work here enclosed and that I have compiled it in my own words. Parts excepted are corrections of form and content by the supervisor.

Title of work (in block letters):

Authored by (in block letters):
For papers written by groups the names of all authors are required.

Name(s): **First name(s):**

With my signature I confirm that
- I have committed none of the forms of plagiarism described in the 'Citation etiquette' information sheet.
- I have documented all methods, data and processes truthfully.
- I have not manipulated any data.
- I have mentioned all persons who were significant facilitators of the work.

I am aware that the work may be screened electronically for plagiarism.

Place, date **Signature(s)**

For papers written by groups the names of all authors are required. Their signatures collectively guarantee the entire content of the written paper.

Contents

Preface

Bla bla ...

Abstract

Hier kommt der Abstact hin . . .

Symbols

Symbols

ϕ, θ, ψ	roll, pitch and yaw angle
b	gyroscope bias
Ω_m	3-axis gyroscope measurement

Indices

x	x axis
y	y axis

Acronyms and Abbreviations

ETH	Eidgenössische Technische Hochschule
EKF	Extended Kalman Filter
IMU	Inertial Measurement Unit
UAV	Unmanned Aerial Vehicle
UKF	Unscented Kalman Filter

Chapter 1

Introduction

Hier kommt die Einleitung DVS is

Chapter 2

Einige wichtige Hinweise zum Arbeiten mit LaTeX

Throughout this work the following notation is employed: W denotes the world frame, C_1 or C_2 denotes a camera frame. T_{AB} is the transformation from frame A to frame B, measured in frame A.
$\boldsymbol{X}$ the position of the event with respect to world or camera frame, $\boldsymbol{x}$ the calibrated coordinates of the event.

2.1 From Events to Frame

We group a set of events $\mathscr{E} \doteq \{e_k\}_{k=1}^{N}$ into a temporal window, optimize the motion and scene parameters within this window, then shift the window to the next set of events and repeat this process. The temporal window size is defined by the event numbers N, which should be chosen small enough so that a constant velocity model could be applied within this window. We choose event numbers against a fixed time interval to define the window size, because this corresponds to the data-driven nature of an event-based camera: the more rapid the apparent motion of the scene is, the larger the event rate will be. If the scene stops moving, no events will be generated, the pose will also not be further updated.
An event frame is thus formed by summing up events within this window. If we simply sum along the time axis, the intensity at each pixel will be the sum of the polarities of all the events that are triggered at this pixel location within the window

$$\mathcal{I}(\boldsymbol{x}) = \sum_{1}^{N} \pm_k (\boldsymbol{x} - \boldsymbol{x}_k), \tag{2.1}$$

with $\pm_k$ and $\boldsymbol{x}_k$ denoting the polarity and pixel coordinates of the kth event, respectively. After warping the events with $\boldsymbol{x}'_k = \boldsymbol{W}(\boldsymbol{x}_k, t; \theta)$, we substitute $\boldsymbol{x}_k$ in the above equation to $\boldsymbol{x}'_k$.

2.1.1 Planar Homography

The warp function $\boldsymbol{x}' = \boldsymbol{W}(\boldsymbol{x}, t; \theta)$ does not only depend on the motion parameters, but also the scene parameters, which is the unknown depth. In the case of a planar scene the problems simplifies, since a plane $\mathbf{P}$ can be parameterized by two sets of parameters: $\boldsymbol{n} \in \mathbb{S}^2$ the unit surface normal of $\mathbf{P}$ with respect to the current camera frame, and d the distance from the camera center to $\mathbf{P}$. The warp function then becomes

$$\boldsymbol{X} = \boldsymbol{R}\boldsymbol{X}' + \boldsymbol{T} \tag{2.2}$$
$$\boldsymbol{X}' = \boldsymbol{R}^\top (\boldsymbol{X} - \boldsymbol{T}) \tag{2.3}$$
$$\boldsymbol{X}' = \boldsymbol{R}^\top \left(\boldsymbol{I} + \boldsymbol{T}\boldsymbol{n}^\top/d\right) \boldsymbol{X}, \tag{2.4}$$

thus $\boldsymbol{x}' \sim \boldsymbol{R}^\top \left(\boldsymbol{I} + \boldsymbol{T}\boldsymbol{n}^\top/d\right) \boldsymbol{x}$. Here $(\boldsymbol{R}, \boldsymbol{T}) \in SE(3)$ denotes the relative pose between two cameras at which the current event being warped and the first event within the window happened. Under a constant velocity model with linear velocity $\boldsymbol{v} \in \mathbb{R}^3$ and angular velocity $\boldsymbol{\omega} \in \mathbb{R}^3$, the translation is given by

$$\boldsymbol{T}(t) = \boldsymbol{v}t, \tag{2.5}$$

the rotation matrix is given by the *exponential map* exp: $\mathfrak{so}(3) \to SO(3)$:

$$\boldsymbol{R}(t) = \exp(\boldsymbol{\omega}^\wedge t), \tag{2.6}$$

where $^\wedge$ is the *hat* operator

$$\boldsymbol{\omega}^\wedge = \begin{bmatrix} \omega_1 \\ \omega_2 \\ \omega_3 \end{bmatrix} = \begin{bmatrix} 0 & -\omega_3 & \omega_2 \\ \omega_3 & 0 & -\omega_1 \\ -\omega_2 & \omega_1 & 0 \end{bmatrix} \in \mathfrak{so}(3), \tag{2.7}$$

2.2 From Frames to Map

The procedure in the above section optimizes the relative pose between successive frames.

2.3 Gliederungen

Ein Text kann mit den Befehlen `\chapter{.}`, `\section{.}`, `\subsection{.}` und `\subsubsection{.}` gegliedert werden.

2.4 Referenzen und Verweise

Literaturreferenzen werden mit dem Befehl `\citep{.}` und `\citet{.}` erzeugt. Beispiele: ein Buch [1], ein Buch und ein Journal Paper [1, 2], ein Konferenz Paper mit Erwähnung des Autors: Pratt and Williamson [3].
Zur Erzeugung von Fussnoten wird der Befehl `\footnote{.}` verwendet. Auch hier ein Beispiel[1].
Querverweise im Text werden mit `\label{.}` verankert und mit `\cref{.}` erzeugt. Beispiel einer Referenz auf das zweite Kapitel: chapter 2.

2.5 Aufzählungen

Folgendes Beispiel einer Aufzählung ohne Numerierung,

- Punkt 1
- Punkt 2

wurde erzeugt mit:

[1] Bla bla.

```
\begin{itemize}
\item Punkt 1
\item Punkt 2
\end{itemize}
```

Folgendes Beispiel einer Aufzählung mit Numerierung,

1. Punkt 1
2. Punkt 2

wurde erzeugt mit:

```
\begin{enumerate}
\item Punkt 1
\item Punkt 2
\end{enumerate}
```

Folgendes Beispiel einer Auflistung,

P1 Punkt 1

P2 Punkt 2

wurde erzeugt mit:

```
\begin{description}
\item[P1] Punkt 1
\item[P2] Punkt 2
\end{description}
```

2.6 Erstellen einer Tabelle

Ein Beispiel einer Tabelle:

Table 2.1: Daten der Fahrzyklen ECE, EUDC, NEFZ.

Kennzahl	Einheit	ECE	EUDC	NEFZ
Dauer	s	780	400	1180
Distanz	km	4.052	6.955	11.007
Durchschnittsgeschwindigkeit	km/h	18.7	62.6	33.6
Leerlaufanteil	%	36	10	27

Die Tabelle wurde erzeugt mit:

```
\begin{table}[h]
  \begin{center}
    \caption{Daten der Fahrzyklen ECE, EUDC, NEFZ.}\vspace{1ex}
    \label{tab:tabnefz}
    \begin{tabular}{ll|ccc}
      \hline
      Kennzahl & Einheit & ECE & EUDC & NEFZ \\ \hline \hline
      Dauer & s & 780 & 400 & 1180 \\
      Distanz & km & 4.052 & 6.955 & 11.007 \\
      Durchschnittsgeschwindigkeit & km/h & 18.7 &  62.6 & 33.6 \\
      Leerlaufanteil & \% & 36 & 10 & 27 \\
```



Figure 2.1: Ein Bild

```
      \hline
    \end{tabular}
  \end{center}
\end{table}
```

2.7 Einbinden einer Grafik

Das Einbinden von Graphiken kann wie folgt bewerkstelligt werden:

```
\begin{figure}
  \centering \includegraphics[width=0.75\textwidth]{images/k_surf.pdf}
  \caption{Ein Bild.}
  \label{fig:k_surf}
\end{figure}
```

oder bei zwei Bildern nebeneinander mit:

```
\begin{figure}
  \begin{minipage}[t]{0.48\textwidth}
    \includegraphics[width = \textwidth]{images/cycle_we.pdf}
  \end{minipage}
  \hfill
  \begin{minipage}[t]{0.48\textwidth}
    \includegraphics[width = \textwidth]{images/cycle_ml.pdf}
  \end{minipage}
  \caption{Zwei Bilder nebeneinander.}
  \label{pics:cycle}
\end{figure}
```



Figure 2.2: Zwei Bilder nebeneinander

2.8 Mathematische Formeln

Einfache mathematische Formeln werden mit der equation-Umgebung erzeugt:

$$p_{me0f}(T_e,\omega_e) \ = \ k_1(T_e) \cdot (k_2+k_3 S^2 \omega_e^2) \cdot \Pi_{\max} \cdot \sqrt{\frac{k_4}{B}} \, . \tag{2.8}$$

Der Code dazu lautet:

```
\begin{equation}
  p_{me0f}(T_e,\omega_e) \ = \ k_1(T_e) \cdot (k_2+k_3 S^2
  \omega_e^2) \cdot \Pi_{max} \cdot \sqrt{\frac{k_4}{B}} \, .
\end{equation}
```

Mathematische Ausdrücke im Text werden mit $formel$ erzeugt (z.B.: $a^2+b^2=c^2$). Vektoren und Matrizen werden mit den Befehlen `\vec{.}` und `\mat{.}` erzeugt (z.B. $\boldsymbol{v}$, $\boldsymbol{M}$).

2.9 Weitere nützliche Befehle

Hervorhebungen im Text sehen so aus: *hervorgehoben*. Erzeugt werden sie mit dem `\epmh{.}` Befehl.
Einheiten werden mit den Befehlen `\unit[1]{m}` (z.B. 1 m) und `\unitfrac[1]{m}{s}` (z.B. 1 m/s) gesetzt.

Bibliography

[1] M. Raibert, *Legged Robots That Balance.* Cambridge, MA: MIT Press, 1986.

[2] M. Vukobratović and B. Borovac, "Zero-moment point — thirty five years of its life," *International Journal of Humanoid Robotics*, vol. 1, no. 01, pp. 157–173, 2004.

[3] G. A. Pratt and M. M. Williamson, "Series elastic actuators," in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 1995, pp. 3137–3181.

Appendix A

Irgendwas

Bla bla ...

Appendix B

Datasheets

EC-max 30 ∅30 mm, brushless, 60 Watt

maxon *EC*-max



M 1:2

Stock program
Standard program
Special program (on request)

Part Numbers

Motor Data			272762	272763	272764	272765
Values at nominal voltage						
1	Nominal voltage	V	12	24	36	48
2	No load speed	rpm	7980	9340	9490	9350
3	No load current	mA	302	191	130	95.4
4	Nominal speed	rpm	6590	8040	8270	8130
5	Nominal torque (max. continuous torque)	mNm	63.6	60.7	63.7	64.1
6	Nominal current (max. continuous current)	A	4.72	2.66	1.88	1.4
7	Stall torque	mNm	381	458	522	519
8	Starting current	A	26.8	18.8	14.5	10.7
9	Max. efficiency	%	80	81	82	82
Characteristics						
10	Terminal resistance phase to phase	Ω	0.447	1.27	2.48	4.49
11	Terminal inductance phase to phase	mH	0.049	0.143	0.312	0.573
12	Torque constant	mNm/A	14.2	24.3	35.9	48.6
13	Speed constant	rpm/V	672	393	266	197
14	Speed/torque gradient	rpm/mNm	21.2	20.6	18.4	18.2
15	Mechanical time constant	ms	4.86	4.73	4.21	4.17
16	Rotor inertia	gcm²	21.9	21.9	21.9	21.9

Specifications

Thermal data

17	Thermal resistance housing-ambient	7.4 K/W
18	Thermal resistance winding-housing	0.5 K/W
19	Thermal time constant winding	2.76 s
20	Thermal time constant motor	1000 s
21	Ambient temperature	-40…+100°C
22	Max. permissible winding temperature	+155°C

Mechanical data (preloaded ball bearings)

23	Max. permissible speed	15000 rpm
24	Axial play at axial load < 6.0 N	0 mm
	> 6.0 N	0.14 mm
25	Radial play	preloaded
26	Max. axial load (dynamic)	5 N
27	Max. force for press fits (static)	98 N
	(static, shaft supported)	1300 N
28	Max. radial loading, 5 mm from flange	25 N

Other specifications

29	Number of pole pairs	1
30	Number of phases	3
31	Weight of motor	305 g

Values listed in the table are nominal.

Connection motor (Cable AWG 20)

red	Motor winding 1	Pin 1
black	Motor winding 2	Pin 2
white	Motor winding 3	Pin 3
	N.C.	Pin 4
Connector	**Part number**	
Molex	39-01-2040	

Connection Sensors (Cable AWG 26)

yellow	Hall sensor 1	Pin 1
brown	Hall sensor 2	Pin 2
grey	Hall sensor 3	Pin 3
blue	GND	Pin 4
green	V_{Hall} 3…24 VDC	Pin 5
	N.C.	Pin 6
Connector	**Part number**	
Molex	430-25-0600	

Wiring diagram for Hall sensors see p. 35

Operating Range



Comments

Continuous operation
In observation of above listed thermal resistance (lines 17 and 18) the maximum permissible winding temperature will be reached during continuous operation at 25°C ambient.
= Thermal limit.

Short term operation
The motor may be briefly overloaded (recurring).

Assigned power rating

maxon Modular System

Overview on page 20 - 25

Planetary Gearhead
∅32 mm
8.0 Nm
Page 266

Koaxdrive
∅32 mm
1.0 - 4.5 Nm
Page 268

Planetary Gearhead
∅42 mm
3 - 15 Nm
Page 271



Encoder MR
500/1000 CPT,
3 channels
Page 302

Encoder HEDL 5540
500 CPT,
3 channels
Page 308

Brake AB 20
24 VDC
0.1 Nm
Page 346

Recommended Electronics:

ESCON 36/3 EC	Page 320
ESCON 50/5, Module 50/5	321
ESCON 70/10	321
DECS 50/5	324
DEC Module 24/2	325
DEC Module 50/5	325
EPOS2 24/5, 50/5	331
EPOS2 P 24/5	334
EPOS3 70/10 EtherCAT	337
Notes	**24**

RE 40 ∅40 mm, Precious Metal Brushes, 25 Watt

NEW

maxon DC motor



M 1:2

Stock program
Standard program
Special program (on request)

Part Numbers

Motor Data		448588	448589	448590	448591	448592
Values at nominal voltage						
1 Nominal voltage	V	9	18	24	42	48
2 No load speed	rpm	2850	2850	2780	2920	2690
3 No load current	mA	49.7	24.8	18.1	11	8.62
4 Nominal speed	rpm	2610	2600	2480	2640	2410
5 Nominal torque (max. continuous torque)	mNm	87.8	87.8	88.2	87.6	87.6
6 Nominal current (max. continuous current)	A	2.96	1.48	1.09	0.65	0.524
7 Stall torque	mNm	873	956	794	895	818
8 Starting current	A	29	15.9	9.66	6.53	4.81
9 Max. efficiency	%	92	92	92	92	92
Characteristics						
10 Terminal resistance	Ω	0.311	1.14	2.49	6.43	9.97
11 Terminal inductance	mH	0.0824	0.33	0.613	1.7	2.62
12 Torque constant	mNm/A	30.2	60.3	82.2	137	170
13 Speed constant	rpm/V	317	158	116	69.7	56.2
14 Speed / torque gradient	rpm/mNm	3.27	2.98	3.51	3.27	3.3
15 Mechanical time constant	ms	4.85	4.29	4.36	4.14	4.13
16 Rotor inertia	gcm²	142	137	119	121	120

Specifications

Thermal data

17	Thermal resistance housing-ambient	4.65 K/W
18	Thermal resistance winding-housing	1.93 K/W
19	Thermal time constant winding	41.5 s
20	Thermal time constant motor	809 s
21	Ambient temperature	-20…+85°C
22	Max. permissible winding temperature	+100°C

Mechanical data (ball bearings)

23	Max. permissible speed	3330 rpm
24	Axial play	0.05 - 0.15 mm
25	Radial play	0.025 mm
26	Max. axial load (dynamic)	5.6 N
27	Max. force for press fits (static)	110 N
	(static, shaft supported)	1200 N
28	Max. radial loading, 5 mm from flange	28 N

Other specifications

29	Number of pole pairs	1
30	Number of commutator segments	13
31	Weight of motor	480 g

Values listed in the table are nominal.
Explanation of the figures on page 71.

Option
Preloaded ball bearings

Operating Range



Comments

Continuous operation
In observation of above listed thermal resistance (lines 17 and 18) the maximum permissible winding temperature will be reached during continuous operation at 25°C ambient.
= Thermal limit.

Short term operation
The motor may be briefly overloaded (recurring).

Assigned power rating

maxon Modular System

Overview on page 20 - 25



Encoder MR
256 - 1024 CPT,
3 channels
Page 303

Encoder HED_ 5540
500 CPT,
3 channels
Page 305/307

Recommended Electronics:

ESCON 36/2 DC	Page 320
ESCON 50/5	321
ESCON Module 50/5	321
EPOS2 24/2	330
EPOS2 Module 36/2	330
EPOS2 24/5	331
EPOS2 50/5	331
EPOS2 P 24/5	334
EPOS3 70/10 EtherCAT	337
Notes	**22**